

HYBRID SYSTEM OF SOLAR WIND ENERGY GENERATION

Gavish Gothria, Akhil

Dronacharya College of Engineering, Gurgaon

Abstract— Hybrid power system can be used to reduce energy storage requirements. The influence of the Deficiency of Power Supply Probability (DPSP), Relative Excess Power Generated (REPG), Energy to Load Ratio (ELR), fraction of PV and wind energy, and coverage of PV and wind energy against the system size and performance were analyzed. The technical feasibility of PV-wind hybrid system in given range of load demand was evaluated. The methodology of Life Cycle Cost (LCC) for economic evaluation of stand-alone photovoltaic system, stand-alone wind system and PV-wind hybrid system have been developed and simulated using the model. The comparative cost analysis of grid line extension energy source with PV-wind hybrid system was studied in detail. The optimum combination of solar PV-wind hybrid system lies between 0.70 and 0.75 of solar energy to load ratio and the corresponding LCC is minimum. The PV-wind hybrid system returns the lowest unit cost values to maintain the same level of DPSP as compared to standalone solar and wind systems. For all load demands the levelised energy cost for PV-wind hybrid system is always lower than that of standalone solar PV or wind system. The PV-wind hybrid option is technoeconomically viable for rural electrification.

Index Terms- model, solar, wind, hybrid, energy, rural electrification..

I. INTRODUCTION

Electricity is most needed for our day to day life. There are two ways of electricity generation either by conventional energy resources or by non-conventional energy resources. Electrical energy demand increases in word so to fulfill demand we have to generate electrical energy. Now a day's electrical energy is generated by the conventional energy resources like coal, diesel, and nuclear etc. The main drawback of these sources is that it produces waste like ash in coal power plant, nuclear waste in nuclear power plant and taking care of this wastage is very costly. And it also damages he

nature. The nuclear waste is very harmful to human being also. The conventional energy resources are depleting day by day. Soon it will be completely vanishes from the earth so we have to find another way to generate electricity. The new source should be reliable, pollution free and economical. The non-conventional energy resources should be good alternative energy resources for the conventional energy resources. There are many non-conventional energy resources like geothermal, tidal, wind, solar etc. the tidal energy has drawbacks like it can only implemented on sea shores. While geothermal energy needs very lager step to extract heat from earth. Solar and wind are easily available in all condition. The non-conventional energy resources like solar, wind can be good alternative source. Solar energy has drawback that it could not produce electrical energy in rainy and cloudy season so we need to overcome this drawback we can use two energy resources so that any one of source fails other source will keep generating the electricity. And in good weather condition we can use both sources combine.

II. HYBRID ENERGY SYSTEM


Hybrid energy system is the combination of two energy sources for giving power to the load. In other word it can defined as "Energy system which is fabricated or designed to extract power by using two energy sources is called as the hybrid energy system." Hybrid energy system has good reliability, efficiency, less emission, and lower cost.

In this proposed system solar and wind power is used for generating power. Both the energy sources have greater availability in all areas. It needs lower cost. There is no need to find special location to install this system.

A. Solar Energy

Solar energy is that energy which is gets by the radiation of the sun. Solar energy is present on the

earth continuously and in abundant manner. Solar energy is freely available. It doesn't produce any gases that mean it is pollution free. It is affordable in cost. It has low maintenance cost. Only problem with solar system it cannot produce energy in bad weather condition. But it has greater efficiency than other energy sources. It only need initial investment. It has long life span and has lower emission.



B. Wind Energy

Wind energy is the energy which is extracted from wind. For extraction we use wind mill. It is renewable energy sources. The wind energy needs less cost for generation of electricity. Maintenance cost is also less for wind energy system. Wind energy is present almost 24 hours of the day. It has less emission. Initial cost is also less of the system. Generation of electricity from wind is depend upon the speed of wind flowing.

The major disadvantages of using independent renewable energy resources are that unavailability of power for all time. For overcoming this we use solar and wind energy together. So that any one source of power fails other will take care of the generation. In this proposed system we can use both sources combine. Another way is that we can use any one source and keep another source as a stand by unit. This will leads to continuity of generation. This will make system reliable. The main disadvantages of this system are that it needs high initial cost. Except that it is reliable, it has less emission. Maintenance cost is less. Life span of this system is more. Efficiency is more.

III. DESIGN OF HYBRID ENERGY SYSTEM

Below figure shows the fig. of the hybrid power generation system using wind and solar power. This block includes following blocks.

- i. Solar panel
- ii. Wind turbine
- iii. Battery bank




Fig.1 Hybrid energy generation system

i. Solar panel

Solar panel is use to convert solar radiation to the electrical energy.. When the junction absorbs light, the energy of absorbed photon is transferred to the electron-proton system of the material, creating charge carriers that are separated at the junction. The charge carriers in the junction region create a potential gradient, get accelerated under the electric field, and circulate as current through an external circuit. Solar array or panel is a group of a several modules electrically connected in series parallel combination to generate the required current and voltage. Solar panels are the medium to convert solar power into the electrical power.




Fig.2 Solar Radiation

ii. Wind turbine

Wind turbine is that system which extracts energy from wind by rotation of the blades of the wind turbine. Basically wind turbine has two types one is vertical and another is horizontal. As the wind speed increases power generation is also increases. The power generated from wind is not continuous its fluctuating. For obtain the non-fluctuating power we have to store in battery and then provide it to the load.




Fig.3 PV-Wind Ratio

iii. Battery Bank

We have to choose battery bank size per the load requirement so that it should fulfill the requirement of load for calculating the battery bank size we need to find following data

1. Find total daily use in watt-hour (Wh).
2. Find total back up time of the battery

For increase in battery bank size we need to connect cell in series so that we can get the larger battery bank size.

IV. CONCLUSION

Hybrid power generation system is good and effective solution for power generation than conventional energy resources. It has greater efficiency. It can provide to remote places where government is unable to reach. So that the power can be utilize where it generated so that it will reduce the transmission losses and cost. Cost reduction can be done by increasing the production of the equipment. People should motivate to use the non conventional energy resources. It is highly safe for the environment as it doesn't produce any emission and harmful waste product like conventional energy resources. It is cost effective solution for generation. It only need initial investment. It has also long life

span. Overall it good, reliable and affordable solution for electricity generation.

ACKNOWLEDGMENT

Authors wish to thanks Dronacharya College of Engineering, Gurgaon (Haryana) India. Also like to pay gratitude towards Head of Department, Electrical and Electronics Engineering and Principal Dronacharya College of Engineering Gurgaon Haryana India for their valuable support and encouragement.

REFERENCES

- [1] I. A. Adejumobi, S.G. Oyagbinrin, F. G. Akinboro & M.B. Olajide, "Hybrid Solar and Wind Power: An Essential for Information Communication Technology Infrastructure and people in rural communities", IJRRAS, Volume 9, Issue1, October 2011, pp 130-138.
- [2] Kavita Sharma, Prateek Haksar "Designing of Hybrid Power Generation System using Wind Energy- Photovoltaic Solar Energy- Solar Energy with Nanoantenna" Internationa Journal of Engineering Research And Applications (IJERA) Vol. 2, Issue 1,Jan-Feb 2012, pp.812-815 .
- [3] Sandeep Kumar, Vijay Kumar Garg, "A Hybrid model of Solar-Wind Power Generation System", International Journal of Advanced Research in Electrical, Electronics and Instrumentation Engineering (IJAREEIE), Vol. 2, Issue 8, August 2013, pp. 4107-4016.
- [4] M. Thomas (Ed) "Solar Electricity", John Wiley and Sons Ltd, Chichester, 2ndEdition. (2004).
- [5] U.K Mehta. "Principle of Electronics", S. Chand & Company Ltd.New Delhi. (2004),
- [6] Technical brief on Wind Electricity Generation: Retrieved from www.windpower.org.(2009).
- [7] E.E. Iheonu, F.O. A. Akingbade, M. Ocholi Wind Resources Variations over selected sites in the West African sub-region. Nigerian J. Renewable Energy, **10**, 43-47(2002).
- [8] W.W.S. Charters. "Solar and Wind Power Technologies for Remote Applications". CSC Technical Publication Services No 187, Commonwealth Science Council. (1985).
- [9] S.I. Iwuoha. Wind Powered Horizontal Maize Grinder, NJRE, **11**, 46-57(2003).

- [10] B.K. Gupta . Weibull Parameters for Annual and Monthly Wind Speed Distributions for Five Locations in India, *Solar Energy*. **37**, 469-477. (1986)
- [11] C.G. Justus, W.R. Hargraves, and A. Yalcin, Nationwide assessment of potential output from wind power generators, *J. Appl. Meteor.* **15**, 673-678. (1976)