

# Malware Detection Using Machine Learning

Akarsh Srivastva<sup>1</sup>, Mayank Sharma<sup>2</sup>, Faraj Chishti<sup>3</sup>

<sup>1,2,3</sup>*Department of Information Technology, ABES Institute of Technology, Ghaziabad, UttarPradesh, India*

**Abstract** - Zero-day or dull malware are made utilizing code befuddling techniques that pass down similar handiness of parent yet with various engravings. Malevolent programming, inferred as malware, is dependably making security danger, thus enormous areas of examination. The basic stage in unmistakable confirmation is evaluation. This consolidates either static or dynamic appraisal of known malware and performing isolation. Results of evaluation are refined into a "signature". One methodology for malware affirmation is the utilization of static engravings to survey programs after they are stacked and before execution. Authentic structures subject to AI are used to find plans identifying with malignant lead). Unusually, deterministic etchings are generally evolved through human expert appraisal. Standard malware domain strategies – both static and dynamic – are executed in programming. In this, we battle against unadulterated programming executions both thinking about their overhead and the going with trust in dealing with base (TCB) swell. Copilot can see certain part level rootkits by checking if these portrayals contrast from their ordinary characteristics.

**Index Terms** - Zero-day malware, Machine Learning, Sandbox, Feature Extraction, Heuristic Analysis, Model Training.

## INTRODUCTION

Malware location includes system to recognize and shield against damage from files (like: viruses, worms, Trojan horses, spyware, and other forms of vindictive code). Malicious file recognition and prevention technologies are broadly existing for servers, gateways, user workstations, and mobile devices, with some tools contribution the skill to centrally monitor malware detection software installed on multiple structures or computers. Malware is one of the most honest security risks and spreads independently through weaknesses or inconsiderateness of clients. To shield a PC from illness or wipe out malware from a damaged PC framework, it is basic to exactly accurately identified malware. We have organized a special technique for using a couple of AI strategies to

separate zero-day malware with high exactness dependent on the replication of Windows API calls. Zero-day malware is an item security blemish that is known to the item vender anyway does not have a fix set up to fix the imperfection. It can be abused by cybercriminals. The Windows API is Microsoft's middle plan of application programming Interface (APIs) open in the Microsoft Windows occupied structures. Basically, all Windows programs partner with the Windows API. It's a lot of limits and data structures that a Windows program can use to demand that Windows achieve something, for example, opening a report, representing a message, etc. Basically, all that a Windows program does incorporates calling various API limits. Regardless of that, there is a decreasing in the dominance near that is compulsory for malware improvement, considering the high receptiveness of assaulting contraptions on the Cyberspace these days. High accessibility of disagreeable to affirmation methods, in like way as capacity to search for malware on the underground market end in the event to change into an aggressor for anybody, barring from the limit level. Current appraisals show that a consistently extending number of assaults are being given by content adolescents or are mechanized. In this manner, malware security of PC structures is one among the head critical network safety tasks for single customers and associations, since even one attack may bring about subverted data and sufficient setbacks. Huge hardships and normal attacks direct the prerequisite for careful and helpful acknowledgment procedures. Therefore, AI based strategies can be used. This paper discusses the focal issues and worries of AI founded malware identification, just as searches for the best element portrayal and grouping strategies

## RELATED WORK

Associated work sector is important in study articles. The overall area is to describe the connected research areas and to place our technique's donations to the field in this context. By clearly recitation earlier work, we have defined the current boundaries and the need for new practice. Some of those previous works are:

In the paper [1] the aim was for evolving a recognition system based on numerous modified perceptron algorithms. For different algorithms, the correctness of 69.91%-97.06% was achieved. It should be specified that the algorithms that caused in best accuracy also produced the highest number of wrong-positives: the most accurate one occasioned in 48 false positives. The greatest stable algorithm with suitable correctness and the low false-positive rate had the accuracy of 93.05%.

In [2] the API functions were used for feature depiction again. This study was to create a dataset by finding runtime system calls made by 7107 malicious software on Windows 7. As a result, a dataset was built that contains the malware behavioural data at runtime and class labels to which the software was included. a organization model is proposed, and this dataset created a model for malware detection by means of deep learning technique LSTM. This model presented a victory rate amongst 83.5% to 98.4% .

In the paper [3], the efficacy of the proposed framework is discussed with adequate experimental results. Paper considered 220 samples of data containing malicious as well as benign files. For malware analysis, the datasets are divided into training and testing sets. Training and testing sets contain 60% and 40% of malware samples respectively.

[4] states that the active investigation has some boundaries due to controlled network behaviour and it cannot be analysed due to partial entree to the network. Measured situation for malware investigation is not much useful due to the tricky nature of malware, the virtualized and correcting modes are quickly demonstrable by malware. The AUC (Area under Curve) of static malware analysis is 99.26% which is better than dynamic analysis. Static analysis has some boundaries due to the basic crowded nature of malware.

[5] Labelled here are personifications of a better system and technique for automated machine-learning, Zero-day malware detection. Incarnations include a complex classifier useful for malware detection. g feature derivation methods in a machine-

learning system. Embodiments include a qualified meta-features (QMF) feature abstraction algorithm for growing accuracy and falling "false positive" faults in malware detection.

[6] debates the discovery technique grounded on revised Random Forest algorithm in mixture with Material Advantage for better feature picture. It should be noticed that the data set consists purely of portable executable files, for which feature withdrawal is usually easier. The result achieved is the correctness of 97.02% and 0.05 false- positive rate.

[7] projected abstraction methods based on PE headings, DLLs and API functions and approaches constructed on Naive Bayes, J48 Decision Trees, and Support Vector Machines. Highest overall accurateness was attained with the J48 algorithm (98.99% with PE heading feature type and hybrid PE header & API purpose feature type, 99.01% with API function feature type). The aim was to develop a detection system based on several modified perceptron algorithms. For changed algorithms, he achieved the correctness of 69.91%-96.8%. It should be specified that the algorithms that caused in best accurateness also formed the maximum number of false-positives: the most accurate one resulted in 48 false positives. The most stable algorithm with suitable accurateness and the small false-positive rate had the exactness of 93.07%.

In [8], the API functions were used for feature illustration again. The best result was accomplished with the Support Vector Machines algorithm with standardized polykernel. The precision of 97.16% was obtained, with a false-positive amount of 0.026. Malware has extended remained acquainted on the Internet currently as one of the most prominent cyber threats. It expands rapidly in volume, velocity and variety, which overcoming the conventional methods used to recognize and distinguish malware. In order to suit the size and difficulty of such a data-accelerated environment, successful analytics methods are required. At the present time with the Big Data platform, the specific methods will help malware researchers successfully do the laborious process of methodically investigating malicious events. Security researchers want to create a use of Machine Learning algorithms with big information measures to evaluate and pathway indeterminate malware in a bulky scale. These techniques consist of dynamic and wide flux of

malicious binaries which aid them to solve the emerging threat environment.

[9] suggests the outline of big data whereby performances of static and dynamic malware recognition are competently amalgamated in order to accurately classify and identify zero-day malware. The framework being familiarized the tested and estimated on a sample files for 0.2 million involving the clean files for 0.02 million and comprehending a wide variety of malware families in 0.12 million malicious binaries. The results show that SVM attained the best accuracy of 93.03% for sensing malware and benign types using 10-fold cross authentication.

[10] attempts to appraise the competence of a feature-based malware arrangement using autoencoders. In doing so, this paper offerings a novel technique for generating a artificial malware dataset constructed on signature and topographies which could be used to train and test both traditional and artificial intelligence-based malware detection systems. Various experiments are carried out using autoencoders training on feature based and signature-based datasets and tested on a synthetic dataset. The experiments also carried out with multiple datasets and topologies. The experiment results show that the feature-based training is proved to be efficient for synthetic, signature and feature based datasets compared to signaturebased approach. Feature based weighted autoencoders (5-layered) is able to achieve a arrangement accuracy of 95.06% more than 11.16% when associated with the signature-based structure which could accomplish only 84.5%.

[11] The PE's were implemented in a windows 7 computer-generated climate utilizing the Cuckoo sandbox. Applicable 4gram API call highlights are extricated operating Term Frequency-Inverse Document Frequency (TF- IDF). Gaussian Naive Bayes, SVM, Random Forest, and Decision Trees were utilized to prepare and test the information. We show that the strategy is effective with precision somewhere in the range of 92% and 96.4%. There are interior varieties in exactness with SVM and Decision Trees performing best and Gaussian Naive Bayes performing most exceedingly terrible.

[12] From tiny static and dynamic examination for understanding the subtleties of malware design and practices, to setting up perceptible AI engineering, preparing model, and assessing model execution, the venture gives an outline of malware examination and

location. The two viewpoints are significant and supplement one another. Without knowing the malware attributes, it's hard to set up a beginning stage for model to "learn". Without the assistance of machine calculation, the network safety specialists will be depleted by considering malware test individually and neglect to get a handle on the theoretical nature.

[13] Malware arrangement is a troublesome issue, to which AI strategies have been applied for quite a long time. However progress has frequently been moderate, to a limited extent because of various special challenges with the undertaking that happen through all phases of the building up an AI framework: information assortment, marking, highlight formation and determination, prototypical choice, and assessment. In this study we will audit some of the present strategies and moves identified with malware arrangement, counting information assortment, highlight extraction, and model development, and assessment. Our conversation will remember considerations for the imperatives that should be considered for AI based arrangements in this area, but to be handled issues for which AI could likewise give an answer. This overview plans to be helpful both to network protection experts who wish to become familiar with how AI is applicable to the malware issue, and to provide information researchers the essential foundation into the difficulties in this exceptionally confounded space.

[14] Malscore joined static investigation with dynamic examination not just sped up the static investigation measure by exploiting the CNN in picture acknowledgment yet in addition gave off an impression of being stronger to confusion by the powerful examination. Not quite the same as other static and dynamic examination strategies, when malware is distinguished, because of the way that malware will no doubt be named exclusively by static investigation, we might diminish the expenditures by powerfully breaking down a couple malware that has more subtle highlights or more prominent disarray in static investigation. We performed investigates 174607 malware tests from 63 malware families. The outcome showed that Malscore accomplished 98.82% precision for malware order. Moreover, Malscore was contrasted and the strategy for utilizing static and dynamic examination. The preprocessing and test time addresses decrease of 59.48% and 61.71%, separately.

[15] In this paper, we have pondered the various advantages and blocks of the Signature-based and Behavior-based methodology. The imprint-based philosophy ends up being inhuman for malwares that are usually found in systems yet is delicate against different and malwares with changed codes. Curiously, the Behavior-based procedure ends up being inhuman for such a malwares. Regardless, it comes up short when malware is analyzed as the common lead of any item that is being noticed. Also, it builds up a demanding environment which may incite customer disillusionment and it may deliver fake alarms for a couple of common errands if the social model of the item isn't grown capably. All in all, it might be contemplated that the Determination based noticing system is a far compelling technique as it fuses both Signature-based and Conduct based approaches which give customers sufficient affirmation and besides extraordinary customer experience.

[16] This research has comparatively analysed the three different malware detection techniques stating their upsides and downsides has come up with a conclusion that no single detection technique is good enough for the detection of recent time malwares but a combination of two or three of them.

[17] In this paper, we have analyzed the paper by learning out about proposed novel structure considered DLMDN for assessing both the MLA's and profound learning techniques. The proposed structure has a consecutive method parceled into five stages, to recognize the malwares. It comprises of gathering crude malware tests, parsing the information, pre-handling, distinguishing and ordering the malware into individual malware families. The classification of malwares is performed by picture preparing method. This paper has demonstrated the matchless quality of profound learning techniques over MLA's regarding precision for discovery of novel malwares, accuracy rate, reviewing variable and F-score.

[18] In this paper, we got to know about the two AI helped methods for static investigation of Android malware. The main methodology depends on authorizations and the additional depends on foundation code investigation using a sack of-confrontations portrayal model. Our authorization-based model is computationally economical, and is executed as the component of OWASP Seraphimdroid Android application that can be gotten from Google

Play Store. Our assessments of the two methodologies demonstrate a F-score of 95.5% and F-proportion of 89.01% for the source code based grouping and consent based arrangement models, separately.

[19] This paper that is dependent on cuckoo sandbox distinguishes and forestalls malwares inside a zero-day time, to ensure two segments: To begin with, the customers' PCs that are ensured by our tweaked created python code that lives in the regulator. Second, assaults on SDN regulator which is forestalled utilizing our proposed and the created UNIX-based Cuckoo sandbox. In this regulator, traffic is checked by the forced location rules. Test results show our proposed system is compelling in recognizing diverse malwares assaults and has a high achievement likelihood in recognizing distinctive malwares. As it can be viewed, all studies finished up with different results. From now, we can accomplish that no unified methodology was formed yet neither for recognition nor feature illustration. The accuracy of each isolated circumstance be contingent on the specifics of malware families used and on the authentic operation.

## METHODOLOGY


This fragment sets up a foundation on AI strategies, required for understanding the pattern of execution. From the start, the blueprint of the AI field is examined, trailed by the depiction of techniques fitting to this assessment. These methods join kNearest Neighbors, Decision Trees, Discretionary Forests, Support Vector Machines and Naïve Bayes.

### A.MACHINE LEARNING FUNDAMENTALS

"A PC disease is maintained to find for a reality E with respect to class of tasks T and execution measure P if its display at tasks in T, as assessed by P, improves with experience E." (Mitchell 1997). The key impression of any AI task is to direct the model, upheld a couple computation, to play out a particular task: gathering, clusterization, slip into wrongdoing, etc Preparing is done ward upon the data dataset, and the model that is made is therefore used to make surmises. The yield of such model depends on the mysterious endeavor and subsequently the use. Potential applications are: given data about house properties, like room number, size, and cost, expect the appraisal of the feasibly faint house; upheld two datasets with sound clinical pictures and subsequently the ones with lump, group a pool of latest pictures;

pack o pictures of creatures to various bunches from an uncategorized pool.

To build up a more critical agreement, it merits experiencing the general work cooperation of the AI framework, which is appeared in the figure given under.



As the situation might be realized, the technique includes 5 phases:

1. Data affirmation- All along, the dataset is stacked after the archive and is protected in recollection.
2. Data change- As of now, the information that was stacked at stage 1 is changed, cleared, and standardized to be reasonable for the calculation. Information is changed over with the target that it lies in a near reach, has a similar arrangement, and so forth By and by join extraction and affirmation, which are dissected further, are proceeded additionally. Notwithstanding that, the information is detached into sets – 'preparing set' and 'test set'. Information from the arranging set is utilized to make the model, which is hence reviewed utilizing the test set.
3. Model Training- At this stage, a model is created utilizing the picked calculation.
4. Model Testing- The model that was created or organized throughout stage 3 is made a pass at utilizing the test enlightening document, and the made outcome is utilized for building another model, that would contemplate past models, for example "learn" since them.
5. Model Deployment- At this point, the best model is picked (either after the depicted number of cycle or when the essential outcome is developed).

**B.FEATURE WITHDRAWAL**

In a little of the models implied overhead, we must constantly be set up to forgo the credits from the data record, all together that it are dependably taken care of to the computation. For example, at the housing costs case, data might be tended to as a multidimensional structure, where each part keeps an eye on a quality and pieces address the mathematical characteristics for

these attributes. In the image case, data are reliably tended to as a RGB examination of every pixel. Such characteristics are insinuated as features, and in this way the structure is implied as feature vector. The course toward killing information from the chronicles is named incorporate extraction. Another essential thing for a reasonable outline of cutoff points is non-overabundance. Having monotonous features for instance incorporates that plot a relative information, furthermore as terrible information properties, that are emphatically trapped in to one another, can make the computation unbalanced and, hence, give a wrong result.


Other potential changes are:

1. Regularization - An occasion of regularization can be isolating a picture x, somewhere x is are the measure of pixels with covering I, by the absolute number of tallies to encode the stream and clear the reliance on the size of the picture. This converts into the recipe:  $x' = x/||x||$ (Guyon and Elisseeff 2006).
2. Standardization - Periodically, even while implying identical articles, features can have various arrangements. For instance, consider the lodging costs model. Here, incorporate 'room size' is a whole number, likely not outflanking 5 and feature 'house size' is evaluated in square meters. In spite of the fact that the two qualities can be looked at, included, replicated, and so on, the outcome would be insane earlier stabilization. The going with scaling is reliably done:  $x'_i = (x_i - \mu_i) / \sigma_i$ , where  $\mu_i$  and  $\sigma_i$  are the mean and the average aberration of feature  $x_i$  over preparing models. (Guyon and Elisseeff 2006).
3. Non-direct developments - Ignoring the way that as a rule we need to diminish the dimensionality of information, now and again it may look great to develop it. This can be helpful for complex issues, where first-request joint endeavors are not adequate for careful outcomes.

**IMPLEMENTATION**

This part sees the distinctive application centred portions of the endeavour. This consolidates information assembly, depiction of malware relations that address the dataset, decision of the features that will be utilized for the estimation additionally, finding

the ideal component depiction methodology, evaluation procedure, and the utilization cycle. Fig. 1 is the User Interface of the software and fig. 2 is the code written for the UI.



(Fig1)

```
import tkinter as tk
from tkinter.filedialog import askopenfilename
import os.path
import tkinter.messagebox
#import malwareTest

class Application(tk.Frame):
    def getResult(self):
        for x in self.outputFrame.grid_slaves():
            x.destroy()
        if os.path.exists(self.entry.get()) and os.path.isfile(self.entry.get()):
            tk.Label(self.outputFrame, text=malwareTest.detect(self.entry.get()).grid()
        else:
            tk.messagebox.showerror("Error", "File Does Not Exist")

    def selectClick(self, event=None):
        filename = askopenfilename()
        self.entry.delete(0, len(self.entry.get()))
        self.entry.insert(0, filename)

    def __init__(self, master=None):
        tk.Frame.__init__(self, master)
        self.grid()
        self.createWidgets()

    def createWidgets(self):
        top = self.winfo_toplevel()
        top.columnconfigure(0, weight=1)
        self.rowconfigure(0, weight=1)
        self.columnconfigure(0, weight=1)
        self.mainLabel = tk.Label(self, text="Select File")
        self.mainLabel.grid(row=0, columnspan=2, padx=10, pady=10)
        self.entry = tk.Entry(self, bd=1, width=200)
        self.entry.grid(row=1, padx=10, pady=10)
        self.quitButton = tk.Button(self, text="Select", command=self.selectClick)
        self.quitButton.grid(row=1, column=1, padx=10, pady=10)
        self.result = tk.Button(self, text="Scan", command=self.getResult)
        self.result.grid(row=2, columnspan=2, padx=10, pady=10)
        self.outputFrame = tk.Frame(self)
        self.outputFrame.grid(row=3, columnspan=2, padx=10, pady=10)

app = Application()
app.master.title("Malware Detection")
app.master.geometry("{}x{}".format(600, 300))
app.master.minsize(400, 300)
#app.master.iconphoto(True, tk.PhotoImage(file="MyIcon.png"))
```

(Fig2)

**CONCLUSION**

Generally, the objectives considered for this examination were accomplished. The perfect element abstraction and portrayal approaches were chosen and the nominated AI solutions were applied and assessed. The ideal part portrayal method was picked to be the joined structure, explaining the rehash of effective and

blockaded API calls near to the appearance codes for them. This was picked in view of its nature of solidifying the certified credits of the archive. Instead of different procedures, it joins data about various changes in the structure, reviewing the developments for the library, mutexes, records, and so forth.

**FUTURE SCOPE**

At the present time, the section abstraction is accomplished after the documentations were run in the sandbox and the information were made. This methodology will accomplish delays in the record assessment when finished. Possibly, it is reprovved dispose of the highlights as they are set up by the sandbox, so that there will be no persuading inspiration to experience the reports once more. Despite the way that the instructive list that was utilized in this assessment is expansive, covering the vast majority of the malware types that are fitting to the bleeding edge world, it doesn't cover every conceivable sort. Gettogether a malware instructive record is a dull undertaking that requires a ton of time additionally, exertion. For intelligently careful assessment of the markers, it is asked to test the models on all the expected kinds of malware: spyware, adware, rootkits, helper area, banking malware, and so forth. In spite of that, comprehend that the model may have the decision to expect the occasions of the lots of data that it has seen already. Taking everything into account, in a veritable application, a greater course of action of data ought to be utilized before the dispatch of the undertaking for authentic conditions.

Execute highlight withdrawal in the inline mode: "Right now, the part extraction is performed after the records were run in the sandbox and the reports were made. This methodology will accomplish delays in the record assessment when finished. Considering everything, it is advised separate the highlights as they are set up by the sandbox, so that there will be no persuading inspiration to go through the reports once more."

Utilize a more expansive dataset. Despite the way that the dataset that was utilized in this examination is clearing, covering by far most of the malware types that are relevant to the forefront world, it doesn't cover each and every understandable

sort. Get-together a malware dataset is a dull assignment that requires a lot of time and exertion. For supplementary precise evaluation of the markers, it is approached to examination the models on the entirety of the ordinary sorts of malware: spyware, adware, rootkits, roaming access, banking malware, etc Notwithstanding that, comprehend that the model may have the decision to expect the events of the families that it has seen as of now. So to speak, in a genuine application, the most extreme movement of potential families should be used before the dispatch of the endeavor for authentic conditions.

Utilize pre-picked APIs

In this work, the titanic above in the information overseeing was made by the requirement of picking the basic API calls and ousting the abundance ones. For extra execution, basically the APIs that were seen as basic in this evaluation can be used. This will reduce the degree of time needed for data preprocessing, decrease the presentation basics of the machine on which the evaluation is being done and decay the level of feature affirmation to be made. In any case, it should be seen, that for more mindful depiction, the colossal APIs should be murdered by the help of the best dataset.

In addition, it is approached to pick the enormous APIs per malware family, as this will achieve another level of versatility & exactness.

#### REFERENCES

- [1] Usukhbayar Baldangombo, Nyamjav Jambaljav, and Shi-Jinn Horng 'A STATIC MALWARE DETECTION SYSTEM USING DATA MINING METHODS' 2020.
- [2] Ferhat Ozgur Catak, Ahmet Faruk Yazı, Ogerta Elezaj and Javed Ahmed 'Deep learning based Sequential model for malware analysis using Windows exe API Calls' 27 July 2020.
- [3] Kamalakanta Sethi, Shankar Kumar Chaudhary 'A Novel Malware Analysis Framework for Malware Detection and Classification using Machine Learning Approach' 18th January 2018.
- [4] Muhammad Ijaz, Muhammad Hanif Durad, Maliha Ismail 'Static and Dynamic Malware Analysis Using Machine Learning' January 2019.
- [5] Bhargav R, Avasarala, Arlington 'SYSTEM AND METHOD FOR AUTOMATED MACHINELEARNING, ZERO-DAY MALWARE DETECTION' Mar. 22, 2016.
- [6] Amir Namavar Jahromi, Sattar Hashemi, Ali, 'An improved two-hidden-layer extreme learning machine for malware hunting' 2020.
- [7] Daniel Gilbert, Carles Mateu, Jordi Planes 'The rise of ML for detection and classification of malware: Research developments, trends and challenges' March, 2020.
- [8] Alazab, Mamoun, Sitalakshmi Venkatraman, Paul Watters, and Moutaz Alazab. 2011. Zero-day Malware Detection based on Supervised Learning Algorithms of API call Signatures. Proceedings of the 9-th Australasian Data Mining Conference, 171181.
- [9] V. R. Niveditha, T. V. Ananthan, S. Amudha, Dahlia Sam and S. Srinidhi 'Detect and Classify Zero Day Malware Efficiently In Big Data Platform' January 2020.
- [10] S S Tirumala 'Evaluation of Feature and Signature based Training Approaches for Malware Classification using Autoencoders' 2020.
- [11] Allan Ninyesiga, John Ngubiri, 'Malware Classification using API System Calls' Dec 2018.
- [12] Hemant Rathore, Swati Agarwal, Sanjay K. Sahay and Mohit Sewak 'Malware Detection using Machine Learning and Deep Learning' 4th Apr 2019
- [13] Edward Raff, Charles Nicholas 'A Survey of Machine Learning Methods and Challenges for Windows Malware Classification' 15th Nov 2019.
- [14] DI XUE, JINGMEI LI, TU LV, WEIFEI WU, AND JIAXIANG WANG 'Malware Classification Using Probability Scoring and Machine Learning' 9th July 2019.
- [15] Adit Kumar Chakravarty, Aditya Raj, Subham Paul, Apoorva S 'A study of signature-based and behaviour-based malware detection approaches' 2019.
- [16] \*Odi, J. N., Hampo, J.A.C, Nwokoma F. O., Onwuama T.U., 'COMPARATIVE ANALYSIS OF MALWARE DETECTION TECHNIQUES USING SIGNATURE, BEHAVIOUR AND HEURISTICS' Vol. 17, No. 7, July 2019.
- [17] Arzu Gorgulu Kakisim, Mert Nar, Necmettin Carkaci, and Ibrahim Sogukpinar 'Analysis and

Evaluation of Dynamic Feature-based Malware Detection Methods' Nov 9th 2019.

- [18] Shaik Moin Sharukh, 'A Hybrid Deep Learning Approach for Detecting Zero-Day Malware Attacks.' April 16, 2020.
- [19] Nikola Milosevic · Ali Dehghantanha 'Machine learning aided malware classification of Android applications' 13th Feb 2017.
- [20] Huthifh Al-Rushdan, Mohammad Shurman, and Sharhabeel Alnabelsi 'On Detection and Prevention of ZeroDay Attack Using Cuckoo Sandbox in Software-Defined Networks' June 9, 2020.