

PAPR Reduction Techniques for OFDM System with High Computational Efficiency

Shreyas G. Bharati¹, Rajaram D. Patil², Abasaheb G. Patil³

¹PG Student, Dept. Of Electronics Engg., PVPIT, Budhgaon

²Asso. Prof., Dept. Of Electronics Engg., PVPIT, Budhgaon

³Asso. Prof., Dept. Of Electronics & Telecom. Engg., PVPIT, Budhgaon

Abstract— To reduce the PAPR of multi-carrier transmission, we propose a new scheme by reordering the null-subcarriers and data-subcarriers. This new method shifts the “innermost” null subcarriers among different data-subcarriers to minimize the PAPR. Considering the practicability for implementation, we propose the “Simplified” version, which degrades the computational load by applying proposed shifting scheme only to the subblock with the largest PAPR. The proposed “Simplified” method is distortionless, does not affect the constellation at the data-subcarriers, maintains better PAPR reduction and BER reduction performance while keeping low computational complexity, needs less CSI, can collaborate with most other PAPR-reduction methods, and can be compatible with existing standards.

Index Terms—Nonlinear distortion, Orthogonal frequency division multiplexing, peak-to-average power ratio (PAPR), Intersymbol interference, Null subcarriers, BER

I. INTRODUCTION

Orthogonal frequency division multiplexing (OFDM) is a most effective multicarrier modulation scheme used in wireless and wire line communications. It is a special case of high-data-rate multicarrier transmission technology, where a single data stream is transmitted over a number of lower rate subcarriers instead of single carrier system. The available spectrum is divided into several sub-bands and one subcarrier is used in each sub-band. These subcarriers are orthogonal to each other. Information bit stream is transmitted in parallel on these sub-bands.

The main reason to use OFDM is its robustness against the selective fading or narrowband interference, high spectral efficiency and easy implementation. Hence, due to these favorable features, it is widely used in modern broadband communication systems. OFDM provides greater bandwidth efficiency, immunity to multi-path

fading and impulse noise, resistance to frequency selective fading, and exemption from the need of complex equalizers and digital signal-processor hardware implementation. It has been widely adopted in the international standards, such as IEEE 802.11, IEEE 802.15, IEEE 802.16, IEEE 802.20, European Telecommunications Standards Institute (ETSI) Broadcast Radio Access Network (BRAN) committees, and 3G Long Term Revolution (LTE) [1].

However OFDM system suffers from serious problem of high instantaneous Peak-to-Average Power Ratio (PAPR) of transmitted OFDM signals. In OFDM system, output is superposition of multiple sub-carriers. In this case, some instantaneous power output might increase greatly and become far higher than the mean power of system. To transmit signals with such high PAPR, it requires power amplifiers with very high power scope. These kinds of amplifiers are very expensive and have low efficiency. If the peak power is too high, it could be out of the scope of the linear power amplifier. This gives rise to non-linear distortion which changes the superposition of the signal spectrum resulting in performance degradation. If no measure is taken to reduce the high PAPR, MIMO-OFDM system could face serious restriction for practical applications [2]-[5]. Therefore, reducing the PAPR is of practical interest.

The peak amplitude of the OFDM signal could be ‘N’ times that of a single-carrier system, where ‘N’ denotes the number of carriers. When the peak amplitudes of the OFDM signals with high PAPR reach or exceed the saturation region of power amplifier at the transmitter and/or receiver, the OFDM signals will suffer from nonlinear distortion, spectrum spreading, in-band distortion and inter modulation interference across the OFDM subcarriers. All these impacts demote the bit-error-

rate (BER) at the receiver. One simple solution is to use expensive power-amplifiers with a large saturation region. However, as high peak amplitudes occur irregularly, this High Power Amplifier (HPA) would be inefficient. Besides, high peaks are also constrained by design-factors such as cost and battery power of electronics [1]. Large PAPR also demands the Digital-to-Analog Converter (DAC) with enough dynamic range to accommodate the large peak of the OFDM signals. High PAPR becomes huge obstruction to harvest all the features of OFDM system for the implementation of high speed broadband communication systems.

II. PROPOSED METHODS

A number of approaches have been proposed to deal with the PAPR problem, along with various schemes and design dimensions for PAPR reduction [8]. These techniques include amplitude clipping, clipping and filtering, coding, tone reservation, tone injection, active constellation extension and multiple signal representation techniques such as partial transmit sequence (PTS) [12], selected mapping (SLM) [11], and interleaving. These techniques achieve PAPR reduction possibly at serious expenses, such as signal transmission power increase, BER increase, data-rate loss, computational complexity increase, and exclusive requirement of Channel Side Information (CSI). No specific PAPR reduction technique is the best solution for all multicarrier transmission systems. Nonetheless, it should be carefully chosen according to various system requirements [5]. In section III, some basics about PAPR problem in OFDM is given. Section IV describes different PAPR reduction techniques which are using null subcarriers. Section V contains the conclusion. In this paper, null subcarriers are exposed to reduce the PAPR of OFDM system [9].

One of the design dimensions is to explore null subcarriers. A null subcarrier is also known as unused subcarrier without carrying transmit energy. The aim is to introduce an improved version of approach called 'Null-Switching' for PAPR reduction with low computational overhead [10]. In a nutshell, the null switching method is to interchange data-subcarriers with some innermost null subcarriers in the guard-band, in order to change the frequencies of some terms input to the IFFT operator. This switching null subcarriers scheme switches one or more null-carriers with to-

be-identified data-subcarriers. This changes the input to the IFFT operator, and thus the IFFT operator's output and its PAPR. The guard-bands of many multi-carrier standards (e.g. IEEE 802.11a's) have null-subcarriers in the transition-band of the transmit spectrum mask (i.e. the band-pass filter matched to the desired user's data-subcarriers). Hence, such a null-subcarrier frequency (now switched to carry data) can pass a good portion of any energy therein onto the receiver. For the above switching, the transmitter is to search for the data-subcarrier that (when switched with a null-subcarrier) would achieve the greatest PAPR reduction [1]. The new method of shifting null subcarriers among data subcarriers is characterized by better BER performance and very low computation complexity.

III. SOME BASICS ABOUT PAPR PROBLEM IN OFDM

OFDM signal exhibits a very high PAPR, which is due to the summation of sine waves and non-constant envelope. Therefore, RF power amplifiers have to be operated in a very large linear region [6]. Otherwise, the signal peaks get into non-linear region causing signal distortion. This signal distortion introduces inter modulation among the subcarriers and out-of-band radiation [7]. PAPR is a very important situation in the communication system because it has big effects on the transmitted signal. Low PAPR makes the transmit power amplifier works efficiently, on the other hand, the high PAPR makes the signal peaks move into the non-linear region of the RF power amplifier which reduces the efficiency of the RF power amplifier. In addition, high PAPR requires a high-resolution DAC at the transmitter, high-resolution analog to digital converter (ADC) at the receiver [7]. Any non-linearity in the signal will cause distortion such as inter-carrier interference (ICI) and inter symbol interference (ISI).

PAPR of OFDM signal is given by,

$$\begin{aligned} \text{PAPR} &= P_{\text{peak}}/P_{\text{avg}} = 10\log_{10} \\ &= \max[|x_n|^2]/E[|x_n|^2] \end{aligned} \quad (1)$$

Where, P_{peak} represents peak output power, P_{avg} means average output power. E denotes the expected value; x_n represents the transmitted OFDM signals. For an OFDM system with N subcarriers, the peak power of received signals is N times the average power when phase values are the same. The PAPR of baseband signal will reach its theoretical maximum at $(dB) = 10\log N$.

The Cumulative Distribution Function (CDF) is used to measure the efficiency of any PAPR reduction technique. Normally, the Complementary CDF (CCDF) is used instead of CDF, which helps us to measure the probability that the PAPR of a certain data block exceeds the given threshold [3]. By implementing the Central Limit Theorem for a Multicarrier signal with a large number of subcarriers, the real and imaginary part of the time domain signals have a mean of zero and a variance of 0.5 and thus follow a Gaussian distribution. So Rayleigh distribution is followed for the amplitude of the multicarrier signal, where as a central chi-square distribution with two degrees of freedom is followed for the power distribution of the system.

IV. PAPR REDUCTION USING NULL SUBCARRIERS

There are two techniques which reduces the PAPR value of OFDM system using null subcarriers. Those techniques are switching null subcarriers and shifting null subcarriers. Fig. 1 below explains the basic flow of those two methods.




Fig.1 OFDM Transceiver With Switching/Shifting Method For Null Subcarriers.

A. Full Version of Proposed Method

Consider OFDM transmission with L subcarriers at ascending frequencies set $\{fl, l = 1, \dots, L\}$, and indexed by $S = \{l = 1, \dots, L\}$. Of these, N where N less-equal L are null-subcarriers, with distinct indices drawn from the ascending set $N = \{gn, n =$

$1, \dots, N\} \subset S$. These N null-subcarriers respectively occupy the increasing frequencies $\{fgn, n = 1, \dots, N\}$, while the remaining $L-N$ subcarriers serve as data-subcarriers, with distinct indices from the ascending set $D = \{hd, d = 1, \dots, L - N\} \subset S$.

These $L-N$ data-subcarriers respectively occupy the increasing frequencies $\{fhd, d = 1, \dots, L-N\}$. Moreover, $N \cup D = S$, and $fgn \neq fhd, \forall n, d$. Assigned to the data-subcarriers at $\{fhd, 1 \leq d \leq L - N\}$ are, respectively, the M -ary data symbols $\{\bar{x}_d, d = 1, \dots, L - N\}$, taken from a quadrature amplitude modulation (QAM) or quadrature phase-shift keying (QPSK) constellation.

Without modifying L, N, D , the proposed method shifts P elements $\{\tilde{g}p, p = 1, \dots, P\}$ of the null-subcarrier set $N = \{gn, n = 1, \dots, N\}$ at the frequency $\{f\tilde{l}p, p = 1, \dots, P\}$ corresponding to P elements $\{\tilde{l}p, p = 1, \dots, P\}$ of the subcarrier set S , such that if $f\tilde{l}p < f\tilde{l}p+1$, then $f\tilde{g}p < f\tilde{g}p+1$. The transmitter is to search for the most advantageous frequencies for the P “innermost” null subcarrier(s) to shift to, for the greatest PAPR reduction. The optimization problem is to identify $\{f\tilde{l}p, p = 1, \dots, P\}$ to minimize the PAPR. There are altogether $\binom{L-N}{P} = \frac{(L-N)!}{P!(L-N-P)!}$ different “shifting” possibilities.

For the IEEE 802.11a/g standard, the number of null subcarriers as guard-bands at low-frequency end is one more than that at high-frequency edge, if P is even; the number of null-subcarriers as guard-bands at low-frequency end equals to that at high-frequency edge, if P is odd [1].

B. Simplified Version for Practical Implementation
Considering the practicability for implementation, the “Simplified” version, which degrades the computational load by applying the basic idea only to the subblock with the largest PAPR.

Specifically, the OFDM symbols \bar{x} are partitioned into V disjoint subblocks $\bar{x}^{(v)} \triangleq [\bar{x}_0^{(v)} \dots \bar{x}_{LV-1}^{(v)}]$ with $\bar{x}_k^{(v)} = \bar{x}d$ or $0, 0 \leq v \leq V - 1$, such that

$$\bar{x} = \sum_{v=0}^{V-1} \bar{x}^{(v)} \tag{2}$$

Only the subblock with the largest PAPR will undergo the basic scheme in “Full” version. Thus, the number of “shifting” possibilities is reduced significantly. With the increasing of V , the computational complexity is reduced dramatically [1].

V. CONCLUSIONS

The PAPR of OFDM system can be reduced by reordering the null-subcarriers and data-subcarriers.

These techniques switch/shifts the “innermost” null subcarriers among different data-subcarriers to minimize the PAPR. These techniques are CSI-free pre-processing algorithms, which can be compatible with most existing OFDM standards, and which can complement many other PAPR-reduction algorithms.

REFERENCES

- [1] Bo Wang, Pin-Han Ho, and Chih-Hao Lin, “OFDM PAPR Reduction by Shifting Null Subcarriers among Data Subcarriers” *IEEE Communications Letters*, Vol. 16, No. 9, pp.1377-1379, September 2012.
- [2] R. W. Chang, “Synthesis of band limited orthogonal signals for multichannel data transmission”, *Bell Syst. Tech J.*, Vol. 45, December 1996.
- [3] Salzberg B. R., “Performance of an efficient parallel data transmission system”, *IEEE transaction comm.*, Vol. COM-15, December 1967.
- [4] Weinstein, S.B. and P.M. Ebert, “Data transmission by Frequency Division Multiplexing using the DFT”, *IEEE Trans. Comm.*, Vol. COM-19, October 1971
- [5] Tao Jian, Yiyang Wu, “An Overview: Peak to Average Power Ratio Reduction Techniques for OFDM Signals”, *IEEE Transaction on broadcasting*, Vol.54, No. 2, June 2008.
- [6] Richard van Nee, Ramjee Prasad, “OFDM for wireless multimedia communications”, *Artech House Publication*, 2000.
- [7] H. Rohling et al., "OFDM Air Interface for the 4th Generation of Mobile Communication Systems," in *Proc. 6th International OFDM Workshop*, Hamburg, Germany, September 2000.
- [8] S. H. Han and J. H. Lee, “An overview of peak-to-average power ratio reduction techniques for multicarrier transmission,” *IEEE Wireless Commun.*, pp. 56–65, Apr. 2005.
- [9] X. Li, F. Y. Li, B. W. Ji, D. C. Yao, and Z. D. Zhong, “A low complex virtual sub-carrier reservation algorithm for PAPR reduction,” in *Proc. 2009 IEEE International Conference on Wireless Communications, Networking and Mobile Computing*, pp. 1366–1369.
- [10] K. T. Wong, B. Wang, and J. C. Chen, “OFDM PAPR reduction by switching null subcarriers and data-subcarriers,” *Electron. Lett.*, vol. 47, no. 1, pp. 62–63, Jan. 6, 2011.
- [11] A. D. S. Jayalath, C. Tellambura, and H. Wu, “Reduced complexity PTS and new phase sequences for SLM to reduce PAP of an OFDM signal,” in *Proc. 2000 IEEE Vehicular Technology Conference – Spring*, pp. 1914–1917.
- [12] T. Jiang, W. D. Xiang, P. C. Richardson, J. H. Guo, and G. X. Zhu, “PAPR reduction of OFDM signals using partial transmit sequences with low computational complexity,” *IEEE Trans. Broadcast.*, vol. 53, no. 3, pp. 719–724, Sep. 2007.