Algae based Biodiesel origination

Salim khan
Masters of technology (M.Tech), Department of Mechanical engineering Eklavya University, Damoh, M.P- 470661

Exploring new sources for biodiesel production, here are some potential areas of biodiesel feedstock origination that are gaining interest:

1. Algae-Based Biodiesel
•Why: Algae have high oil content, can grow in non-arable land, and have rapid growth rates.
•Focus: Microalgae strains, optimization of growing conditions, oil extraction methods, and cost-effectiveness.

KEY ASPECTS YOU CAN EXPLORE

1. Why Algae for Biodiesel?
•High Oil Yield: Certain algae species can contain up to 60% of their dry weight as oil, much higher than traditional crops.
•Non-Arable Land: Algae can grow in saline, wastewater, or non-arable land, avoiding competition with food crops.
•Rapid Growth: Algae have a fast growth cycle, allowing for continuous biomass production.
•Carbon Sequestration: Algae can absorb CO_2 during photosynthesis, potentially reducing greenhouse gases.

2. Types of Algae for Biodiesel:
•Microalgae: Single-celled organisms that grow in water and can produce high oil yields.
Examples: Chlorella vulgaris, Nannochloropsis, Botryococcus braunii.
•Microalgae (Seaweed): Larger algae species, although less oil-rich than microalgae, they can be used for biofuel production.

3. Key Focus Areas:
•Strain Selection: Researching algae species with high lipid content and suitable growth conditions.
•Cultivation Techniques:
Open Pond Systems: Cost-effective but vulnerable to contamination and low productivity.
Closed Photo bioreactors: Controlled systems that increase efficiency but are more expensive.
•Nutrient and Water Optimization: Algae can thrive in wastewater, potentially integrating with water treatment facilities, reducing both cost and environmental impact.
•Oil Extraction Techniques:
Mechanical Extraction: Pressing or using ultrasonication to release oil.
Chemical Extraction: Solvent extraction methods such as hexane or supercritical CO_2.
•Transesterification Process: The chemical process used to convert algal lipids into biodiesel.

4. Challenges in Algae-based Biodiesel:
•Cost: Current production methods are expensive compared to traditional fossil fuels and even other biodiesel sources.
•Scalability: Although promising in labs, scaling up algae cultivation and oil extraction for industrial purposes is challenging.
•Energy Inputs: Maintaining the necessary environmental conditions (light, nutrients, CO_2) requires significant energy, which can negate some environmental benefits.

5. Environmental and Economic Benefits:
•Wastewater Treatment: Algae can be used to clean wastewater by absorbing excess nutrients, making them dual-purpose for biodiesel production and environmental management.
•CO_2 Sequestration: Algae farming can be coupled with carbon capture initiatives, helping reduce emissions from industries.
•Sustainability: Algae don't require arable land or freshwater, making them a sustainable option compared to traditional biodiesel feedstock.

ENGINE PERFORMANCE OF ALGAE BASED BIODIESEL

The engine performance of algae-based biodiesel is a critical aspect of its viability as a fuel alternative. Here’s a detailed breakdown of how algae-based biodiesel impacts engine power, along with key factors and studies that can guide your thesis:

1. Engine Power Output:
•Power Comparison: Biodiesel typically produces slightly lower engine power compared to conventional

diesel because of its lower energy content (calorific value). Algae-based biodiesel is no exception, though the difference in power output can vary based on:
The specific algae strain used.
The quality of the Transesterification process (which converts algae oil to biodiesel).
•B20 and B100 Blends:
oB20 (20% biodiesel, 80% diesel): Typically results in a marginal reduction (1-2%) in engine power compared to pure diesel.
oB100 (100% biodiesel): May lead to a 5-10% reduction in power due to its lower energy content.

2. Factors Influencing Engine Power:
•Energy Content (Calorific Value): Algae biodiesel tends to have a lower energy density than diesel. The energy content of algae biodiesel is around 37-40 MJ/kg, compared to 42-45 MJ/kg for petroleum diesel. This affects the total power output of the engine.
•Combustion Properties: Biodiesel has a higher oxygen content, which can improve combustion efficiency. This can lead to better torque and power recovery despite the lower energy content.
•Cetane Number: Algae biodiesel has a higher cetane number (50-58) than petroleum diesel (~45), meaning it ignites faster and combusts more completely, potentially mitigating power loss in some cases.

3. Engine Efficiency and Performance:
•Torque: While there is often a slight reduction in torque when running algae biodiesel, it remains within acceptable limits for most engines. Some studies report a minor increase in torque at certain engine speeds due to better combustion properties.
•Brake-Specific Fuel Consumption (BSFC): Algae biodiesel engines generally show higher BSFC, meaning more fuel is consumed to maintain the same power output. This is mainly due to the lower energy content of biodiesel. Increases in BSFC are typically 5-10% for B100 algae biodiesel compared to diesel.
•Engine Emissions: Algae biodiesel generally improves emissions, which may offset power losses:
Lower CO and HC Emissions: Algae biodiesel contains oxygen, leading to more complete combustion and lower carbon monoxide (CO) and hydrocarbon (HC) emissions.
NOx Emissions: However, biodiesel can lead to a slight increase in nitrogen oxides (NOx) due to higher combustion temperatures.

4. Performance in Diesel Engines:
•Fuel Injection and Timing: Adjustments to fuel injection timing and pressure may help recover some of the power lost with algae biodiesel. Modern diesel engines with common rail injection systems can be tuned to optimize the combustion of biodiesel blends.
•Cold Flow Properties: Algae biodiesel may suffer from poor cold flow properties, which can affect starting and performance at low temperatures. Additives or blending with regular diesel (e.g., B20) can help mitigate this issue.

5. Improving Engine Power with Algae Biodiesel:
•Blending: Using algae biodiesel in blends (e.g., B20) helps maintain engine power closer to conventional diesel while still reaping environmental benefits.
•Engine Tuning: Optimizing injection timing and air-fuel ratios for biodiesel combustion can help maintain power levels.
•Additives: Adding fuel additives to improve the energy content, lubricity, and combustion characteristics of algae biodiesel can lead to improved engine performance.

B20 and B100 Blends in Algae Based Biodiesel

In the context of algae-based biodiesel, B20 and B100 refer to the proportion of biodiesel in a blend with conventional petroleum diesel:
1. B20: This is a blend containing 20% biodiesel and 80% petroleum diesel. It is often favored for its balance between utilizing renewable fuel and maintaining compatibility with most diesel engines. The use of B20 can reduce harmful emissions like carbon monoxide, particulate matter, and hydrocarbons while still providing reliable performance similar to traditional diesel.

2. B100: This refers to 100% biodiesel, meaning it contains no petroleum diesel. It represents the most sustainable option in terms of renewable fuel use and significantly reduces greenhouse gas emissions, especially CO_2, when compared to regular diesel. However, B100 can have some challenges:
Cold weather performance: Pure biodiesel can gel in cold temperatures, making it less suitable for certain climates.
Material compatibility: B100 may affect rubber components or seals in older engines not designed for biodiesel.
Oxidation and storage: B100 can be more prone to oxidation and may have shorter shelf life due to the presence of unsaturated fatty acids.

Algae-Based Biodiesel

Algae are considered an excellent feedstock for biodiesel production due to their high lipid content, fast growth rate, and ability to be cultivated on non-arable land. When algae oils are used for producing biodiesel blends (B20, B100), the benefits of algae include:

•High yield: Algae can produce more oil per acre compared to terrestrial crops like soybeans or palm.

•CO_2 absorption: Algae can be grown using CO_2 emissions from industrial sources, thus acting as a carbon sink.

•Non-competition with food crops: Since algae can be grown in non-arable lands, they do not compete with food crops for land or water resources.

While B100 from algae offers the most significant environmental benefits, B20 provides a practical balance between environmental performance and compatibility with existing diesel engines. Both blends, when derived from algae, can contribute to reducing the carbon footprint and enhancing fuel sustainability.

PERFORMANCE METRICS OF ALGAE-BASED BIODIESEL

The performance metrics of algae-based biodiesel, particularly in blends like B20 and B100, are typically evaluated based on several parameters, including fuel efficiency, engine performance, emissions, and combustion characteristics. Here are some key metrics commonly assessed:

1. Fuel Properties

•Cetane Number: This indicates the ignition quality of the fuel. Algae-based biodiesel typically has a higher cetane number (50–60) compared to petroleum diesel (around 40–50), resulting in better ignition and smoother engine operation.

•Energy Content (Calorific Value): Biodiesel, including algae-based, generally has about 8-10% lower energy content than conventional diesel. This translates to slightly lower fuel efficiency, though the difference is minimal in B20 blends but more noticeable in B100.

•Viscosity: Algae biodiesel generally has a higher viscosity compared to petroleum diesel. This can affect fuel atomization and combustion but is manageable in B20 blends. B100 may require engine modifications in certain cases.

2. Engine Performance

•Brake Specific Fuel Consumption (BSFC): This measures how much fuel is consumed per unit of power produced. B100 tends to have higher BSFC due to its lower energy density. B20 blends typically show minimal changes compared to conventional diesel.

•Engine Power and Torque: In blends like B20, engine power and torque are comparable to conventional diesel. However, in B100, a slight decrease in power and torque can be observed, attributed to the lower energy content.

•Brake Thermal Efficiency (BTE): Algae-based biodiesel usually demonstrates slightly lower thermal efficiency compared to petroleum diesel. B20 shows minimal differences, while B100 can show a small drop in efficiency due to combustion characteristics.

3. Emissions

•Carbon Dioxide (CO_2): Algae-based biodiesel emits significantly less CO_2 across the lifecycle compared to petroleum diesel. B100 reduces CO_2 emissions by up to 78%, whereas B20 provides a 15–20% reduction.

•Particulate Matter (PM): Both B20 and B100 blends reduce PM emissions, with B100 showing up to 47% reductions in some cases.

•Nitrogen Oxides (NOx): One of the trade-offs of biodiesel, including algae biodiesel, is a slight increase in NOx emissions, particularly at higher blends like B100. This is because of the oxygen content in biodiesel, which promotes higher combustion temperatures.

•Hydrocarbons (HC) and Carbon Monoxide (CO): Biodiesel blends, especially B100, reduce HC and CO emissions significantly, with reductions up to 50% or more in B100 and noticeable reductions even in B20.

4. Combustion Characteristics

•Ignition Delay: Due to the higher cetane number, the ignition delay (time between injection and combustion) for algae-based biodiesel is shorter, promoting a more efficient combustion process.

•Exhaust Gas Temperature: Typically, exhaust gas temperatures are slightly higher in biodiesel engines due to higher oxygen content in the fuel, which leads to more complete combustion.

•Heat Release Rate: The heat release pattern is smoother for algae-based biodiesel, which can result in a reduction in engine noise and vibration, particularly with B20 blends.

5. Cold Flow Properties

•Cloud Point and Pour Point: Algae-based biodiesel can have relatively poor cold flow properties, especially in B100. Cloud and pour points (the temperatures at which the fuel starts to gel or become solid) are higher than conventional diesel, limiting its use in cold climates without additives or blending with petro-diesel (as in B20).

6. Oxidation Stability
•Storage Stability: Algae biodiesel, especially B100, is prone to oxidation during long-term storage, which can affect its quality and performance. Antioxidants or blending with diesel can mitigate this effect in B20.

7. Lubricity
•Engine Wear: Algae-based biodiesel, like other biodiesel, provides better lubricity compared to petroleum diesel, reducing engine wear and extending engine life, even in lower blends like B20.
Summary of Blend-Specific Performance:
•B20: Offers a good balance of performance and environmental benefits, with minimal impact on power, fuel efficiency, and emissions. Suitable for use in standard diesel engines without modifications.
•B100: Provides maximum environmental benefits, but requires careful management of cold flow properties, slightly reduced power output, and possible engine modifications. Best suited for controlled environments or warmer climates.

PRODUCTION METHOD OF ALGAE BASED BIODIESEL

The production of algae-based biodiesel involves several steps, including the cultivation of algae, harvesting, oil extraction, and conversion of the extracted oil into biodiesel. Here's an overview of the process:

1. Algae Cultivation
Open Ponds: These are shallow, open-air ponds where algae can grow naturally using sunlight, carbon dioxide, and nutrients. Though cost-effective, they are more prone to contamination and have lower yields.

Photo bioreactors (PBRs): These closed systems provide a controlled environment with optimized light, CO_2, and nutrients, leading to higher productivity and less contamination. They can be made from glass tubes, plastic bags, or other transparent containers.

Wastewater Treatment Plants: Algae can also be grown using wastewater, which provides essential nutrients. This method also doubles as a water treatment process.
2. Harvesting the Algae
After cultivation, the algae biomass needs to be harvested, typically using processes like flocculation, centrifugation, or filtration. Harvesting can be a challenge due to the small size of the algae cells and the large amounts of water involved in their cultivation.

3. Oil Extraction
Algae are rich in lipids (fats), which are needed for biodiesel production. Extraction of these lipids is a critical step:
Mechanical Extraction: Methods like expeller press or ultrasonic-assisted extraction can be used to physically break open the algae cells and release the oil.
Solvent Extraction: Solvents like hexane are often used to dissolve and extract the oil from the algae biomass.
Supercritical Fluid Extraction: This is a more advanced method using supercritical CO_2 as a solvent, which provides higher extraction efficiency but is more expensive.
Wet Extraction: This allows oil extraction without the need to dry the algae first, which can save energy.

4. Transesterification (Conversion to Biodiesel)
The extracted oil is then converted to biodiesel through a chemical process called Transesterification. This involves reacting the algae oil with an alcohol (usually methanol) in the presence of a catalyst (commonly sodium or potassium hydroxide).
The result is fatty acid methyl esters (FAMEs), which are the chemical compounds that make up biodiesel, and glycerol as a by-product.

5. Purification
The biodiesel produced must be purified to remove any remaining impurities such as alcohol, glycerol, and catalyst residues.
This step ensures that the biodiesel meets quality standards for use as fuel.