Efficient Controlling of Climate Parameters Using ESP32

Dr.G.Aparna[1], Nivas Reddy[2], Sai Ram[3], Shirly[4], and Rishik Reddy[5]
[1]*Associate Professor, Hyderabad institute of technology and management, Medchal, Telangana*
[2,3,4,5] *UG student, Hyderabad institute of technology and management, Medchal, Telangana*

***Abstract*—This paper presents an ESP32-based climate control system designed to regulate temperature, humidity, and light for climate-sensitive environments. Leveraging the ESP32's processing power and integration with the Blynk app, the system allows real-time monitoring and control through IoT. By using various sensors, the system maintains optimal climate conditions efficiently, with experimental results showing high accuracy and low power consumption. This scalable, costeffective approach demonstrates the ESP32's potential in automated climate control, with future enhancements planned for predictive management and advanced data analytics.**

***Index Terms*—ESP32,Climate control system, Internet of Things(IOT),Temperature Regulation, Blynk App, Environmental Sensors**

I. INTRODUCTION

Climate control is crucial in various fields, including agriculture, industrial processing, laboratories, and indoor environments, where precise management of temperature and humidity is required to maintain optimal conditions. Traditional climate control systems are often complex, costly, and difficult to integrate with modern IoT platforms. With the rise of affordable, high-performance microcontrollers, like the ESP32, it has become feasible to design efficient, low-cost solutions for climate management that can be controlled and monitored remotely.

This paper presents the development of a climate control system using the ESP32 microcontroller, which is well-suited for Internet of Things (IoT) applications due to its built-in Wi-Fi and Bluetooth capabilities, low power consumption, and ease of programming. By integrating the ESP32 with the Blynk app, users can monitor and adjust climate parameters in real time from a mobile device, enhancing the convenience and accessibility of climate management.

The proposed system uses sensors to monitor temperature and humidity levels, and actuates a heater and humidifier via a relay module based on preset thresholds. The integration of an OLED display allows for immediate, on-site feedback on climate parameters, while push buttons provide manual control options for key functions. This setup offers a scalable, adaptable solution for environments where continuous climate control is essential.

The following sections of this paper will cover the system's design, implementation, and testing results. Our findings demonstrate that the ESP32-based climate control system is both efficient and reliable, with potential applications in various climatesensitive settings. Future work aims to enhance the system with predictive algorithms and more advanced data analysis capabilities to further improve its responsiveness and adaptability.

II. LITERATURE SURVEY

Climate control systems are crucial in various fields, including agriculture and industrial processing, where maintaining precise environmental conditions can enhance productivity and efficiency. Traditional climate control solutions are often complex and costly, making them challenging to implement in smaller-scale or remote settings. Recent advances in IoT technology have introduced new possibilities, with microcontrollers like the ESP32 offering lowcost, flexible options for real-time monitoring and control.

The ESP32 microcontroller, with built-in Wi-Fi and Bluetooth, has gained attention for IoT applications due to its reliability and cost-effectiveness. Research by Kumar et al. (2021) demonstrated an ESP32-based system for greenhouse monitoring, which effectively controlled temperature and humidity to improve crop health. Patel and Sharma (2020) further explored integrating ESP32 with the Blynk app, enabling remote climate management via mobile devices. These studies underscore the potential of ESP32 for efficient, scalable, and accessible climate control,

particularly in settings where real-time adjustments are crucial.

However, limitations remain in achieving high accuracy and predictive management with microcontroller-based systems. Processing power constraints on the ESP32, for example, can limit complex data analysis capabilities. Building on previous research, this project seeks to develop an ESP32-based climate control system with DHT11 sensors, an OLED display, and relay-controlled actuators, managed via the Blynk app. This study aims to enhance existing models by providing a reliable, power-efficient, and adaptable solution for climate-sensitive environments.

III. METHODOLOGY

This climate control system is built around the ESP32 microcontroller, which functions as the central processor for data collection, monitoring, and control. The system includes a DHT11 sensor to gather realtime temperature and humidity data, essential for maintaining the desired environmental conditions. An OLED display is connected to the ESP32 to show live temperature and humidity readings, allowing users to monitor conditions on-site. To regulate climate parameters, a 2-channel relay module is incorporated, enabling the system to control a heater and a humidifier based on preset threshold values.

The ESP32 continuously reads data from the DHT11 sensor. When temperature or humidity levels fall outside the target range, the microcontroller activates or deactivates the heater and humidifier via the relay module to restore optimal conditions. Additionally, push buttons are included to allow users manual control over the heater and humidifier as well as the ability to switch between different operating modes, such as automatic and manual.

For remote monitoring and control, the ESP32 is integrated with the Blynk IoT platform. Through the Blynk app, users can access real-time data, receive notifications, and control devices from their mobile devices. This integration allows users to manage the climate control system remotely, enhancing convenience and accessibility. The complete system architecture, including component connections, is illustrated in the circuit diagram (Figure X). This setup provides an affordable, scalable, and effective solution for climate regulation in environments that require precise control.

IV. IMPLEMENTATION

The implementation of this climate control system involves setting up the hardware components, programming the ESP32 microcontroller, and configuring the Blynk IoT platform for remote monitoring and control.

Hardware Setup:

The hardware setup begins with connecting the DHT11 temperature and humidity sensor to the ESP32 microcontroller to monitor environmental conditions. The DHT11 sensor's data pin is connected to a GPIO pin on the ESP32, which reads the sensor data in real time. An OLED display is then wired to the ESP32 via the I2C interface, allowing it to display current temperature and humidity readings locally.

A 2-channel relay module is integrated with the ESP32 to control external devices such as a heater and a humidifier. The relay module is connected to GPIO pins on the ESP32, enabling the system to switch these devices on and off as needed. Additionally, push buttons are connected to the ESP32 to allow manual control, letting the user turn on the heater or humidifier or switch between automatic and manual operation modes.

ESP32 Programming:

The ESP32 is programmed using the Arduino IDE, which provides libraries for both the DHT11 sensor and the OLED display. The program initializes the sensor and display, continuously reads data from the sensor, and displays it on the OLED screen. The code also includes logic to compare sensor readings with predefined threshold values. When temperature or humidity deviates from the set range, the ESP32 activates the appropriate relay to control the heater or humidifier.

In addition to environmental control, the code includes functions for manual operation through push buttons. A button press toggles between different modes, allowing users to override automatic settings when desired.

Integration with Blynk:

For remote monitoring and control, the ESP32 connects to the Blynk IoT platform via Wi-Fi. The Blynk app is configured to display real-time

temperature and humidity data from the DHT11 sensor. Virtual buttons within the Blynk app are set up to allow users to remotely turn the heater or humidifier on and off or adjust threshold values for automatic control. The ESP32 program uses the Blynk library, enabling it to communicate with the Blynk app and sync data continuously.

Users can access the Blynk app from any device with internet access, allowing them to monitor climate conditions and control the system remotely. This remote access provides convenience and ensures that the environment remains within optimal conditions, even when the user is not on-site.

V. HARDWARE COMPONENTS

A. ESP32 MODULE

The ESP32 is a powerful microcontroller with integrated Wi-Fi and Bluetooth capabilities, making it an ideal choice for Internet of Things (IoT) projects. Developed by Espressif Systems, the ESP32 is widely popular for applications requiring reliable wireless connectivity, energy efficiency, and robust performance.

B. DHT11 SENSOR



The DHT11 sensor is a popular digital sensor for measuring temperature and humidity. Known for its affordability and ease of use, it's widely used in DIY electronics projects, environmental monitoring systems, and home automation

C. 5V TWO CHANNEL RELAY

A 5V channel relay is an electrically operated switch used to control high-power devices (like lights, fans, motors, heaters, etc.) with a low-power control signal, typically from a microcontroller such as an Arduino, ESP32, or Raspberry Pi. Relays allow small electronic circuits to control larger electrical loads, making them essential in many IoT, home automation, and embedded systems projects.

D. MIST MAKER(HUMIDIFIER)



The mist maker module, or ultrasonic humidifier, is used in the climate chamber to control and increase the humidity levels. It's a crucial component when specific humidity levels are needed, such as for plant growth, material testing, or other environmental simulations.

E. 220V100W HALOGEN BULB

F. 0.96" I2C OLED DISPLAY

VI. RESULT

The ESP32-based climate control system effectively maintained temperature and humidity within the target range during testing, showing prompt responsiveness to changes in environmental conditions. When temperature or humidity levels strayed from preset thresholds, the ESP32 quickly activated the appropriate relay, controlling the heater or humidifier to restore optimal conditions. The DHT11 sensor provided accurate readings that were consistent with the values displayed on both the OLED screen and the Blynk app, ensuring reliable real-time monitoring.

The integration with the Blynk app enabled seamless remote access, allowing users to view live data and adjust settings with minimal delay. This remote control functionality was further enhanced by timely notifications from the Blynk app when significant deviations occurred. The system also demonstrated energy efficiency, thanks to the ESP32's low power consumption and the intermittent operation of the heater and humidifier. Overall, the results indicate that this system is reliable, efficient, and suitable for climate-sensitive applications across various fields, such as agriculture and industrial environments.

VII. CONCLUSION

This project successfully developed a low-cost, efficient climate control system using the ESP32 microcontroller, designed for applications requiring precise temperature and humidity management. By integrating a DHT11 sensor, an OLED display, and a relay-controlled heater and humidifier, the system maintains environmental conditions effectively and accurately. The incorporation of the Blynk IoT platform allows users to remotely monitor and control the system, enhancing accessibility and convenience, especially in remote or off-site scenarios.

Testing demonstrated the system's quick responsiveness and reliability, with consistent sensor accuracy and seamless remote control via the Blynk app. Additionally, the ESP32's low power consumption and the relay-based operation of climate-control devices contribute to the system's energy efficiency, making it suitable for prolonged use.

Overall, this project highlights the potential of IoTbased climate control systems in diverse fields, such as agriculture, laboratories, and industrial settings. Future enhancements could include integrating predictive algorithms and more advanced sensors to further improve accuracy and adaptability, advancing this system as a versatile tool for climate-sensitive environments.

REFERENCES

[1] Kumar, R., Gupta, S., & Singh, P. (2021). IoT-Based Greenhouse Monitoring and Climate Control Using ESP32 and Sensors. International Journal of Agricultural Engineering, 12(2), 45-53.

[2] Patel, A., & Sharma, M. (2020). Integrating Blynk with ESP32 for Remote Environmental Control Systems. Journal of Internet of Things and Smart Technology, 8(4), 312-318.

[3] Parvez, A. H., & Rahman, M. (2019). RealTime IoT-based Climate Monitoring System using DHT11 and ESP32. Journal of Computer and Electronics Engineering, 6(1), 22-30.
[4] Smith, J., & Lee, T. (2018). Designing Low-Power IoT Systems with ESP32: Applications in Agriculture and Environmental Control. Journal of Low Power Electronics and Applications, 8(3), 142-155.
[5] Arduino. (n.d.). ESP32 with DHT11 Temperature and Humidity Sensor. Arduino Tutorials. Retrieved from https://www.arduino.cc/en/Tutorial
[6] Blynk. (n.d.). Blynk IoT Platform Documentation. Retrieved from https://blynk.io/docs
[7] Brown, D. (2022). Smart Environmental Monitoring: Leveraging Microcontrollers and IoT Platforms. IoT Applications Journal, 5(2), 89-102.
[8] Shen, Q., & Wang, L. (2019). Improving Efficiency of Climate Control Systems with IoT Technology in Industrial Environments. IEEE Transactions on Industrial Informatics, 15(8), 4457-4464.