Homeautomation Using Ardino Uno And Blutooth Module 06

Vivek V. Patil[1], Jitendra. A. Gaikwad[2]
[1,2] *Dept. of instrumentation &control engg. Vishwakarma Institute ofTechnology* Pune, India

Abstract: This project focuses on designing and implementing a smart home automation system using an Arduino Uno microcontroller and an HC-06 Bluetooth module. The aim is to enable users to control various household appliances remotely using a smartphone. The system provides a cost-effective, user-friendly, and wireless solution, eliminating the need for complex wiring and installation. Integrating the HC-06 Bluetooth module with Arduino Uno, the project facilitates communication between the smartphone and the microcontroller via Bluetooth. Commands sent from a mobile application are processed by the Arduino, which then controls connected appliances like lights, fans, or other devices through relays. The system supports basic automation tasks such as turning devices on/off and scheduling operations. It also ensures flexibility, as additional sensors or components can be integrated to expand its functionality. This solution promotes convenience, energy efficiency, and enhances the quality of life by providing smart control over home appliances with minimal infrastructure changes. The project serves as a practical demonstration of IoT principles and highlights how inexpensive hardware components can be leveraged to build reliable automation systems.

Keywords: Home automation, Arduino Uno, Bluetooth module HC-06, Wireless control, IoT, Smart home system, Mobile app control, Energy, Relay control

1. INTRODUCTION

Nowadays, we have remote controls for our television sets and other electronic systems, which have made our lives real easy. Have you ever wondered about home automation which would give the facility of controlling tube lights, fans and other electrical appliances at home using a remote control? Off-course, Yes! But, are the available options cost-effective? If the answer is No, we have found a solution to it. We have come up with a new system called Arduino based home automation using Bluetooth. This system is super-cost effective and can give the user, the ability to control any electronic device without even spending for a remote control. This project helps the user to control all the electronic devices using his/her smartphone. Time is a very valuable thing. Everybody wants to save time as much as they can. New technologies are being introduced to save our time. To save people's time we are introducing Home Automation system using Bluetooth. With the help of this system you can control your home appliances from your mobile phone. You can turn on/off your home appliances within the range of Bluetooth.

2. LITERTURE SURVEY

Home automation has grown significantly due to advancements in microcontroller technology, wireless communication, and the Internet of Things (IoT). Arduino Uno and Bluetooth communication are popular for home automation due to their low cost, open-source hardware, and ease of use. Arduino Uno is ideal for real-time control and modular architectures, while Bluetooth provides a reliable and affordable wireless medium for local control of home appliances. Bluetooth-based systems are effective for small-scale environments and offer quick response times. While Wi-Fi offers a broader range and internet-based control, Bluetooth tendrasystems are preferred for simpler applications. Bluetooth home automation has applications in controlling lighting, fans, door locks, and security alarms.

3. EXISTING SYSTEM

Several existing systems have been implemented using the Arduino Uno microcontroller in combination with the HC-06 Bluetooth module for home automation. These systems provide basic control of household appliances, such as lights, fans, and other electrical devices, using smartphone-based Bluetooth communication. Here are some key aspects and challenges of the existing systems

4. REQUIRED COMPONENTS

4.1 ARDUINO UNO- Arduino is an open source computer hardware and software company, project, and user community that designs and manufactures

single-board microcontrollers and microcontroller kits for building digital devices and interactive objects that can sense and control objects in the physical and digital world. The project's products are distributed as open-source hardware and software, which are licensed under the GNU Lesser General Public License (LGPL) or the GNU General Public License (GPL), permitting the manufacture of Arduino boards and software distribution by anyone. Arduino boards are available commercially in preassembled form, or as do-it-yourself (DIY) kits. Arduino board designs use a variety of microprocessors and controllers. The boards are equipped with sets of digital and analog input/output (I/O) pins that may be interfaced to various expansion boards or Breadboards (shields) and other circuits. The boards feature serial communications interfaces, including Universal Serial Bus (USB) on some models, which are also used for loading programs from personal computers. The microcontrollers are typically programmed using a dialect of features from the programming languages C and C++. In addition to using traditional compiler toolchains, the Arduino project provides an integrated development environment (IDE) based on the Processing language project. The Arduino project started in 2003 as a progin for students at the Interaction Design Institute Ivrea in Ivrea, Italy,aim to provide a low- cost and easy way for novices and professionals to create devices that interact with their environment using sensors and actuators. Common examples of such devices intended for beginner hobbyists include simple robots, thermostats, and motion detectors.

The name Arduino comes from a bar in Ivrea, Italy, where some of the founders of the project used to meet. The bar was named after Arduin of Ivrea, who was the margrave of the March of Ivrea and King of Italy from 1002 to 1014.

Fig. Arduino Uno

4.2 REALY- A relay is an electrically operated switch used to control circuits by a separate low-power signal or multiple circuits. They were first used in long-distance telegraph circuits as amplifiers, telephone exchanges, and early computers for logical operations. Solid-state relays control power circuits without moving parts, using semiconductor devices for switching. Magnetic latching relays require one pulse of coil power to move contacts in one direction and another redirected pulse to move them back. They can have single or dual coils, with single coils operating in one direction and resetting when polarity is reversed. AC controlled magnetic latch relays have single coils with steering diodes for differentiating between operate and reset commands. The Arduino Relay module allows a wide range of microcontrollers with digital outputs to control larger loads and devices like AC or DC motors, electromagnets, solenoids, and incandescent light bulbs.



Fig. 4 Channel Relay Module

4.3 HC-06 BLUETOOTH MODULE - The HC-06 Bluetooth module is a popular, low-cost Bluetooth serial transceiver module commonly used in DIY electronics, Arduino, and other microcontroller projects for wireless communication. It operates on Bluetooth Version 2.0 and provides a simple and reliable way to communicate wirelessly via UART (Universal Asynchronous Receiver Transmitter) interface.

Key Features:

- Bluetooth Version: 2.0 + EDR (Enhanced Data Rate)
- Communication: Serial/UART (Tx and Rx pins)
- Default Baud Rate: 9600 bps (adjustable between 1200 to 115200 bps)
- Operating Voltage: 3.3V (but compatible with 5V systems using level shifters)
- Range: 10 meters (in open space)
- Modes: Only operates in Slave mode (unlike the HC-05, which can switch between Master and

Slave modes)
- Default Settings:
  - Device Name: HC-06
  - PIN: 1234 or 0000
  - Baud Rate: 9600
- Supported Profiles: Serial Port Profile (SPP)
- Operating Current: ~30mA

Pinout:

1. VCC: Power supply (3.6–6V, though 3.3V is recommended)
2. GND: Ground
3. TXD: Transmit data (3.3V logic, should be voltage-divided if connected to 5V systems)
4. RXD: Receive data (3.3V logic)

Fig. Blutooth Module

5.CIRCUIT DIAGRAM



Fig. Circuit Diagram

6.FUTURE SCOPE

Existing home automation systems using Arduino Uno and the HC-06 Bluetooth module can be improved to meet future needs. These include integration with IoT platforms, improved automation with sensors, enhanced security features, scalability and expandability, energy management and scheduling, mobile app enhancements, Bluetooth 5.0 adoption, and renewable energy integration. Hybrid systems can enable remote control via Wi-Fi or GSM modules, while cloud connectivity can be achieved through IoT platforms like Blynk or MQTT. Sensors can be added for environmental conditions, motion detection, and power monitoring. Security features can be enhanced through two-factor authentication, encrypted communication, and biometric access. Modular design allows easy integration of additional devices, and multi-controller networks can cover larger areas. Bluetooth 5.0 can offer extended range, lower energy consumption, and mesh networking for wider area coverage.

7.ADVANTAGES

Cost-Effective: Utilizes affordable components like the Arduino UNO, HC-06, and relay modules, making it a budget-friendly solution for home automation.

Ease of Use: Simple command-based control using a Bluetooth Terminal App, requiring minimal technical knowledge to operate.

Wireless Control: Eliminates the need for physical switches, allowing appliances to be controlled remotely within the Bluetooth range (~10 meters).

Customizable: Easily scalable to control more appliances or include additional features such as sensors, timers, or smartphone app integration.

Energy Efficiency: Helps conserve energy by enabling users to turn off appliances remotely when not in use.

8. CODE

```
include <SoftwareSerial.h>

// Define the pins for the relay module

const int relay1 = 2;

const int relay2 = 3;

const int relay3 = 4;

const int relay4 = 5;

// Define the pins for the Bluetooth module

const int bluetoothTx = 10; // Changed to pin 10

const int bluetoothRx = 11; // Changed to pin 11

// Create a SoftwareSerial object for the Bluetooth module

SoftwareSerial bluetooth(bluetoothTx, bluetoothRx);

void setup() {

// Initialize the relay pins as outputs

pinMode(relay1, OUTPUT);

pinMode(relay2, OUTPUT);
```

```
pinMode(relay3, OUTPUT);
pinMode(relay4, OUTPUT);
// Initialize the Bluetooth module
bluetooth.begin(9600);

// Initialize the serial monitor
Serial.begin(9600);
}
void loop() {
// Check if there is incoming data from the Bluetooth module
if (bluetooth.available() > 0) {
char command = bluetooth.read();
// Turn on/off the relays based on the received command
switch (command) {
case 'a':
digitalWrite(relay1, HIGH);
Serial.println("Relay 1 ON");
break;
case 'b':
digitalWrite(relay1, LOW);
Serial.println("Relay 1 OFF");
break;
case 'c':
digitalWrite(relay2, HIGH);
Serial.println("Relay 2 ON");
break;
case 'd':
digitalWrite(relay2, LOW);
Serial.println("Relay 2 OFF");
break;
case 'e':
digitalWrite(relay3, HIGH);
Serial.println("Relay 3 ON");
break;
case 'f':
digitalWrite(relay3, LOW);
Serial.println("Relay 3 OFF");
break;
case 'g':
digitalWrite(relay4, HIGH);
Serial.println("Relay 4 ON");
break;
case 'h':
digitalWrite(relay4, LOW);
```

9. CONCLUSION

This project demonstrates a basic yet effective home automation system using an Arduino UNO, HC-06 Bluetooth Module, 4-Channel Relay Module, and a Bluetooth Terminal App. It allows wireless control of home appliances through simple commands sent from a smartphone.

The system is easy to implement, cost-effective, and highly customizable, making it an excellent choice for beginners in electronics and DIY automation. It provides a practical example of integrating wireless communication and relay control to automate appliances.

While the setup is functional, it has limitations like a short Bluetooth range and basic user interaction. These can be addressed in future iterations by incorporating Wi-Fi for broader connectivity or adding sensors for smarter, autonomous operation.

Overall, this project lays the foundation for exploring more advanced smart home technologies and provides valuable insights into how microcontrollers and wireless modules can enhance convenience in daily life.

10. REFFERENCE

[1] Wikipedia
[2] Wireless Sensor Networks: Concepts, Applications, Experimentation and Analysis. 2016. p. 108. ISBN 9811004129. The use of standardized, with open standards over proprietary protocols provides the industry with the freedom to choose between suppliers with guaranteed interoperability. Standardized solutions usually have a much longer lifespan than proprietary solutions.

[3] Jump up^ "Research and Markets: Global Home Automation and Control Market 2014-2020 - Lighting Control, Security & Access Control, HVAC Control Analysis of the $5.77 Billion Industry". Reuters. 2015-01-19. Archived from the original on 2016-05-05.

[4] Home Automation & Wiring (1 ed.). New York: McGraw Hill/TAB Electronics. 1999-03- 31. ISBN 9780070246744.