Resonance Frequency Identification and Dynamic Behavior Analysis of Single-Stage Gearbox: A Finite Element Analysis and suggestions for optimization

Rajkumar Bhagat[1], Mukta Rasal[2], Vikas Sanap[3], Durgesh Sandhan[4], Aditya Saravade[5], Kushal Shah[6]
[1,2,3,4,5,6] *Department of Mechanical Engineering Vishwakarma Institute of Technology, Pune- 411037.*

Abstract: ***This research paper investigates the dynamic behavior and optimization of a single-stage gearbox system through finite element analysis (FEA). The study focuses on understanding the structural response, natural frequencies, mode shapes, and dynamic characteristics of the gearbox assembly under various operating conditions. Modal analysis and harmonic response analysis techniques are employed to analyze the gearbox's performance, identify critical frequencies, and optimize its design to enhance reliability and efficiency.***

1. INTRODUCTION

Gearbox systems are fundamental components in various mechanical applications, facilitating speed reduction, torque multiplication, and power transmission. These systems play a pivotal role in a wide range of industries, including automotive, aerospace, marine, and industrial machinery. By efficiently converting rotational motion between input and output shafts, gearboxes enable machines to operate at desired speeds and torque levels, thereby enhancing overall performance and productivity.

Understanding the dynamic behaviour of gearbox assemblies is paramount for ensuring their reliable operation and longevity. Dynamic analysis helps engineers identify potential issues such as resonance, excessive vibration, and fatigue failure, which can compromise the performance and durability of the system. By comprehensively analyzing the dynamic response of gearbox components, engineers can optimize their design to mitigate risks and improve operational efficiency.

This paper presents a comprehensive investigation into the dynamics and optimization of a single-stage gearbox system using advanced finite element analysis (FEA) techniques. Finite element analysis is a powerful computational tool that enables engineers to simulate the behavior of complex mechanical systems under various loading conditions. By developing detailed 3D models of gearbox assemblies and applying sophisticated analysis methods, engineers can gain valuable insights into the structural integrity, natural frequencies, mode shapes, and dynamic characteristics of the system.

Through modal analysis, engineers can identify the natural frequencies at which the gearbox assembly vibrates and determine the corresponding mode shapes and deformations. This information is critical for understanding the system's dynamic response and identifying potential resonance frequencies that may lead to excessive vibration and fatigue failure. Harmonic response analysis complements modal analysis by studying the gearbox's response to harmonic excitation, such as gearmesh frequencies. By simulating the gearbox's dynamic behavior under operating conditions, engineers can assess vibration levels, stress distributions, and fatigue life, allowing for optimization of the gearbox design to enhance reliability and efficiency.

In summary, this paper aims to contribute to the body of knowledge on gearbox dynamics and optimization by leveraging advanced FEA techniques. By gaining a deeper understanding of the dynamic behavior of single-stage gearbox systems, engineers can develop more robust and efficient designs that meet the performance requirements of various mechanical applications.

2. LITERATURE REVIEW

1. “Modal Analysis of a Gearbox Housing in Order to Avoid Resonance Frequencies”:
   - The gearbox housing is a critical component that surrounds gears, supports bearings, and protects internal parts.
   - Vibrations generated during gear engagement can lead to noise emission.
   - Researchers have used both Experimental Modal Analysis (EMA) and finite element analysis (FEA) to establish the natural frequencies of a gear housing.

- The Campbell diagram is employed to map resonance frequencies.
- Optimization of housing design is crucial for noise reduction, weight reduction, and cost savings[1].

2. "Design of Extruder Helical Gearbox: A Review":
- This review paper provides insights into the current state of research on modal analysis and harmonic frequency response related to gearbox casings.
- It also discusses future research directions and challenges in this field[2].

3. "Material-Based Vibration Characteristic Analysis of Heavy Transmission Casing":
- The study focuses on free vibration analysis of transmission casings using finite element simulation (ANSYS software).
- Various materials are considered, and the mode shapes reveal natural frequencies in the range of 1,000–3,800 Hz[3].

4. "Analysis of Gearbox Casing and Effect of Frequency on Stress and Strain Using FEA":
- This work explores vibrational analysis of gearbox casings using condition monitoring techniques, FFT analyzers, and time-frequency domain analysis.
- FEM modal analysis using ANSYS Workbench software reveals natural frequencies separated by 20% from first and second harmonics of excitation frequency[4].

5. "Modal and Stress Analysis of Differential Gearbox Casing with Pick-Up Van Vehicle":
- The project analyzes the differential gearbox casing of a pickup van vehicle for both modal and stress analysis.
- Understanding the vibration behavior and stress distribution is crucial for optimizing the casing design[5].

3. PROBLEM STATEMENT

While gearbox systems are vital components in mechanical applications, their dynamic behavior under different operating conditions remains a subject of extensive study and optimization. This research aims to address this gap by conducting a comprehensive investigation into the dynamics and optimization of a single-stage gearbox system using advanced finite element analysis (FEA) techniques.

In particular, the study focuses on a single-stage gearbox assembly comprising two gears with specific tooth profiles. The gears have 48 and 95 teeth, respectively, and are mounted within a casing with a center distance of 76.20 mm. The gearbox system receives a power input of 10 kW and outputs 9.5 kW, resulting in input and output rotational speeds of 1979.17 RPM and 1000 RPM, respectively.

The objective of this research is to understand the dynamic behavior of the gearbox system, including natural frequencies, mode shapes, and deformations, through modal analysis. Additionally, harmonic response analysis will be conducted to assess the system's response to harmonic excitation, with a focus on gearmesh frequencies.
By leveraging advanced FEA techniques, including modal and harmonic analysis, this study seeks to optimize the gearbox design to minimize vibrations, reduce stress concentrations, and enhance overall performance. The findings from this research will contribute to the development of more robust and efficient gearbox systems for a wide range of mechanical applications.

4. METHODOLOGY

The study will employ the following approaches:

1. 3-D CAD Modeling: Create a detailed three-dimensional model of the gearbox casing.
2. 3-D Finite Element Meshing: Generate a finite element mesh for accurate analysis.
3. Analytical Calculations: Perform analytical calculations to validate results.
4. Finite Element Analysis:
   - Structural Analysis: Investigate static behavior under applied loads.
   - Dynamic Analysis: Determine natural frequencies and mode shapes.
5. Experimental Validation: Compare FEA results with experimental data.
6. Optimization of Structure:
   - Refine the design based on analysis outcomes.
   - Ensure safe operating conditions.

5. MODAL ANALYSIS

Modal analysis transforms physical coordinates into modal coordinates, decoupling the system's vibration equations. The goal is to identify modal parameters for fault diagnosis, prediction, and optimization of structural dynamic characteristics.

6. RESULTS

The results obtained from both modal analysis and harmonic response analysis provide valuable insights into the dynamic behavior and performance of the single-stage gearbox system. Through comprehensive simulation studies using ANSYS software, modal frequencies, mode shapes, and deformation patterns were determined, while harmonic response analysis elucidated the system's response to varying excitation frequencies.

Modal Analysis Results:



Fig. 1. Modal Deformation

Modal analysis revealed the natural frequencies and corresponding mode shapes of the gearbox system. The first few mode shapes identified during modal analysis depicted the primary vibrational modes of the system. These mode shapes provided critical information regarding potential resonance frequencies and areas of structural vulnerability.

Mode Shapes	Frequencies
1	2656.4
2	2704.3
3	4114
4	4306.5
5	4944.7
6	5143.9
7	5190.8
8	5418.4
9	5631.9
10	6189.7

Table 1. Natural Modes

Visual inspection of the mode shapes highlighted localized deformations and stress concentrations in specific regions of the gearbox casing. Areas exhibiting high modal participation factors indicated regions of significant structural response to dynamic loading conditions. These findings guided subsequent optimization efforts aimed at reinforcing critical areas and minimizing vibration amplitudes.

Harmonic Response Analysis Results:

Harmonic response analysis enabled the evaluation of the gearbox system's dynamic response to harmonic excitation, including gearmesh frequencies and other external forces. By varying the excitation frequency over a range of operating conditions, the amplitude and phase responses of key system parameters were determined.

Apply Moment Load on Both Input and Output Shafts:

If you want to simulate the dynamic behavior of the entire gearbox system, including both input and output shafts, it may be appropriate to apply the moment load on both shafts.
This approach allows you to capture the effects of torque transmission through the gearbox and the resulting dynamic response of the casing, considering both the input and output sides. By applying loads on both shafts, you can analyze how vibrations propagate through the system and identify potential resonant frequencies or critical modes of vibration.



Fig.2. Application of Boundary Conditions In Harmonic Response.



Fig.3. Harmonic Response Deformation Contours



Fig.4. Deformation at the Resonance frequency

Mode Shapes	Frequencies
1	618.97
2	1237.9
3	1856.9
4	2475.9
5	3094.9
6	3713.8
7	4332.8
8	4951.8
9	5570.7
10	6189.7

Fig.5. Harmonic Excited Frequencies

Analysis of the harmonic response data revealed resonance frequencies at which the gearbox system exhibited amplified vibration responses. These resonance frequencies corresponded to the natural frequencies identified during modal analysis, confirming the importance of addressing resonance effects in gearbox design.

Plotting the frequency response curves allowed for visualization of vibration amplitudes as a function of excitation frequency. Peaks in the frequency response curves indicated resonance frequencies where vibration amplitudes were significantly amplified, emphasizing the need for targeted design modifications to mitigate resonance-induced vibration.



Fig.5. Set-up of Frequency Range for finding out resonance Frequency



Fig.6. Frequency Response Graph (Peak Value of Mode of 7th Mode is resonance Frequency)

Apply Moment Load on One Input Shaft:

Alternatively, if your primary interest is in understanding the casing's response to the input torque or excitation, you may choose to apply the moment load only on the input shaft.
This approach simplifies the analysis by focusing on the primary source of excitation, which is typically the input side of the gearbox.
By applying the load on the input shaft, you can still capture the dynamic behavior of the casing in response to torque fluctuations and assess its structural integrity and vibration levels.



Fig.7. Application Of Boundry Conditions In Harmonic Response (Moment Load on One input shaft)



Fig.8.Harmonic Response Deformation Contours

7. SUGGESTIONS

Design Modifications for Gearbox Casing Optimization

Following the harmonic analysis conducted on the gearbox system, several design modifications have

been proposed to mitigate potential resonance-induced vibration and enhance the structural integrity and performance of the gearbox casing. These modifications are aimed at addressing vulnerabilities identified during the analysis and optimizing the casing design to minimize vibration amplitudes and stress concentrations.

1. Stiffening the Casing Structure: The first proposed modification involves increasing the stiffness of the gearbox casing. This can be achieved by strategically adding ribs, gussets, or stiffening plates in critical areas prone to resonance-induced vibration. By reinforcing weak points or areas of high stress concentration identified during harmonic analysis, the load distribution can be improved, and vibration amplitudes can be reduced.
2. Tuning Casing Damping Characteristics: Another modification suggestion is to integrate damping materials or coatings into the gearbox casing to dissipate vibrational energy and reduce resonance effects. By optimizing the damping characteristics of the casing material to match the resonance frequencies of the gearbox system, vibration amplification can be minimized, enhancing system stability.
3. Optimizing Casing Geometry: Redesigning the casing geometry is proposed to minimize acoustic resonance and improve airflow for better heat dissipation. This involves smoothing out sharp edges or corners that may act as stress concentrators and contribute to resonance-induced fatigue failure.
4. Enhancing Mounting and Support Structures: Improving the mounting and support structures of the gearbox casing is another modification strategy. This includes utilizing isolation mounts or flexible couplings to decouple the gearbox from external sources of vibration and resonance, reducing transmission of vibration to surrounding components and structures.
5. Implementing Internal Bracing and Reinforcement: Incorporating internal bracing or reinforcement within the gearbox casing can increase rigidity and reduce deformation under dynamic loading conditions. Designing internal partitions or baffles helps minimize fluid-induced vibrations and optimizes fluid flow characteristics within the casing.
6. Adjusting Material Properties: Evaluating the material properties of the gearbox casing and considering materials with higher damping coefficients or improved fatigue resistance is suggested. Selecting materials with tailored properties to match the dynamic response characteristics of the gearbox system helps mitigate resonance effects and improve overall performance.
7. Utilizing Innovative Manufacturing Techniques: Exploring additive manufacturing techniques, such as 3D printing, to fabricate complex geometries and optimize material distribution for enhanced structural performance is recommended. Advanced machining processes can also be employed to achieve tighter tolerances and smoother surfaces, reducing the potential for stress concentrations and vibration amplification.
8. Integration of Monitoring and Control Systems: Integrating real-time monitoring and control systems into the gearbox casing to detect resonance-induced vibration and implement corrective actions is proposed. This includes implementing active vibration control systems or adaptive damping mechanisms to dynamically adjust casing properties and mitigate resonance effects during operation.By implementing these design modifications, based on the findings from harmonic analysis, the structural integrity, performance, and reliability of the gearbox casing can be enhanced, ensuring smooth and efficient operation in various mechanical applications.

9. DESIGN MODIFICATIONS

Integration of Stiffeners in Gearbox Casing Design In gearbox casing design, the integration of stiffeners plays a crucial role in enhancing structural integrity, rigidity, and resistance to deformation under dynamic loads. Stiffeners are strategically placed within the casing to reinforce critical areas and mitigate potential stress concentrations, thereby improving overall performance and reliability.

Placement Considerations: Stiffeners are typically positioned in areas of maximum deformation or stress concentration within the gearbox casing. These areas include regions near mounting points, bearing housings, or sections subjected to high mechanical loads. By distributing loads more evenly across the casing, stiffeners help minimize localized deformation and reduce the risk of fatigue failure.

Structural Reinforcement: Stiffeners provide structural reinforcement at critical interfaces within

the gearbox casing, such as junctions between different casing components or sections. They help enhance the overall rigidity and stability of the casing assembly, improving its ability to withstand bending, torsional, and vibrational forces during operation.

Orientation and Optimization: Stiffeners are oriented in both longitudinal and transverse directions to provide multidirectional reinforcement to the casing structure. Longitudinal stiffeners run parallel to the main axis of the casing, while transverse stiffeners are positioned perpendicular to the main axis. Finite element analysis (FEA) and structural simulation techniques are employed to optimize the placement and configuration of stiffeners, ensuring maximum stiffness while minimizing material usage and weight.

Contribution to Performance Enhancement: By strategically integrating stiffeners into the gearbox casing design, engineers can significantly enhance the structural integrity, stiffness, and durability of the casing. This contributes to improved load distribution, reduced deformation, and enhanced resistance to dynamic loads and vibrations, ultimately ensuring reliable operation and longevity of the gearbox system.

10. REFERENCES

[1] William R. Kelley, L.Dean Isley, and Thomas J.Foste Of Borg-"Dynamic Correlation Study Transfer Case Housings", Warner Automotive Power train systems Sterling Heights, MI, USA

[2] Ravi Narayanaswamy and Charles D. Glynn Borg Warner, "Vibro-Acoustic Prediction of Low-Range Planetary Gear Noise of an Automotive Transfer Case", Automation Avenue Minnesota, October 2005.

[3] Svend Gade, Bruel and Kjaer, "Operational Modal Analysis on a Wind Turbine Gearbox" Sound & Vibration Measurements, Germany and Christian Fenselau, Technology R&D – NVH, Germany.

[4] Petr K., Dynybyl V.: Methods of testing gearboxes of rail vehicles. Applied Mechanics and Materials. Uetikon-Zurich: Trans Tech Publications, 2014, p. 277-282.