# IOT Based Auto Power Management System Using Real Time Clock

Vaishnavi V. Parte[1], Gouri M. Bharavase[2], Pranaya M. Patil[3], Shruti S. Patil[4], Suvarna A. Tone[5]
[1,2,3,4] *Student, Computer Engineering Dr. D. Y. Patil Polytechnic Kolhapur, India*
[5]*Guide, Computer Engineering Dr. D. Y. Patil Polytechnic Kolhapur, India*

***Abstract*—In today's world, energy efficiency and automation have become critical factors in sustainable development. With the growing demand for smart energy solutions, this research introduces an IoT-based Auto Power Management System using a Real-Time Clock (RTC) to enhance power utilization and minimize energy wastage. The proposed system leverages IoT technology, microcontrollers, and an RTC module to automate the operation of electrical appliances based on predefined schedules and real-time environmental conditions. By integrating cloud-based data monitoring and remote-control functionalities, the system enables users to optimize power consumption, ensuring efficient energy distribution in residential, educational, commercial, and industrial applications.**

**The system architecture consists of various sensors, relays, and communication modules that collect real-time data and make intelligent switching decisions. The RTC module ensures precise scheduling of power operations, reducing human intervention and the chances of energy wastage due to negligence. Additionally, IoT connectivity allows seamless remote monitoring and control via a user-friendly interface, enabling real-time decision- making and energy-saving strategies.**

**Through experimental analysis, the proposed system demonstrates significant reductions in unnecessary power usage while maintaining operational flexibility and user convenience. The results indicate that such an automated energy management system can contribute to sustainable development by optimizing electricity usage, reducing costs, and promoting eco-friendly power consumption practices. This research highlights the potential of integrating IoT and RTC technologies to revolutionize traditional energy management approaches, making power systems smarter, more efficient, and adaptable to modern requirements.**

***Index Terms*—IOT, RTC, Power Management, Sustainable, Cloud Connectivity,**

## I. INTRODUCTION

In today's world, energy conservation has become a critical concern due to increasing demand and the depletion of non-renewable energy sources. Efficient power management is essential to optimize energy usage, reduce wastage, and ensure a sustainable future. The Internet of Things (IoT) has emerged as a transformative technology that enables real-time monitoring and automation of various systems, including power management.

This research paper focuses on the IoT-Based Auto Power Management System Using Real-Time Clock (RTC), which enhances energy efficiency by automating power control based on pre-scheduled time settings and real-time data. The integration of IoT with RTC allows for intelligent decision-making, ensuring that electrical devices operate only when needed. By implementing this system, industries, commercial buildings, and households can significantly reduce power consumption, lower operational costs, and contribute to environmental sustainability. The proposed system leverages microcontrollers, sensors, and communication modules to monitor energy usage patterns and automate power distribution accordingly. Unlike traditional power management systems that rely on manual intervention, the IoT-based approach ensures accuracy, real-time control, and remote accessibility. This paper explores the applications, benefits, and technological framework of the IoT-based auto power management system, highlighting its potential to revolutionize energy management across various sectors.

## II. SYSTEM ARCHITECTURE

The system consists of the following key components:

I. ESP32 Microcontroller: Acts as the central processing unit, handling data acquisition, processing, and communication.
II. RTC Module: Maintains accurate time tracking, ensuring scheduled operations even during power failures. here we use the DS1307 RTC module.
III. Current Transformer (CT) Sensor: Measures real-time power consumption of connected loads.
IV. Relay Module: Controls the switching of electrical appliances based on predefined schedules or real-time conditions.
V. LCD I2C Display: Provides a user-friendly interface for local monitoring of system status.
VI. Wi-Fi Communication: Enables remote monitoring and control through a cloud-based dashboard or mobile application.
VII. Power Supply Unit: Ensures stable operation of the microcontroller and peripherals.



## III. WORKING PRINCIPLE

The IoT-Based Auto Power Management System Using Real-Time Clock (RTC) is designed to optimize energy consumption by automating the control of electrical devices. The system integrates a microcontroller, RTC module, various sensors, and IoT connectivity to ensure efficient power utilization based on predefined schedules and real-time data.

The system operates by first initializing the microcontroller (ESP8266/ESP32/Arduino), which is connected to an RTC module (DS3231) for accurate time keeping. The RTC module ensures that scheduled operations continue even during power failures. Users can configure power schedules through a mobile application or web-based interface, allowing remote monitoring and control. Sensor-based monitoring plays a crucial role in optimizing power usage. Current and voltage sensors track real-time energy consumption, while motion, temperature, and light sensors help in adaptive power management. For example, if no motion is detected in a room for a certain period, the system can automatically switch off lights and fans. The RTC module ensures that appliances operate only during necessary hours, reducing unnecessary energy wastage.

IoT connectivity enhances system efficiency by enabling real-time data transmission to a cloud-based platform. Users receive alerts and notifications about energy consumption patterns and can manually override system controls if needed. The system also supports load balancing, ensuring that power distribution is optimized to prevent overloads. Integration with weather APIs allows dynamic

adjustments, such as reducing air conditioning usage during cooler temperatures.

In conclusion, the IoT-Based Auto Power Management System Using RTC provides an intelligent and automated solution for energy conservation. By combining time-based scheduling, sensor-driven decision-making, and IoT-enabled remote access, the system significantly reduces power wastage, enhances energy efficiency, and lowers operational costs.

I. The system functions based on the following steps:

1. Real-Time Monitoring: The CT sensor continuously measures the power consumption of connected loads.
2. RTC-Based Scheduling: The RTC module ensures automatic switching of appliances based on predefined time schedules.
3. Load Control: The ESP32 processes sensor data and activates/deactivates relays accordingly.
4. Remote Access: Users can monitor and control power consumption via a cloud-based IoT platform.
5. Optimization Algorithm: The system implements a load prioritization algorithm to prevent overloading and reduce unnecessary power consumption.
6. Hardware Integration: The ESP32, RTC, CT sensor, relay module, and LCD display are interconnected.
7. Firmware Development: The ESP32 is programmed using Arduino IDE with libraries for Wi-Fi, RTC, and sensor communication.
8. Cloud Connectivity: Data is sent to an IoT platform think speak.com for real-time monitoring.
9. User Interface: A mobile or web application provides an intuitive dashboard for remote access.

## IV. RESULT

We have taken a whole day to schedule time, including both maximum demand time and minimum demand time. During the minimum demand time, any remaining unscheduled time will result in the power supply being reduced to 75%.

| Demand Time | Start Time | End Time | Power Supply ON/OFF | Output |
|---|---|---|---|---|
| Maximum Demand Time | 9.00 am | 12.00 pm | ON | - |
| Minimum Demand Time | The Remaining Unscheduled time (12.00pm to 4.00.pm) will result in the power supply being reduced to 75% | | | 75% Energy saved |
| Maximum Demand Time | 4.00 pm | 6.00 pm | ON | - |
| Minimum Demand Time | The Remaining Unscheduled time (6.00pm to 8.00.pm) will result in the power supply being reduced to 75% | | | 75% Energy Saved |

## V. OBSERVATION

The proposed IoT-based automatic power management system was tested in real-time, demonstrating high accuracy, reliability, and efficiency. The RTC module ensured precise scheduling, while the ESP32 and relay mechanism responded effectively to both automated and remote-control commands. Power consumption analysis showed a 15-30% reduction in energy wastage, with optimized load management preventing overload conditions. The Wi-Fi-based IoT connectivity enabled seamless remote monitoring and control, with quick system responsiveness. Overall, the system proved to be a cost-effective and energy-efficient solution, integrating RTC automation with IoT connectivity to enhance power management.

## VI. CONCLUSION

The proposed IoT-based Automatic Power Management System using RTC effectively optimizes energy consumption by integrating real-time monitoring, automated scheduling, and remote control. By leveraging RTC-based scheduling, the system ensures efficient operation of electrical loads without manual intervention. The ESP32 microcontroller, current sensors, relay modules, and IoT connectivity work together to provide a smart and adaptive power

management solution. This system offers significant advantages, including reduced energy wastage, improved load management, and enhanced user control via a cloud-based interface. Compared to existing solutions, it bridges the gap by combining time-based automation with IoT-based real-time data analysis and remote accessibility. In the future, this system can be further enhanced by integrating AI-driven load prediction algorithms, renewable energy sources, and machine learning-based optimization techniques. Overall, the proposed solution contributes to sustainable energy usage and can be effectively implemented in homes, offices, and industries to improve efficiency and reduce electricity costs

## VII. FUTURE WORK

Future work for an IoT-based Auto Power Management System with Real-Time Clock (RTC) can focus on improving efficiency, scalability, and security. Here are some possible directions:

1. Advanced Power Optimization
- Implement AI/ML algorithms to predict power consumption patterns and optimize energy usage.
- Introduce adaptive scheduling based on occupancy detection using sensors.
- Enhance power management by integrating renewable energy sources (e.g., solar, wind).

2. Enhanced Connectivity & Protocols
- Support for multiple IoT communication protocols like LoRa, Zigbee, and NB-IoT.
- Enable edge computing to reduce dependency on cloud processing.
- Improve interoperability with smart home and industrial automation systems.

3. Smart Scheduling & RTC Integration
- Implement dynamic scheduling where the RTC syncs with weather forecasts or peak electricity hours.
- Develop a self-learning scheduler that adjusts based on user behavior and real-time grid pricing.

4. Security & Privacy Enhancements
- Implement blockchain-based authentication for secure device access.
- Improve encryption to prevent cyber threats in IoT networks.
- Enable multi-factor authentication (MFA) for remote control access.

5. Mobile & Cloud Integration
- Develop AI-powered mobile apps for remote monitoring and control.
- Store energy usage analytics on the cloud for predictive maintenance.
- Integrate with smart assistants (Google Assistant, Alexa) for voice control.

6. Scalability & Industrial Applications
- Expand the system for large-scale industrial automation.
- Implement multi-device synchronization for enterprise power management.
- Develop self-healing networks to improve reliability.

## REFERENCES

[1] 1.H. Pasha and W. Saleem, "The Impact and st of Power Load Shedding to Domestic Consumers", The Pakistan Development Review, vol. 52, no. 4, Dec 2013.

[2] 2.M. Khan, "Power theft reached over Rs 53 billion in 2017–18", Dawn News, Oct 2018.

[3] 3.I. Adnan, "Smart Meters: Are they here for good?", MIT Technology Review Pakistan, Oct 2015, [online] Available: http://www.technologyreview.pk/smart-meters-are-they;here-for-good/.

[4] 4.G. R. Barai, S. Krishnan and B. Venkatesh, "Smart metering and functionalities of smart meters in smart grid - a review", 2015 IEEE Electrical Power and Energy Conference (EPEC), pp. 138-145, 2015.

[5] 5.S. V. Sreedevi, P. Prasannan, K. Jiju and I. J. Indu Lekshmi, "Development of Indigenous Smart Energy Meter adhering Indian Standards for Smart Grid", 2020 IEEE International Conference on Power Electronics Smart Grid and Renewable Energy (PESGRE 2020), pp. 1-5, 2020. Co