A Research Paper on Movie Recommendation System

Vipul Kunwar[1], Benu Gopal Panday[2], Rohit Kumar Prince[3], Mr. Manish Kumar Mehrotra[4]
[1,2,3,4] *School of Computer Application and Technology, Galgotias University, Greater Noida, UP, India*

***Abstract*—In this project, a movie recommendation system is built based on the TMDB datasets. We used a content-based filtering method to recommend other movies that are similar to the selected movies. The movie recommendation algorithm already has enough stuff available. Presenting the suggested films is crucial. in order to save the user time when looking for the stuff that he or she might find appealing. As a result, the movie recommendation system is essential for providing users with tailored movie recommendations. Following extensive web research and consulting numerous research papers, we discovered that the suggestions provided by content-based filtering employ a single text-to-vector conversion method and a single method to identify the correspondence between the vectors. Several texts were converted using vector conversion techniques in this study, and the final suggestion list was obtained by manipulating the output of several algorithms. It can be viewed as a hybrid strategy that solely uses the content-based filtering technique.**

I. INTRODUCTION

Making Recommendations A recommendation system (or recommendation engine) aims to predict a user preference to offer a personalized suggestion based on the user's behaviour and interests. Such systems are already widely used throughout domains such as entertainment and food, books and fashion and more. Within cinema, one of the most fundamental aspects of modern life, recommendation systems carve through user tastes and inform them of what movies to watch efficiently, eliminating the labour of searching through multiple films only to be disappointed.

There are many ways to categorize movies, including that Org. by genre (action, comedy, thriller, animation), director, language or year of release. For instance, there are educational and children’s animation genres, as well as horror and purely entertaining films. Recommendation systems use these categories and the data of users when curious about a certain category, then they can give you lists that are tailored to you — which improves your viewing experience. such personalization increases user satisfaction, thus making the recommendation system a powerful marketing tool for companies that are striving to improve customer engagement and revenue. Regarding movie streaming platforms, these tools are successful in building user- loyalty by regularly serving up attractive contents. Nevertheless, the potential benefits of movie recommendation systems are overshadowed by the concern over scalability and accuracy loss if these systems take advantage only of the collaborative filtering method. Circumventing these shortcomings is very much important for the systems to be stable and to impart proper recommendations that are in line with Individuals divergent preferences.

1.1 Problem Statement

The project's objective is to suggest a film to the user. supplying users of internet service providers with related content derived from a collection of items that are both relevant and irrelevant.

1.2 Objective of the Project

- Improving the Accuracy of the recommendation system
- Improve the Quality of the movie Recommendation system
- Improving Scalability
- Enhancing the user experience.

1.3 Scope of the Project

This project seeks to provide users with good and trustworthy movie recommendations. The foresight is to enhance the quality, scalability, and correctness of movie recommendation systems by transcending traditional methods. In order to do it, a mixed method approach is implemented, i.e., the one combining the two filters' benefits, namely, collaborative filtering and content-based filtering.

Recommendation systems are important information filtering tools, especially on social networking sites, to deal with the overwhelming amount of data.

Consequently, there is great potential for research in this area to enhance the scalability, accuracy, and efficiency of these systems. Movie recommendation systems are powerful tools. However, traditional collaborative filtering approaches often experience scalability and a decrease in the quality of recommending. This project solves these issues by using a hybrid type making the model more resilient and Quicker in its recommendations**.**

II. LITERATURE SURVEY

A range of movie recommender systems that are being used in the project, is briefly overviewed by Mahesh et al. [1]. It involves deep learning techniques, hybrid approaches, content-based filtering, and collaborative filtering. Several similarity metrics are also tested. It points out that a large number of companies including, Facebook, LinkedIn, Pandora, Netflix, and Amazon are using recommendation systems. The review provides a succinct summary of different methodologies and strategies, thereby offering useful information for future research on recommendation systems. The paper by Jiang et al. [2] focuses on the scalability of movie recommendation systems and the feedback of users. It proposes a user clustering-based recommendation system that is very efficient. The method is performed with a lower time complexity and the same results as the classical CF systems can be achieved. Rishabh and his group are working on a study which seeks to create a movie recommendation system with the help of K Means Clustering and K Nearest Neighbour Algorithms [3]. The utilized dataset is called MovieLens and the system executes in Python. We are introducing a number of machine learning concepts, tools, and techniques, like Content-Based Filtering, KNN, K-Means Clustering, and Collaborative Filtering. The architecture, process flow, and pseudocode of the new system are explained. The results show that the system we propose is better than the methods with the best root mean square error value of 1.081648. Recommender systems (RS), which are developed by Choudhury et al. [4], deal with the problem of information overload, like movie suggestions. Different models including Back Propagation Neural Network (BPNN), Singular Value Decomposition (SVD), Deep Neural Network (DNN), and DNN with the confidence comparison between DNN with Trust and DNN without Trust. The DNN with Trust model, a movie recommendation method, is shown to be a good option as it has an accuracy of 83% and MSE of 0.74. Sahu et al. [5] note a movie-texture based recommendation system, which considers the various features of the movie such as genre direction and expression of the film, to make personalized movie recommendations. The CNN deep learning model is a predictor of the film's popularity in RS. The input data include film ratings and voting. Negi's method got a higher accuracy of 96.8% compared to the 96.4% accuracy of the other four models. Behera et al. [6] have suggested a collaborative filtering approach for movie recommendations that incorporates temporal effects. As evidenced by their MovieLens dataset analysis, the performance of ML-100K has been better by 1.35% than the other models and of 1M by 1.28% in comparison with the leading models. Airen et al. [7] studied the use of weighted co-clustering techniques to develop movie recommendation systems, associating optimal user and movie communities with changing row and column cluster properties. It is the experiments on a movie database that prove that their approach is better than the already existing methods by 7.91%, thereby offering more personalized recommendations that are more precise. Gupta et al. [8] advocated the use of cosine similarity with K-NN algorithms and collaborative filtering to solve the problem of content-based filtering shortcomings as well as the advantages of both methods. Their results show that the precision of this technique with cosine similarity is similar to that with Euclidean distance. Tahmasebi et al. [9] came up with a hybrid social recommender system based on deep autoencoder networks that include user social influence from Twitter along with the content-based and collaborative filtering approach. The results show that this technology is not only more accurate but also faster in performing than the current state-of-the-art methods. Pecune et al. [10] pointed out that it is crucial to explain how movie recommendation systems work. They created a conversational agent by using a human-centered design approach; the agent provides users with explanations that are periodical to human ones. The model, which was a newly added coding part to the agent and was overseen by the users, showed that the increased quality of social explanations, apart from the system recommendation accuracy, made the user and system interactions more enriched. Darban et al. [11] introduced a novel graph-based model that incorporates geographic and demographic information as well as user similarities. By employing autoencoder-based feature extraction, the model effectively addresses the cold-start problem and enhances recommendation reliability. Experimental results confirm the approach's effectiveness. Kalyan Kumar et al. [12] utilized the MovieLens dataset to develop a neural network model for accurate movie recommendations, implemented in Python. Their model achieved an 87% hit ratio, showcasing its predictive capability. Lastly, Fiagbe [13] employed matrix factorization with the MovieLens dataset to forecast ratings for unseen movies, recommending those with the highest predicted ratings. The model's low RMSE scores validate its accuracy. Darban et al. [11] came up with a new graph-based model that is based on the physical locations and ages of the users as well as their likeness. Through autoencoder-driven feature extraction, the model is able to solve the cold start issue and also make the recommendations more reliable. The application of this strategy is backed by the experimental results. Kalyan Kumar et al. [12] used MovieLens data to make a deep learning-based movie recommendation model and coded it in Python. The obtained results of their model were an 87% hit rate; thus, its high predictive power was established. Last but not least, Fiagbe [13] made use of matrix factorization with the MovieLens dataset in order to predict ratings of the movies that are not watched by the user, preferring the best reviewed ones. According to the RMSE scores, the model is highly accurate.

III. RESEARCH GAP

Content-based filtering systems play a crucial role in personalizing movie recommendations. However, several limitations in existing approaches provide opportunities for further advancements.

These gaps include the following:

1. Restricted Representation of Features: Current Research: To create user profiles and generate recommendations, a lot of content- based filtering systems mostly rely on restricted parameters like genres, stars, directors, or movie plots. suggestions. Research Gap: Although these parameters offer a fundamental comprehension of user preferences, they frequently overlook more intricate characteristics like themes, tone, cinematography style, or social metadata (such social media popularity). Possibility: The gap is in creating models that use richer feature extraction, such deep learning to analyse movie posters, trailers, or even script writing styles.
2. Cold-Start Issue: Current Studies: Since content-based systems don't depend on user preferences, they are able to suggest new films.

Nevertheless, consumers experience the cold-start issue, particularly if they haven't engaged with enough films. study Gap: Not much study has been done on how to help new users who haven't given enough feedback to create accurate profiles get over the cold-start issue. Possibility: By creating innovative methods, including using implicit feedback from clicks and browsing history, it may be possible to enhance suggestions for cold-start users without the need for explicit ratings.

3. Sentiment Analysis Integration: Current Research: Conventional content-based systems ignore user opinions regarding various parts of a film in favour of metadata (genres, actors, etc.). Research Gap: Sentiment analysis of user reviews is not well integrated to improve suggestions. As an illustration, a user might like comedies but not all forms of humour. Possibility: By applying natural language processing (NLP) techniques to sentiment analysis of user reviews, the system can better comprehend user preferences and suggest films that suit their sentiments and preferences.

Opportunities to further develop the field of content-based filtering in movie recommendation systems are presented by the aforementioned research gaps. Closing these gaps may result in recommendation systems that are more effective, scalable, and tailored to the intricacies of context, user preferences, and system performance limitations. Future systems can increase the precision and user satisfaction of movie recommendations by integrating components like sentiment analysis and more sophisticated feature extraction.

IV. METHODOLOGY

A Content- Grounded Filtering Movie Recommendation System Content- grounded filtering algorithms are employed depending on stoner attributes. When details about a point, including its identity, position, or descriptions, are known but not about the stoner, this system is employed. It uses stoner moxie to read aspects, just like cooperative approaches, but it ignores other druggies' benefactions entirely. frequently, it makes unequivocal or implicit use of the information that the stoner has handed. When the stoner adds further content- grounded filtering ways (similar as a content- grounded recommender) to the suggestions, the machine becomes more accurate. In a content-based recommendation engine, each user is assumed to operate autonomously. When analysing the item's traits or attributes, it looks for similarities among items and suggests the alternative that is most comparable to other users without requiring information about other users. If we examined the film's content, for example, each actor, director, and writer could be regarded as a feature. The user is shown with items that are substantially similar to the one they voted for.

Similarity Score:
On a scale of 0 to 1, it's a numerical value that represents the degree of similarity between two particulars. This similarity score is calculated by measuring how analogous the textbook details of the two particulars are. The similarity score measures the degree of resemblance between two objects' textual details. This can be fulfilled by using cosine-similarity.

How Cosine Similarity works?
Two vectors that are comparable to each other using a mathematical metric known as cosine similarity can be used to represent text content in a vector space model. Because this method considers the direction of the vectors rather than their magnitude, it is particularly useful for comparing documents of varying lengths. We calculate the similarity between two vectors in a multi-dimensional space using the cosine of their angle. A lower angle is associated with greater similarity. Regardless of document sizes, cosine similarity emphasizes the vectors' alignment or orientation rather than their separation. Even if two documents are drastically different in length, this feature allows one to determine how similar they are based on the overlap of their words.

CountVectorizer:
The CountVectorizer is a potent tool offered by the scikit-learn Python library. Depending on how often each word occurs in the given text, this tool converts it into a vector representation. Because it enables the conversion of words into numerical vectors that may be used in a variety of text analysis activities, it is especially useful when working with many texts.

Content-based filtering in recommender systems forecasts and suggests new but related items to the user using machine learning techniques. Recommendations based on a product's qualities may only be produced when its features and user preferences are clearly established. The recommender system uses historical user data, including clicks, ratings, and likes, to create a user profile. The more a client engages, the more accurate the recommendations are in the future.

Project Flow Diagram:
First, the data sets needed to construct a model are loaded. The tmdb_credits.csv and tmdb_movies.csv data sets are necessary for this project. You may access all of the data sets on Kaggle.com. In essence, the Streamlit Python library for web app development is used to generate three models using a content-based methodology, which are then imported into a website. Finally, the Heroku server has been used to deploy the Website.



Figure 1: Project Flow Diagram

```
import numpy as np
import pandas as pd
movies = pd.read_csv('tmdb_5000_movies.csv')
credits = pd.read_csv('tmdb_5000_credits.csv')
movies.head()
```

	budget	genres	homepage	id	keywords	original_language	original_title	overview	popularity	production_companies
0	237000000	[{"id": 28, "name": "Action"}, {"id": 12, "nam...	http://www.avatarmovie.com/	19995	[{"id": 1463, "name": "culture clash"}, {"id"...	en	Avatar	In the 22nd century, a paraplegic Marine is di...	150.437577	[{"name": "Ingenious Film Partners", "id": 289...
1	300000000	[{"id": 12, "name": "Adventure"}, {"id": 14, "...	http://disney.go.com/disneypictures/pirates/	285	[{"id": 270, "name": "ocean"}, {"id": 726, "na...	en	Pirates of the Caribbean: At World's End	Captain Barbossa, long believed to be dead, ha...	139.082615	[{"name": "Walt Disney Pictures", "id": 2}, {"...
2	245000000	[{"id": 28, "name": "Action"}, {"id": 12, "nam...	http://www.sonypictures.com/movies/spectre/	206647	[{"id": 470, "name": "spy"}, {"id": 818, "name...	en	Spectre	A cryptic message from Bond's past sends him o...	107.376788	[{"name": "Columbia Pictures", "id": 5}, {"nam...

```
credits.head()
```

	movie_id	title	cast	crew
0	19995	Avatar	[{"cast_id": 242, "character": "Jake Sully", "...	[{"credit_id": "52fe48009251416c750aca23", "de...
1	285	Pirates of the Caribbean: At World's End	[{"cast_id": 4, "character": "Captain Jack Spa...	[{"credit_id": "52fe4232c3a36847f800b579", "de...
2	206647	Spectre	[{"cast_id": 1, "character": "James Bond", "cr...	[{"credit_id": "54805967c3a36829b5002c41", "de...
3	49026	The Dark Knight Rises	[{"cast_id": 2, "character": "Bruce Wayne / Ba...	[{"credit_id": "52fe4781c3a36847f81398c3", "de...
4	49529	John Carter	[{"cast_id": 5, "character": "John Carter", "c...	[{"credit_id": "52fe479ac3a36847f813eaa3", "de...

```
movies.info()
```

```
<class 'pandas.core.frame.DataFrame'>
RangeIndex: 4809 entries, 0 to 4808
Data columns (total 23 columns):
 #   Column                Non-Null Count  Dtype
---  ------                --------------  -----
 0   budget                4809 non-null   int64
 1   genres                4809 non-null   object
 2   homepage              1713 non-null   object
 3   id                    4809 non-null   int64
 4   keywords              4809 non-null   object
 5   original_language     4809 non-null   object
 6   original_title        4809 non-null   object
 7   overview              4806 non-null   object
 8   popularity            4809 non-null   float64
 9   production_companies  4809 non-null   object
 10  production_countries  4809 non-null   object
 11  release_date          4808 non-null   object
 12  revenue               4809 non-null   int64
 13  runtime               4807 non-null   float64
 14  spoken_languages      4809 non-null   object
 15  status                4809 non-null   object
 16  tagline               3965 non-null   object
 17  title                 4809 non-null   object
 18  vote_average          4809 non-null   float64
 19  vote_count            4809 non-null   int64
 20  movie_id              4809 non-null   int64
 21  cast                  4809 non-null   object
 22  crew                  4809 non-null   object
dtypes: float64(3), int64(5), object(15)
memory usage: 864.2+ KB
```

V. DISCUSSION

The study discussed in this paper demonstrates the importance of recommendation systems to the film industry. Numerous techniques, such as content-based filtering, collaborative filtering, and hybrid approaches, have been studied and compared. It is evident that the effectiveness and usefulness of movie recommendation systems can be increased by utilizing various techniques, such as emotional analysis. The significance of incorporating dynamic aspects when developing recommendation systems is also emphasized in the paper. The temporal and dynamic character of user-item interactions is frequently overlooked by traditional techniques. Nevertheless, temporal effects have been included into content-based filtering algorithms, leading to encouraging results in terms of increased suggestion accuracy. Positive results have also been obtained by integrating emotive analysis and explanations into recommendation systems. Utilizing social traits and behaviours can improve the calibre of recommendations and yield valuable information.

VI. CONCLUSION

In conclusion, movie recommendation systems have evolved into vital tools for viewers to help them navigate the vast amount of content that is available. This review research provides an overview of the various techniques and strategies employed in movie recommendation systems. It is clear that combining multiple techniques—such as collaborative filtering, content-based filtering, and deep learning algorithms—can produce recommendations that are more precise and tailored. The study also highlights how important it is that dynamic factors like temporal effects and shifting user preferences be considered by recommendation systems. These components can significantly improve the advice' efficacy and relevance.

Moreover, recommendation algorithms that include explanations and social impact have shown promising results. The application of social characteristics and behaviours enhances user happiness and system perception in addition to providing rationale for recommendations.

All things considered by offering a comprehensive analysis of the numerous techniques and tactics used in movie recommendation systems, this review paper contributes to the corpus of knowledge. It clarifies the challenges these systems face and offers suggestions for next research directions. For example, the effectiveness of movie recommendation systems could be greatly increased by include user comments and contextual information.

REFERENCE

[1] Goyani, Mahesh; Chaurasiya, Neha. "A Review of Movie Recommendation System: Limitations, Survey and Challenges". ELCVIA: Electronic Letters on Computer Vision and Image Analysis, Vol. 19 No. 3 (2020), p. 18-37 DOI 10.5565/rev/elcvia.1232 https://ddd.uab.cat/record/232276

[2] J. Zhang, Y. Wang, Z. Yuan and Q. Jin, "Personalized real-time Movie Recommendation System: Practical prototype and evaluation," in Tsinghua Science and Technology, vol. 25, no. 2, pp. 180-191, April 2020, doi: 10.26599/TST.2018.9010118.

[3] R. Ahuja, A. Solanki and A. Nayyar, "Movie Recommender System Using KMeans Clustering AND K-Nearest Neighbor," 2019 9th International Conference on Cl Computing, Data Science & Engineering (Confluence), Noida, India, 2019, pp. 263-268, doi: 10.1109/CONFLUENCE.2019.8776969.

[4] S. Sahu, R. Kumar, M. S. Pathan, J. Shafi, Y. Kumar and M. F. Ijaz, "Movie Popularity and Target Audience Prediction Using the Content-Based Recommender System," in IEEE Access, vol. 10, pp. 42044-42060, 2022, doi: 10.1109/ACCESS.2022.3168161.

[5] Gopal Behera, Neeta Nain, Collaborative Filtering with Temporal Features for Movie Recommendation System, Procedia Computer Science, Volume 218, 2023, Pages 1366-1373, ISSN 1877-0509, https://doi.org/10.1016/j.procs.2023.0 1.115.

[6] Sonu Airen, Jitendra Agrawal, Movie Recommender System Using Parameter Tuning of User and Movie Neighbourhood via Co-Clustering, Procedia Computer Science, Volume 218, 2023, Pages 1176-1183, ISSN. 1877-0509, https://doi.org/10.1016/j.procs.2023.0 1.096.

[7] M. Gupta, A. Thakkar, Aashish, V. Gupta and D. P. S. Rathore, "Movie Recommender System Using Collaborative Filtering," 2020 International Conference on Electronics and Sustainable Communication Systems (ICESC), Coimbatore, India, 2020, pp. 415420, doi: 10.1109/ICESC48915.2020.9155879.

[8] Tahmasebi, H., Ravanmehr, R. & Mohamadrezaei, R. Social movie recommender system based on deep autoencoder network using Twitter data. Neural Comput & Applic 33, 1607–1623 (2021). https://doi.org/10.1007/s00521-020-05085-1

[9] Florian Pecune, Shruti Murali, Vivian Tsai, Yoichi Matsuyama, and Justine Cassell. 2019. A Model of Social Explanations for a Conversational Movie Recommendation System. In Proceedings of the 7th International Conference on Human-Agent Interaction (HAI '19).

[10] Zahra Zamanzadeh Darban, Mohammad Hadi Valipour, GHRS: Graph-based Hybrid recommendation system with application to movie recommendation, Expert Systems with Applications, Volume 200, 2022, 116850, ISSN 0957- 4174, https://doi.org/10.1016/j.eswa.2022.116850

[11] Jena, K.K., Bhoi, S.K., Mallick, C. et al. Neural model based Collaborative filtering for Movie Recommendation System. Int. j. inf. tecnol. 14, 2067–2077 (2022). https://doi.org/10.1007/s41870022