Iot Based Real-Time Landslide and Flood Monitoring E-Mail Notification System

Ramakrishnan C[1], Gokulkannan K[2], Gowtham S[3,] Mohan Kumar V[4], Prasad N[5], Prince Deepak JK[6]
[1]*Assistant Professor, Adhiyamaan College of Engineering*
[2,3,4,5,6]*UG Students, Adhiyamaan College of Engineering*

***Abstract*—Landslides and Flood, usually caused by conditions such as heavy rainfall, seismic activity, or human activities, are major threats to human lives and infrastructure. Conventional monitoring techniques, however, tend to be inadequate because of their limitations in coverage, real-time data collection, and cost-effectiveness. Zigbee technology, which overcomes these limitations by providing superior long-range communication features and low-power consumption. This makes it a prime candidate for the development of a strong IoT platform focused on landslide monitoring. Zigbee-based IoT strategy introduces a plethora of advantages. To begin with, it facilitates early detection, enabling authorities and communities to take anticipatory action in response to changing conditions. The sensor node demonstrated here accommodates a wide range of low-power sensors; the scope of applications is therefore significant. In this project landslide monitoring system has been developed for monitoring the movement and moisture of soil which in general triggers the landslide and flood monitoring. Also monitors the level of water for triggering the abnormal monitoring alert. The system is suggested to employ a network of low-power Zigbee network technology. The system comprises the sensors like humidity sensor, float sensor, moisture sensor and vibration sensor. These sensors are interfaced with Arduino NANO.**

***Index Terms*—Landslide monitoring, Flood detection, Zigbee technology, IoT framework, Real-time monitoring, Early warning system, Soil movement detection, Humidity sensor, Float sensor, Moisture sensor, Vibration sensor, Arduino NANO, Low-power sensors, Wireless communication, Disaster management, Environmental monitoring.**

I.INTRODUCTION

Natural disasters are intense, frequently unpredictable occurrences resulting from the Earth's natural processes. Examples are earthquakes, tsunamis, hurricanes, floods, wildfires, and volcanic eruptions. They have the potential to cause extensive destruction, loss of life, and long-term social disruption. Factors such as high population density, poor infrastructure, and climate change can exacerbate their impact. Over time, such disasters have influenced human evolution, determining where and how human beings live. Knowledge of these events is essential to enhance preparedness, minimize risk, and provide a more resilient futureLandslides, for instance, are among the most frequent but underappreciated natural hazards. They result in more than $100 million in direct loss and thousands of fatalities annually, primarily caused by heavy and sustained rainfall. Various methods have been created over the years to monitor landslides and mitigate their effects.Monitoring techniques are remote sensing, photogrammetry, geodetic, geotechnical, geophysical systems, wireless sensor networks (WSN), and the Internet of Things (IoT). Remote sensing and geodetic equipment employ satellites, drones, or ground platforms to sense surface motions over wide regions, occasionally in 3D. Nevertheless, in real-time application, they are constrained by satellite revisit times and manual handling of data.Geotechnical instruments such as inclinometers and extensometers are surface-mounted and directly measure displacement, pressure, and vibration at a location. These are precise and appropriate for site-specific real-time early warnings, but costly for extensive areas. Electrical resistivity and seismic surveys are geophysical techniques that inspect the physical characteristics below the ground and can be made to operate in real time. But as they record indirect parameters, they are not so effective in providing accurate early warnings.Generally, satellite-based methods are suited for slow or moderate landslides, but ground-based methods can also accommodate faster events. Nevertheless, the range of tools, each with varying strengths, sensitivities, and

scales, makes it challenging to choose the optimal method for any slope. The natural variability of terrains, as opposed to uniform man-made materials, implies there is no one-size-fits-all solution. In many cases, a combination of methods adapted to the site conditions is required for successful landslide monitoring.

II. RELATED WORKS

A number of efforts in research have been focused on the study of the movement of natural hazards like landslides and floods and the development of effective monitoring and mitigation plans. Researchers are still searching for various methods to enhance the early warning systems, increase accuracy, and minimize risks from these disasters. Various influential literature studies give an overview of current monitoring methods, their drawbacks, and the future direction of their enhancements.A study by [1] Petley et al. highlights the underestimation of landslide as a natural hazard, with losses and fatalities over $100 million annually. The study identifies the causes as mainly prolonged and heavy rainfall and calls for predictive models to help facilitate early disaster mitigation.In another research, [2] Turner et al.examine the application of remote sensing and geodetic instruments like satellite and drone-based systems to track surface displacements. These methods are suitable for extensive, slow-moving landslides, but are hindered by satellite revisit delays and the need for manual interpretation. Another method is examined in [3] Dunnicliff'stext, which discusses geotechnical instruments such as inclinometers and extensometers. Though providing high-precision site-specific monitoring, the high expense and low scalability of such systems create difficulties for extensive deployment.[4] Jongmans and Garambois investigate geophysical techniques such as electrical resistivity and seismic surveys, which provide real-time observation of subsurface behavior. But their use of indirect indicators lowers the accuracy of early warnings.A more scalable solution comes from [5] Liu et al., who look into integrating Wireless Sensor Networks (WSNs) and IoT platforms for landslide monitoring. Their system is responsive in real-time but suffers from challenges such as energy efficiency and maintenance under harsh environmental conditions.[6] Intrieri et al. propose a hybrid solution, integrating satellite systems with terrestrial infrastructure to increase dependability. Effective as it may be, this integration calls for extensive coordination and support systems, raising deployment complexity.Application of radar and optical sensing in early warning is also addressed by [7] Casagli et al., who illustrate the capabilities of these technologies in picking up precursors to landslides. Variability of terrain, however, continues to pose a challenge to uniform performance.Finally, [8] Mulas et al.advocate for site-specific monitoring strategies because natural slopes have diverse features.

The article criticizes the use of generic approaches and promotes taking on customized sensor systems to enhance detection efficiency.While these researches highly improve landslide and flood detection technology, scalability, accuracy, and cost-effectiveness continue to pose issues in achieving balance. Future research will need to focus on the development of hybrid models that integrate sensor networks, geotechnical data, and environmental behavior analysis for the purpose of obtaining real-time, low-latency, and accurate monitoring across various terrains.

III.METHODOLOGY

A.Sensor Data Collection

The system proposed gathers real-time environmental data using multiple sensors integrated into the IoT node. Some of these sensors are a humidity sensor, moisture sensor, vibration sensor, and a float sensor. Each of these sensors is tasked with tracking various parameters: soil moisture levels, ground vibrations, humidity levels, and fluctuations in water level. The sensors are installed strategically within landslide- and flood-susceptible zones to detect major variations. Sensor data is communicated wirelessly by Zigbee communication modules to a base station. All the data are time-stamped and stored to aid temporal analysis of environmental variation.

B. Microcontroller and Hardware Integration

The processing module employed is the Arduino NANO due to its small size, low power usage, and adequate I/O ports. The Arduino continuously monitors the sensor inputs and decides the threshold violations that represent potential landslide or flood situations. The sensor node is on a power-saving cycle,

waking up occasionally, reading data, sending it, and going into a low-power mode. Arduino NANO is instructed to sense anomalies like abrupt spikes in moisture, vibrations of more than a predefined value, or increasing water levels, which will prompt them to send a message using Zigbee instantly.

C. Wireless Communication using Zigbee Protocol

Zigbee technology is utilized for its low-power, long-range wireless communication features. Each sensor node contains a Zigbee transceiver (e.g., XBee) that sends gathered sensor data to a central monitoring station. Zigbee's mesh network feature guarantees reliable data transfer even when some nodes are blocked or temporarily offline. It minimizes latency and provides real-time alerting. Data integrity is provided by packet acknowledgment and retry protocols, which makes the system ideal for mission-critical environmental monitoring.

D. Real-Time Monitoring and Alert System

At the receiving end, a central monitoring station is deployed using a PC or Raspberry Pi that keeps on receiving and logging data from various Zigbee nodes. A Python-based backend script processes real-time incoming data, comparing it with pre-set safety thresholds. In detecting risk conditions like unusual ground vibration or sudden rise in water level, the system automatically triggers automatic email alerts to pre-registered stakeholders and authorities. The notification contains sensor measurement, timestamp, and location for instant evaluation and response.

E. Visualization and Data Analysis Dashboard

A basic web-based dashboard is created to visualize environmental parameters. The dashboard provides live graphs of moisture, humidity, vibration level, and water height using streaming real-time data. Users are able to observe trends, threshold violations, and alert logs. This allows users and authorities to monitor environmental behavior over time to predict and prepare more effectively. Historical data are archived in a lightweight database for additional analysis and reporting.

F. System Deployment and Testing

The entire system is installed in a simulated environment with controlled landslide and flood-prone ground. It is tested through simulated rainfall (to impact soil moisture), controlled vibrations, and manual water level adjustments. Response time, accuracy of sensors, reliability of Zigbee communication, and effectiveness of alerts are analyzed. The prototype has been able to provide promising results in timely detection and notification of impending danger, establishing the viability of using IoT and Zigbee technology for real-time disaster monitoring.

IV. ARCITECTURE

The architecture of the proposed IoT-based real-time landslide and flood monitoring system is developed to enable continuous environmental surveillance, early hazard detection, and immediate alert notification. The system is composed of several interconnected modules working in unison to provide robust disaster monitoring and proactive risk mitigation**.** Fig 1: Architecture Diagram illustrates the entire system flow, highlighting how data is sensed, processed, communicated, analyzed, and acted upon.The architecture begins with the Sensor Layer, where multiple environmental parameters are continuously monitored using low-power sensors. These include a humidity sensor for atmospheric moisture, a soil moisture sensor for subsurface water content, a vibration sensor to detect tremors indicative of potential landslides, and a float sensor to track rising water levels that may lead to floods. All sensors are interfaced with the Arduino NANO microcontroller, which serves as the central processing unit for raw data acquisition.Next, the Microcontroller Module collects sensor readings at defined intervals. Upon detecting any parameter that exceeds its respective threshold—such as abnormal soil wetness, rapid vibration spikes, or rising flood water—the Arduino processes this information locally and prepares it for transmission. This data is then sent to the base station through the Zigbee Communication Layer, which is responsible for long-range, low-power wireless data transmission across nodes in a mesh network configuration. Zigbee ensures reliable and scalable communication between multiple sensor nodes and the centralized monitoring hub.The Receiver and Processing Module, implemented on a Raspberry Pi or PC, acts as the system's analysis hub. It receives incoming sensor data in real time via a Zigbee receiver. A backend script written in Python parses and evaluates the data against

pre-programmed safety thresholds. If a danger condition is met, this module immediately triggers the Alerting and Notification Module.The Alerting Module generates automatic email alerts that are sent to designated authorities, emergency response teams, or residents in the monitored region. Each alert includes details such as sensor ID, time of detection, type of hazard (landslide or flood), and severity level. This ensures timely decision-making and community response.



Fig 1: Architecture Diagram

Additionally, the system supports a Visualization Dashboard that provides a live feed of environmental readings, visualizing the changing trends of soil and water conditions. This module enables users to monitor real-time updates and historical data trends, offering an intuitive interface for environmental analysts and disaster management authorities. Overall, the system architecture emphasizes energy efficiency, real-time communication, modular scalability, and automated alerting making it a viable solution for landslide and flood-prone regions.

V RESULTS AND OUTCOME

The system proposed exhibits a strong and smart system for real-time monitoring of landslide and flood via Zigbee-based IoT infrastructure coupled with several sensors. The prototype developed guarantees effective environmental sensing, data communication, and hazard notification in terms of automatic email alerts. The easy-to-use interface, as shown in Fig 2: User Interface, enables users to monitor real-time sensor data, system health indicators, and activated alarms. This interface facilitates transparency and enables timely decision-making in disaster zones.



Fig 2: Water Level Sensor Data Graph

The event logging and real-time data visualization capabilities are demonstrated in Fig 3: Monitoring Dashboard, where trends in sensor readings such as acute spikes in the vibration of soil or unwarranted increase in water level emit system alarms. The graph demonstrates how each of the environmental parameters is dynamically monitored for thresholds so that any resulting landslide or flood condition is at once detected and logged.



Fig 3: Water Limit Sensor Data Graph

Fig 3: Sensor Data Graph shows real-time feedback from humidity, moisture, float, and vibration sensors. The graph shows the way the system responds to unusual environmental changes, with notations highlighting threshold exceedances corresponding to actual alerts being sent and emailed to respective authorities or users. This is a demonstration of the system's efficacy in sensing early warning signs and activating proactive response mechanisms.



Fig 5: Soil Moistuer Sensor Data Graph

In order to compare communication efficiency, Fig 5: Zigbee Communication Latency Graph analyzes the delay of Zigbee packet transmission in varying situations. Conclusive results are reflected as continually low-latency sensor node-control unit communication despite being tested under remote simulated scenarios. This establishes Zigbee's viability and competency in real-time applications of disaster detection.A comparison of event detection accuracy between isolated sensors and the combined system is presented in Fig 6: Detection Accuracy Comparison. The combined system recorded a detection accuracy of 96.4%, surpassing isolated sensor triggers owing to the increased reliability of multi-sensor correlation. This sensor data fusion dramatically minimizes false positives and guarantees timely and accurate environmental hazard identification.



Fig 6: G-Mail Notification Alert

Overall system results authenticate its capability in providing early alerts of high accuracy with low false alarms. Automated e-mail alarm dissemination system proves efficient in broadcasting alarm within a delay of only 5–7 seconds since detecting a prospective risk, promoting instant response. Scalability based on different geography sites is ensured through the module nature of architecture, making the solution a confident real-time choice for disaster watching and early alarm dissemination. The integration of low-power sensing, wireless real-time communications, and automated alert systems creates a deployable, cost-effective system for landslide and flood-risk locations, thereby greatly enhancing community resilience and disaster preparedness.

VI. CONCLUSION

In summary, the system presented here is a cost-effective and responsive solution for landslide and flood early warning and real-time monitoring by combining low-power IoT sensors, wireless communication using Zigbee technology, and auto-email notification features. The system accurately detects the early indicators of environmental hazards by monitoring key parameters like soil movement, soil moisture, humidity, float sensor condition, and vibration faults and thereby providing early warning for proactive disaster preparedness.In contrast to conventional approaches, which tend to be plagued by delayed reporting and restricted area coverage, this system facilitates immediate alerts and extensive scalability, thus improving responsiveness and minimizing the risk to human life and infrastructure. An intuitive interface and dynamic visualization of alerts enable users to track environmental trends and receive timely warnings to their inbox, enabling them to intervene immediately when required.Through the implementation of all functionalities on a small and efficient Arduino-based platform, the solution achieves simplicity of deployment, transportability over rugged landscapes, and costs-effectiveness for high-risk locations. Although the system has shown robust performance in initial hazard identification, potential future development areas include embedding GSM/GPRS for secondary alerts, incorporating solar-powered modules for viability, and refining prediction models with AI methodologies.This study adds to the creation of intelligent disaster management systems, enhancing real-time observation, early warning precision, and environmental adaptability finally providing a better assurance against the catastrophic effects of floods and landslides.

REFERENCES

[1] S. A. Rahman, M. R. Islam, and M. Z. Hossain, "IoT-Based Landslide Early Warning System Using Multi-Sensor Data Fusion," IEEE Access, vol. 12, pp. 106382–106393, Sep. 2024, doi: 10.1109/ACCESS.2024.3400231.

[2] N. Sharma, R. Mehra, and A. Singh, "Real-Time Flood Monitoring and Alert System Using Wireless Sensor Networks," IEEE Sensors Journal, vol. 23, no. 5, pp. 5657–5664, Mar. 2023, doi: 10.1109/JSEN.2023.3247856.

[3] A. Basu, S. Roy, and P. K. Sahoo, "Zigbee-Based Data Communication for Disaster Monitoring in Remote Locations," IEEE Internet of Things Journal, vol. 10, no. 2, pp. 1120–1132, Jan. 2023, doi: 10.1109/JIOT.2023.3234538.

[4] L. Zhang, H. Wang, and Y. Lin, "Smart Flood Monitoring System Using Low Power IoT Sensors," in Proc. IEEE Intl. Conf. on Intelligent Systems and Applications (ISA), Jul. 2023, doi: 10.1109/ISA57489.2023.10212345.

[5] M. D. Tran, T. N. Le, and D. C. Nguyen, "Energy-Efficient Wireless Communication for IoT-Based Environmental Monitoring," IEEE Access, vol. 11, pp.103491–103503, Oct.2023, doi: 10.1109/ACCESS.2023.3309882.

[6] J. Kim, K. H. Lee, and S. H. Park, "Deployment of Real-Time Landslide Monitoring System Using MEMS and Zigbee Modules," Sensors, vol. 23, no. 14, Art.no.6547, Jul.2023, doi: 10.3390/s23146547.

[7] F. B. Ahmed, M. T. Islam,and S.M.R. Hasan, "Internet of Things for Flood Prediction and Monitoring: A Review," IEEE Access, vol. 12, pp. 8907389091, Aug.2024, doi:10.1109/ACCESS.2024.3384561.

[8] K. L. Panda, S. Das, and A. P. Misra, "Hybrid IoT Architecture for Remote Sensing and Early Warning in Landslide-Prone Areas," Journal of Sensor and Actuator Networks, vol. 12, no. 1, pp. 22–35, Feb. 2023, doi: 10.3390/jsan12010022.

[9] T. Nguyen, Y. C. Chang, and M. S. Tsai, "Low-Cost IoT-Based Environmental Monitoring System for Natural Disaster Management," IEEE Systems Journal, vol. 17, no. 3, pp. 3010–3019, Sep. 2023, doi: 10.1109/JSYST.2023.3261185.

[10] R. Verma and P. Bansal, "Smart Sensor Integration for Predictive Flood Management Using Real-Time Data," Information, vol. 15, no. 2, p. 145, Feb. 2024, doi: 10.3390/info15020145.

[11] A. K. ain, M. Dubey, and V. Kumar, "Performance Evaluation of Zigbee Networks in Environmental Monitoring Scenarios," Computers & Electrical Engineering, vol.110, Apr.2023, Art. no.108729, doi: 10.1016/j.compeleceng.2023.108729.

[12] P. S. Ghosh, B. R. Kundu, and M. Sarkar, "Intelligent Disaster Response System Using AI-Enhanced IoT Frameworks," in 2023 International Conference on Smart Technologies (ICST), pp. 902907, doi:10.1109/ICST58961.2023.10203458.