Arduino-Based Fire Extinguisher Robot

Shikhar Tripathi[1], Sidharth Sandilya[2], Rakesh Sharma[3]
Electronics and Communication, Galgotias College of Engg. and Tech.

***Abstract*— Fire hazards pose a significant threat to life and property, especially in areas that are difficult for humans to access during emergencies. This paper presents the development of a low-cost, Arduino-based fire extinguisher robot designed to autonomously detect and suppress small fires. The system employs flame sensors to locate the fire source and uses a motor-driven water pump for extinguishing. A motor driver module enables the robot to navigate toward the fire by processing real-time sensor data. The robot operates in autonomous mode, continuously scanning for fire and responding accordingly. The design is simple, affordable, and adaptable for environments such as homes, farms, and small industrial setups. By eliminating the need for temperature sensors and complex actuators, the prototype remains efficient and accessible. The proposed solution demonstrates a practical step toward automated fire safety systems in compact, hazardous, or remote zones.**

Key Words: Firefighting robot, Arduino, flame detection, autonomous system, water pump mechanism

I. INTRODUCTION

A. Background and Context

Fire hazards remain a significant concern in both residential and industrial settings, particularly in areas where immediate human intervention is challenging. Traditional fire safety measures, such as alarms and handheld extinguishers, heavily rely on human presence and prompt action. In scenarios where fires ignite in inaccessible or hazardous locations, this dependency can lead to delayed responses, exacerbating potential damage.

The integration of robotics into fire detection and suppression offers a promising solution. Arduino-based platforms, known for their affordability and versatility, have been instrumental in developing autonomous systems capable of identifying and extinguishing fires without human intervention [1]. By employing flame sensors for detection and water pumps for suppression, these robots can navigate toward fire sources and mitigate hazards effectively.

Research has demonstrated the feasibility of such systems. For instance, a study detailed the design of a fire- fighting robot that utilizes flame sensors to detect fire and a water pump mechanism for extinguishment, all controlled via an Arduino microcontroller [2]. This approach underscores the potential of combining simple electronic components to address complex safety challenges.

B. Problem Statement

Fire emergencies often occur in locations where human access is difficult, delayed, or dangerous—such as chemical storage areas, narrow mechanical rooms, or remote farm buildings. Traditional fire safety measures depend heavily on human presence for detection and response, which is not always practical. Delayed intervention can escalate minor incidents into major disasters, leading to significant property damage and endangering lives. In such scenarios, a mobile robotic solution capable of reaching the source and extinguishing the fire can offer a crucial advantage.

While some autonomous fire-fighting robots have been developed, they frequently involve complex architectures, such as temperature-based sensors or servo-controlled arms, which increase cost and limit scalability. There is a need for a simple, cost-effective solution that uses basic components like flame sensors and water pumps, without compromising on functionality. This project aims to fill that gap by designing a robot that operates autonomously using an Arduino microcontroller, basic sensors, and water-based extinguishing mechanisms—ideal for low-risk, small-scale environments.

C. Objectives of the Study

The primary objective of this project is to design and prototype an autonomous fire extinguisher robot using the Arduino platform, capable of detecting and extinguishing small fires without human intervention. The robot is required to traverse its surroundings, detect the flame's direction through flame sensors, and engage a water pump mechanism to effectively extinguish the fire. To achieve this, the project sets the following specific goals:

1. Develop an autonomous robotic system using Arduino, capable of movement control via motor drivers based on sensor inputs.
2. Integrate flame sensors to detect the presence and direction of fire.
3. Implement a water pump system that activates upon fire detection, ensuring timely extinguishment
4. Eliminate the use of temperature sensors and servo motors to simplify design and reduce cost, while maintaining effective functionality.
5. Ensure the robot is compact, affordable, and reliable for use in small-scale environments such as homes, workshops, or farms

D. Scope and Significance

This project focuses on developing a compact, Arduino- based autonomous fire extinguisher robot that can detect and suppress small fires using simple electronic components. The scope is limited to indoor or semi- enclosed environments such as residential areas, small warehouses, classrooms, or workshops where the fire risk is manageable, and water-based extinguishment is appropriate. The robot is not intended for large-scale industrial or high-risk chemical fires, nor does it integrate advanced features like wireless control, temperature-based detection, or AI-based navigation.

Despite this limited scope, the significance of the project lies in its affordability, accessibility, and simplicity. By excluding complex elements like temperature sensors and servo motors, the design remains cost-effective and easy to replicate, making it ideal for educational use and basic safety applications. The robot serves as a practical example of how embedded systems and basic robotics can be applied to solve real-world problems efficiently, potentially inspiring further innovations in automated safety systems.

II. LITERATURE REVIEW

A. Evolution of Firefighting Robots

The development of firefighting robots has been propelled by the necessity to enhance safety and efficiency in fire suppression activities. Traditional firefighting methods often expose personnel to hazardous environments, making it imperative to explore robotic solutions that can operate autonomously in such conditions. Initial firefighting robots were mainly controlled remotely, providing minimal autonomy and necessitating continuous human oversight. These initial models were equipped with basic sensors and lacked the capability to make real-time decisions, which restricted their effectiveness in dynamic fire scenarios. Over time, advancements in microcontroller technology, sensor integration, and control algorithms have led to the development of more sophisticated autonomous firefighting robots.

These contemporary systems are capable of detecting fire, navigating towards it, and commencing extinguishing procedures autonomously, without the need for human involvement.. For instance, a study by Rithik Krisna (2024) detailed the development of an autonomous firefighting robot using flame sensors and a microcontroller to detect and suppress fires automatically. The ongoing development aims to enhance the robot's mobility, fire detection accuracy, and extinguishing efficiency, while reducing size and cost to promote widespread use in domestic and industrial settings [3].

B. Role of Arduino in Fire-Fighting Robotics

Arduino microcontrollers have significantly impacted the development of fire-fighting robots by providing an affordable and versatile platform to integrate sensors, actuators, and control logic. Many researchers have leveraged Arduino UNO as the central processing unit to manage real-time fire detection and response. This includes interfacing with flame sensors to detect fire presence and intensity, which allows the robot to respond effectively by activating extinguishing mechanisms [4]. Arduino's flexibility also supports additional features such as wireless communication modules for remote control or alert notifications, enhancing the robot's operational capabilities.

The open-source nature of Arduino encourages experimentation and rapid prototyping, enabling researchers and developers to design and test various configurations efficiently. [5] Fire-fighting robots built around Arduino often control motors for navigation and pumps for water or foam discharge, allowing precise control in hazardous environments. This widespread adoption has made Arduino a cornerstone in creating cost-effective, scalable fire-fighting robots suitable for diverse applications ranging from residential safety to industrial hazard management.

C. Sensor Integration for Fire Detection and Navigation

Effective fire detection and safe navigation are critical for the performance of fire-fighting robots. Researchers have extensively incorporated a range of sensors with Arduino platforms to enhance these capabilities. Flame sensors are widely used to detect the presence and intensity of fire by sensing infrared radiation emitted by flames, enabling the robot to accurately identify fire sources. Ultrasonic sensors commonly assist in obstacle detection and avoidance, allowing the robot to navigate complex environments safely without human intervention [6].

Additionally, temperature sensors help monitor the heat levels in the surroundings, providing complementary data to flame sensors to avoid false alarms and improve detection accuracy. Some designs also utilize gas sensors to detect smoke or hazardous gases, increasing the system's ability to respond to fire-related emergencies comprehensively [7]. The integration of these sensors with Arduino microcontrollers enables real-time processing of environmental data, facilitating autonomous decision- making. This multi-sensor approach has been demonstrated to improve both the precision and reliability of fire-fighting robots during operations.

D. Control Systems and Communication Technologies

The control architecture and communication modules are vital components in Arduino-based fire-fighting robots, enabling effective coordination and remote operation. Many designs employ Arduino microcontrollers as the central processing unit due to their versatility, ease of programming, and cost-effectiveness. These microcontrollers process sensor inputs and control actuators like motors and water pumps, facilitating autonomous or semi-autonomous operation [8].

Communication technologies such as Bluetooth, Wi-Fi, and RF modules are commonly integrated to enable remote control and monitoring. Bluetooth offers a short-range, low-power solution for close-proximity control, while Wi- Fi and RF provide extended range and real-time data transmission. These communication features are essential, especially when robots operate in hazardous environments inaccessible to humans [9]. The combination of reliable control systems and robust communication technologies contributes significantly to the operational efficiency and safety of fire-fighting robots.

E. Challenges and Future Trends

Despite significant progress in Arduino-based fire-fighting robots, several challenges remain that limit their widespread deployment. One major issue is the robot's navigation and obstacle avoidance capabilities in complex, smoke-filled, or debris-laden environments. While ultrasonic and infrared sensors help, their effectiveness is often hampered by environmental conditions, affecting accurate fire localization and path planning. Battery life and power management also constrain operational duration, especially in prolonged fire incidents requiring continuous activity [10].

Future trends focus on enhancing autonomy and intelligence through the integration of machine learning algorithms and advanced sensor fusion techniques. This would allow robots to better interpret sensor data, adapt to dynamic fire scenes, and make real-time decisions with minimal human intervention. Additionally, advancements in wireless communication, such as 5G connectivity, promise improved remote monitoring and control with lower latency [11]. The incorporation of thermal imaging and gas sensors is also being explored to expand detection capabilities beyond visible flames. Addressing these challenges will be crucial in developing more reliable, versatile, and effective fire-fighting robots suitable for both industrial and domestic applications.

III. METHODOLOGY

A. System Design and Architecture

The fire-fighting robot's system design centers around the Arduino Uno microcontroller, chosen for its ease of use, versatility, and wide community support. This microcontroller acts as the control hub, processing data from various sensors and coordinating the robot's actions. Primary sensors include flame sensors that detect the presence and direction of fire by sensing infrared light emitted by flames. Ultrasonic sensors are integrated to help the robot navigate safely by detecting obstacles in its path, ensuring smooth mobility in complex environments.

The robot's movement is facilitated by DC motors, which are controlled through a motor driver module connected to the Arduino. This configuration enables accurate regulation of both speed and direction. In the event of a fire, a compact water pump linked through a relay is employed to disperse water upon confirmation of fire detection by the flame sensor. Power is supplied through a rechargeable battery pack, which makes the robot portable and suitable for indoor and outdoor environments. The overall system design emphasizes robustness and autonomy, enabling the robot to operate effectively without human intervention in hazardous scenarios.



Fig 1: Block Diagram of the Arduino-Based Fire Fighting Robot System

B. Sensor and Actuator Integration

The effective functioning of the Arduino-based fire-fighting robot is significantly dependent on the accurate integration of sensors and actuators with the main microcontroller unit. The primary sensors employed include flame sensors, ultrasonic sensors, and temperature sensors, each serving a critical role in fire detection and navigation. Flame sensors identify the presence of fire by detecting the infrared light emitted by flames, enabling the robot to pinpoint the precise location of the fire source. Ultrasonic sensors are used to measure distances and help the robot avoid obstacles while navigating through complex environments. Temperature sensors provide additional verification of fire presence by detecting abnormal heat levels.

These sensors are interfaced with the Arduino microcontroller via analog or digital input pins, ensuring real-time data acquisition. On the actuator side, DC motors enable the robot's movement, controlled through motor drivers interfaced with the Arduino. The water pump, responsible for extinguishing the fire, is activated based on sensor inputs. The coordination between sensors and actuators through precise programming allows the robot to autonomously detect fire, maneuver safely, and deploy extinguishing mechanisms effectively, all while minimizing human intervention.



Fig 2: Working principle of flame sensor for fire detection

C. Control Algorithm Development

The control algorithm forms the core of the fire-fighting robot's autonomous behavior, enabling it to sense its environment, make decisions, and execute actions efficiently. Programmed using Arduino IDE, the algorithm processes inputs from various sensors such as flame sensors and ultrasonic sensors to detect fire presence and obstacles. It follows a structured decision-making flow: first, continuously scanning for fire signals, then navigating towards the detected fire while avoiding obstacles, and finally activating the extinguishing mechanism upon reaching the target.

The logic incorporates threshold values for sensor readings, ensuring reliable detection despite noise or environmental variations. For instance, flame intensity beyond a set limit triggers movement towards the fire, while obstacle proximity signals a course correction. The program uses conditional statements and interrupts to prioritize critical actions, such as stopping immediately if an obstacle is too close or sending alerts in emergencies. This robust control system ensures the robot's autonomy, responsiveness, and safety during firefighting operations.

The control algorithm forms the core intelligence of the fire-fighting robot, enabling it to interpret sensor inputs and execute appropriate actions in real-time. It continuously monitors data from the flame sensor to detect fire presence and processes signals from

obstacle sensors to avoid collisions. Based on these inputs, the microcontroller executes decision-making routines to control the movement of motors and activate the water pump for extinguishing fires. The algorithm also incorporates fail-safe checks and timing sequences to ensure smooth operation and prevent false triggers. Overall, this structured control logic ensures that the robot operates autonomously and effectively in dynamic and hazardous fire environments.



Fig 3: Control Algorithm Flowchart of Fire-Fighting Robot

D. Testing and Calibration

Testing and calibration are essential to ensure the fire- fighting robot operates accurately and reliably in real-world scenarios. The process begins with individual testing of each sensor, particularly the flame sensor, to verify its sensitivity and detection range. Calibration involves adjusting sensor thresholds so the robot can distinguish between actual fire signals and false positives caused by ambient light or reflections. Similarly, motor functions are tested for precise maneuverability, including obstacle avoidance and navigation toward the fire source.

Calibration also extends to the water pump system, ensuring appropriate timing and flow rate to effectively extinguish flames without wasting resources. Repeated trials in controlled environments allow fine-tuning of sensor readings and actuator responses. These iterative adjustments help improve the robot's performance, minimizing errors and increasing operational confidence. Thorough testing and calibration guarantee the robot's readiness for unpredictable fire emergencies while maintaining safety and efficiency.

E. Power Management and Safety

Effective power management is critical to ensure the fire-fighting robot functions smoothly and safely during operation. The robot typically uses a rechargeable lithium- ion or lithium-polymer battery pack, providing a stable voltage supply suitable for the Arduino microcontroller, sensors, and actuators. Voltage regulators are employed to maintain consistent power levels, preventing damage from voltage fluctuations or overloads.

Safety features are integrated to protect both the robot and its surroundings. Overcurrent protection circuits prevent excessive current draw, which could lead to overheating or component failure. Additionally, thermal sensors can monitor the robot's internal temperature to avoid overheating, especially when operating near fire sources. Power management also includes low battery detection, allowing the robot to return to a safe location or shut down gracefully, avoiding abrupt failures during critical tasks. These measures collectively enhance reliability, longevity, and operational safety of the robot in hazardous environments.

IV. COMPONENTS

A. Arduino Uno Microcontroller

The Arduino Uno serves as the central processing unit of the fire-fighting robot. It is a widely used microcontroller board based on the ATmega328P, known for its ease of programming, reliability, and extensive community support. In this project, the Arduino Uno is responsible for reading sensor inputs, such as from the flame sensor, and executing control algorithms to navigate the robot and activate the extinguishing mechanism.



Fig 4: Arduino Uno Microcontroller

Its multiple digital and analog input/output pins enable seamless interfacing with sensors, motors, and other peripherals. The Arduino's onboard

memory and processing speed are sufficient for real-time decision- making, which is critical for fire detection and prompt response. Additionally, programming the Arduino using the Arduino IDE allows for flexible updates and improvements to the robot's logic. Overall, the Arduino Uno's versatility and robust performance make it an ideal choice for this autonomous fire-fighting application.

B. Flame Sensor

The flame sensor used in this project is an infrared (IR) based sensor designed to detect the specific wavelength emitted by fire or flame sources. This sensor plays a critical role in identifying the presence of fire by sensing the infrared light intensity, which is generally around the 760 nm to 1100 nm wavelength range. When the sensor detects this IR radiation, it sends an analog or digital signal to the Arduino microcontroller for further processing.

In the system, the flame sensor is positioned strategically to monitor the surroundings continuously. Its sensitivity to infrared light enables the detection of flames even from a certain distance, making it effective for early fire detection. The sensor provides reliable real-time data that helps the microcontroller trigger alarms or fire extinguishing mechanisms promptly. Moreover, this sensor is compact, energy-efficient, and easy to interface with the Arduino board, making it a suitable choice for fire detection in embedded robotic applications.

In this project, the module receives control signals from the Arduino and translates them into the necessary voltage levels for the motors. The IN1, IN2, IN3, and IN4 pins are connected to the Arduino's digital outputs, allowing full control over motor rotation direction, while the ENA and ENB pins receive PWM signals to adjust speed.

The L298N is chosen due to its robust dual H-bridge configuration, enabling efficient motor control in both forward and reverse directions. Additionally, it includes an onboard 5V voltage regulator, which can be used to power the Arduino if needed. However, in this design, a dedicated power source is preferred to ensure consistent operation. Its compact size, affordability, and ease of use make the L298N a widely adopted choice in robotic applications.



Fig 5: Flame sensor (infrared sensor)

C. DC Motors

DC motors are employed in this fire extinguisher robot to facilitate movement and navigation. These motors transform electrical energy into mechanical movement, allowing the robot to advance towards the source of the fire upon detection. In the current design, a pair of DC motors is connected to the wheels, allowing for differential drive control—meaning the robot can move forward, backward, and turn by varying the speed and direction of each motor.

Controlled through an L298N motor driver module, these motors receive signals from the Arduino to execute motion commands based on sensor inputs. The speed and direction of the motors are modulated using pulse width modulation (PWM) signals, which the Arduino generates dynamically as per the control algorithm. The motors are powered by a rechargeable battery pack, ensuring sufficient torque and operational time for the robot to function effectively. The selection of DC motors was influenced by their straightforward design, affordability, and seamless integration into systems based on microcontrollers. Their responsiveness and compatibility with common driver modules make them ideal for autonomous robotic applications.

D. L298N Motor Driver Module

The L298N motor driver module plays a critical role in controlling the direction and speed of the DC motors used in the fire extinguisher robot. Since microcontrollers like Arduino cannot directly supply the current required by motors, the L298N acts as an interface that safely bridges this gap. It allows bidirectional control of two DC motors

simultaneously and supports PWM input to regulate motor speed.



Fig 6: L298 Motor Driver Module

V. WORKING PRINCIPLE

A. Overview of Operation

The Arduino-Based Fire Extinguisher Robot operates autonomously to detect and suppress fires using a combination of sensors, actuators, and control logic. When powered on, the robot enters an active monitoring state, continuously scanning its surroundings using the IR flame sensor. Upon detecting a flame within its range, it triggers the decision-making algorithm embedded in the Arduino microcontroller. This initiates a movement sequence, guiding the robot toward the source of the fire using preprogrammed logic that controls the motor driver.

Once in close proximity to the flame, the Arduino activates a relay module, which switches on the water pump. The pump sprays water through a nozzle, targeting the fire. The robot continues this extinguishing action until the flame sensor no longer detects a flame, indicating that the fire has been suppressed. The robot then stops spraying and returns to a standby or patrol state, ready to detect any new fire instances. This cycle allows the robot to operate independently in a dynamic environment, offering a reliable, low-cost fire response solution for domestic or small industrial applications.

B. Sensor Activation and Fire Detection

The core fire detection mechanism of the robot is based on an IR flame sensor, which responds to infrared light emitted by flames. Upon startup, the Arduino initializes the sensor and continuously reads its digital output. When no fire is present, the sensor maintains a LOW state. However, when it detects a flame, it switches to HIGH, instantly triggering the next stage of the robot's response.

The IR flame sensor operates effectively within a limited range and angle—typically around 60–120 degrees and up to 1 meter—making it ideal for focused fire detection in enclosed spaces. To avoid false positives caused by ambient IR sources (like sunlight), the system is calibrated during development to fine-tune the sensor's sensitivity using its onboard potentiometer. The sensor's signal is directly connected to a designated digital pin on the Arduino Uno, which constantly polls it using simple digitalRead() commands. This input acts as the primary trigger in the robot's decision-making algorithm, initiating movement and fire suppression actions when flames are detected.



Fig 7: IR Flame Sensor Detection Mechanism

C. Decision-Making and Movement Logic

The robot's decision-making process is governed by the Arduino Uno, which executes a simple yet effective control logic using digital sensor inputs. Once powered on, the robot enters a scanning mode where it continuously reads data from the IR flame sensors. Depending on which sensor detects fire — left, right, or center — the Arduino determines the relative direction of the flame.

Using conditional statements (if conditions) in the program, the robot moves forward if the center sensor detects fire, turns left if the left sensor is triggered, or right if the right sensor is active. This directional movement logic allows the robot to navigate toward the fire source with reasonable accuracy. If no sensor detects fire, the robot continues to patrol or rotate, scanning the area.

```
else if (digitalRead(Forward_S) ==0&&
         (digitalRead (Forward_F) ==0)
{
//Move the robot forward
digital Write (LM1, HIGH);
digitalWrite (LM2, LOW);
digitalWrite (RM1, HIGH);
digitalWrite (RM2, LOW);
fire=true;
}
```

Fig 8: Code snippet for robot to move in forward direction upon detecting fire

This logic not only ensures the robot approaches the fire correctly but also prevents erratic movements. The microcontroller continually evaluates sensor input in real time, enabling a reactive navigation model suitable for dynamic environments. This structure balances autonomy with simplicity, ideal for cost-effective fire-fighting solutions.

D. Fire Detection and Suppression

The core functionality of the robot hinges on accurate flame detection and timely suppression. The IR flame sensors play a crucial role in identifying the presence of a fire by detecting infrared radiation emitted by flames. When a sensor senses a flame, it sends a LOW signal to the Arduino Uno, which interprets this as fire detection and initiates the movement logic to approach the source. Once the robot aligns itself directly in front of the fire usually when the center flame sensor is triggered, it activates the DC fan mounted at the front. The fan functions as the primary suppression mechanism, generating enough airflow to extinguish small to medium-sized flames effectively. The suppression continues for a few seconds before the system re-evaluates whether the fire has been put out by checking if any sensors are still triggered.

```
voidput_off_fire()
{
delay (500);
digitalWrite (LM1, HIGH);
digitalWrite (LM2, HIGH);
digitalWrite(RM1, HIGH);
digital Write(RM2, HIGH);
digitalWrite(pump, HIGH); delay(500);
fire=false;
}
```

Fig 9: Code snippet for pump activation to suppress fire

This cycle of detection, approach, and suppression is automated and can repeat as long as fire is detected. The simplicity of using a fan instead of water or chemical extinguishers also ensures safety, low cost, and suitability for electronics-sensitive environments like labs or offices.

E. Obstacle Avoidance and Navigation

Effective navigation in complex environments is critical for the robot's autonomous operation. Although this project does not utilize ultrasonic sensors, the robot uses its three IR flame sensors not only for fire detection but also for basic navigation by continuously monitoring the presence or absence of flame signals. The robot moves forward while monitoring these sensors to stay on course toward the fire source.

Additionally, the robot is designed with simple obstacle avoidance capabilities using its differential drive system. By controlling the speed and direction of the two DC motors independently, the robot can make turns or stop to prevent collisions with objects detected indirectly through sensor feedback or when the flame signals fluctuate unexpectedly.

The navigation algorithm runs continuously in the microcontroller, processing sensor inputs and adjusting

motor commands in real time. This ensures the robot maintains its trajectory toward the detected fire while avoiding obstacles that may impede progress, thereby enhancing operational reliability in cluttered or indoor spaces.

VI. MERITS

The proposed Arduino-based autonomous fire-fighting robot demonstrates several key advantages that make it suitable for domestic and industrial fire safety applications. Its design focuses on reliability, cost-effectiveness, and ease of use, addressing common limitations in traditional fire suppression methods. These merits emphasize the robot's potential to enhance safety and reduce human risk in hazardous environments.

1. Autonomous Operation and Real-Time Fire Detection: The integration of flame sensors with microcontroller-based control enables the robot to detect fires and respond without human intervention. This reduces the need for manual firefighting efforts, minimizing the risk to human personnel and allowing faster response times.

2. Cost-Effective and Simple Design: Utilizing readily available components like Arduino Uno and IR flame sensors keeps the system affordable and accessible. This cost efficiency supports widespread adoption in both residential and small- scale industrial settings.
3. Enhanced Mobility and Navigation: The differential drive system combined with sensor feedback allows the robot to navigate towards the fire source effectively, even in constrained or cluttered spaces, improving its operational reach.
4. Ease of Maintenance and Scalability: The modular design and open-source hardware/software enable easy maintenance and potential upgrades, allowing customization for diverse firefighting requirements.
5. Cost-Effectiveness: The robot utilizes affordable and widely available components like Arduino and IR flame sensors, making it an economical solution for fire detection and suppression. This cost-efficiency supports easier adoption in both residential and small-scale industrial settings.

VII. DEMERITS

Despite its advantages, the Arduino-based fire-fighting robot also presents certain limitations that need to be addressed for broader application and improved performance. Recognizing these demerits helps guide future enhancements and realistic expectations of the system.

1. Limited Fire Detection Range: The flame sensors used have a constrained detection distance and may struggle in environments with heavy smoke or poor visibility, reducing reliability in large or complex fire scenarios.
2. Basic Obstacle Avoidance: Without advanced sensors like ultrasonic or LIDAR, the robot's navigation is limited to simple obstacle detection, which can hinder its movement in cluttered or unpredictable environments.
3. Dependence on Battery Life: The robot's operational time is restricted by battery capacity, requiring frequent recharging or replacement during extended firefighting missions, which could delay response.
4. Lack of Sophisticated Decision-Making: The control algorithm is rule-based and lacks advanced AI or machine learning capabilities, limiting its adaptability to varying fire conditions or complex environments.

VIII. CONCLUSION

A. Summary of Achievements

The Arduino-based autonomous fire-fighting robot project successfully achieved its primary goal of developing a low-cost, reliable system capable of detecting and extinguishing fires without direct human intervention. Through the integration of flame sensors and an efficient control algorithm, the robot demonstrated timely and accurate fire detection, initiating extinguishing actions autonomously. The system's design balanced simplicity with functionality, ensuring ease of replication and potential scalability.

B. Practical Implications and Benefits

This project underscores the significant benefits of employing robotics in hazardous firefighting scenarios. By minimizing human exposure to dangerous environments, the robot enhances safety for firefighters and reduces potential damage to property. The use of widely available components such as Arduino and flame sensors contributes to the robot's affordability, making it a practical solution for both domestic and industrial applications. Moreover, the modular nature of the design facilitates future upgrades and adaptations to specific use cases.

C. Future Scope and Recommendations

While the current implementation meets essential functional requirements, there are opportunities for improvement. Future work could focus on enhancing mobility with advanced locomotion mechanisms, incorporating additional sensors for multi-parameter fire detection, and enabling wireless communication for remote monitoring and control. Expanding the robot's autonomy and adaptability would increase its effectiveness in diverse and complex fire scenarios. Overall, this project lays a strong foundation for continued innovation in autonomous fire-fighting technologies.

REFERENCES

[1] Rahul Ray, Sunny Singh, Vinay Kumar Gupta, and Sandeep Maurya, "*Design and Study of Fire Fighting Robot*," International Journal of Engineering Research & Technology (IJERT), vol. 6, no. 4, pp. 203–206, Apr. 2017.
[2] Abdul Waris Memon, Juan Du, Abdul Haleem

Abro, Sharmeen Iftikhar Shah, and Moazzam Ali Bhutto, "*Design and Implementation of Fire Extinguisher Robot with Robotic Arm*," MATEC Web of Conferences, vol. 160, pp. 06008, Apr. 2018.

[3] R. Krisna, *"Automatic Fire Detection and Extinguishing Robot Using Arduino*," element14 Community, 31 May 2024..

[4] Patel Mohd. Rehan Adilshah, Sarvesh Rajiv Kukde, Ussaid Faiyyaz Shaikh and Jagdish Bhalchandra Choudhari "Autonomous Fire Fighting Robot Using Arduino," *International Journal of Research in Engineering, Science and Management (IJRESM)*, vol. 5, no. 3, pp. 107-110, 2022..

[5] L. Guruprasad, M. U. Yashwanth, P. Vydyanath Prasad, B. V. Shreekara, and Gangappa "*Autonomous Fire Fighting Robot*," International Journal of Research in Engineering, Science and Management (IJRESM), vol. 2, no. 1, pp. 34-37, 2019..

[6] Dr Rajendra R Chaudhari, Sunil R Kewate and C.R. Chaudhari, "Prototype of Fire Fighting Robot," *International Journal of Scientific Research in Science and Technology (IJSRST)*, vol. 11, no. 1, pp. 1-4, 2024.

[7] Rahul Ray, Sunny Singh, Vinay Kumar Gupta and Sandeep Maurya, "Design and Study of Fire Fighting Robot," *International Journal of Engineering Research & Technology (IJERT)*, vol. 8, no. 5, 2020..

[8] Maruthi Naik R K, Chandrashekhar R Kambli, Raghu S and Sanjay Kumar K, Mandara V, "Fire Fighting Robot with a Voice," *International Journal of Engineering Research & Technology (IJERT)*, vol. 9, no. 7, pp. 1–3, 2021.

[9] Mohith S Reddy, et. al., "Design And Implementation Of Autonomous Fire Fighting Robot," *Turkish Journal of Computer and Mathematics Education*, vol. 12, no. 11, pp. 1573–1582, 2021.

[10] Nurain Izzati Shuhaimi et al., "Autonomous Fire Fighting Robot with Smart Monitoring System," *International Journal of Academic Research in Business and Social Sciences*, vol. 11, no. 6, pp. 1122–1135, 2021.

[11] Prithviraj Anil Rathod et al., "Arduino Fire Fighting Robot With SMS And Call Alert," *International Journal for Scientific Research & Development (IJSART)*, vol. 7, no. 3, 2021.