Gas Sensing and Alert Interface for Safety Monitoring

Aaditi Thibe[1], Abhirup Sengupta[2], Pravin Agarwal[3], Apurva Bagadi[4]
[1,2,3,4,] *Department of Electronics and Telecommunication Engineering, Vishwakarma Institute of Technology, Pune, 411037, Maharashtra, India*

***Abstract*- An ESP8266 microcontroller, MQ-2 gas sensor, and Blynk platform are used in this study to create an Internet of Things-based gas level monitoring system. An I2C-enabled LCD shows the readings from the system's gas concentration measurement. When gas levels above a certain threshold, it instantly notifies users via smartphone notifications, a buzzer, and LEDs. Using Blynk, the system incorporates a timer for recurring monitoring and virtual dashboard updates. For improved safety in gas detection applications, this technology provides a scalable and affordable solution.**

***Index Terms*-[Gas detection, IoT, ESP8266, Blynk, real-time monitoring]**

I. INTRODUCTION

Gas leakage detection is vital in ensuring safety in residences, industries, and commercial environments; undetected leaks could create catastrophic situations like fires, explosions, or health hazards. This project introduces a real-time monitoring and alert system for gas leakage using the MQ series sensor with ESP8266 acting as the microcontroller and the IoT interface for real-time monitoring and alert through the Blynk platform, thus upgrading its safety measures with minimal deployment complexity.

The MQ-series gas sensor measures the concentration of gases in the surrounding atmosphere. Data is thus captured by the ESP8266 microcontroller that processes the signals and sends them for interpretation. Once the level of gas surpasses a threshold, the system triggers several safety means: a buzzer sounds an alarm, red and green LEDs detect the state of gas in the air, and a servo motor disperses the gas collected, minimizing the possibilities of its ignition. An LCD module displays real-time gas levels and alerts locally, ensuring accessibility even without internet connectivity.

Fully integrated with the Blynk IoT platform, it allows users to remotely monitor gas level through a smartphone or a web-based dashboard. Virtual pins transmit the sensor readings to the platform, while push notifications and event logging ensure immediate user awareness of dangerous gas concentrations. A virtual gauge widget appears with gas levels so that it is easy to interpret the data.

This project validates the significant potential of IoT in advancing safety automation. It is affordable, reliable, and scalable enough for deployment in multiple environments. The inclusion of local alerts, real-time visualization of data, and remote monitoring has helped the system address key safety concerns to a good extent. After all, it portrays the transformative role of IoT in bringing about proactive, responsive solutions to everyday safety challenges.

II. METHODOLOGY

In this project, IoT-enabled gas leakage detection and alerting has been proposed using the Blynk platform in which for real-time monitoring and alerts. Here, ESP8266 forms the microcontroller that interfaces with the MQ-series gas sensor for measuring the concentration level of gases.

Some other subsystems are lights for status indication, a buzzer for acoustic warning, an LCD for local display of messages and also a fan servo to help as a dispersing method of the accumulation of gas in case it senses a leak.

The same is the case with hardware setup. Gas sensor is stuck to the A0 analog pin in ESP8266. LEDs are connected with pins D4 (Green) and D5 (Red), buzzer with D6 pin, and servo motor with D7 pin.
LCD module is connected with the ESP8266 through I2C connection at SDA and SCL pins. Thus it also aids in giving quite accurate detection and immediate response to variation in the gas levels.

The ESP8266 connects to the WiFi through the Blynk library. It integrates very smoothly with the cloud-

based dashboard of Blynk. Periodically, sensor readings are transmitted to application via virtual pins for users to check gas levels from a remote mobile device in real-time.

This will activate the system to take its self-defence measures, starting with the red LED on; it will activate the buzzer and make the servo motor rotate to let the fan blow. It would send push notifications by Blynk and log for later review. It provides for a pretty detailed dashboard, providing virtual gauges for the visualization of gas concentration and also has a notification system for alerts. In this project, it is illustrated how IoT-based technologies can enhance the safety associated with gas leakage detection and prevention, low-cost, reliable, and scalable.

A. SOFTWARE DEVELOPMENT

The software for this gas leakage detection system is developed using the Arduino IDE and takes advantage of the ESP8266 microcontroller with IoT features. Primary programming involves interfacing MQ gas sensors with other peripherals like LEDs, a buzzer, an LCD display, and a servo motor. Logic for the system written in C++ utilizes libraries such as `BlynkSimpleEsp8266` for IoT connectivity and LiquidCrystal_I2C for LCD handling as well as Servo for motor control.

The beginning of the code would involve hardware initialization, such as pin input and output configuration and WiFi connection with the Blynk cloud. The sensor was reading through an analog input pin; its readings would be processed to see if the gas levels went past the predefined threshold. Accordingly, activation of LEDs, buzzing, rotation of the servo, and LCD update would happen.

Real-time gas levels are transmitted to the Blynk platform using virtual pins. The readings are displayed to the end-user on a very user-friendly dashboard. Notifications for high gas levels ensure immediate alerts to the user. Software is designed with reliability, scalability, and efficient resource management in mind and would be safe enough for real-world deployment in safety-critical environments.



Fig 1- Serial Monitor of Gas Sensor

C. HARDWARE DEVELOPMENT

The hardware for this gas leakage detection system involves an ESP8266 microcontroller, an MQ-series gas sensor, LEDs, a buzzer, a servo motor, and an LCD display. The MQ-series gas sensor is linked to the analog input of the ESP8266 for detecting gas concentrations. Two LEDs (green and red) are linked to digital pins for status indication—green when gas levels are normal, while red indicates high levels. The buzzer has been joined to another digital pin to ring an alarm when dangerous gas concentrations have been detected.

Fig 2- Node MCU ESP 8266 as Microcontroller

Fig 3- MQ-2 Gas Sensor to detect hazardous gas

A servo motor, acting as a fan, is connected to a pin to activate when gas levels are at a threshold. An I2C LCD module will display real-time data on gas levels. All these work in tandem for local and remote monitoring to ensure comprehensive safety management.

III. RESULTS AND DISCUSSIONS

The gas leakage detection system measures gas concentrations successfully and monitors them online using the Blynk IoT platform. In case of excessive gas levels beyond the threshold, the system activates safety devices that trigger a warning buzzer, LEDs, and a servo motor acting as a fan, thus dispersing gas and minimizing potential risks. Local feedback is achieved by the display on the LCD; however, at a remote end, data is shown in the dashboard of the Blynk portal. The system has proven to be reliable in detecting gas leaks and sending alerts in timely manners. To be noted here is that the future changes could improve its accuracy along with reliability with machine learning for predictive analysis or integration of more sensors for broader hazard detection.

IV. FUTURE SCOPE

1.Integration with Other Sensors: Additional sensors that are part of the system can include environmental sensors; for example, temperature, humidity, or smoke detectors. This would increase the range of hazards that the system could detect and respond to.
2.Machine Learning for Predictive Analysis: This system will use machine learning algorithms that can analyze historical data on the gas sensors to predetermine leak patterns or hazards that will occur before they happen. The system will thus enhance proactive safety practices, reducing false alarms.
3.Enhanced Connectivity and Automation: Future versions may interface with smart home or industrial automation systems. This will allow automatic actions such as closing gas valves, controlling ventilation, or even alerting emergency services to enhance the efficiency and responsiveness in case of a gas leak.

V. CONCLUSION

This gas leakage detection system uses IoT technology to include real-time monitoring in residential, industrial, and commercial areas. With the integration of an MQ-series gas sensor and an ESP8266 microcontroller along with the Blynk application, it surely detects quick leaks of gas immediately. As a response, it will trigger the safety measures consisting of LEDs, buzzers, and a servo motor to spread out the toxic gas. It has localized alerts and remote surveillance, which allows quick responses to emergent threats, thus limiting the possibilities of incidents. The adaptable configuration also allows monitoring of gas concentrations with a mobile application, thus enhancing access and control. Expected improvements may include predictive analytics and smart home connectivity, thus making it an all-inclusive, adaptable approach towards preventing gas-related incidents in various settings.

REFERENCES

[1] Bobadilla, J., Ortega, F., Gonzalo, J., & Ruiz, J. (2013). Recommender Systems Survey. Knowledge-Based Systems, 46, 109-132. doi:10.1016/j.knosys.2013.03.012
"IoT Based Smart Gas Monitoring System" – A. Pandey, D. Pandey, IEEE International Conference on Power Electronics, Intelligent Control and Energy Systems (ICPEICES), 2018.
[2] "IoT-Based Gas Leakage Detection System with Arduino and Cloud Integration" – R. K. Gupta, A. Jain, IEEE International Conference on Computing, Communication, and Automation (ICCCA), 2019.
[3] "Gas Leakage Detection and Smart Alerting System Using IoT" – S. M. S. Kumar, A. Kumar, IEEE International Conference on Communication and Signal Processing (ICCSP), 2020.
[4] "A Low-Cost IoT-Based System for Gas Leakage Detection Using Wireless Sensor Networks" – H. P. Singh, K. Singh, IEEE International Conference on Internet of Things and Applications (IOTA), 2019.
[5] "A Reliable IoT-Based Wireless Sensor Network for Gas Leakage Detection and Control in Smart Buildings" – J. Kim, M. Lee, IEEE Access, 2021.
[6] "Development of Smart Gas Monitoring System Using IoT and Cloud Integration" – N. S. Saxena, V. Singh, Journal of IoT and Cloud Computing, 2019.
[7] "IoT-Based Gas Leak Detection and Localization System with Real-Time Notification" – M. R. Chowdhury, A. Islam, IEEE Sensors Journal, 2020.
[8] "Design of an IoT-Based Gas Detection System Using ESP8266 and MQTT Protocol" – P. R. Mandal, IEEE International Conference on Electronics, Computing and Communication Technologies (CONECCT), 2019.

[9] "IoT-Based LPG Gas Leakage Detection System Using MQ Sensors and NodeMCU" – S. Sharma, A. Mishra, International Journal of Recent Technology and Engineering (IJRTE), 2019.

[10] "A Comparative Study on IoT-Based Gas Detection Systems: Sensors, Platforms, and Protocols" – T. B. Nguyen, IEEE Internet of Things Journal, 2021.