# Real-Time Attendance Tracking System Using Facial Recognition

Prachi Parmar[1], Palak Agrawal[2], Kamini Vishwakarma[3,] Hare Ram Jha[4], Prachi Hingole[5]
[1]*Student, CSE, Medicaps University*
[2] *Student, CSE, Medicaps University*
[3]*Assistant Professor, CSE, Medicaps University*
[4] *Assistant Professor, EC, Medicaps University*
[5] *Student, CSE, Medicaps University*

***Abstract*—Facial recognition is a highly efficient image processing application with a significant impact on technology. Identifying human faces is a critical topic, especially for validating student attendance. The attendance mechanism uses facial biostatistics. Recognition depends on high-resolution monitoring and modern computing technology. The aim of the design of this system is to digitize the established way of taking attendance, which utilizes verbal exchanges and maintained records. Current presence methods are time-consuming and at risk of distortion due to manual input. Old attendance marking as well as current biometric technologies is at risk to fake proxies. This paper seeks to overcome these difficulties. The suggested system makes use of the OpenCV, Haar cascade method, Pandas, MySQL and Dlib. The reports of ttendance are generated using facial recognition and exported in Spreadsheet format. The method is tested under several settings, including lighting, head motions, and distance between the camera and student. Intensive testing assesses total complexity and correctness. The suggested system effectively manages classroom attendance, reducing manual labor and time sources and facial expressions, with the identification rate as the primary statistic.***

***Index Terms*—About four(minimum) key words or phrases in alphabetical order, separated by commas.**

## I. INTRODUCTION

Facial analysis, like voice identification, fingerprint identification and iris identification provides effective biometric authentication by recognizing persons in images and Clips. Real-life uses include guiding the visually challenged, conducting forensic analysis, finding absent individuals, and securing mobile devices. The project focuses on creating a facial recognition-based attendance system. It outperforms previous approaches (location based, RFID, and fingerprint) by eliminating substitute attendance and Delivering verified data. To reduce human workload, the system captures video in the classroom, compares faces to stored photographs, and logs attendance. Traditional approaches struggle with lighting and position, but the suggested solution improves accuracy through feature extraction and analysis. The system is tested in several scenarios, including different light sources and facial expressions, with the identification rate as the primary statistic.

## II. LITERATURE REVIEW

Our study is inspired by earlier research on facial recognition, notably In this strategy, we focus on facial traits. Improved recognition efficiency by concentrating on two-dimensional facial characteristics rather than sophisticated three-dimensional models. Geometry[1]. Face recognition relies on computer vision technologies to assess facial features and verify identities. Face recognition consists of two main components: detection and matching. This technology analyses facial traits and processes data from photos or video sources[2]. At the time of the software design phase, user demands were converted into a form that could be enacted by developers. The system design method started with the identification of the logical structure of the system and progressed to the identification of its functionality in the real world. We used Object-based system design to describe processes and data through visual aids such as diagrams. These communication sources are functional and easy to understand for stakeholders. [3].All students in the class will register and share the required information. Registration will be followed by

the taking of pictures and storing them in a dataset. The classroom's live video stream will detect faces during each session. The detected faces will be compared with pictures in the dataset to verify if they are a match and, if not, then attendance without a picture, will be also taken for that student, if the submitted face picture was not a match. At the end of every session, the instructor will receive an email with a list of absent students. [4]. We have proposed a method that will start with registering the students in the system. The approach involves acquiring and pre-processing photos, detecting faces with the Haar Cascade classifier, building a dataset, and recognizing faces with the LBPH algorithm [5].The smart attendance automation system with facial recognition has multiple key components that operate together seamlessly. The method begins with an input layer that gathers facial images. These images are then processed and ready in a pre-processing layer. During the early phase, tasks may include

resizing photographs, enhancing Lighting and color selection, as well as face feature extraction for recognition. Following priming, the photographs are routed to the facial detection layer for processing. The layer helps to recognizes faces and identifies people using deep learning algorithms that have been trained on a dataset. This layer may involve model fine-tuning and functional testing. After correctly detecting a face, the attendance management layer takes control and manages attendance data. The layer's tasks may include running reports, updating records, and tracking presence. [6]. The system effortlessly and automatically records student attendance utilizing a facial recognition algorithm alone. The black box facial recognition algorithm records attendance in the following manner. When the lesson starts, the file stores the begin time and room number. In every 10 minutes, an image is captured of the class. The facial recognition algorithm scans the images that contain students (understanding that in the gap of 10 minutes the algorithm can scan images). A student's presence for a course is recorded if the student is identified in a minimum number of 'n' pictures, as stipulated by the lecturer. The versatility of this approach allows students to exit in case of emergency without penalty to their attendance [7]. Our facial recognition algorithm simply analyses the entire face as a singular input. unlike traditional methods that separate facial components such as the eyes and lips. The current method enhances our comprehension of face identification in literacy examinations because it clarifies a two-step method: first establishing whether the visual information is facial or non-facial and then performing an in-depth search for functional interpretation and appearance.

## III. METHODOLOGY

Facial detection has two components: pre-detection processing, which could be considered "facial recognition" and actual recognition and detection, which is referred to as "feature matching and extraction".

### A. Facial localization:

This stage identifies and positions human faces inside a picture. During this stage, segments will be generated that contain each detected face in the input image. The objective here is to build a reliable face recognition system that is easy to use.

### B. Facial segmentation:

Face is followed by face extraction (segmentation) occurs when the software isolates and returns the facial features from the background image. This technique crops detected faces using the marking boxes created during face detection. To improve accuracy, the extracted facial parts are normalized for uniform size, orientation, and lighting conditions before further processing.

### C. Face Recognition:

Once facial photos are captured, the identification process begins. Building a face database is essential for automatic recognition. A number of photos are used to extract particular features, and later recorded in a database. The technique involves detecting and extracting facial traits from an input image, comparing them, and storing the results in a database.

### D. Types of Algorithms:

The system uses a variety of algorithms, including:

*1. Eigen Faces:*

This methodology uses statistical approaches to identify characteristics that influence photos. The training database is critical to the recognition process

because it treats photographs from different classes as if they were one.




*2. Linear Discriminant Analysis (LDA):*

More commonly referred to as Fisher faces, the Linear Discriminant Analysis is an iterative method, and also a type of principal components analysis (similar to Eigen faces). The primary difference is in how the algorithm treats classes. Fisher Faces uses LDA to differentiate between images from different classes during the training phase, while Eigen faces does not. Fisher Faces distinguish between images of distinct classes, but the aggregate average influences each image.

*3. Local Binary Feature Histograms:*

Local Binary Feature Histograms are an important texture descriptor in image analysis. The functionality assesses individual pixels against their neighboring pixels. LBP tries to describe an image's local structure by encoding the interaction between its primary elements. The intensity of a pixel and its neighbours. Encoding typically involves thresholding pixel values to create binary patterns. The binary patterns are transformed into decimal values, resulting in a histogram. In facial recognition and attendance management systems, proper identification of persons requires good feature extraction methods.

*4. Haar Classifiers:*

classifier or Haar cascade classifier is a machine learning-based object detection system that helps identify objects in a digital image. It is mostly used for face identification, but can also recognize other objects with training. Haar features, like convolutional kernels, help detect visual features. These features include different sorts; this includes edge, line, and four-rectangle characteristics. Each feature has exactly one value based on pixels' contrast in black and white rectangles. There are many advantages to Haar cascades, based on Haar features, and cascaded structure. Improve processing efficiency to facilitate live object tracking in images and video. Resizing the search window allows the system to distinguish things of various sizes. Haar cascades are versatile and can recognize a wide range of objects when trained with sufficient datasets.

## IV. PROPOSED SYSTEM

Impactful attendance monitoring is crucial for maintaining efficient processes in current organization. Established face-to-face attendance system relies on manual processes that are susceptible to human error and take a large amount of time and resources to locate the student. The new attendance technology allows for attendance to be managed in an more effiecient way using facial recognition to identify a student. Facial recognition is a recombinant identifier of biological data and can be utilized for attendance recording. Facial recognition systems are able to identify individuals based on facial features, such as facial textures and patches to identify and validate accurately. The technology presented is much superior than traditional attendance management methods because it greatly improves awareness, streamlining user engagement and speed. The attendance management system integrated the facial recognition technology, making it convenient to identify attendance monitoring in only in the business organization. This technology improves awareness and effectiveness for monitoring employee attendance and student attendance. Facial recognition technology does not require factual attachments. Exchanging factual identifiers allows personnel to improve security and engagement level. The proposed method applies Haar classifiers based on machine-learning algorithm to identify faces in photos. Local binary pattern histograms (LBPH) are meant to improve facial identification through local texture varieties grouped into photos. For machine learning and image processing Python is the preferred programming language due to its huge libraries, simplicity and readability. Structured query language (SQL) will display facial photos and associated data in the data engine, allowing for fast retrieval and management of

attendance reports. The recommended facial recognition-based attendance solution automates and simplifies attendance capture recognition. through real-time The system is divided into several interconnected phases, as explained below:

*A. Data Acquisition*

Each student receives high-resolution facial photographs taken using a webcam or digital camera. Each photo is tagged with the student's name and ID. To improve recognition accuracy, photographs are shot at various angles and lighting conditions.

*B. Face Detection*

Face detection uses methods such as Haar Cascades or Histogram of Oriented Gradients (HOG). The system finds and extracts facial parts from photos, rejecting the background. Bounding boxes are used to define identified facial areas for processing.

*C. Data Preprocessing*

Pre-processing involves shrinking the retrieved faces, turning them to greyscale, and applying normalization methods such as histogram equalization. These methods improve the quality of input data and reduce computing strain during feature extraction.

*D. Feature Extraction*

FaceNet and OpenFace are examples of sophisticated feature extraction techniques. The face image is converted into a fixed-size numerical vector (often 128-dimensional) that represents the individual's unique facial traits.

*E. Face recognition and matching*

Faces are taken from real-time video streams and converted into feature vectors. Vectors are matched against a database using distance based similarity measurements, such as Euclidean distance. A match within a threshold verifies the student's identity.

*F. Attendance Marking and Database Management*

After identifying a student, the system records their attendance using their ID and a timestamp. Attendance data is kept in a relational database, such as MySQL, for easy reporting and analysis. Intrinsic checks prevent duplicate entries on the same day.

*G. User Interface and Administrative Control*

Administrative users can use a graphical user interface (GUI) to manage student data, track attendance, and generate reports. The interface allows for adding/deleting student records and exporting attendance information in various formats.

*H. Security and Optimization*

Integrating anti-spoofing measures, such as liveness detection, can enhance system security and accuracy. Regularly updating the recognition model with new data can improve performance over time.

## V. BLOCK DIAGRAM




## VI. FLOWCHART




The training procedure begins with evaluating the training data directory. Images from the training dataset are initially converted to grayscale. Then each

image's core is located and compared to surrounding regions using a predefined threshold. The central portion is labelled as 1 if its intensity equals or exceeds that of the surrounding portions, and 0 otherwise. The images are then resized and converted to a NumPy array, which is the NumPy library's primary data structure. After identifying each face in the shot, it is divided into various lists and assigned a unique ID. Next, the faces are then trained alongside their corresponding IDs. A flowchart of the system's operation is required to clarify the process. The technology scans pictures for faces and converts them to grayscale. To identify faces in photos, the Haar Cascade frontal face module is used. The LBPH algorithm is used to predict faces in images. After prediction, The faces are highlighted in green, accompanied by their names.

## VII. SOFTWARE USED

### *A. Open CV*

The input image is after collection.The phone camera has very quickly processed the image, which is being converted to grayscale. The Haar Cascade frontal face module detects faces in the images. Next, the discovered faces are forecasted using the LBPH algorithm. Predicted faces are highlighted in green and identified by their names. OpenCV is a freely available software library that's focused on computer vision and machine learning in general. It is cross-platform, and works on Windows, Android, Linux, and macOS. It has interfaces in C, Java, and Python. OpenCV's features include real-time vision applications
that utilize SSE and MMX instructions. CUDA and OpenCL interfaces are currently being developed to ensure complete functionality. OpenCV primarily utilizes C and has an interface based on templates that interfaces with STL containers. It offers a wide range of algorithms and functions.

### *B. PANDAS*

Pandas, an open-source Python package, provides a variety of tools for data analysis. There are multiple data structures included with the package that can serve a variety of data manipulation needs.It offers several data analysis algorithms to facilitate data science integration with machine learning tasks in Python.

### *C. PyCharm*

PyCharm is created by JetBrains. It is a powerful and feature-rich integrated development environment (IDE) for Python development. If you want to develop Python applications on Windows, macOS, or Linux, PyCharm provides a uniform approach to code editing. PyCharm is founded on the IntelliJ platform, which offers intelligence and reliability suitable for both beginner and advanced professional developers. PyCharm's intelligent Python code editor includes clever syntax highlighting, error detection, and code completion for Python. PyCharm's interface is customisable, and the IDE provides strong debugging help as well as great support for project-specific virtual environments and frameworks such as Django. PyCharm is a great option for advanced Python development.

### *D. Microsoft Excel*

The Microsoft Excel is part of the Microsoft Office package, a spreadsheet program. Excel sheets provide users the ability to organize data in a tabular format. Users can use the rows and columns to perform basic and advanced arithmetic computations. Microsoft Excel includes extensive graphing and charting features, Visual Basic for Applications (VBA) programming capability, and Dynamic Data Exchange(DDE) for retrieving data from various sources. Excel is an electronic spreadsheet platform that allows for easy data management, editing, and storage. Early electronic spreadsheets were inspired by paper spreadsheets used for accounting, resulting in a similar form. With computerized spreadsheets, the same layout and format of paper spreadsheets exists, with data organized into uniform rows/columns of small rectangular cells (boxes).

## VIII. RESULTS






## IX. FUTURE SCOPE

It is a reasonable plan for Integrating Artificial Intelligence and machine learning into the attendance management system for future plans. Keep this advancement in mind in terms of a facial recognition system that recognises faces and has a very high level of stability and accuracy. Deep learning can detect faces, even in unusual angles and dim light. This improvement will lead to less error with increased user confidence. Also, in terms of machine learning expertise, the system can start to learn attendance data trends over time. The system may begin to see patterns of delay or patterns of unexpected absences to enable improved attendance management and operational efficiency. The potential for predictive analytics is also significant. Imagine the system being able to predict attendance patterns based on previous data. Premonitory skills can help improve scheduling and allocation of resources which improves operations in general and production. If we include IoT devices, it will increases automation. For example, imagine smart locks or sensors that grants arrivals and departures, rather than having a human check-in or counting people while attending to other factors in attendance surveillance. As learning progresses in the system, this capability will grow over time. In reality, the capacity to revert and change patterns of attendance and environmental conditions would help to ensure the long-term workability of the project through operational development, continuous education and upgrading, in addition to ongoing technological enhancements informed by attendance patterns. However, security upgrades might also be possible. Facial recognition technology can improve measures for access or attendance. Moreover, you could make some restricted locations available only to authorized workers hence improving corporate security levels. By integrating the system with Faculties and attendance providers, you can significantly improve the efficiency of your administration. Using automation for data transfers between systems, you can improve time tracking, leave processing, and compliance by reducing error and other workflows. In summary, integration of attendance management systems with machine learning and artificial intelligence increases accuracy, security, efficiency and improve attendance tracking and operations for everyone involved.

## X. CONCLUSION

This paper proposes real time attendance tracking users of facial recognition that is more effective and efficient than traditional attendance tracking methods. An automated system minimizes human error, decreases time consumption, and eliminates proxy attendance. The proposed attendance tracking system uses machine learning and image processing technology which allow for precise face detection and recognition. The system is programmed in near-real time with a contactless user interface and least hardware, making it suitable for educational environments with high interest in hygiene and automation. A secure database preserves university attendance records for storage and access. This is a user-friendly attendance tracking system which provides secure, complete, and accurate attendance records that relieve stress on administrative tasks. The proposed method is adjustable to large data records that is likely to engage to large universities with many student enrolments. There are opportunities for future integration of biometric security and cloud computing. The system will be scaled to include commercial insights, mobile app functionality and the ability to inspect emotions for more extensive educational and behavioral monitoring. This process digitizes today's

traditional educational methods, produces accurate data, increases productivity, and moves towards innovative teaching methods. Future enhancements will strive to improve the facial recognition algorithm, develop Real-time data processing which would not only make it a real time process but also enable clarification across local and online platforms as well as various devices.

REFERENCES


[1].S. K. Jha, "Face Recognition Based Attendance Management System," INTERANTIONAL JOURNAL OF SCIENTIFIC RESEARCH IN ENGINEERING AND MANAGEMENT, vol. 08, no. 05, pp. 1–5, May 2024, doi: 10.55041/ijsrem33911.

[2].S. Smitha, A. Afshin, and P. Hegde, "Face Recognition based Attendance Management System," International Journal of Engineering Research and, vol. V9, no. 05, Jun. 2020, doi: 10.17577/ijertv9is050861.

[3].A. Rao, "AttenFace: A Real Time Attendance System Using Face Recognition," Nov. 2022, vol. 3, pp. 1–5. doi: 10.1109/cict56698.2022.9998001.

[4].O. A. R. Salim, R. F. Olanrewaju, and W. A. Balogun, "Class Attendance Management System Using Face Recognition," Sep. 2018. doi: 10.1109/iccce.2018.8539274.

[5].A. R. S. Siswanto, M. Galinium, and A. S. Nugroho, "Implementation of face recognition algorithm for biometrics based time attendance system," Sep. 2014, vol. 5, pp. 149–154. doi: 10.1109/ictss.2014.7013165.

[6].M. Abuzar, A. A. B. Ahmad, and A. B. Ahmad, "A Survey on Student Attendance System Using Face Recognition," Jun. 2020, pp. 1252–1257. doi: 10.1109/icrito48877.2020.9197815.

[7].R. K and K. Y, "CATASTROPHE HITS THE GLOBE: SARS (NCOV-19), A SILENT EXECUTIONER," International Journal of Advanced Research, vol. 08, no. 04, pp. 77–79, Apr. 2020, doi: 10.21474/ijar01/10747.

[8].E. K and S. U, "Students' Attendance Management in Higher Institutions Using Azure Cognitive Service and Opencv Face Detection & Recognition Attendance System," British Journal of Computer, Networking and Information Technology, vol. 5, no. 1, pp. 43–55, Feb. 2022, doi: 10.52589/bjcnit-alqqmeee.

[9].P. Manke, H. Pednekar, Q. Abdul Qadir, M. Hamza Siddiqui, and P. Sakat, "Facial Recognition-based Attendance System," International Journal of Innovative Science and Research Technology (IJISRT), pp. 673–679, Apr. 2024, doi: 10.38124/ijisrt/ijisrt24apr1482.

[10].H. Yang and X. Han, "Face Recognition Attendance System Based on Real-Time Video Processing," IEEE Access, vol. 8, pp. 159143–159150, Jan. 2020, doi: 10.1109/access.2020.3007205.

[11].S. Sen, M. Patel, and A. K. Sharma, "Software Development Life Cycle Performance Analysis," springer singapore, 2021, pp. 311–319. doi: 10.1007/978-981-16-3915-9_27.

[12].Dr. S. Sanap, Mr. S. Goge, Ms. S. Narwade, and Mr. K. Pandit, "Face Recognition Based Attendance System Using Histogram of Oriented Gradients and Linear Support Vector Machine," European Journal of Theoretical and Applied Sciences, vol. 1, no. 6, pp. 904–915, Nov. 2023, doi: 10.59324/ejtas.2023.1(6).87.

[13].M. Sonawane, M. Kavde, M. Ahire, M. Tambat, and M. Tupe, "'Face Log' (Attendance Management System using Face Recognition)," International Journal of Advanced Research in Science, Communication and Technology, pp. 182–187, Feb. 2024, doi: 10.48175/ijarsct-15535.

[14].N. K. Jayant and S. Borra, "Attendance management system using hybrid face recognition techniques," Jun. 2016, vol. 1, pp. 412–417. doi: 10.1109/casp.2016.7746206.

[15].A. Ansari, M. Hilal, and S. Tyagi, "Automatic Attendance Management System Using Face Recognition," INTERANTIONAL JOURNAL OF SCIENTIFIC RESEARCH IN ENGINEERING AND MANAGEMENT, vol. 06, no. 03, Mar. 2022, doi: 10.55041/ijsrem11992.

[16].A. Sain, S. Dutta, R. Saha, and U. Mandal, "Automated Facial Recognition based Attendance System using OpenCV in Python," International Journal of Scientific Research in Computer Science, Engineering and Information Technology, pp. 105–111, Nov. 2023, doi: 10.32628/cseit2390617.

[17]."Facial Recognition Based Attendance System with Cloud-Integrated Data Management," International Journal for Modern Trends in Science and Technology, vol. 10, no. 06, pp. 1–4, Jun. 2024, doi: 10.46501/ijmtst1006001.

[18].G. G L, K. Srivastava, and V. Krishnamurthy, "FACIAL RECOGNITION-BASED ATTENDANCE MANAGEMENT USING HAAR CASCADE AND LBPH," Iterative International Publishers Selfypage Developers Pvt Ltd, 2024, pp. 9–19. doi: 10.58532/v3biai9p2ch1.