Vehicle Emergency and Rescue System

Sanika Uday Kamble, Kranti[1] Vijay Nalawade[2], Padmavati Ganpatrao Sawant[3], Prof. Ajinkya B. Patil[4].
[1-2-3]Student, Department of Electrical Engineering, NMCOE, Peth, India.

Abstract—**Vehicle Emergency and Rescue System (VERS) is a comprehensive, real-time safety solution designed to rapidly respond to vehicle emergencies. VERS integrates advanced sensors, GPS, and communication technologies to detect and report critical situations, such as accidents, medical emergencies, or vehicle breakdowns. Upon detection, VERS automatically alerts emergency services, transmits vital vehicle and occupant information, and provides precise location data. The system also enables voice communication between occupants and emergency responders. VERS aims to reduce response times, improve accident outcomes, and enhance overall vehicle safety. Its modular architecture allows for seamless integration with existing vehicle systems and accommodation of future technological advancements.**

Index Terms—**Vehicle Emergency, Rescue System, Real-time Safety, Accident Detection, Emergency Response, GPS, Communication Technologies**.

I. INTRODUCTION

The Vehicle Emergency and Rescue System is a pioneering technology designed to transform the landscape of vehicle safety and emergency response. This innovative system seamlessly integrates cutting-edge sensors, GPS, alert rescue teams promptly, and ensure timely assistance to minimize damage and save lives. Upon detecting an accident, the system instantly alerts emergency services, rescue teams, and vehicle owners, providing critical information such as location coordinates, accident severity, and vehicle details.

II. METHEDOLOGY

The development of the Vehicle Emergency and Rescue System (VERS) involved a comprehensive methodology that commenced with a thorough requirements analysis. This stage entailed identifying key stakeholders, understanding their needs and expectations, and defining the functional and non-functional requirements of the system. Following this,

the system design stage involved designing the architecture of the VERS, selecting hardware and software components, defining system interfaces, and designing and developing the hardware components of the VERS, including the accelerometer, GPS, and communication module. This stage entailed selecting appropriate sensors and communication protocols, designing circuit boards, and testing hardware components. Concurrently, the software development stage involved designing and developing the software components of the VERS, including firmware for the microcontroller and application software for the communication module.

Upon completion of the hardware and software development stages, the system integration stage involved integrating the hardware and software components of the VERS. This stage entailed connecting sensors and communication modules to the microcontroller, integrating firmware and application software, and testing the integrated system. Subsequently, the testing and validation stage involved conducting simulations and real-world trials to test the system's performance, reliability, and effectiveness.

Finally, the deployment and maintenance stage involved deploying the VERS in vehicles and maintaining the system. This stage entailed installing the system in vehicles, providing training to users, and performing regular maintenance and updates to ensure the system remains operational and effective.

Assistant Professor, Department of Electrical Engineering, NMCOE, Peth, India.

GPS Module Neo-6m:

The NEO-6M is a popular GPS module used in a wide range of applications, including robotics, drones, automotive systems, and more. The NEO-6M GPS module is a compact, rectangular board featuring a small GPS antenna on top, a 6-pin header for UART, VCC, and GND connections, and a small LED

indicator for power and GPS fix status. At its core lies the tiny u -blox NEO-6M GPS chip, surrounded by a few passive components such as resistors and capacitors.

GSM Module 8001:

The GSM Module 800L is a compact and versatile wireless communication module that operates on the Global System for Mobile Communications (GSM) network. It is designed to provide a simple and cost-effective solution for adding GSM connectivity to a wide range of application including M2M (Machine-to-Machine), IoT (Internet of Things), and industrial automation.

ADXL 335:

The ADXL335 is a low-power, 3-axis accelerometer sensor manufactured by Analog Devices. It is designed to measure acceleration, tilt, and vibration in a wide
• The system can be integrated with smart city infrastructure to enhance traffic management and emergency response.
• The system can provide valuable data for insurance companies and telematics service providers.

III. OBJECTIVES

• Provide quick access to emergency information.
• Improve response time in emergency situations.
• Enhance safety for vehicle occupants.
• Streamline emergency response efforts.
• Increase efficiency in emergency response.

IV. CONCLUSION

The Vehicle Accident Detection and Rescue System for Vehicle is successfully Assembled by use of database services, API and satisfied all requirements. The devices are capable of receiving and storing the data. If the accident happens the system is capable of communicating family and ambulance that are near to accident spot.

V. ACKNOWLEDGMENT

range of applications, including industrial, medical, and consumer electronics. The ADXL335 is a popular choice among engineers and hobbyists due to its high sensitivity, low noise, and ease of use.

ESP 32:

The ESP32 is a low-cost, low-power system-on-chip (SoC) microcontroller developed by Espressif Systems. It is the successor to the popular ESP8266 microcontroller and offers a wide range of features and improvements. The ESP32 is designed to provide a robust and reliable platform for developing a wide range of applications, including IoT devices, robots, and other embedded systems.

Communication Module:

The communication module is a vital component of the Vehicle Emergency and Rescue System (VERS), enabling seamless communication between the vehicle and emergency services. Equipped with cellular, satellite, or wireless connectivity, the communication module transmits critical data, such as location, speed, and impact severity, to emergency responders in real time. This facilitates prompt and effective response, ensuring that help arrives quickly and efficiently in emergency situations.

4G sim Card

A 4G SIM (Subscriber Identity Module) card is a type of SIM card that operates on the 4G (Fourth Generation) wireless communication standard. 4G SIM cards were widely used in the early 2000s for mobile phones and other wireless devices.

VI. SCOPE OF PROJECT

The Vehicle Emergency Reporting System (VERS) has a wide scope of application, including:

• VERS aims to reduce road accidents and fatalities by providing real-time emergency response.
• The system integrates with emergency services, such as ambulance, fire, and police, to ensure prompt response.
• VERS can be installed in various types of vehicles, including cars, buses, trucks, and motorcycles.

REFERENCES

[1] REFERENCES Dr. P. Santhanalakshmi, Aasna yasmine, SMART ACCIDENT DETECTION AND RESCUE SYSTEM SYTEM USING IOT, IARJSET2024.

[2] Suraj Pratap Shubham, Dr. Sarika Jain, A Survey on IoT based Automatic Road Accident Detection, IEEE2020.

[3] Pranto Karmokar, Saikot Bairagi, Anuprova Mondal, Fernaz Narin Nur, Nazmun Nessa, A Novel IoT based Accident Detection and Rescue System, IEEE2020.

[4] A. Kumar, A Real-Time Vehicle Emergency Response System Using GPS, GSM, and Cloud Computing, IEEE2019

[5] Frahim Wadud Taj, Abdul Kadar Muhammad Masum Automatic Accident De tection and Human Rescue System: Assistance through Communication Technologies, IEEE2018

[6] S. K. Singh, Vehicle Emergency Response System Using IoT and Machine Learning, IEEE2018.

[7] A. K. Singh,Design and Development of Vehicle Emergency Response System (VERS), IEEE2017.

[8] R. K. Sharma, A Low-Cost Vehicle Emergency Response System Using GPS, GSM, and RFID, IEEE2015.