An Home Automation System Using Arduino Module

Naik D C[1], Usha H N[2], Purva Kamat Mhamai[3]
[1,2,3,4] *Dept. of Electronics and Communication, APS College of Engineering Bangalore, India, 560116*

Abstract: This home automation system, which utilizes Arduino Nano and Bluetooth technology, allows users to control household devices remotely through a smartphone. It enhances convenience, optimizes energy usage, and improves security by allowing users to operate devices wirelessly. The system is customizable, scalable, and provides hands-on learning in electronics, IoT, and embedded systems. With a simple design and user-friendly interface, it offers an affordable solution for modernizing traditional homes.

Index terms: Smart home, ontology, automation rules, rule conflict, conflict classification

I. INTRODUCTION

By facilitating wireless operation of devices, it increases convenience, enhances energy efficiency, and bolsters security, reducing manual effort and optimizing power consumption. Traditional home control methods rely on physical switches and complex wiring, which can be inconvenient and inefficient.

This system is adaptable and expandable, offering practical learning opportunities in electronics, the Internet of Things (IoT), and embedded systems.

The suggested system is particularly well-suited for home use, providing a flexible platform that can be enhanced with extra functionalities, including voice activation, integration with the Internet of Things (IoT), and improved security features. Additionally, this initiative offers an enriching educational opportunity in the fields of embedded systems, IoT, and wireless communication, representing a noteworthy advancement in both scholarly research and practical applications within smart home technology.

II. LITERATURE REVIEW

The Author in [1] this document outlines a comprehensive approach to developing a smart home automation controller. By leveraging the Internet of Things (IoT), it transforms conventional home appliances into intelligent devices through effective design control. The system is engineered for energy efficiency and enables remote access to the smart home via IoT connectivity. Central to the proposed solution is the Node MCU (Microcontroller Unit), which serves as the microcontroller unit. Additionally, IFTTT (If This Then That) is utilized to process voice commands, while the Adafruit library functions as an MQTT (Message Queuing Telemetry Transport) broker, and the Arduino IDE (Integrated Development Environment) is employed for programming the microcontroller. This versatile system integrates Google Assistant and a web-based application to facilitate smart home management. The main controller unit is continuously connected to a Wi-Fi (Wireless Fidelity) network, ensuring 24/7 availability. To maintain a stable connection, the controller is programmed to automatically reconnect to the network and is linked to a backup power source.

The work proposed in [2], this study examines a system designed for home automation that leverages the Internet of Things (IoT) for seamless operation. In addition to its automation capabilities, the system incorporates a camera module to enhance home security. The accompanying Android application effectively transforms a smartphone into a remote control for all household appliances. Security measures are implemented through motion sensors that detect movement at the entrance; when triggered, these sensors send real-time notifications, including a photo of the entryway, to the homeowner via the internet. This allows the homeowner to respond promptly, either by raising an alarm in the event of an intrusion or by controlling appliances, such as unlocking the door for guests. The system is powered by a Raspberry Pi, a compact computer that serves as the central server. The smart home setup comprises two main modules: the home automation module, which includes controls for fans, lights, and doors, and the security module, which features smoke detectors, motion sensors, and the camera.

The Author in [3], this paper presents a methodology for creating an affordable Home Automation System (HAS) that utilizes Wireless Fidelity (Wi-Fi) technology. This

approach embodies the concept of interconnecting smart devices. A Wi-Fi-based Wireless Sensor Network (WSN) is established to monitor and manage various environmental, safety, and electrical parameters within a smart, interconnected home. The components of the HAS include temperature and humidity sensors, a gas leak detection system, a fire alarm, a burglar alarm, rain sensors, and systems for load switching and voltage and current regulation. The essential function of the HAS, which is to oversee and control devices, is achieved through a smartphone application. This application is developed using Android Studio on the Java platform, featuring a user-friendly interface. The main objective of this paper is to create a cost-effective and flexible solution for device control while implementing a diverse array of sensors to capture different parameters.

The work proposed in [4] This paper introduces a system designed to create a model that alleviates the computational burden present in current smart home solutions that employ various encryption technologies, such as AES (Advanced Encryption Standard), ECHD (Elliptic Curve Hyperelliptic Cryptography), and hybrid methods. These existing solutions typically rely on an intermediate gateway to connect different sensor devices. The proposed model offers a method for automation through sensor-based learning. While the system primarily utilizes a temperature sensor for its development, it can also accommodate additional sensors based on specific needs. These smart home devices, equipped with sensors, are capable of self-configuration and can function independently without human oversight. This approach reduces the need for encryption and decryption processes, emphasizing authentication and the automation of smart home devices through learning. By eliminating the local gateway used in previous systems, the model enhances security for smart home devices and sensor data while minimizing computational overhead. A real-time broker cloud is directly linked to the smart home, managing all incoming and outgoing requests between users and devices. The primary goal of utilizing this real-time broker cloud is to expedite cryptographic operations.

The author in [5] this study examines significant research challenges and future prospects within the Internet of Things (IoT) field, focusing on essential elements such as security, scalability, data management, interoperability, and real-time processing. The paper offers valuable insights into the role of IoT in various smart environments, including home automation, healthcare, industrial automation, and smart city initiatives. Stankovic emphasizes the necessity for enhanced network protocols, energy-efficient communication methods, and the smooth integration of IoT devices into daily life. This research serves as an important resource for academics, engineers, and technology enthusiasts striving to advance IoT applications.

The work proposed in [6] this paper offers an in-depth examination of the Internet of Things (IoT), outlining its vision, essential architectural elements, and potential applications across various sectors. The authors analyze the role of IoT in smart environments, such as healthcare, transportation, and smart homes, while also tackling significant challenges like security, scalability, and data management. Furthermore, the study investigates the integration of cloud computing with IoT and suggests future research avenues, positioning it as a valuable reference for researchers, engineers, and industry professionals aiming to comprehend and develop IoT-based solutions.

III. System Design & Architecture

A. Overview

The Home Automation System is developed to offer an affordable and effective method for remotely managing household appliances through the use of Arduino Nano and Bluetooth technology. The system eliminates the need for traditional switches by enabling users to turn ON/OFF appliances via a smartphone app. It ensures wireless connectivity, ease of use, energy efficiency, and scalability for future enhancements such as IoT integration and voice control.

This system is particularly useful for:

- Residential automation – Managing lights, fans, and other appliances.
- Elderly and disabled assistance – Enabling remote control for those with mobility challenges.
- Energy conservation – Reducing electricity waste by turning off unused devices.

Security enhancements – Integrating motion sensors and automated lighting for better home security.

B. Hardware Components

The primary hardware elements utilized in this project include:

1. Arduino Nano – A compact and efficient microcontroller based on the ATmega328P chip. It

processes commands received via Bluetooth and executes corresponding actions by controlling appliances through the relay module. It operates at 5V, has multiple GPIO (General Purpose Input/Output) pins, and is widely used in embedded systems due to its small size and low power consumption.HC-05 Bluetooth Module – Establishes wireless communication between the smartphone and the Arduino Nano.

2. HC-05 Bluetooth Module – A commonly utilized serial communication module that facilitates wireless connectivity between the smartphone and the Arduino Nano. It operates on Bluetooth 2.0 technology, supports both Master and Slave modes, and enables data transfer within a range of 10 meters. It uses UART (Universal Asynchronous Receiver-Transmitter) protocol for serial communication with the Arduino.

3. 4-Channel Relay Module – A high-voltage switching module that acts as an electromechanical switch, allowing low-power microcontrollers to control high-power electrical appliances like lights, fans, and other devices. Each relay operates on 5V DC control signals and can switch AC loads up to 250V/10A or DC loads up to 30V/10A. The optocoupler isolation enhances safety by preventing back-voltage damage to the microcontroller.

4. Power Supply (5V/12V) – The system requires a regulated power source to operate different components. The Arduino Nano and Bluetooth module typically operate on 5V, while the relay module may require 12V depending on the design. A power adapter or battery pack can be used to ensure continuous operation, and voltage regulators (e.g., 7805) can help maintain a stable power supply.

5. Home Appliances (Lights, Fans, etc.) – Electrical devices linked to the relay module that can be controlled remotely through the smartphone, The system allows automation of household appliances, office equipment, or industrial machines, providing energy efficiency, convenience, and remote operation. Smart scheduling and voice control integration can further enhance functionality.

Each of these components is carefully selected to ensure low-cost implementation, reliability, and expandability for future upgrades.

C. Block Diagram

The system follows a simple architecture:

The system follows a structured workflow to ensure smooth operation:

1. User Input: The user sends a command (e.g., “Turn ON Light”) from a smartphone app.
2. Wireless Communication: The HC-05 Bluetooth module captures the command and relays it to the Arduino Nano.
3. Processing Unit: The Arduino Nano interprets the command and determines which relay to activate or deactivate.
4. Appliance Control: The relay module switches the corresponding home appliance ON/OFF.
5. Feedback Mechanism: The system can provide feedback through the smartphone app, confirming whether the appliance was successfully controlled.

The figure 1 represents a Bluetooth-based home automation system that allows for users to control multiple electrical appliances remotely using an Android device. The system's operation begins with the Android device, which sends control signals via a Bluetooth module (such as HC-05 or HC-06). These signals are received by an Arduino Nano, which processes the commands and controls a relay board. The relay board acts as an intermediary switch, turning appliances to be turned ON or OFF according to the received commands. The block diagram represents this architecture visually, showing how components interact within the system.



Figure 1: Block Diagram of Architecture.

Each relay is linked to a different appliance (Appliance 1, Appliance 2, Appliance 3, and Appliance 4), allowing independent control of multiple devices. This setup provides a wireless, efficient, and user-friendly automation system, enabling remote operation of household or industrial appliances using a smartphone.

1. Android Device (User Interface

- The system is controlled using an Android smartphone equipped with a mobile application.
- The user sends commands (such as ON/OFF) through the app to control appliances remotely.
- The smartphone communicates wirelessly with the Bluetooth Module via Bluetooth connectivity.

2. Bluetooth Module (HC-05)

- The HC-05 Bluetooth module serves as the communication link between the Android device and the Arduino Nano.
- It receives commands from the smartphone and transmits them serially to the Arduino Nano for processing.
- Bluetooth ensures short-range wireless Communication, typically within 10 min.

3. Arduino Nano (Processing Unit)

- The HC-05 Bluetooth module serves as a communication link between the Android device and the Arduino Nano.
- It receives control commands from the smartphone via Bluetooth connectivity.
- The received commands are transmitted serially to the Arduino Nano for processing.
- The Arduino processes the commands and controls the relay board to switch appliances ON or OFF.
- Bluetooth enables short-range wireless communication, typically within a 10-meter range.

4. Relay Board (Switching Module)

- The relay module functions as an electrically operated switch that manages high-voltage home appliances according to signals received from the Arduino Nano.
- Each relay corresponds to a separate appliance, allowing multiple appliances to be controlled.
- When the Arduino sends a HIGH signal, the relay activates, turning the connected appliance ON.
- When the Arduino sends a LOW signal, the relay deactivates, turning the appliance OFF.

5. Home Appliances (Load Control)

- The relay board controls four different appliances (such as lights, fans, or other electronic devices).
- Each appliance is connected to a separate relay channel, ensuring individual control.
- The system can be expanded to support more appliances by adding additional relay modules.

6. Working Process Summary:

- The user sends an ON/OFF command from the Android smartphone via Bluetooth – The user interacts with a custom-built mobile application that has buttons for controlling different appliances. When the user taps a button, the smartphone transmits a specific command (e.g., "ON1" for turning on Light 1) via Bluetooth communication using the serial protocol (UART).
- The HC-05 Bluetooth module receives the command and transmits it to the Arduino Nano – The HC-05 module, operating in slave mode, receives the command wirelessly and forwards it to the Arduino Nano through its RX (Receive) and TX (Transmit) pins. This module supports a 10-meter range, ensuring short-range communication without requiring an internet connection.
- The Arduino Nano processes the command and sends an activation signal to the Relay Board – The Arduino Nano, programmed using C/C++ in the Arduino IDE, reads the received command and determines which appliance should be turned ON or OFF. It then sends a digital HIGH (5V) or LOW (0V) signal to the appropriate relay channel, triggering the switching action.
- The Relay Module switches the respective home appliance ON/OFF – The relay module acts as an electrically controlled switch that allows the low-power Arduino signal to control high-voltage appliances (AC 220V or DC loads). When the relay is activated, it closes the circuit, turning the appliance ON, and when deactivated, it opens the circuit, turning the appliance OFF.
- The system provides wireless and remote control, reducing manual effort and enhancing energy efficiency – By allowing users to remotely operate home appliances, the system minimizes the need for manual switching, making it is especially beneficial for elderly individuals, disabled persons, or busy professionals. Additionally, scheduled automation and energy monitoring features can be integrated to optimize power consumption, reducing electricity wastage.

Key Advantages of This Design:

1. Wireless Operation: Eliminates the need for manual switches.
2. Low Power Consumption: Uses an energy-efficient Arduino Nano.
3. User-Friendly: Controlled via a simple mobile app.
4. Scalable System: More appliances can be added using additional relays.

5. Affordable & Easy to Implement: Uses low-cost components for budget-friendly home automation.
This block diagram represents a basic an efficient yet impactful smart home automation system that can be further enhanced with IoT integration, cloud-based monitoring, and voice control in future developments.

D. Circuit Diagram

The circuit connections are established as follows:

1. HC-05 Bluetooth Module is linked to the Arduino Nano for wireless data transmission.
2. Relay Module is linked to digital output pins (D2–D5) of the Arduino Nano to switch appliances ON/OFF.
3. AC appliances such as lights and fans are wired to the relay's COM (Common) and NO (Normally Open) terminals.
4. Power supply (5V/12V) is used to provide necessary voltage to the microcontroller and relays.

Figure 2: Circuit diagram.

The figure 2 depicts a smart home automation system that enables users to manage electrical appliances through a mobile app using Bluetooth communication. This system is constructed with an Arduino Nano microcontroller, a 4-channel relay module, and a Bluetooth module (HC-05 or HC-06) for wireless connectivity. The relay module is responsible for switching AC appliances, such as lights, a ceiling fan, and an electrical socket, by receiving commands from the Arduino. The mobile app interface displays ON/OFF buttons for various appliances, allowing users to operate them from a distance. A 5V, 2A power supply powers the circuit, while the 220V AC mains are connected via the relay to control high-voltage devices safely. The integration of wireless communication, automation, and remote control makes this system an efficient and modern solution for home automation, providing convenience and energy management.

E. Software Components

1. Arduino IDE – Used for writing and uploading code to the Arduino Nano.
2. Embedded C Programming – Controls the interaction between Arduino, Bluetooth, and relays.
3. Smartphone App (Bluetooth Terminal/App Inventor) – Sends commands to the Bluetooth module.

F. Working Principle

1. The user opens the mobile app and connects to the Bluetooth module.
2. When a button is pressed in the app, a command (e.g., 'A' for light ON) is sent.
3. The Arduino Nano receives the command via the Bluetooth module.
4. The Arduino activates/deactivates the relay corresponding to the received command.
5. The connected appliance (fan/light) turns ON/OFF accordingly.

G. System Features

1. Wireless Bluetooth Control – Operates within a 10-meter range.
2. Low Power Consumption – Efficient and optimized for home use.
3. Expandable & Customizable – Additional features like IoT integration can be added.
4. User-Friendly Interface – Simple smartphone-based operation.

[7] This extensive survey examines the core concepts, technologies, and challenges linked to the Internet of Things (IoT). The authors present a thorough analysis of IoT architecture, communication protocols, and enabling technologies such as RFID, wireless sensor networks, and cloud computing. They also explore significant application domains, including smart homes, healthcare, industrial automation, and intelligent transportation systems. The paper emphasizes critical research challenges concerning security, interoperability, and scalability, making it a valuable resource for academics, researchers, and professionals seeking a comprehensive understanding of IoT and its future advancements.

The author in [8] offers a comprehensive examination of the expanding Internet of Things (IoT) ecosystem from an industrial perspective. The authors investigate significant IoT market trends, technological innovations,

and industry applications, such as smart cities, healthcare, manufacturing, and home automation. They discuss challenges such as security, interoperability, scalability, and data management, along with future research directions. This paper serves as a crucial reference for researchers, industry professionals, and policymakers aiming to understand the evolving role of IoT in modern industries.

[9] This paper offers an extensive survey of the Internet of Things (IoT) and its significance across various industrial sectors, including manufacturing, healthcare, transportation, and energy. The authors explore essential enabling technologies such as wireless sensor networks, cloud computing, and big data analytics, highlighting their effects on industrial automation and efficiency. Furthermore, the paper addresses critical challenges, including cybersecurity, data privacy, and system interoperability. By concentrating on practical applications and future research pathways, this work serves as a valuable resource for researchers, engineers, and industry professionals seeking to utilize IoT technologies for advancements in industry.

The author in [10] provides a comprehensive overview of the Internet of Things (IoT), addressing its foundational technologies, communication protocols, and diverse applications. The authors examine critical elements such as machine-to-machine (M2M) communication, network protocols, cloud integration, and security challenges. They also investigate IoT applications in fields like smart residences, healthcare, industrial automation, and intelligent transportation systems. This survey serves as a vital resource for researchers, engineers, and professionals seeking to understand the current state and future potential of IoT technologies.

IV. METHODOLOGY & IMPLEMENTATION

A. Overview

The Home Automation System allows users to manage household appliances via a smartphone app using Bluetooth communication**.** The system consists of Arduino Nano**,** HC-05 Bluetooth module**,** and a 4-channel relay module to automate electrical devices like lights and fans.

B. System Workflow

1. User Input: Commands sent via a smartphone app.
2. Wireless Communication: HC-05 Bluetooth module transmits commands to Arduino Nano.
3. Processing Unit: Arduino interprets commands and controls relays.
4. Appliance Control: Relay module switches devices ON/OFF.
5. Feedback: Status updates sent to the app.

C. Implementation Steps

1. Hardware Setup
    1. Arduino Nano processes commands and controls relays.
    2. HC-05 Bluetooth Module enables wireless communication.
    3. 4-Channel Relay Module switches appliances ON/OFF.
    4. Power Supply (5V/12V) supports the Arduino and relays.
2. Software Development
    1. Arduino IDE used to program the Arduino Nano.
    2. Embedded C Code manages Bluetooth communication and relay control.
    3. Smartphone App (MIT App Inventor/Bluetooth Terminal) sends control signals.
3. Testing & Validation
    1. Connectivity Tests: Verify Bluetooth pairing and command transmission.
    2. Relay Operation Tests: Ensure appliances respond correctly.
    3. System Integration: Test complete functionality in a real setup.

D. Features of the Implemented System

1. Remote Control via smartphone.
2. Wireless Communication using Bluetooth.
3. Low Power Consumption for efficient operation.
4. User-Friendly Interface for easy control.

E. Advantages and Disadvantages

1. Advantages
    1. Automation and Efficiency: Reduces manual effort and improves efficiency in the process.
    2. Real-Time Monitoring: Provides instant updates and data tracking.
    3. Cost-Effective: Reduces labor costs and operational expenses.

4. User-Friendly: Designed for ease of use with minimal training required.
5. Scalability: Can be expanded or modified as per Requirements.
6. Energy Efficient: Optimized for lower power consumption.

2. Disadvantages

1. Initial Setup Cost: Requires investment in hardware and software.
2. Maintenance Challenges: Needs regular updates and maintenance.
3. Dependency on Power and Network: Requires continuous electricity and internet for smooth functioning.
4. Technical Expertise: Some level of technical knowledge is needed for troubleshooting.
5. Limited Adaptability: May require customization for particular applications

F. Applications

1. Home Automation: Allows users to manage lights, fans, and other household appliances remotely.
2. Smart Office Systems: Automates electrical devices in offices for energy efficiency and convenience.
3. Industrial Automation: Helps in remotely controlling machinery and monitoring equipment.
4. Smart Classrooms: Enables automated control of projectors, lights, and fans for an efficient learning environment.
5. Elderly and Disabled Assistance: Provides easy control of appliances for individuals with mobility challenges.
6. Security Systems: Integrates with smart locks, alarms, and surveillance cameras for enhanced security.
7. Agriculture Automation: can be utilized to manage irrigation systems and monitor farm equipment remotely.
8. IoT-Based Projects: acts as a basis for a range of Internet of Things (IoT) applications.

The Author in [11] examines the role of the Internet of Things (IoT) in shaping the development of smart cities, focusing on key technologies, architectures, and applications. The authors discuss IoT-enabled solutions for urban infrastructure, including smart transportation, energy management, environmental monitoring, and public safety. They highlight challenges such as data security, network scalability, and interoperability while proposing innovative strategies for efficient citywide IoT deployment. This work serves as a crucial reference for researchers, policymakers, and urban planners interested in leveraging IoT to improve the quality of life in modern cities.

The Work proposed in [12] paper offers an in-depth overview of IoT technology, covering its future vision, fundamental architecture, key challenges, and emerging services. The authors discuss various IoT applications, including intelligent urban environments, healthcare systems, industrial automation, and intelligent transportation. They highlight critical challenges such as security, scalability, interoperability, and energy efficiency, proposing potential solutions for widespread IoT adoption. This work serves as an essential resource for researchers, engineers, and industry professionals seeking to understand the evolving IoT landscape and its impact on various sectors.

V. RESULTS & DISCUSSION

A. Results

The implemented Home Automation System successfully controls home appliances using a smartphone app via Bluetooth communication**.** When a user sends a command (e.g., "ON" for Light ON**),** the Arduino Nano processes it and activates the relay module, switching the appliance ON/OFF. The system was tested with lights and fans**,** demonstrating accurate and responsive control**.**

Figure 3: Prototype of system.

The figure 3 shows a home automation system prototype that uses an Arduino-based microcontroller, a relay module, and various electrical appliances. The setup consists of a breadboard with a microcontroller, which serves as the main control unit, connected to a two-channel relay module. This relay module acts as an electronic switch, allowing the microcontroller to control high-power AC devices such as the two light bulbs and a cooling fan. A power adapter is also included to offer the necessary voltage for the circuit. Additionally, there exists a socket, possibly for external device connections, enabling further automation. The system appears to be tailored for smart home applications, where devices can be controlled remotely using sensors, voice commands, or a mobile app. Such a setup could offer features like motion-based automation, scheduled power management, and remote switching, making it an energy-efficient and convenient solution for modern homes.

B. Discussion

1. Efficiency: The system operates efficiently within the 10-meter Bluetooth range.
2. Ease of Use: The smartphone app provides a simple and user-friendly interface.
3. Energy Optimization: Allows users to turn off devices remotely, reducing power consumption.
4. Limitations: Bluetooth range is limited compared to Wi-Fi-based automation, and there is no real-time status feedback in basic implementations.
5. Future Enhancements: The system can be expanded with Wi-Fi connectivity, voice control, and IoT integration for improved flexibility.

VI. CONCLUSION

The Arduino-Based Home Automation System and Bluetooth provides an efficient and cost-effective v remotely. It enhances convenience, energy efficiency, and security by allowing users to operate devices through a smartphone. The system serve as simple, scalable, and customizable, making it suitable for various applications. Bluetooth communication ensures wireless control, though its range is limited. Future improvements like IoT integration, voice control, and cloud monitoring can enhance functionality. The project demonstrates the practical use of embedded systems in smart homes. Overall, it offers an affordable and user-friendly approach to modernizing home automation.

REFERENCES

[1] Satyendra K. Vishwakarma, Prashant Upadhyaya, Babita Kumari, Arun Kumar Mishra. “IoT-Based Smart Energy Efficient Home Automation System.” 4th International Conference on the Internet of Things: Smart Innovation and Usages (IoT SIU), Issue on April 2019.

[2] Shardha Somani Parikshit Solunke Shaunak Oke, Parth Medhi, Prof. P. P. Laturkar. “Smart Security and Home Automation Using IoT.” Fourth International Conference on Computing, Communication, Control, and Automation (ICCUBEA), Issue on August 2018.

[3] Vikram N., Harish K. S., Nihaal M. S., Raksha Umesh, Shetty Aashik Ashok Kumar. “An Affordable Home Automation System Utilizing a Wi-Fi-Based Wireless Sensor Network Integrated with the Internet of Things.” IEEE 7th International Advance Computing Conference (IACC), January 2017.

[4] Tushar Churasia and Prashant Kumar Jain. “Improved Smart Home Automation System Utilizing the Internet of Things.” Automated Secure Computing for Next-Generation Systems (pp.243-273), Issue on November 2023.

[5] John A. Stankovic. "Research Directions for the Internet of Things," *IEEE Internet of Things Journal*, Volume 1, Issue 1, February 2014.

[6] Jayavardhana Gubbi, Rajkumar Buyya, Slaven Marusic, Marimuthu Palaniswami. "Internet of Things (IoT): A Vision, Architectural Elements, and Future Directions," *Future Generation Computer Systems*, Volume 29, Issue 7, September 2013.

[7] Luigi Atzori, Antonio Iera, Giancarlo Morabito. "The Internet of Things: A Survey," *Computer Networks*, Volume 54, Issue 15, October 2010.

[8] Charith Perera, Chi Harold Liu, Srimal Jayawardena. "The Emerging Smart Device network Marketplace From an Industrial Perspective: A Survey," *IEEE Transactions on Emerging Topics in Computing*, Volume 3, Issue 4, December 2015.

[9] Li Da Xu, Wu He, Shancang Li. "Internet of Things in Industries: A Survey IEEE Transactions on Industrial Information Systems, Volume 10, Issue 4, November 2014.

[10] Al-Fuqaha Ala, Mohsen Guizani, Mehmet Ercetin, Abdallah Mohamad."Internet of Things: A Comprehensive Review of Enabling Technologies, Protocols, and Applications," *IEEE Communications Surveys & Tutorials*, Volume 17, Issue 4, Fourth Quarter 2015.

[11] Andrea Zanella, Nicola Bui, Angelo Castellani, Lorenzo Vangelista, Michele Zorzi. "Internet of Things for Smart Cities," *IEEE Internet of Things Journal*, Volume 1, Issue 1, February 2014.

[12] Dhananjay Singh, Gaurav Tripathi, Antonio J. Jara. "A Survey of Internet-of-Things: Future Vision, Architecture, Challenges and Services," *2014 IEEE orld Forum on Internet of the Things (WF-IoT)*, March 2014.