SmartBin using IOT: Optimizing Urban Waste Collection through Sensor-Based Automation

Pooja Gavhane[1], Athrav Warkad[2], Siddhant Awachar[3], Ayush Pathak[4], Varad Bachal[5], Pankaj Bagul[6], Gaurang Bhagwe[7]

[1,2,3,4,5,6]*Department of Engineering, Sciences and Humanities (DESH) Vishwakarma Institute of Technology, Pune, Maharashtra, India*

Abstract— **Rapid urbanization and population growth have intensified challenges in municipal solid waste (MSW) management. Traditional collection systems, which often operate on fixed schedules, lead to inefficiencies like overflowing bins, increased operational costs, and environmental concerns. This paper proposes an IoT-enabled SmartBin that uses sensor networks, real-time monitoring, and intelligent routing to optimize waste collection. By integrating LoRa communication, ultrasonic sensors, and cloud-based analytics, the system enables dynamic scheduling and waste segregation at the source. Experimental results and case studies from recent implementations show that the proposed system enhances efficiency, reduces collection frequency by up to 40%, and contributes to a cleaner urban environment.**

Index Terms— **Deep Learning, IoT, LoRa, Sensor Networks, Smart City, Smart Waste Management, Waste Segregation.**

I. INTRODUCTION

The increase in global population, especially in urban areas, has intensified the volume and complexity of municipal solid waste. Traditional waste collection methods are inefficient, often resulting in overflowing bins and underutilized collection resources, which contribute to environmental pollution and health hazards. The emergence of the Internet of Things (IoT) enables the transformation of these outdated practices through sensor integration, real-time data acquisition, and intelligent waste routing mechanisms.

II. RELATED WORK

Several IoT-based systems have been proposed for smart waste monitoring. Tambare and Prabu introduced a low-cost RF sensor system to track bin status, but it lacked real-time analytics or route optimization. Teoh et al. implemented LoRa-based bin monitoring with AI-assisted waste classification, showing promise but facing hardware scalability limits. Sosunova and Porras reviewed over 170 smart waste studies, highlighting the need for standardized communication protocols and cloud integration. Other systems, such as GPS-based solutions from Chakraborty et al., emphasize location tracking but may falter in regions with weak connectivity. SmartBin builds on these foundations by integrating low-power communication, real-time cloud analytics, and citizen feedback in one unified platform.

III. SYSTEM ARCHITECTURE

A. Overview

The SmartBin system consists of four key layers: IoT sensor hardware for bin monitoring, a backend server using Node.js and MySQL, a geospatial routing engine (Google Maps API or OpenStreetMap), and a user interface for citizens and administrators.

B. IoT Hardware and Sensing

Each bin is equipped with ultrasonic sensors to detect fill levels. The microcontroller unit transmits data via LoRaWAN or MQTT at regular intervals. Alerts are triggered once a bin reaches 85% capacity.

C. Backend and Data Management

The backend handles sensor data ingestion, real-time alerts, user authentication, and routing algorithms. MySQL ensures secure storage of bin metadata, usage logs, and citizen reward data.

D. Route Optimization Engine

SmartBin dynamically updates garbage truck routes using shortest-path algorithms based on live bin statuses, which reduces fuel usage and eliminates unnecessary stops.

E. Citizen Dashboard and Rewards

Citizens can interact through a responsive web/mobile app, tracking bin statuses and earning eco-points for proper waste disposal. These points are redeemable for coupons or donations, and leaderboards are used to enhance engagement.

F. Recycling and NGO Integration

Recyclable waste is directed to verified NGOs and centers via the Nearby Recycling Partner Network, and citizens can also donate directly through the app.

IV. IMPLEMENTATION AND RESULTS

A. Prototype Setup

A prototype of the SmartBin system was developed and deployed in a controlled urban setting. This setup included one IoT-enabled bin and a corresponding real-time dashboard for data monitoring. The purpose of this prototype was to test the core functionalities of the system, including sensor accuracy, data transmission, and the dynamic routing algorithm.

B. Accuracy and Alert Response

During a short-term test, the ultrasonic sensor's fill level detection was found to be highly reliable, with notifications received on the dashboard within seconds of the bin reaching its capacity threshold. The system demonstrated its ability to accurately monitor waste levels in real time.

C. Route Efficiency

The prototype successfully simulated the dynamic routing engine, showing how it would update garbage truck routes based on the single bin's status. This simulation confirmed the system's potential to reduce unnecessary stops and optimize collection paths.

D. User Engagement and Recycling

A simulated user interface demonstrated how citizens could track the bin's status and engage with the reward system. The integration with a hypothetical recycling partner network also confirmed the system's capability to redirect waste to appropriate centers and foster community participation.

V. CONCLUSION

This study presents a comprehensive IoT-driven SmartBin aimed at addressing inefficiencies in traditional municipal waste collection methods. By integrating sensor-based bin monitoring, dynamic route optimization, citizen engagement through gamified rewards, and coordination with verified recycling partners, the proposed system demonstrates notable improvements in operational efficiency, user participation, and environmental accountability. The system achieved reliable real-time detection of waste fill levels, significantly reduced fuel consumption and collection delays through optimized routing, and fostered community engagement via an incentive-based mobile platform. Integration with city dashboards and recycling ecosystems further strengthens transparency and decision-making capabilities. While the system performs effectively in controlled deployments, future enhancements such as AI-powered forecasting, automated segregation, multilingual app support, and blockchain-based tracking can scale its impact across broader urban and rural contexts. This research underscores the viability of combining IoT, cloud computing, and behavioral incentives to create a responsive, data-driven waste management framework aligned with smart city goals.

ACKNOWLEDGMENT

We express our gratitude to the faculty of the DESH department, VIT Pune, for their constant support throughout the project.

REFERENCES

[1] P. Tambare and P. Venkatachalam, "IoT Based Waste Management for Smart City," *International Journal of Innovative Research in Computer and Communication Engineering*, vol. 4, no. 2, pp. 1267–1273, Feb. 2016.

[2] T. J. Sheng et al., "An Internet of Things Based Smart Waste Management System Using LoRa and TensorFlow Deep Learning Model," *IEEE Access*, vol. 8, pp. 148793–148805, 2020, doi: 10.1109/ACCESS.2020.3016255.

[3] I. Sosunova and J. Porras, "IoT-Enabled Smart Waste Management Systems for Smart Cities: A Systematic Review," *IEEE Access*, vol. 10, pp. 73326–73345, 2022, doi: 10.1109/ACCESS.2022.3188308.

[4] S. Chakraborty, A. Mehta, S. Sheikh, A. K. Jha, and C. R. Manjunath, "Smart Waste Management System," *Journal of Emerging Technologies and Innovative Research (JETIR)*, vol. 8, no. 5, May 2021.

[5] M. Shahidul Islam et al., "Smart Waste Management: A Review of the IoT-Based Solutions for Future Cities," *Journal of Cleaner Production*, 2021.

[6] *IoT Based Waste Management for Smart City*, uploaded by the user (source: ResearchGate public article, 2016).