© November 2025 | IJIRT | Volume 12 Issue 6 | ISSN: 2349-6002

A Hybrid Optimization Framework to Reduce Deep Learning Training Time Using Mixed Precision, Gradient Accumulation, and Adaptive Batch Scaling

Prof. Kalpana Dongre[1], Bhakti Radhehsyam Thombare[2]
Wainganga Collage of Engineering and Management (Artificial Intelligence and Data Science)

***Abstract*—Deep learning models have achieved state-of-the-art performance in several domains, but their training time remains a major bottleneck due to high computational cost, large-scale datasets, and increasingly complex architectures. This paper proposes a hybrid optimization framework combining mixed precision training, adaptive batch scaling, and gradient accumulation to significantly reduce model training time without compromising accuracy. Experimental validation on ResNet-50 and Transformer models using the CIFAR-100 and IMDB sentiment datasets shows up to 38.6% reduction in total training time** and **22.4% lower GPU memory usage while maintaining accuracy within ±0.5% of full-precision baselines. The study integrates insights from state-of-the-art works on efficient DL training, but introduces a unified workflow capable of running on a single GPU, multi-GPU, or cloud compute environment. The proposed approach provides a practical and scalable solution for researchers and industries aiming to reduce computational cost in model development.**

***Index Terms*—Deep learning optimization, mixed precision, batch scaling, training acceleration, GPU efficiency, model training time reduction.**

I. INTRODUCTION

Deep learning has become the foundation of modern artificial intelligence, powering applications such as autonomous vehicles, natural language generation, medical image diagnosis, and large-scale recommendation systems. As model architectures evolve from early convolutional networks to advanced transformer-based systems like GPT, ViT, and LLaMA, the number of trainable parameters has grown from a few million to several hundred billion, resulting in exceptional performance gains. However, this rapid scaling has also introduced significant challenges related to computational time, energy consumption, and hardware dependency. Training a state-of-the-art model can require weeks of GPU time, high memory bandwidth, and expensive cloud or cluster resources, making deep learning research increasingly inaccessible to smaller organizations, academic labs, and individual researchers.

The long training cycles not only increase financial cost but also hinder iterative experimentation, model refinement, and deployment timelines. As a result, there is a growing need for training-time optimization techniques that reduce computational overhead without sacrificing accuracy or model robustness. Previous research has explored a variety of approaches, including mixed precision training to minimize numerical computation cost [1], data-parallel or model-parallel distributed training across multiple GPUs or nodes [2], gradient checkpointing to trade computation for memory [3], structured pruning and quantization during training [4], and large-batch optimization strategies [5]. While each of these methods provides measurable improvements, most of them focus on isolated performance dimensions either computation speed, memory efficiency, or scalability and often require specialized hardware, complex code modification, or multi-node environments.

A critical gap exists in the development of unified and reusable optimization pipelines that can be applied to existing deep learning models without altering their architecture, hyperparameters, or training objectives. Moreover, many published optimizations lack reproducible implementation frameworks, making them difficult to adopt in real-world workflows.

To address these limitations, this paper introduces a hybrid optimization framework that integrates three complementary techniques: mixed precision training, adaptive batch scaling, and gradient accumulation, to significantly reduce deep learning training time while ensuring stable model convergence. Unlike prior work, the proposed method is hardware-agnostic, supports both single-GPU and multi-GPU environments, and can be incorporated into existing PyTorch and TensorFlow pipelines with minimal modification. The experimental results demonstrate that the proposed hybrid method achieves up to 38.6 percent reduction in training time and over 20 percent reduction in memory footprint, without any notable loss in model accuracy.



Figure1. System Architecture

II. LITERATURE SURVEY

Author	Technique	Speedup	Notes
Micikevicius et al. (2017) [1]	Mixed precision	1.5–2.0×	FP16 with loss scaling
Tang et al. (2020) [2]	Distributed training	3.2×	Requires multi-node setup
Zhuang et al. (2023) [3]	Efficient Transformer training	28% reduction	Focus on attention layers
Menghani (2023) [4]	Training-aware pruning	35% smaller model	Works post epoch-5
Foret et al. (2020) [5]	Sharpness-Aware Minimization	Fewer epochs	Improves generalization

III. METHEDOLOGY

The proposed framework integrates three complementary optimization techniques Mixed Precision Training (MPT), Gradient Accumulation (GA), and Adaptive Batch Scaling (ABS) to significantly reduce deep learning model training time while maintaining model accuracy. Each technique targets a different computational bottleneck: precision computation, memory limit handling, and GPU utilization efficiency.

- Mixed Precision Training

1. Uses both FP16 (half precision) and FP32 (single precision) for forward and backward passes.
2. FP16 reduces GPU memory usage and speeds up matrix multiplications.
3. FP32 is retained for critical parameters to prevent numerical instability.
4. Loss scaling is applied to avoid underflow during back propagation.

- Advantages
  1. 2–3× faster computation on GPUs with TensorCores.

2. 50% reduction in memory usage.

- Gradient Accumulation

When batch size exceeds GPU memory, gradients are accumulated over n smaller mini-batches:

for i in range(accum_steps):

```
    loss = model(data[i]) / accum_steps
    loss.backward()
optimizer.step()
```

- Evaluation Metrix:

Metric	Description
Training Time (min)	End-to-end duration
Memory Usage (GB)	Peak VRAM during training
Accuracy (%)	Validation accuracy
Speedup Ratio	Baseline / Optimized training time

- Experimental Result

1. Training time reduction achieved without distributed training or hardware upgrade**.**
2. Accuracy drop remains below 0.5%**,** validating that precision loss is negligible.
3. Improvements scale well on both image (CNN) and text (Transformer) models.
4. Works on single-GPU laptops, cloud GPU, and multi-GPU servers**.**

Model	Dataset	Baseline Time	Optimized Time	Speedup	Accuracy Δ
ResNet-50	CIFAR-100	162 min	102 min	37.0%	−0.3%
Transformer	IMDB	128 min	78 min	38.9%	−0.4%

- Adaptive Batch Scaling (ABS)

1. Batch size is dynamically adjusted based on GPU utilization and training stability.
2. Starts with a smaller batch size, gradually increases when:
   a. GPU memory is not fully used
   b. Loss curve is stable (no oscillation)
3. If instability or gradient explosion is detected, batch size is reduced again.

- Combine Hybrid Framing:

Stage	Optimization Applied	Objective
Data Loading	Prefetching & caching	Reduce I/O latency
Forward Pass	Mixed Precision (FP16)	Faster computation
Backward Pass	Gradient Accumulation	Memory-efficient training
Optimization Step	Loss scaling + FP32 master weights	Stability
Runtime Monitoring	Adaptive Batch Scaling	Maximize GPU throughput

- Implementation:

Component	Specification
Dataset	CIFAR-10 / ImageNet / Custom
Model Architecture	ResNet-50 / Transformer / CNN
Framework	PyTorch 2.0 (CUDA 12)
Hardware	NVIDIA RTX 4090 / A100 GPU
Baseline	Standard FP32 training without optimization

IV. CONCLUSION

This paper demonstrates that combining mixed precision, gradient accumulation, and adaptive batch control forms an effective hybrid optimization technique capable of reducing training time by up to 38% while preserving model accuracy. Future work will include integrating automated memory profiling, dynamic LR warm up, and TPU-based benchmarking**.**

REFERENCE

[1] P. Micikevicius et al., "Mixed Precision Training," *Proc. ICLR*, 2017.

[2] H. Tang et al., "Communication-Efficient Distributed Deep Learning," *IEEE TPDS*, 2020.

[3] H. Zhuang et al., "A Survey on Efficient Training of Transformers," *IJCAI*, 2023.

[4] G. Menghani, "Efficient Deep Learning: A Survey," *arXiv preprint*, 2023.

[5] P. Foret et al., "Sharpness-Aware Minimization for Efficient Training," *NeurIPS*, 2020.