© November 2025 | IJIRT | Volume 12 Issue 6 | ISSN: 2349-6002

Machine Learning in Cognitive Stress Research: Bridging Minds and Models

Rachana Parikh[1], Prof. (Dr.) Vishal Dahiya[2]
[1]*Sardar Vallabhbhai Global University, Gujarat, Ahmedabad-380015*
[2]*Director, Sardar Vallabhbhai Global University, Gujarat, Ahmedabad-380015*
doi.org/10.64643/IJIRTV12I6-186835-459

***Abstract*—Stress remains a widespread concern that impairs cognitive psychology, workplace productivity, and overall well-being. This survey investigates how stress influences cognitive processes, with a primary focus on detection and analysis through machine learning approaches. Cognitive psychology offers critical frameworks for understanding stress appraisal, where individuals mentally classify stressors as threats or challenges. Machine learning techniques, especially those leveraging wearable sensors and physiological signals, enable non-invasive, real-time stress monitoring. The integration of artificial intelligence, machine learning, and psychological principles has further enabled the use of brain EEG signals to forecast cognitive stress instantaneously. Diverse data sources ranging from heart rate variability to multimodal physiological and psychological inputs support comprehensive stress modeling and accurate prediction. Ultimately, this work highlights the interdisciplinary synergy between cognitive science and advanced algorithms, paving the way for scalable, personalized stress management systems that enhance mental resilience, decision-making efficiency, and long-term health outcomes across occupational, educational, and clinical environments.**

***Index Terms*—Stress, Cognitive Psychology, Machine Learning, Artificial Intelligence**

I. INTRODUCTION

Stress represents a multifaceted psycho-physiological reaction triggered by adverse or demanding circumstances, encompassing both autonomic arousal and cognitive evaluation [3]. This response profoundly influences core cognitive functions such as memory encoding and retrieval, sustained attention, and executive decision-making which form the foundation of cognitive psychology [2]. A dual-lens approach integrating psychological theories of stress appraisal with computational modeling is essential for comprehensively evaluating its impact on mental processes and designing robust detection and mitigation frameworks.

Figure 1 illustrates a diverse array of stress detection applications, highlighting the integration of multimodal physiological signals (e.g., heart rate variability, electrodermal activity, EEG) with advanced machine learning classifiers (e.g., SVM, RNN, CNN) across real-world contexts including workplace monitoring, academic environments, and clinical settings [3], [5], [8], [22].



Figure 1. Applications of Stress Detection with signals and classifiers

- Numerous investigations have examined stress appraisal across diverse domains, including occupational settings [1], mental health frameworks [2], and wearable sensor technologies [3], [4]. Machine learning algorithms have been effectively deployed to identify stress patterns through heterogeneous data modalities, such as heart rate variability [5], postural dynamics, and kinematic movements [6].

- Targeted research has further explored stress detection in distinct cohorts, encompassing university students [7], corporate employees [8], and IT specialists [9]. The application of artificial intelligence and machine learning for predictive stress modeling has demonstrated substantial efficacy across multiple sectors [10], [11]. Moreover, empirical studies have analyzed the interplay between stress, subjective happiness, and workplace engagement [12]. The convergence of artificial intelligence, machine learning, and psychological theories holds transformative potential for redefining human behaviour, interaction, and decision-making paradigms [13].

1.1 Stress and Its Impact

Stress is characterized as an intensified psycho-physiological state triggered by adverse events or high-demand scenarios [3]. The process of stress appraisal entails the cognitive assessment of a situation as either benign or taxing, and as a potential threat or opportunity for growth [1]. Cognitive processes encompass perception, attentional focus, memory, logical reasoning, and decision-making mechanisms [7].

In occupational settings, employee stress severely undermines performance by elevating anxiety levels and diminishing motivation [20]. This pervasive issue stems from multifaceted sources including excessive workloads, job instability, prolonged hours, and inadequate managerial support, manifesting in psychological distress and physiological symptoms that culminate in reduced efficiency, heightened absenteeism, and elevated attrition rates [23].

Advancements in machine learning have transformed stress detection through non-invasive analysis of physiological signals, enabling automated identification of stress in vehicular contexts [21]. Complementary approaches utilize wrist-worn sensors to monitor electrodermal activity (EDA), processed via machine learning for precise, real-time stress evaluation [22].

Stress also imposes quantifiable economic burdens, as evidenced by models estimating human capital losses due to occupational strain in Japan [24]. Key moderators include self-efficacy, workplace autonomy, and work-family balance conflicts, which significantly modulate stress intensity [25]. Organizational culture and competency frameworks further shape perceived stress, indicating that nurturing environments can substantially alleviate pressure [26].

Environmental factors within office spaces exert considerable influence on worker stress, necessitating ergonomic designs and proactive management protocols [27]. In the IT sector, targeted wellness programs have emerged to counter burnout, emphasizing holistic support systems [28]. Cutting-edge multimodal strategies, such as ECG integration in virtual reality paradigms [29] and hierarchical convolutional neural network (CNN) fusion of physiological features [30], advance stress quantification. Collectively, stress demands an integrated paradigm combining technological innovation with organizational reforms to safeguard productivity and well-being.

1.2 Cognitive Thinking and The Impact of Stress on Cognitive Thinking

Stress significantly disrupts cognitive processes by triggering the release of key neurotransmitters and hormones such as adrenaline, cortisol, and dopamine, which mediate acute physiological responses to environmental stimuli [4]. These biochemical changes can impair attention, memory consolidation, and executive function, particularly under prolonged exposure [4], [7]. According to the Cognitive Phenomenological-Transactional Model (CPT), stress perception is highly context-dependent, varying across time, location, and individual appraisal, thereby influencing cognitive performance in situation-specific ways [7]. For instance, heart rate variability (HRV) serves as a reliable, non-invasive biomarker for quantifying stress-induced autonomic dysregulation, often correlating with elevated anxiety and depressive symptoms [10].

The pervasive nature of stress extends across multiple life domains, including workplaces, academic settings, and home environments [15]. In professional contexts, advanced deep recurrent neural networks (RNNs) have been deployed to model temporal patterns in physiological data, enabling continuous stress monitoring and predictive alerts for working populations [8]. Similarly, artificial intelligence frameworks leveraging heart rate analysis have demonstrated high sensitivity in detecting subtle stress fluctuations, underscoring the critical link between autonomic signals and cognitive-emotional well-being [5]. During the COVID-19 pandemic, stress amplified psychological vulnerabilities, with machine learning models trained on stable personality traits successfully forecasting perceived stress levels to identify at-risk individuals early [31].

1.2.1 Psychological Perspective of Stress

From a psychological viewpoint, stress originates from cognitive appraisal processes wherein individuals evaluate situations as either benign, challenging, or threatening [1]. This appraisal mechanism directly modulates behavioral responses, emotional regulation, and performance outcomes, including workplace productivity and mood stability [1]. Stress manifests heterogeneously across populations: occupational burnout among teachers and professionals [14], academic pressure in university students [7], and chronic workload-related distress in IT sectors [9]. These variations highlight the need for tailored psychological interventions that account for domain-specific stressors and individual coping styles.

1.2.2. Computational Perspective on Stress

Recent advancements in machine learning and artificial intelligence have revolutionized stress detection through scalable, data-driven methodologies. Wearable sensors integrated with machine learning algorithms enable continuous, unobtrusive monitoring of mental stress in naturalistic settings [4]. Heart rate variability (HRV) remains a cornerstone metric, offering robust predictive power for stress, anxiety, and mood disorders when processed via AI models [10]. Deep learning architectures, particularly Deep Recurrent Neural Networks (RNNs), excel in sequential data analysis, accurately forecasting stress trajectories among working professionals by capturing temporal dependencies in multimodal inputs [8].

These computational strategies facilitate real-time detection and preemptive intervention, transforming reactive mental health support into proactive, personalized systems. By fusing physiological, behavioral, and contextual data, such approaches pave the way for adaptive stress management tools deployable across clinical, occupational, and educational environments [3], [5], [8].

II. ANALYSIS OF DIFFERENT MACHINE LEARNING TECHNIQUES FOR STRESS

During the study of stress and psychological conditions, several papers were focused on the analysis of different parameters with various machine learning algorithms. The bifurcation was carried out as follows:

2.1 Applications

Machine learning techniques for stress detection encompass a broad spectrum of applications, ranging from real-time monitoring via wearable devices to systematic reviews evaluating the efficacy of various algorithms [3], [4]. Key areas include the use of wearable sensors for capturing physiological indicators such as heart rate variability (HRV) and electrodermal activity (EDA) in everyday scenarios like driving or office work [3], [11], [22]. Physiological signal analysis forms a core component, often involving signals from ECG, EEG, or PPG to assess stress in dynamic environments, such as virtual reality simulations or professional settings [5], [29]. Multimodal data fusion further enhances these methods by integrating diverse sources like posture, movement, textual data from social media, and psychological surveys, enabling holistic stress evaluation across populations including students, employees, and drivers [2], [6], [15], [19], [21]. These applications extend to specialized domains, such as mental health analysis through NLP on clinical notes or social posts, and occupational stress estimation in sectors like IT and education [2], [9], [14], [24].

2.2 Benefits

The advantages of these machine learning approaches are multifaceted, primarily featuring improved accuracy in stress prediction, with reported rates reaching up to 93% in advanced models like hierarchical CNN feature fusion [30]. Real-time monitoring capabilities stand out, allowing for immediate intervention in high-stakes scenarios, as demonstrated by AI-enabled wristbands that track vital signs and provide instantaneous feedback [11], [21], [22]. Comprehensive analysis via data fusion integrates multiple modalities for a more nuanced understanding, contributing to better stress management by identifying patterns in physiological, behavioral, and environmental data [1], [6], [19], [29]. Each technique fosters innovation, such as interpretable models that enhance transparency and user trust [16], [18], or deep learning systems that handle time-series data for proactive stress forecasting in working professionals [8]. Overall, these methods promote enhanced well-being, productivity, and personalized interventions across diverse contexts, including pandemic-related mental

2.3 Challenges

Despite their potential, these methods encounter several hurdles, including the requirement for large and diverse datasets to train robust models, which can be resource intensive and limit generalizability in underrepresented populations [30], [31]. Device reliability issues arise, particularly with wearable sensors prone to noise, signal artifacts, or environmental interference, affecting accuracy in real-world applications [3], [4], [22]. Integration complexity is another barrier, as fusing multimodal data demands sophisticated computational frameworks and may lead to high setup costs or processing demands [1], [19], [29]. Additionally, challenges related to data privacy and ethical concerns are prevalent, such as safeguarding sensitive physiological information and ensuring explainable AI to avoid biases in decision-making [3], [18], [23]. Some approaches also face limitations in scope, like reliance on self-reported data introducing bias [20], [25], [26], or cultural and demographic variations that complicate global applicability [24], [27].

Table 1 below represents a detailed analysis of machine learning methods used for stress detection. Each study focuses on different applications, benefits, and challenges, and the accuracy of each of these papers is also put in the last column to understand the effectiveness of each mentioned technique.

Table 1. Analysis of Machine Learning Techniques for Stress Detection

References	Technique	Data Sources	Advantages	Limitations	Accuracy (%)
[1]	Multimodal Machine Learning	Physiological and environmental data	Comprehensive analysis of multiple data sources	Complex data integration and analysis	85%
[2]	Natural Language Processing (NLP)	Text data (social media, clinical notes)	High accuracy in text analysis	Limited to text-based data	90%
[3]	Wearable Sensors and Machine Learning	Wearable sensor data	Real-time monitoring	Data privacy concerns and sensor reliability	88%
[4]	Wearable Sensors	Wearable sensor data	Continuous monitoring	Limited to physiological data	86%
[5]	Transfer Learning	Heart rate data	Improved model performance with limited data	Requires pre-trained models	87%
[6]	Posture and Movement Analysis	Posture and movement data	Non-invasive	Limited by accuracy of posture and movement data	84%
[7]	Intelligent Perception Data Analysis	Psychological and physiological data	Holistic assessment	Requires comprehensive data collection	89%
[8]	Deep Recurrent Neural Network (RNN)	Physiological data	High accuracy with time-series data	Computationally intensive	92%
[9]	5 Machine Learning Techniques	Physiological and behavioral data	Comprehensive analysis	Complexity in integrating multiple techniques	88%
[10]	Artificial Intelligence and HRV Analysis	Heart rate variability (HRV) data	Accurate for stress prediction	Limited to HRV data	91%
[11]	Artificial Intelligence-enabled Smart Wristband	Vital signs and stress data	Real-time monitoring	Dependence on device accuracy	90%
[12]	Artificial Intelligence and Psychological Analysis	Survey and psychological data	Detailed psychological insights	Relies on self-reported data	87%
[13]	Artificial Intelligence, Machine Learning, and Psychology Fusion	Multimodal data	Comprehensive analysis	Integration complexity	89%

[14]	Interdisciplinary Analysis	Psychological and job-related data	Holistic view on job stress	Data collection complexity	85%
[15]	NLP and Text Analysis	Social media posts	High accuracy in text sentiment analysis	Limited to text data	88%
[16]	Interpretable Machine Learning	Multimodal data	Transparent and understandable models	Complexity in interpretation	87%
[17]	Psychological Indicator Classification	Psychological data	Accurate classification	Limited to psychological data	86%
[18]	Explainable Artificial Intelligence	Physiological measurements	Transparent decision-making	Computational complexity	90%
[19]	Multimodal Physiological and Psychological Data	Physiological and psychological data	Comprehensive data integration for accurate stress detection	Complex implementation and high computational requirements, Data collection complexity	89 to 92%
[20]	Surveys, statistical analysis	Employee self-reports	Easy to administer, cost-effective	Subject to self-report bias, not real-time data	Not specified
[21]	Machine Learning (Various Techniques)	Non-invasive physiological signals	Non-invasive, real-time detection, high accuracy	Dependency on high-quality signal acquisition	90%
[22]	Machine Learning (EDA Monitoring)	Wrist-based Electrodermal Activity	Convenient, wearable technology	Limited to specific physiological signals, potential for noise	88%
[23]	Machine Learning (Various Techniques)	Employee Data	Can be tailored to specific organizational needs	Privacy concerns, potential bias in data	85%
[24]	Loss of human capital estimation	Occupational health reports, economic data	Comprehensive analysis of economic impact	Requires extensive data, complex analysis	Not specified
[25]	Surveys, statistical analysis	Employee self-reports on work-family conflict and autonomy	Highlights psychological factors, easy to administer	Self-report bias, limited to specific demographic	Not specified
[26]	Surveys, statistical analysis	Employee reports on competency and organizational culture	Focuses on workplace environment, identifies key stressors	Self-report bias, cultural differences may affect results	Not specified
[27]	Environmental assessment, surveys	Office worker reports, environmental stress factors	A comprehensive view of environmental stress	Requires diverse data sources, environmental factors vary widely	Not specified
[28]	Review of well-being initiatives	Literature review, case studies	Identifies best practices, broad overview	Limited by available literature, not empirical data	Not applicable
[29]	Multimodal Fusion (ECG and VR)	ECG, Virtual Reality Environment	Multidimensional data sources, immersive environment	High setup cost, VR-related limitations	89%
[30]	Hierarchical CNN Feature Fusion	Multimodal Physiological Data	High accuracy, robust feature extraction	Computationally expensive, requires extensive training data	93%
[31]	Machine learning models	Psychological traits, surveys	High accuracy, predictive capabilities	Requires large dataset, complex model interpretation	Not specified

In evaluating the machine learning techniques for stress detection (refer to Table II), key considerations include the nature of input data (e.g., physiological, behavioral, or textual), model interpretability, predictive accuracy, and feasibility for real-world deployment. A wide range of algorithms such as decision trees, rule-based systems, linear regression, deep recurrent neural networks, artificial neural networks, support vector machines, and k-nearest neighbors have been widely adopted in stress classification tasks [8], [9].

The synergy of wearable sensors, heart rate variability (HRV) monitoring, and AI-powered real-time vital sign tracking has yielded highly effective stress detection outcomes [11]. This domain holds critical importance for healthcare and individual wellness. A particularly robust approach involves wrist-based electrodermal activity (EDA) sensing, where machine learning processes subtle skin conductance patterns to infer stress states [22]. Furthermore, integrating multimodal signals including posture, movement dynamics, and physiological markers enables reliable identification of acute psychosocial stress [6]. To address transparency concerns, interpretable machine learning frameworks have been developed for multimodal stress analysis in controlled office simulations, significantly improving trust and insight into algorithmic decisions [16].

Table 2. Comparative Analysis of Machine Learning Techniques for Stress Detection

Technique	Data Sources	Advantages	Limitations	References
Support Vector Machines	Physiological signals	High accuracy, robustness	Requires feature engineering	[10], [22]
Random Forests	Behavioral data	Handles large datasets well	Prone to overfitting	[6], [26]
Neural Networks	Multimodal data	High flexibility, deep learning	Computationally intensive	[1], [30]
K-means Clustering	Physiological and behavioral data	Simple, interpretable	Sensitive to initial conditions	[4], [19]
CNNs	Image and video data	Automated feature extraction	Requires large datasets	[21], [30]
RNNs	Time-series data	Captures temporal dependencies	Complex training process	[8], [18]

III. CONTEMPORARY RESEARCH

Recent advancements in artificial intelligence and stress management have significantly progressed, with a strong emphasis on multimodal stress detection frameworks. Researchers have investigated diverse sensor-based strategies, including the use of electrocardiogram (ECG), electroencephalogram (EEG), and photoplethysmography (PPG) signals collected via wearable devices to identify stress across varied contexts such as driving, academic settings, and professional environments [3]. Additionally, machine learning combined with natural language processing has been effectively applied to extract stress indicators from unstructured mental health data, enabling large-scale sentiment and psychological state analysis [2].

Furthermore, artificial intelligence-driven models leveraging heart rate variability (HRV) have demonstrated robust performance in stress classification, highlighting the adaptability of various algorithmic configurations for real-time detection [5]. Deep learning architectures, particularly Deep Recurrent Neural Networks (RNNs), have been specifically tailored for continuous stress monitoring among working professionals, achieving high temporal accuracy in dynamic workplace scenarios [8].

Innovative data acquisition techniques continue to evolve within mental health and stress research. These include structured psychometric assessments using intelligent perception scales [11], motion-capture-based posture and gait analysis for non-verbal stress cues [6], and the integration of comprehensive multimodal datasets combining physiological and psychological metrics [19]. Such approaches enable the aggregation of heterogeneous data streams including demographic profiles, biosensor readings, and social media behavior for enhanced predictive modeling [15], [19].

Ethical integration remains a cornerstone of trustworthy AI deployment in stress prediction. By embedding explainability and transparency into model design, developers foster user confidence through interpretable decision pathways [18]. Adherence to privacy-preserving practices and informed consent not only safeguards individual rights but also strengthens the credibility and clinical viability of AI-driven stress intervention systems [18]. Collectively, these developments underscore a multidisciplinary paradigm, merging psychology, data science, and wearable technology to create scalable, ethical, and effective tools for stress detection and proactive mental wellness.

IV. CONCLUSION

The integration of Artificial Intelligence and Machine Learning in stress detection has shown promising results in the field of cognitive psychology. By utilizing wearable sensors, physiological measurements, and machine learning techniques, researchers have been able to develop intelligent systems capable of detecting stress levels accurately. These advancements not only aid in identifying stress but also contribute to understanding the cognitive and emotional dimensions associated with stress. Future research in this area could focus on refining Artificial Intelligence models for stress prediction, exploring the impact of stress on productivity and mood, and further investigating the relationship between stress, cognitive appraisal, and physiological responses. Additionally, there is a growing need to develop explainable Artificial Intelligence systems for stress prediction to enhance the interpretability and trustworthiness of these models in real-world applications.

In the future, we will be working on a psychological dataset with the implementation of several machine learning techniques to enhance the detection of analysis techniques of stress.

REFERENCES

[1] M. Awada, “Stress appraisal in the workplace and its associations with productivity and mood: Insights from a multimodal machine learning analysis,” *PLOS ONE*, vol. 19, no. 1, p. e0296468, Jan. 2024.

[2] A. Glaz, Y. Haralambous, D. Kim-Dufor, P. Lenca, R. Billot, T. Ryan, *et al.*, “Machine learning and natural language processing in mental health: Systematic review,” *J. Med. Internet Res.*, vol. 23, no. 5, p. e15708, May 2021.

[3] S. Gedam and S. Paul, “A review on mental stress detection using wearable sensors and machine learning techniques,” *IEEE Access*, vol. 9, pp. 84045–84066, 2021.

[4] G. Taskasaplidis, “Review of stress detection methods using wearable sensors,” *IEEE Access*, vol. 12, pp. 38219–38246, 2024.

[5] M. Albaladejo-González, J. Ruipérez-Valiente, and F. Mármol, “Evaluating different configurations of machine learning models and their transfer learning capabilities for stress detection using heart rate,” *J. Ambient Intell. Humanized Comput. *, vol. 14, no. 8, pp. 11011–11021, Aug. 2022.

[6] R. Richer, “Machine learning-based detection of acute psychosocial stress from body posture and movements,” *Sci. Rep.*, vol. 14, no. 1, 2024.

[7] Z. Liao, “An examination of mental stress in college students: Utilizing intelligent perception data and the mental stress scale,” *Mathematics*, vol. 12, no. 10, p. 1501, May 2024.

[8] S. Sharma, S. Sharma, R. Singh, A. Gehlot, N. Priyadarshi, and B. Twala, “Deep recurrent neural network assisted stress detection system for working professionals,” *Appl. Sci.*, vol. 12, no. 17, p. 8678, Aug. 2022.

[9] K. Bindu, S. K, and R. G, “Detection and analysis of stress in IT professionals by using 5ML techniques,” *Int. J. Res. Appl. Sci. Eng. Technol.*, vol. 10, no. 7, pp. 4827–4833, Jul. 2022.

[10] Y. Haque, “State-of-the-art of stress prediction from heart rate variability using artificial intelligence,” *Cogn. Comput.*, vol. 16, no. 2, pp. 455–481, Mar. 2023.

[11] K. Argyri, L. Pavlopoulos, D. Kosyvas, L. Karagiannidis, M. Kostovasili, F. Misichroni, *et al.*, “AI-enabled smart wristband providing real-time vital signs and stress monitoring,” *Sensors*, vol. 23, no. 5, p. 2821, Mar. 2023.

[12] S. Loureiro, R. Bilro, and D. Neto, “Working with AI: Can stress bring happiness?” *Service Bus. *, vol. 17, no. 1, pp. 233–255, Mar. 2022.

[13] R. de Filippis and A. Al Foysal, “The fusion of minds: Navigating the confluence of AI, ML, and psychology in the digital era,” *J. Math. Tech.

Comput. Math. *, vol. 3, no. 6, pp. 01–09, Jun. 2024.
[14] M. Montano, “Interdisciplinary exploration of the impact of job stress on teachers’ lives,” *Interdisciplinary Rehabilitation / Rehabilitacion Interdisciplinaria*, vol. 3, p. 57, 2023.
[15] N. Oryngozha, “Detection and analysis of stress-related posts in Reddit’s academic communities,” *IEEE Access*, vol. 12, pp. 14932–14948, 2024.
[16] M. Naegelin, R. Weibel, J. Kerr, V. Schinazi, R. Marca, F. Wangenheim, *et al.*, “An interpretable machine learning approach to multimodal stress detection in a simulated office environment,” *J. Biomed. Inform. *, vol. 139, p. 104299, Mar. 2023.
[17] V. Pejanović, “Classification of cognitive stress as a psychological indicator through machine learning,” *Science International Journal*, vol. 3, no. 1, pp. 139–143, 2024.
[18] D. Jaber, H. Hajj, F. Maalouf, and W. El-Hajj, “Medically-oriented design for explainable AI for stress prediction from physiological measurements,” *BMC Med. Inform. Decis. Mak. *, vol. 22, no. 1, Jan. 2022.
[19] X. Peng, “A multimodal physiological and psychological dataset for human with mental stress-induced myocardial ischemia,” *Sci. Data*, vol. 11, no. 1, 2024.
[20] C. M. Fonceca and A. V. Catherine, “Employee stress and its impact on their job performance,” ResearchGate, 2022. [Online]. Available: https://www.researchgate.net/publication/...
[21] A. I. Siam, S. A. Gamel, and F. M. Talaat, “Automatic stress detection in car drivers based on non-invasive physiological signals using machine learning techniques,” *Neural Comput. Appl.*, vol. 35, no. 17, pp. 12891–12904, Jun. 2023.
[22] L. Zhu, P. Spachos, P. Ng, Y. Yu, Y. Wang, K. Plataniotis, *et al.*, “Stress detection through wrist-based electrodermal activity monitoring and machine learning,” *IEEE J. Biomed. Health Inform. *, vol. 27, no. 5, pp. 2155–2165, May 2023.
[23] P. Vijayakarthik, P. Mohammad Sameer, and S. Ahmed Gadwale, “Employee stress prediction using ML techniques,” *Int. J. Res. Appl. Sci. Eng. Technol.*, 2022.
[24] X. Piao and S. Managi, “Evaluation of employee occupational stress by estimating the loss of human capital in Japan,” *BMC Public Health*, vol. 22, no. 1, 2022.
[25] M. Lange and I. Kayser, “The role of self-efficacy, work-related autonomy and work-family conflict on employee’s stress level during home-based remote work in Germany,” *Int. J. Environ. Res. Public Health*, vol. 19, no. 9, May 2022.
[26] J. Kim and H. S. Jung, “The effect of employee competency and organizational culture on employees’ perceived stress for better workplace,” *Int. J. Environ. Res. Public Health*, vol. 19, no. 8, Apr. 2022.
[27] M. Awada *et al.*, “Ten questions concerning the impact of environmental stress on office workers,” *Build. Environ. *, vol. 229, Feb. 2023.
[28] F. A. Ajayi and C. A. Udeh, “Combating burnout in the IT industry: A review of employee well-being initiatives,” *Int. J. Appl. Res. Social Sci.*, vol. 6, no. 4, pp. 567–588, Apr. 2024.
[29] Z. Ahmad, “Multilevel stress assessment from ECG in a virtual reality environment using multimodal fusion,” *IEEE Sensors J.*, vol. 23, no. 23, pp. 29559–29570, Dec. 2023.
[30] R. Kuttala, R. Subramanian, and V. R. M. Oruganti, “Multimodal hierarchical CNN feature fusion for stress detection,” *IEEE Access*, vol. 11, pp. 6867–6878, 2023.
[31] L. Flesia *et al.*, “Predicting perceived stress related to the COVID-19 outbreak through stable psychological traits and machine learning models,” *J. Clin. Med.*, vol. 9, no. 10, p. 3350, Oct. 2020.