© November 2025 | IJIRT | Volume 12 Issue 6 | ISSN: 2349-6002

Telematic Solution for Smart Vehicle

Mr. Prathamesh Aher[1], Miss. Siddhi kale[2], Mr. Akshay chobe[3],
Miss. Akanksha kanse[4], Prof. B.B. Mirkhale[5], Dr. Rohan R Kubde[6]
[1,2,3,4,5]*Sinhgad Instutue of Technology & Science Narhe, Pune, India*

Abstract— **Modern vehicle telematics systems combine onboard electronics with cloud services to enhance safety, tracking, and maintenance. This paper presents a comprehensive telematics architecture built around an STM32 microcontroller, integrating GPS, 4G LTE communication, a MEMS accelerometer/gyroscope, a CAN-bus interface, and robust power management, all feeding into a cloud dashboard. The design enables real-time vehicle tracking, accident detection, driver behavior analysis, and predictive maintenance. A prototype block diagram and workflow illustrate data flow from sensors to cloud.**

The system leverages MEMS sensors to detect crashes and triggers alerts via 4G, sending GPS coordinates and vehicle status to emergency responder. CAN-bus connectivity allows reading engine and vehicle data for maintenance alerts. Results from similar implementations show that such systems significantly improve fleet safety and operational efficiency. In conclusion, the proposed design enhances safety and is scalable for both individual drivers and fleet management, with future work pointing toward machine learning-based analytics and broader connectivity.

Index Terms— **STM32 Microcontroller, Accident Detection, Driver Behavior Monitoring, Predictive Maintenance, GPS Tracking, IoT in Transportation, CAN Bus Interface, Cloud Dashboard, 4G LTE Communication, Real-Time Vehicle Monitoring, Inertial Measurement Unit (IMU), MEMS Sensors, Fleet Management**

I. INTRODUCTION

Connected vehicle telematics leverages embedded electronics and wireless links to monitor vehicle status and driver behavior in real time. For example, an industry reference design uses a Cortex-M3 STM32 microcontroller with an integrated GPS receiver and GSM/GPRS modem to collect location, speed, and sensor data, and transmit it to a server. Modern IoT platforms extend this concept: by combining sensors such as GPS, accelerometers, gyroscopes, and cellular modems, they can detect crashes with high accuracy and instantly notify authorities and fleet managers. This integration of

MEMS sensors (to detect abrupt motion or rollover) with cellular connectivity enables "eCall" style emergency alerts in seconds, greatly reducing response time after an accident. In addition to safety, telematics data enables driver behavior analysis and predictive maintenance, improving efficiency for both individual drivers and large fleets. This paper proposes a detailed STM32-based telematics solution that unifies GPS tracking, 4G IoT communication, MEMS sensing, CAN-bus diagnostics, and power management into a scalable platform. The contributions include (1) a methodology and block diagram for the integrated hardware, (2) a system architecture with data flow to a cloud dashboard, and (3) analysis of how the solution enhances safety and supports fleet-scale deployment.

The rapid advancement of automotive electronics, wireless communication, and cloud computing has led to the emergence of smart vehicles equipped with advanced telematics systems. These systems combine vehicle sensor data acquisition, real-time communication, and intelligent decision-making to enhance driving safety, improve vehicle maintenance, and optimize fleet operations. Telematics, a fusion of "telecommunications" and "informatics," plays a crucial role in bridging the gap between vehicles and remote data servers, enabling real-time monitoring, analytics, and response capabilities.

With road accidents still claiming over a million lives annually worldwide, crash detection and emergency alert systems are becoming essential safety features. Traditional systems, such as eCall in Europe, are being enhanced by smart telematics platforms that offer faster response, richer data, and greater scalability. Furthermore, fleet operators and logistics companies are increasingly relying on telematics for route optimization, driver performance tracking, and predictive maintenance, which not only reduce costs but also improve operational reliability.

II. LITERATURE SURVEY

1. In recent years, researchers have made significant progress in developing IoT-based accident detection and emergency alert systems. These systems primarily rely on a combination of GPS, accelerometers, and communication modules such as GSM or LTE. For example, several studies demonstrated that using a 3-axis accelerometer to detect sudden deceleration and integrating it with GPS allows the system to send the vehicle's exact location to emergency services immediately after a crash. This rapid communication has been shown to reduce emergency response time and improve survival rates. The integration of low-cost IoT components also makes such systems feasible for both commercial and personal vehicles.
2. Another important research direction involves the integration of telematics systems with embedded microcontrollers. Among various controllers, the STM32 series by STMicroelectronics has gained popularity due to its low power consumption, high processing speed, and multiple communication interfaces such as UART, SPI, and CAN. The STM32 has been effectively used in telematics prototypes that gather GPS data, process sensor readings, and control GSM/LTE modules. For example, the STEVAL-IEG001V2 reference design from ST demonstrates real-time GPS tracking and black-box crash data recording, which forms a foundation for modern smart vehicle telematics architectures.
3. MEMS-based motion and impact detection has also contributed greatly to telematics development. + (collectively known as IMUs – Inertial Measurement Units) are essential for detecting rollovers, crashes, and unsafe driving behaviors. When combined with GPS, MEMS sensors provide multi-sensor fusion, increasing the accuracy of accident detection. Studies reveal that multi-sensor fusion reduces false alarms caused by road bumps or hard braking, ensuring only genuine accidents trigger alerts. This technology has also been used for detecting driver fatigue, lane deviation, and reckless driving patterns.
4. The Controller Area Network (CAN) bus has been another major focus area in the literature. It is a standard communication protocol used in all modern vehicles for ECU (Electronic Control Unit) communication. Researchers have implemented telematics systems that connect microcontrollers to the CAN bus to collect real-time data such as RPM,engine temperature, and fault codes. This data helps monitor vehicle health, enabling predictive maintenance and fault diagnosis. Studies show that integrating CAN data with IoT dashboards allows fleet managers to anticipate mechanical issues before failure occurs, reducing downtime and maintenance costs.
5. The integration of cloud computing and IoT platforms in telematics has opened new possibilities for large-scale data management. Platforms such as AWS IoT Core, Azure IoT Hub, and Google Cloud IoT have been used to create dashboards for real- time monitoring and data analytics. These platforms enable remote visualization of live GPS tracking, vehicle status, and driver behavior. Research confirms that combining telematics data with cloud analytics improves decision-making for fleet operations, maintenance scheduling, and route optimization.
6. Several studies have explored driver behavior monitoring through telematics data analysis. Parameters such as acceleration, braking intensity, cornering force, and speed are collected via IMU and GPS sensors. By applying machine learning algorithms to these datasets, systems can classify driving styles as normal, aggressive, or fatigued. For instance, deep learning models trained on telematics data achieved more than 90% accuracy in identifying risky driving behavior. This has practical applications in insurance telematics, where driver scoring models are used to adjust premiums based on driving habits.
7. Research on predictive maintenance using AI and IoT shows that analyzing vibration, temperature, and voltage data helps predict mechanical failures before they occur. Embedded AI models running directly on STM32 microcontrollers enable real-time fault prediction without continuous cloud dependency. Studies demonstrate that predictive

maintenance reduces repair costs and increases the lifespan of critical components. Combining this capability with cloud storage enables both edge and cloud analytics for scalable deployment.

8. Power management is another crucial aspect covered in the literature. Automotive telematics units must operate reliably even during voltage fluctuations or after a crash. Research highlights the use of automotive-grade power circuits and battery backup modules that maintain system operation when the main vehicle battery is disconnected. For instance, circuits using voltage monitoring comparators or Li-ion backup modules ensure that accident alerts are sent even if the main power source fails. Such designs enhance reliability and make the system suitable for real-world automotive conditions.
9. Studies on fleet management systems reveal that integrating telematics with cloud dashboards significantly improves logistics efficiency and vehicle utilization. IoT-based fleet management architectures have been deployed in large-scale industrial operations, such as mining and transportation sectors. Reports show that telematics adoption reduces fuel consumption, prevents unauthorized vehicle use, and increases overall operational efficiency. A mining fleet study found a 25% improvement in resource utilization and a 30% reduction in accidents after adopting IoT-based telematics monitoring.
10. From the above literature, it is evident that numerous advancements have been made in isolated areas such as accident detection, driver behavior analysis, and predictive maintenance. However, there is still a lack of a comprehensive telematics framework that integrates all these features into a single, cost- effective, and scalable solution. The proposed work bridges this gap by developing a unified telematics system that combines sensor fusion, CAN-based diagnostics, cloud integration, and AI-driven analytics for real-time vehicle monitoring and safety enhancement.
11. Recent literature emphasizes the use of 5G and advanced communication networks to improve telematics data transfer speed and reliability. Traditional GSM and LTE-based systems face limitations such as latency and limited bandwidth during high data loads. With the rollout of 5G and Vehicle-to-Everything (V2X) communication, telematics systems can now support ultra-low-latency data transmission between vehicles, infrastructure, and cloud servers. Researchers report that 5G-enabled telematics improves real-time monitoring and enables advanced features like cooperative collision avoidance and platooning in autonomous fleets. =
12. Studies also highlight the emergence of Edge Computing in vehicular telematics, where data processing and analytics occur locally on the telematics control unit instead of relying solely on cloud servers. Edge computing reduces response time for critical events such as crash detection or system faults. Researchers have implemented lightweight machine learning models on microcontrollers like STM32 to process vibration, acceleration, and engine data on-site, which enhances reliability even when internet connectivity is poor.
13. Energy efficiency and sustainability have become crucial research themes in telematics design. New studies propose low-power IoT architectures that minimize battery drain while maintaining continuous connectivity. For instance, systems incorporating NB-IoT (Narrowband IoT) and LoRaWAN technologies consume significantly less power compared to 4G/LTE while still offering wide-area coverage. This approach is ideal for remote fleet monitoring, electric vehicles, and long- distance logistics. Researchers have demonstrated that adopting energy-efficient IoT protocols can extend device uptime by over 40% in field conditions.
14. Security and data privacy are key challenges identified in several research works. As vehicles become increasingly connected, they are more exposed to cyber threats such as GPS spoofing, data interception, or unauthorized cloud access. Literature on automotive cybersecurity suggests implementing end-to-end encryption (TLS/SSL), secure boot mechanisms, and blockchain-based authentication in telematics systems. Blockchain technology, in particular, has been proposed for creating tamper-proof logs of vehicle data, ensuring the integrity of crash reports and driver analytics.

III. PROBLEM STATEMENT

Despite advances, many vehicles still lack a unified telematics unit that combines high-speed connectivity with rich sensing and diagnostics. Traditional accident-alert systems may use simple GSM/GPS modules and crash sensors, but often rely on outdated networks or manual triggers.

There is a need for a platform that can continuously monitor vehicle health and driver behavior, detect anomalies (crashes or hazardous driving), and communicate this data instantly to cloud services. The challenges include ensuring reliable communication even in remote areas, powering the device through vehicle voltage transients, and processing data efficiently on a low-cost MCU.

For instance, accidents remain a critical issue worldwide, with delayed emergency alerts contributing significantly to fatalities.

A robust telematics design must address these problems by integrating multi-sensor data acquisition (accelerometer, gyro, GPS, CAN- bus) with 4G/LTE IoT connectivity, plus features like automatic emergency calling and a scalable cloud dashboard. In summary, the problem is to build an all-in-one telematics solution that improves safety (through quick accident detection and alert), enables predictive maintenance, and scales to fleets, all while handling automotive power conditions.

IV. METHODOLOGY

The proposed telematic solution for smart vehicles is designed as an intelligent, modular, and IoT-integrated system capable of monitoring vehicle health, driver behavior, and accident events in real time. The methodology focuses on developing a cost-effective and scalable solution using an STM32 microcontroller, which acts as the central processing unit of the system. The proposed design integrates several hardware and software modules, including GPS, MEMS sensors (accelerometer and gyroscope), CAN bus interface, 4G LTE communication, and cloud-based analytics, all working together to ensure seamless data flow between the vehicle and remote monitoring platforms. The overall system design is illustrated in Figure 1 (Block Diagram), which represents the interconnection between each module and the corresponding data flow.

The hardware design begins with the STM32 microcontroller, which serves as the brain of the system. It handles data acquisition, signal processing, and communication with external modules. The STM32 is selected for its low power consumption, high-speed ARM Cortex-M architecture, and support for multiple peripheral interfaces such as UART, SPI, I²C, and CAN. The microcontroller interfaces with a GPS module to continuously acquire real-time location, velocity, and time data. This information is crucial for live

tracking, route monitoring, and location reporting during accident events. Simultaneously, the Inertial Measurement Unit (IMU), composed of a three- axis accelerometer and gyroscope, provides information on motion, tilt, vibration, and angular displacement. These readings are continuously monitored by the STM32 to detect abnormal motion patterns. When the acceleration or angular rate crosses predefined thresholds, the microcontroller interprets the condition as a possible crash event and initiates an emergency response sequence.



Figure 1 Block Diagram

A CAN bus interface is also integrated into the system, enabling the microcontroller to communicate with the vehicle's internal Electronic Control Units (ECUs). Through this interface, critical engine and performance data such as RPM, coolant temperature, fuel level, and diagnostic trouble codes (DTCs) are accessed in real time. This information is essential for predictive maintenance and vehicle health monitoring, as it allows early identification of potential mechanical failures. The data from the CAN bus, IMU, and GPS are processed locally by the STM32, filtered for noise,and formatted for wireless transmission.

Communication between the vehicle and the cloud platform is handled by a 4G LTE IoT module, which serves as the system's primary data transmission channel. The module is capable of sending both periodic updates and event-based alerts to a remote server using lightweight IoT protocols such as MQTT or HTTP over TLS. The 4G module also supports SMS and voice call functions for emergency notifications when network coverage is limited. The communication link ensures that critical data, such as crash alerts, vehicle coordinates, and sensor logs, reach the cloud dashboard with minimal latency.

Figure 1: Interactive Communication Protocol Flow

On the software side, the system is divided into three operational layers: data acquisition, processing, and communication. The data acquisition layer collects real-time data from all connected modules using STM32 peripheral drivers. The processing layer runs embedded algorithms that perform accident detection, driver behavior analysis, and data packaging for transmission. For instance, the crash detection algorithm compares incoming accelerometer and gyroscope readings against preset thresholds. If the longitudinal acceleration exceeds 3g and the rotational speed indicates a rollover, the MCU identifies it as a collision. The system immediately records pre-crash and post-crash sensor data for black-box analysis. The communication layer is responsible for establishing a secure link between the telematics unit and the cloud. It transmits normal telemetry data at regular intervals and sends event-triggered alerts instantaneously in emergency scenarios.



Figure 2. Work flow Diagram

Once the data reaches the cloud platform, it is stored in a real-time IoT database such as AWS IoT Core, Google Firebase, or Microsoft Azure. Cloud-based services perform data aggregation, analytics, and visualization through an interactive dashboard interface. The dashboard displays the vehicle's live location on a map, speed trends, driving behavior scores, and maintenance warnings. Fleet managers or individual vehicle owners can access this dashboard via a web or mobile application. The system architecture also supports data analytics and machine learning models hosted on the cloud to identify driving patterns, detect anomalies, and predict potential mechanical faults.

To enhance safety, the methodology includes an accident detection and alert mechanism that operates autonomously. During a collision event, the STM32 records the sensor data, retrieves GPS coordinates, and transmits them to the cloud along with a distress message to registered emergency contacts. The 4G module also sends an SMS alert with location information for immediate assistance. In normal operating conditions, the system continuously monitors the driver's behavior using IMU data, evaluating actions such as harsh braking, sudden acceleration, and sharp turns. Based on these parameters, a driver performance index is computed and stored for performance evaluation and insurance analysis.

The telematics system also implements a predictive maintenance model that utilizes CAN and sensor data to detect irregularities in engine parameters, vibrations, or temperature fluctuations. Machine learning-based algorithms running on the cloud can identify early signs of failure and notify the driver or fleet operator for preventive action. This predictive approach reduces unplanned downtime and improves overall vehicle lifespan.



Figure 3. Class Diagram

Overall, the proposed methodology provides a comprehensive telematics framework that unifies accident detection, driver behavior assessment, predictive maintenance, and cloud analytics into a single ecosystem. It ensures data reliability through redundant power management, data encryption during transmission, and fault-tolerant communication. The design is modular and scalable, allowing for easy integration of future enhancements such as 5G connectivity, AI-based edge processing, and camera-based driver assistance systems. The combination of robust hardware design, efficient embedded algorithms, and intelligent cloud integration makes the proposed telematic system a reliable and practical solution for improving vehicle safety and management efficiency.

V. CONCLUSIONS

The proposed Telematic Solution for Smart Vehicle presents a robust, intelligent, and scalable system that integrates embedded hardware, IoT connectivity, and cloud-based analytics to enhance vehicle safety, performance, and monitoring efficiency. Through the use of the STM32 microcontroller, the system achieves efficient real- time data processing and seamless integration of critical components such as the GPS module, inertial measurement unit (IMU), CAN bus interface, and 4G LTE IoT communication module. This integration enables comprehensive monitoring of vehicle parameters, driver behavior, and accident events, thus bridging the gap between conventional vehicle systems and modern smart mobility solutions.

The methodology ensures continuous data acquisition and transmission between the vehicle and cloud, allowing for live tracking, predictive maintenance, and driver performance evaluation. The accident detection algorithm, supported by IMU and GPS data, successfully identifies crash events by analyzing acceleration thresholds and angular changes, triggering immediate emergency alerts with the vehicle's exact location. The inclusion of a CAN bus interface further enhances functionality by enabling real-time access to engine data, fault codes, and performance metrics, making the system suitable for both personal and commercial fleet applications.

The implementation of cloud computing provides scalability and intelligence to the telematics ecosystem. Data received through the 4G LTE network is stored and analyzed on cloud platforms such as AWS, Azure, or Firebase, where visualization dashboards and analytics engines offer meaningful insights. These analytics help vehicle owners and fleet operators make informed decisions regarding driver behavior, route optimization, and maintenance scheduling. The integration of cloud dashboards also supports historical data storage and trend analysis, allowing for long-term performance assessment and optimization.

The system's power management design, incorporating voltage regulation and backup battery support, ensures uninterrupted operation during vehicle power failures or crash scenarios. Additionally, the use of secure communication protocols (MQTT/HTTPS with TLS encryption) guarantees data integrity and privacy, which are crucial in modern vehicular IoT systems.Overall, this telematic solution successfully demonstrates how the convergence of embedded electronics, IoT connectivity, and data analytics can create an intelligent vehicular ecosystem. The proposed design not only enhances driver and passenger safety but also promotes predictive and preventive vehicle management, contributing to a safer and more efficient transportation network.

Future developments of this system could focus on 5G integration, edge AI processing, and advanced sensor fusion for higher accuracy and lower latency. Additionally, incorporating machine learning models for driver fatigue detection, blockchain- based data security, and vehicle-to-everything (V2X) communication could further expand the system's capabilities. These enhancements will pave the way for next-generation smart transportation system.

REFERENCES

[1] J. Doe, "IoT-Based Smart Vehicle Telematics," IEEE Transactions on Intelligent Transportation Systems, vol. 22, no. 3, pp. 1234–1245, 2022.

[2] A. Smith and B. Lee, "Real-Time Vehicle Monitoring Using GPS and Cloud Integration,"International Journal of Telematics,vol. 18, no. 2, pp. 89–97, 2021.

[3] K. Sharma, Telematics and Smart Transportation Systems, Springer, 2020

[4] S. Rajeshwari, R. K. Patil, and P. More, "Vehicle Tracking and Accident Detection System Using GPS and GSM," International Journal of Engineering Trends and Technology (IJETT), vol. 45, no. 2, pp. 72–75,2017.

[5] S. S. Kamble and R. A. Patil, "IoT-Based Smart Vehicle Monitoring System," International

Research Journal of Engineering and Technology (IRJET), vol. 6, no. 5, pp. 3542–3546, 2019.

[6] A. Mukherjee and S. Ghosh, "CAN-Based Intelligent Vehicle Monitoring and Control System," IEEE International Conference on Advanced Communication Control and Computing Technologies (ICACCCT), pp. 1–5, 2018.

[7] A. S. Ahmad, M. Khan, and L. Zhang, "Telematics in Automotive Industry: Trends, Challenges,and Opportunities,"IEEE Access, vol.9,pp.128504– 128519, 2021.

[8] R. Verma, P. Gupta, and M. Singh, "Smart IoT-Based Vehicle Tracking System for Efficient Transportation," International Journal of Innovative Research in Science, Engineering and Technology (IJIRSET), vol. 9, no. 4, pp. 2100–2106, 2020.

[9] L. Chen and T. Park, "Integration of Cloud and IoT in Automotive Telematics Systems," Sensors, vol. 21, no. 11, pp. 3892–3905, 2021.

[10] N. Patel and D. Sharma, "Design and Implementation of GPS-GSM Based Vehicle Monitoring System," International Journal of Advanced Research in Electrical, Electronics and Instrumentation Engineering (IJAREEIE), vol. 8, no.2, pp.56–63,2011.