

TRI Technology Security System

Rakesh Kumar¹, Prince², Nikhil³, Partik Kumar Dubey⁴

¹Assistant Professor, Electronics and Communication Engineering R.D. Engineering College (AKTU University) Ghaziabad, India

^{2,3,4}Department of Electronics and Communication Engineering R.D. Engineering College (AKTU University) Ghaziabad, India

Abstract—In an era where safety and protection of property have become critical concerns, the development of reliable and cost-effective security solutions is of paramount importance. This project presents the design and implementation of a microcontroller-based "Tri Technology Security System" that enhances security by integrating three different sensing technologies Infrared (IR), Magnetic sensing, and Light Dependent Resistance (LDR)-to monitor multiple intrusion zones. The proposed system is intended to provide a simple, efficient, and user-friendly security mechanism suitable for both domestic and small-scale commercial environments.

Index Terms—Embedded Security System, AT89C51 Microcontroller, IR Sensor, Magnetic Sensor, LDR Sensor, Intrusion Detection

I. INTRODUCTION

In today's world, ensuring the safety and security of personal and commercial property has become a major concern due to increasing incidents of theft, unauthorized access, and intrusion. Conventional security methods such as manual guarding and simple lock-based systems are often insufficient, expensive, or prone to human error. With the rapid advancement of embedded systems and sensor technologies, automated security solutions have emerged as an effective and reliable alternative for continuous monitoring and quick response to potential threats.

This project presents the design and development of a Tri Technology Security System, an embedded security solution that integrates three different sensing technologies-Infrared (IR), Magnetic sensors, and Light Dependent Resistance (LDR)-to provide multi-zone protection. The use of multiple sensors enhances the reliability of intrusion detection by covering different modes of unauthorized entry such

as physical movement, door or window opening, and sudden illumination in restricted areas. Each sensing unit is assigned to a specific security zone, enabling precise identification of the affected area in case of a breach.

The core of the system is an AT89C51/AT89S52 microcontroller, which continuously monitors the sensor inputs and processes the signals to determine the occurrence of an intrusion. Upon detection, the system immediately triggers an audible alarm through a buzzer and displays the corresponding zone information on a seven-segment display.

This real-time alert mechanism helps in taking prompt corrective action, thereby reducing the risk of loss or damage.

The proposed system is designed to be cost-effective, user-friendly, and easily deployable in homes, offices, and small commercial establishments. By combining multiple technologies into a single platform, the Tri Technology Security System provides a practical foundation for building more advanced and intelligent security solutions in the future.

The system is built around the AT89C51/AT89S52 microcontroller, which serves as the central processing unit responsible for continuously monitoring sensor inputs, processing intrusion signals, and generating appropriate alerts. Three distinct security zones are implemented to provide multi-layered protection. Zone 1 employs IR transmitter and receiver pairs to detect unauthorized entry through a gate or passage; interruption of the IR beam is interpreted as an intrusion event. Zone 2 utilizes magnetic sensors mounted on doors or windows to detect opening or forced entry by monitoring the separation of magnetic contacts. Zone 3 is based on an LDR sensor that responds to sudden

changes in light intensity, enabling detection when an intruder uses a torch or any external light source in a restricted area.

Upon detection of any intrusion in one or more zones, the microcontroller activates an audible buzzer to alert the surroundings and simultaneously displays the affected zone information on a seven-segment (FND) display. This immediate visual and audio feedback enables quick identification of the breach location, thereby improving response time and situational awareness. A manual reset or safety switch is also incorporated to deactivate the alarm and restore the system to a secure state after verification, with a "SAFE" indication displayed to confirm normal operation.

The hardware design includes a regulated power supply using an LM7805 voltage regulator, along with supporting components such as resistors, capacitors, transistors, and connectors. The system is developed using embedded programming techniques compatible with the MCS-51 family of microcontrollers and designed on a printed circuit board (PCB) platform for robustness and compactness.

Overall, the Tri Technology Security System demonstrates how combining multiple sensing modalities can significantly improve the reliability and effectiveness of intrusion detection systems. The modular nature of the design allows future enhancements, such as password-based access control, computer or mobile alerts, and integration of biometric authentication techniques

II. RELATED WORK

Security systems have evolved significantly from traditional lock-and-key mechanisms to advanced electronic and embedded solutions. Early electronic security systems primarily relied on single-sensor approaches, such as simple burglar alarms using magnetic reed switches on doors and windows. While these systems were effective for detecting basic intrusion attempts, they suffered from limitations including false alarms, limited coverage, and the inability to accurately identify the mode or location of intrusion.

Infrared (IR) based intrusion detection systems have been widely used in security applications to monitor human movement across entry points. IR beam

sensors and passive infrared (PIR) sensors are commonly implemented in homes and offices to detect motion or beam interruption. However, IR-based systems alone are susceptible to environmental factors such as dust, sunlight interference, and misalignment of transmitters and receivers, which can reduce detection accuracy. Similarly, magnetic sensor-based systems are popular for door and window security, but they are limited to detecting only physical opening and cannot identify intrusions through other means.

Light Dependent Resistor (LDR) based security mechanisms have been explored for detecting unauthorized illumination in restricted areas, such as vaults, laboratories, or storage rooms. These systems provide a simple method to sense changes in ambient light but are generally used as supplementary security features rather than standalone solutions. More advanced systems reported in literature integrate microcontrollers with GSM, Wi-Fi, or IoT platforms to provide remote alerts and monitoring, increasing system complexity and cost.

In recent years, multi-sensor security systems have gained attention due to their improved reliability and robustness. By combining different sensing technologies, these systems reduce false positives and improve coverage of diverse intrusion scenarios. The proposed Tri Technology Security System aligns with this trend by integrating IR, magnetic, and LDR sensors under a single microcontroller platform. Compared to IoT-based and biometric systems, the proposed solution emphasizes simplicity, low cost, and ease of implementation, making it suitable for small-scale applications and educational prototypes while still offering a practical level of security.




Fig 1. Related work

III. PROPOSED WORK

The proposed work focuses on the design and implementation of a Tri Technology Security System that provides reliable and efficient protection by integrating three different sensing technologies Infrared (IR), Magnetic sensors, and Light Dependent Resistance (LDR) into a single embedded platform. The objective is to develop a low-cost, real-time intrusion detection system capable of monitoring multiple zones and generating immediate alerts when unauthorized access is detected.

In the proposed system, an AT89C51/AT89S52 microcontroller acts as the central control unit. The microcontroller continuously monitors the digital and analog signals received from the IR sensor, magnetic sensor, and LDR sensor placed at different strategic locations. Each sensor corresponds to a dedicated security zone: the IR sensor is used to detect intrusion through gates or passages by monitoring beam interruption; the magnetic sensor is employed to detect unauthorized opening of doors or windows; and the LDR sensor is utilized to sense sudden illumination in restricted or dark areas. This multi-zone approach improves the reliability of the system by covering different possible intrusion methods.

When any of the sensors detect abnormal activity, the microcontroller processes the input signal and triggers an alert mechanism. The alert system consists of a buzzer for audible warning and a seven-segment display to indicate the specific zone where the intrusion has occurred. This enables quick identification of the breach location and facilitates prompt action. Additionally, a manual reset switch is incorporated to deactivate the alarm and restore the system to a secure state after verification.

The proposed system emphasizes simplicity, modularity, and scalability. The hardware is designed using easily available components and a regulated power supply for stable operation. The modular design allows future enhancements such as wireless communication, mobile alerts, password-based access control, and integration with advanced authentication mechanisms. Overall, the proposed work aims to deliver a practical, user-friendly, and expandable security solution suitable for residential and small commercial applications.




Fig 2. Flow Diagram

IV. RESULT AND DISCUSSION

The Tri Technology Security System was successfully designed, implemented, and tested under various simulated intrusion scenarios to evaluate its performance and reliability. The system demonstrated effective real-time monitoring of three distinct security zones using IR, magnetic, and LDR sensors. During testing, each sensor was able to accurately detect its respective intrusion event and generate a prompt response from the microcontroller. Interruption of the IR beam at the entry gate was immediately detected and correctly identified as Zone 1 intrusion. Similarly, separation of the magnetic sensor contacts upon opening the door triggered the alarm for Zone 2. While sudden illumination near the LDR sensor resulted in proper detection of Zone 3. The buzzer alert mechanism proved effective in providing immediate audible notification, making the system suitable for on-site security applications. The seven-segment display successfully indicated the corresponding zone number, enabling quick identification of the intrusion location. When multiple zones were activated simultaneously, the system was able to display alerts sequentially, confirming its capability to handle multi-zone breach conditions. The manual reset switch functioned reliably, allowing authorized users to acknowledge the alert and restore the system to a safe state after inspection. From a performance perspective, the system showed stable operation with minimal false triggering under normal ambient conditions. However, environmental factors such as excessive ambient light and minor misalignment of IR components were observed to

affect sensitivity, highlighting the importance of proper sensor placement and calibration. The use of a regulated power supply ensured consistent performance and reduced noise-related disturbances. Overall, the results validate the effectiveness of integrating multiple sensing technologies into a single embedded security platform. The system offers a good balance between cost, simplicity, and functional

reliability. While it does not provide remote monitoring or advanced authentication, the obtained results demonstrate that the proposed solution is suitable for basic home and small commercial security needs and can serve as a foundation for future enhancements such as wireless alerts and smart monitoring features.

Table 1: Zone-Wise Intrusion Detection Performance

Test No.	Zone Activated	Sensor Type	Intrusion Detected (Yes/No)	Buzzer Activated	Display Output	Response Time (MS)
1	Zone 1	IR Sensor	Yes	Yes	Z1	210
2	Zone 2	Magnetic Sensor	Yes	Yes	Z2	185
3	Zone 3	LDR Sensor	Yes	Yes	Z3	230
4	Zone 1	IR Sensor	Yes	Yes	Z1	205
5	Zone 2	Magnetic Sensor	Yes	Yes	Z2	190
6	Zone 3	LDR Sensor	Yes	Yes	Z3	225

Table 2: Accuracy and False Trigger Analysis

Sensor Type	Total Tests	Successful Detections	Failures	Accuracy
IR Sensor	10	9	1	90%
Magnetic Sensor	10	10	0	100%
LDR Sensor	10	9	1	90%

- The magnetic sensor zone showed the highest reliability due to minimal environmental interference.
- Minor false triggers in IR and LDR zones were observed under strong ambient light and alignment disturbances.
- multi-zone intrusion tests confirmed the system's ability to handle simultaneous breach events.

V. CONCLUSION

The design and implementation of the Tri Technology Security System (TSS) presented in this work offers a robust, multi-layered solution to the growing need for reliable and affordable property protection. While traditional security methods often rely on a single point of failure, this project successfully demonstrates that integrating three distinct sensing modalities-infrared (IR), Magnetic, and Light Dependent Resistor (LDR)-significantly minimizes the limitations of any single technology used in isolation. By leveraging the AT89C51/AT89552 microcontroller as the central processing unit, independent security zones. Experimental results confirm the high efficiency of the system, hosting an average detection accuracy of 93.5% and a rapid response time of approximately 205 Ms. The hardware architecture, regulated by an LM7805 voltage regulator, proved stable and resilient

Table 3: Multi-Zone Intrusion Test

Test Case	Zone	Buzzer Triggered	Display Status	System Response
1	Zone 1 & Zone 2	ON	Z1-Z2	Correct
2	Zone 2 & Zone 3	ON	Z2-Z3	Correct
3	All Zones	ON	Z1-Z2-Z3	Correct

Observation Summary

- The system achieved an average detection accuracy of 93.3% across all zones.
- The average response time of the system was approximately 205 ms, indicating near real-time alert generation.

against common electrical notes. Each zone performed its intended function with high precision: the IR sensors effectively monitored passages, the magnetic contacts secured physical entry points like doors and windows, and the LDR sensor provided a unique layer of protection against unauthorized light sources in dark environments. One of the primary strengths of this TSS project is its modularity and cost-effectiveness. Unlike expensive high- and commercial systems or complex lot-based solutions that require constant internet connectivity. This embedded system provides a standalone, user-friendly interface suitable for both residential homes and small-scale commercial offices. The inclusion of a seven-segment display for zone identification and a manual reset switch ensures that the user has full situational awareness and control over the security state of the premises.

Despite the high security, the project also identified areas for environmental optimization, particularly regarding sensor calibration in varying light conditions to further reduce the 6.7% margin of error observed during testing. Moving forward, the Tri Technology Security System serves as a scalable foundation for more advanced smart-city initiatives. Future enhancements could include the integration of GSM modules for remote mobile alerts. Wi-Fi connectivity for cloud-based logging, or biometric authentication to replace manual reset switches. Ultimately, this project proves that a highly effective, real-time intrusion detection system can be built using accessible electronic components, providing a professional grade security framework for the modern era. secure, automated, and intelligent management systems in the future.

ACKNOWLEDGMENT

We express our gratitude to each author for their exceptional contributions to this work

REFERENCES

[1] R. Kumar, P. Singh, and N. Kumar, "Design and Implementation of Multi-Zone Intrusion Detection Systems using AT89C51 Microcontrollers," *International Journal of*

Embedded Systems and Applications, vol. 12, no. 3, pp. 45-52, 2024.

- [2] S. Sharma and A. Copta, "Comparative Analysis of Infrared (IR) and Magnetic Read Sensors for Domestic Security Applications," *Journal of Sensor Technology*, vol. 9, no. 2, pp. 112-118, 2022.
- [3] J. Smith and L. Brown, "LDR-Based Light Sensitivity Detection in Restricted Environments for Enhanced Security," *Embedded Solutions Research*, vol. 15, no. 1, pp. 22-28, 2022.
- [4] M. Verma and K. Das, "Robust Power Supply Design using LM7805 for 8-bit Microcontroller Projects," *Electronics Design Quarterly*, vol. 7, no. 4, pp. 88-94, 2021.
- [5] T. Wilson, "Multi-Sensor Integration for Real-Time Alerting; Combining Magnetic, IR, and LDR Modalities," *International Conference on Smart Security Systems*, pp. 301-310, 2023.
- [6] ATMEL Corporation, "AT89CS1/AT89S52 8-bit Microcontroller with 4K/8K Bytes Flash Datasheet, Rev. 2487D-MICRD-6/08.
- [7] A. Z. H. Phahriz Gunawan, "Pengamanan Ramah Menggunakan Kamera Vc0706 Dan Sins Gateway Berbasis Mikrokontroler," *SNASTIKOM*, vol. 9, 2019.
- [8] F. Rozi, "Security Menggunakan Arduino Berbasis Internet of Things," *Inovasi Vokasional dan Teknologi*, vol. 07, on. 01, 2018.