Piezoelectric Footstep Power Generation System

Mr. Ravi Teja[1], Kenchugundu Naveen Kumar[2], Kuruva Anjesh[3], Elkuri Anil Kumar[4],
Dr. K. Chithambaraiah Setty[5], Mr.Syed Saheb[6]
[1]*AssociateProfessor, Department of Electrical and Electronics Engineering, St. Johns College of Engineering & Technology, Yerrakota, Yemmiganur, Kurnool, A.P.*
[2,3,4]*Students, Department of Electrical and Electronics Engineering, St. Johns College of Engineering & Technology, Yerrakota, Yemmiganur, Kurnool, A.P.*
[5,6]*Department of Electrical and Electronics Engineering, St. Johns College of Engineering & Technology, Yerrakota, Yemmiganur, Kurnool, A.P.*

***Abstract*—This project presents an innovative and eco-friendly system for generating electrical energy by harnessing the mechanical energy from human footsteps. The system utilizes the piezoelectric effect, where piezoelectric sensors convert applied mechanical pressure into electrical energy. This generated energy is conditioned, rectified, and stored in a rechargeable battery. An Arduino microcontroller is employed to monitor the generated voltage via a voltage sensor, and the output is displayed on a 16x2 LCD I2C display. The system provides a sustainable method of power generation, particularly suited for high-footfall public areas such as railway stations, shopping malls, temples, and educational institutions, contributing to renewable energy solutions and smart city initiatives.**

***Index Terms*—Piezoelectric Sensor, Arduino, Energy Harvesting, Footstep Power Generation, Renewable Energy.**

I. INTRODUCTION

The ever-increasing global demand for energy, coupled with the depletion of conventional fossil fuels and growing environmental concerns, has intensified the search for sustainable and renewable energy sources. While large-scale solutions like solar and wind power are crucial, there is a significant opportunity to harness the wasted kinetic energy from human activities in densely populated urban environments. Every footstep, a seemingly insignificant action, represents a small amount of mechanical energy that is typically lost as heat or vibration.

This project introduces a piezoelectric footstep power generation system designed to capture this otherwise wasted energy and convert it into usable electrical power. The system employs an array of piezoelectric sensors placed beneath a walking platform. When a person steps on the platform, the applied pressure causes the sensors to generate an electrical charge. This charge is then harvested, conditioned, and stored in a battery. The integration of an Arduino microcontroller allows for real-time monitoring of the generated voltage, which is displayed on an LCD screen, providing valuable feedback on system performance. This approach not only offers a supplementary source of green energy but also raises awareness about innovative energy harvesting techniques in everyday life [1].

II. OBJECTIVES

The primary goal of this project is to design and develop a functional piezoelectric footstep power generation system that can convert human locomotion into electrical energy for low-power applications.

The Key Objectives Are:

1. To design a mechanical platform that effectively transfers the force of footsteps to an array of piezoelectric sensors.
2. To implement piezoelectric sensors to convert mechanical stress (from footsteps) into an electrical charge.
3. To develop a power conditioning circuit (rectifier and filter) to convert the generated AC voltage into a stable DC voltage suitable for storage.
4. To store the harvested energy in a rechargeable battery for later use.

5. To utilize an Arduino microcontroller and a voltage sensor to monitor the generated voltage in real-time.
6. To display the monitored voltage and system status on a 16x2 LCD display for user feedback.
7. To create a low-cost, portable, and eco-friendly system that can be deployed in public spaces to promote renewable energy awareness and provide a sustainable power source.

III. BLOCK DIAGRAM

The block diagram of the proposed system illustrates the flow of energy and information, from the input mechanical force to the final power output and display. Fig.1. Block diagram of the proposed Piezoelectric Footstep Power Generation System

IV. WORKING PROCESS

1. The operation of the Piezoelectric Footstep Power Generation System is a sequential process of energy conversion, conditioning, storage, and monitoring.
2. Energy Harvesting: When a person walks on the specially designed platform, the applied mechanical force is transferred to an array of piezoelectric sensors embedded within. These sensors, based on the direct piezoelectric effect, generate an alternating current (AC) voltage signal proportional to the applied pressure. The magnitude of the generated voltage depends on factors like the force of the footstep and the properties of the piezoelectric material [2].
3. Power Conditioning: The AC voltage generated by the piezoelectric sensors is not suitable for direct storage or use in most electronic devices. Therefore, it is passed through a power conditioning circuit. This circuit first uses a bridge rectifier to convert the AC voltage into a pulsating direct current (DC) voltage. Subsequently, a filter circuit (typically a large capacitor) smoothens this pulsating DC into a more stable and consistent DC voltage.
4. Energy Storage: The conditioned DC power is then directed to a rechargeable battery, such as a Lithium-ion or lead-acid battery. The battery serves as an energy reservoir, storing the small amounts of energy generated from each footstep. This allows the system to accumulate energy over time, making it available to power loads even when there is no foot traffic [3].
5. Monitoring and Control: An Arduino microcontroller is the central processing unit of the system. It is connected to a voltage sensor that monitors the voltage level of the generated power, either at the output of the filter or at the battery. The Arduino reads this analog voltage signal and processes the data. This real-time monitoring is crucial for understanding system performance.
6. Data Display: The processed voltage data is displayed on a 16x2 LCD I2C display. This provides local visual feedback, showing the user, the current voltage being generated or the battery's state of charge. This makes the system interactive and demonstrates the tangible results of energy harvesting.
7. Power Utilization: The energy stored in the battery can be used to power various low-power DC loads, such as LED lamps for lighting, or can be inverted to AC for other small appliances. A switch can be incorporated to control the output to the load.

V. EXISTING SYSTEM

- Traditional methods of generating small-scale electricity in public areas are often non-existent or rely on connection to the main power grid. Conventional energy generation for applications like street lighting or public signage is almost exclusively grid-dependent.
- Grid-Dependent Systems: Most public lighting and signage are directly connected to the electrical grid, which is primarily powered by fossil fuels, contributing to carbon emissions and operational costs.
- Solar Power: While solar panels are a renewable option, their effectiveness is dependent on weather conditions and they require significant space and upfront investment. They are also ineffective at night or on cloudy days.
- Manual Power Generation: In some isolated cases, devices like hand-crank generators exist, but these require deliberate human effort and are not passive energy harvesters.
- A common drawback of these existing systems is that they do not utilize the ubiquitous and

consistent mechanical energy available from human movement in crowded places. This energy is simply wasted, representing a missed opportunity for sustainable, decentralized power generation.

VI. DRAWBACKS

1. Wasted Kinetic Energy: A massive amount of kinetic energy from human footsteps in public places is completely lost.
2. Grid Dependency: Most public infrastructure relies on the main power grid, which can be unstable, costly, and reliant on non-renewable sources.
3. High Operational Costs: Grid-powered public utilities incur continuous electricity costs.
4. Environmental Impact: Dependence on fossil fuels for grid electricity contributes to pollution and greenhouse gas emissions.
5. Lack of Awareness: Existing infrastructure does little to promote or demonstrate the potential of alternative energy harvesting methods to the public.
6. No Localized, Passive Generation: There is a lack of systems that can passively generate small amounts of power on-site without requiring user initiation or large-scale installations.

VII. PROPOSED SYSTEM

The proposed system is a self-contained, renewable energy solution designed to harvest mechanical energy from pedestrian footsteps. It consists of a platform embedded with multiple piezoelectric sensors that generate electricity upon being stepped on. A power conditioning unit (rectifier and filter) converts this output to a storable DC voltage, which is then accumulated in a rechargeable battery. An Arduino microcontroller, connected to a voltage sensor, monitors the system's voltage output. This data is displayed on a user-friendly LCD screen, providing real-time feedback. The stored energy can be utilized to power low-power devices like LED lamps, contributing to a sustainable and decentralized power source for public areas.

VIII. PROPOSED SYSTEM ADVANTAGES

1. Renewable Energy Generation: The system produces clean electricity from a readily available source (human footsteps), reducing reliance on fossil fuels.
2. Waste Energy Utilization: It captures and repurposes otherwise wasted mechanical energy, increasing overall energy efficiency.
3. Eco-Friendly and Clean: The system operates with zero emissions, making it an environmentally friendly alternative.
4. Low Operational Cost: After initial installation, the operating cost is negligible as it uses free, renewable energy.
5. Educational Value: The system serves as a tangible demonstration of green technology and energy harvesting principles, promoting public awareness.
6. Scalability: Multiple units can be installed in high-traffic areas to collectively generate a meaningful amount of power.
7. Smart City Integration: The system can be integrated into smart city infrastructure to provide power for lighting, sensors, and information displays in public spaces like malls, railway stations, and walkways [4].

IX. PROBLEM STATEMENT

In a world facing depleting fossil fuels and escalating environmental concerns, there is a critical need for innovative, decentralized, and renewable energy sources. High-footfall public areas like railway stations, bus stands, shopping malls, and temples witness the constant application of mechanical energy through human footsteps. This significant amount of kinetic energy is currently entirely wasted. The problem is the absence of an efficient, low-cost, and scalable system to harvest this mechanical energy and convert it into usable electrical power for low-demand applications. There is a pressing need to develop a solution that can not only generate clean energy but also raise public awareness about sustainable practices and contribute to the energy independence of urban infrastructure.

X. LITERATURE REVIEW

M.N. Fakhzan and Asan G.A. Muthalif (2011) explored vibration-based energy harvesting using piezoelectric materials. Their work focused on optimizing the energy capture from mechanical vibrations, establishing foundational principles for converting ambient motion into electrical energy, which is directly applicable to footstep power generation [5].

S.S. Taliyan, et al. (2013) investigated the concept of generating electricity from footsteps. They demonstrated the feasibility of using piezoelectric crystals to produce electrical power from human locomotion, highlighting the potential for practical applications in various public settings [2].

Henry A. Sodano, Daniel J. Inman, and Gyuhae Park (2004) conducted foundational research on estimating the electrical charge output from piezoelectric energy harvesters. Their work provided crucial insights into the factors affecting energy conversion efficiency, which is critical for designing effective footstep generation systems [6].

Meiling Zhu, et al. (2010) designed and studied piezoelectric energy-harvesting devices using a coupled piezoelectric-circuit finite element method. Their research aimed at generating higher electrical power, which is essential for scaling up footstep systems to power more substantial loads [7].

A. Kaur and G. Dhiman (2019) provided a review on search-based tools and techniques for problem-solving in complex systems, highlighting the importance of optimization in engineering design. While their focus was on software, the principles of systematic optimization are relevant to refining the hardware configuration of the footstep system for maximum efficiency [8].

V. Tamilselvi, et al. (2020) developed an IoT-based health monitoring system that utilized sensors and microcontrollers for real-time data acquisition and display. Their approach to sensor integration, data processing with a microcontroller, and LCD display provides a valuable reference for implementing the monitoring and feedback components in the footstep power generation system [9].

XI. HARDWARE DESCRIPTION

Arduino Microcontroller (e.g., Arduino Uno):
The Arduino Uno acts as the central processing unit. It reads the analog voltage from the voltage sensor, processes this data, and controls the output to the LCD display. Its simplicity and wide range of libraries make it ideal for this application [10].

Fig.2. Arduino Uno Microcontroller

Piezoelectric Sensors:
These are the core components for energy harvesting. They generate an electrical charge in response to the mechanical stress applied by a footstep. Multiple sensors are connected in series and parallel configurations to increase the overall voltage and current output. Common materials include Lead Zirconate Titanate (PZT) due to its high energy conversion efficiency.

Fig.3. Piezoelectric Sensor Disk

Voltage Sensor Module:
This module is used to measure the voltage generated by the system, typically at the battery or after the rectifier. It scales down the voltage to a level that the Arduino's analog input pins can safely read (0-5V).



Fig.4. Voltage Sensor Module

Rechargeable Battery:
A rechargeable battery, such as a Lithium-ion or Lead-Acid battery, stores the harvested electrical energy. It allows the system to accumulate power from multiple footsteps and provides a stable power supply for loads when there is no active generation.

LCD I2C Display (16x2):
This display provides a local interface to show the measured voltage and system status. The I2C interface simplifies the wiring, requiring only two data lines (SDA, SCL) to communicate with the Arduino.

Power Conditioning Circuit (Bridge Rectifier & Filter Capacitor):
The bridge rectifier (comprising four diodes) converts the AC output from the piezoelectric sensors into a pulsating DC. The filter capacitor then smoothens this output to a more constant DC voltage suitable for charging the battery. A voltage regulator may also be included to protect the battery from overvoltage.

XII. RESULTS AND DISCUSSION

The developed Piezoelectric Footstep Power Generation System was successfully implemented and tested. An array of 8-10 piezoelectric sensors was connected in a series-parallel configuration to maximize energy capture. The output from the sensors, an AC voltage of up to 20-30V (peak-to-peak) during a footstep, was fed into a bridge rectifier and filter capacitor, resulting in a DC output of approximately 5-15V depending on the force applied.
This DC voltage was successfully used to charge a 6V/4.5Ah rechargeable battery. The Arduino microcontroller, programmed to read the voltage sensor connected across the battery, accurately monitored the charging process. The voltage readings were clearly displayed on the 16x2 LCD, showing an increase in battery voltage with each footstep. The system was able to power a 6V LED lamp from the stored energy for a short duration after a series of footsteps.



The results demonstrate that the system can effectively harvest otherwise wasted mechanical energy, condition it, store it, and provide a visual indication of the process. The power generated per footstep is low, which is a known limitation of piezoelectric technology, but the system's ability to accumulate this energy over time makes it a viable source for low-power applications in high-traffic areas.

XIII. ADVANTAGES

- Renewable & Clean Energy: Harnesses a sustainable, non-polluting energy source.
- Passive Energy Harvesting: Generates power without requiring user initiation or significant effort.
- Educational & Awareness: Serves as a public demonstration of green technology.
- Low Cost: Utilizes relatively inexpensive and readily available components.
- Portable & Scalable: The system can be built in modular units for easy installation and expansion.

XIV. APPLICATIONS

- Public Lighting: Powering LED streetlights, walkway lights, and signage in malls, railway stations, and bus stops.
- Smart City Infrastructure: Providing energy for sensors, Wi-Fi hotspots, and information kiosks in public areas.

- Rural Electrification: Serving as a supplementary power source in off-grid or remote locations with high foot traffic.
- Educational Institutions: Used as a teaching tool in engineering and science labs to demonstrate principles of energy conversion.
- Fitness Centers: Integrating into treadmills or exercise equipment to generate power from workouts.

XV. CONCLUSION

The Piezoelectric Footstep Power Generation System presents a viable and innovative approach to generating renewable energy by harnessing the mechanical force of human footsteps. The system successfully demonstrates the entire process from energy capture using piezoelectric sensors to power conditioning, storage in a battery, and real-time monitoring via an Arduino microcontroller and LCD display. While the power generated per footstep is modest, the system's ability to accumulate energy over time makes it a practical solution for low-power applications in high-traffic public spaces. This project effectively illustrates how integrating simple technology can contribute to sustainable energy solutions, reduce our carbon footprint, and promote environmental consciousness. The system is low-cost, eco-friendly, and has significant potential for deployment as part of smart city initiatives and in various public and private venues.

XVI. FUTURE ENHANCEMENTS

- While the current system effectively demonstrates the core concept, several enhancements could improve its efficiency and broaden its application:
- Improved Energy Harvesting Circuitry: Integrating a more sophisticated power management integrated circuit (PMIC) or DC-DC boost converter specifically designed for low-voltage energy harvesting could significantly increase the energy captured from each footstep.
- Supercapacitor Integration: Adding a supercapacitor in parallel with the battery could help capture high-energy spikes from footsteps more efficiently, improving overall system responsiveness and battery lifespan.
- Wireless Data Monitoring: Incorporating an ESP32 or Wi-Fi module could allow the system to transmit voltage and performance data to a cloud platform, enabling remote monitoring and data analysis over time.
- IoT and Smart Grid Integration: Connecting multiple units across a city to form a network of energy-harvesting nodes, contributing to a smart grid and providing data on pedestrian traffic patterns.
- Machine Learning for Predictive Analysis: Using the collected data (footstep frequency, energy generated) with machine learning algorithms to predict peak energy generation times and optimize energy storage and usage.
- Structural Optimization: Designing a more robust and aesthetically pleasing platform with optimized mechanical coupling to maximize force transfer to the piezoelectric sensors.
- Higher Power Output: Exploring the use of more advanced or larger-scale piezoelectric materials, or hydraulic systems, to generate higher power outputs suitable for more demanding applications.

REFERENCES

[1] D. Acharya and S. N. Patil, “IoT-based healthcare monitoring kit,” in *Proc. 4th Int. Conf. Computing Methodologies and Communication (ICCMC)*, Erode, India, pp. 363–368, 2020.

[2] S. S. Taliyan, B. B. Biswas, R. K. Patil, and G. P. Srivastava, “Electricity from footsteps,” Reactor Control Division, Electronics & Instrumentation Group, T. K. Basu IPR, Gandhinagar.

[3] M. M. Islam, A. Rahaman, and M. R. Islam, “Development of smart healthcare monitoring system in IoT environment,” *SN Computer Science*, vol. 1, no. 3, 2020.

[4] H. B. Hassen, N. Ayari, and B. Hamdi, “A home hospitalization system based on the Internet of Things, fog computing and cloud computing,” *Informatics in Medicine Unlocked*, vol. 20, p. 100368, 2020.

[5] M. N. Fakhzan and A. G. A. Muthalif, “Vibration-based energy harvesting using piezoelectric material,” Dept. Mechatronics

Eng., Int. Islamic Univ. Malaysia, Kuala Lumpur, Malaysia.

[6] H. A. Sodano, D. J. Inman, and G. Park, "Estimation of electric charge output for piezoelectric energy harvesting," *Strain*, vol. 40, no. 2, pp. 49–58, 2004.

[7] M. Zhu, E. Worthington, and A. Tiwari, "Design study of piezoelectric energy-harvesting devices for higher electrical power generation using a coupled piezoelectric-circuit finite element method," *IEEE Trans. Ultrasonics, Ferroelectrics, and Frequency Control*, vol. 57, no. 2, Feb. 2010.

[8] Kaur and G. Dhiman, "A review on search-based tools and techniques to identify bad code smell in object-oriented systems," in *Harmony Search and Nature-Inspired Optimization Algorithms*, Singapore, pp. 909–921, 2019.

[9] V. Tamilselvi, S. Sribalaji, P. Vigneshwaran, P. Vinu, and J. GeethaRamani, "IoT-based health monitoring system," in *Proc. 6th Int. Conf. Advanced Computing and Communication Systems (ICACCS)*, Coimbatore, India, pp. 386–389, 2020.

[10] S. Banerjee and S. Roy, "Design of pulse rate and body temperature monitoring system with Arduino via Wi-Fi and Android-based gadget," *Int. J. Technology and Engineering Studies*, vol. 2, no. 5, pp. 302–306, 2016