

IOT-Enabled Advanced Water Quality System for River Management

Mrs. D. Radhika¹, V. Pavithra², R. Raksha³, T. Rogini⁴

¹*Assistant Professor, Department of Computer Science and Engineering,
Vivekanandha College of Engineering for Women, Tamilnadu, India*

^{2,3,4}*UG Scholar, Department of Computer Science and Engineering,
Vivekanandha College of Engineering for Women, Tamilnadu, India*

Abstract—Water Pollution in rivers has become a serious environmental and public health concern due to rapid industrialization, urbanization, and improper waste disposal. Continuous monitoring of water quality is essential to ensure safe and sustainable water resources. This paper presents the design and development of an IOT-enabled advanced water quality monitoring system for effective river management. The proposed system utilizes multiple sensors to measure important water parameters such as pH, turbidity, temperature, dissolved oxygen, and salinity. These sensors are interfaced with a microcontroller to collect real-time data, which is then processed and transmitted to a cloud-based platform using IOT communication technologies. To enhance decision-making, a machine learning approach based on Support Vector Machine (SVM) algorithm is used to categorize water quality conditions as safe or unsafe in order to improve decision-making. Techniques for feature extraction and data preprocessing are used to increase system dependability and prediction accuracy. Additionally, the system produces automatic alerts when surpass allowable limits and has a web-based interface for real-time visualization of water quality data. Continuous monitoring, early pollution detection, and remote access to water quality data are all made possible by this integrated solution. The suggested system provides an economical, scalable and effective method for managing river water, assisting authorities in taking prompt action to safeguard public health and environmental resources.

Index Terms—Internet of Things (IOT), Water Quality, River Management, Sensors, Machine Learning, Support Vector Machine (SVM), Real Time Monitoring, Cloud Computing.

I. INTRODUCTION

River Water is essential to aquatic ecosystems, industry, agriculture, and human life. However, the quality of river water has been greatly impacted by rising domestic sewage, industrial discharge, and agricultural runoff. Serious health problems, environmental harm, and biodiversity loss can result from contaminated water. As a result, maintaining safe water supplies and managing rivers effectively now depend on ongoing water quality monitoring. Conventional techniques for monitoring water quality primarily rely on laboratory analysis and manual sampling. These techniques don't provide real-time information and are labor-intensive and time-consuming. Because of this, abrupt changes in the quality of the water could go unnoticed, delaying action and raising risks. To evaluate the general state of the water, important water parameters like pH, turbidity, temperature, dissolved oxygen and salinity must be routinely checked.

This project suggests an IOT-enabled sophisticated water quality monitoring system combined with artificial intelligence methods to address these issues. The system gathers data in real time from sensors and uses IOT communication to send it to a cloud platform. Water quality is categorized as safe or unsafe using a Support Vector Machine (SVM) algorithm. In order to facilitate quicker decision-making and better environmental protection, the system also offers a web-based interface for data visualization and generates alerts when parameters surpass safe limits.

II. METHODOLOGY

The suggested system uses artificial intelligence and the Internet of Things to continuously monitoring, it combines sensors, a microcontroller, and cloud communication. Sensors linked to an ESP32 microcontroller are used to measure water parameters like pH, turbidity, temperature, dissolved oxygen, and salinity. An Analog-to-Digital Converter (ADC) transforms the fathered analog signals into digital data, which is then processed in real time. For remote monitoring and storage, the processed data is sent via Wi-Fi or GSM to a cloud platform. To increase accuracy, methods for feature extraction and data preprocessing are used. Water quality is categorized as safe or unsafe using a Support Vector Machine (SVM) algorithm, and alerts are produced when values surpass safe thresholds.

III. BATTERY PARAMETER MONITORING

The water quality monitoring web application is developed to offer an interface for real-time visualization and management of river water quality. The system receives real- time sensor readings of pH, turbidity, temperature, dissolved oxygen, and salinity from an IOT based monitoring unit. The web application presents the collected data in numeric as well as graphical form, making it easier for the user to understand the current water conditions and trends over a period of time. Charts and graphs are used to represent the variations in the parameters, which can be used to identify the patterns of water pollution and sudden changes in water quality. The application also includes the results of the proposed SVM-based prediction model, which categorizes water quality as safe or unsafe. If any parameter is found to exceed the predetermined limits, the system will highlight the condition on the dashboard and alert the user for immediate attention. The web app help in proper decision-making, environmental monitoring, and proper management of river water.

IV. SYSTEM USERS

The system has the capacity to handle different types of users in order to facilitate the proper monitoring and management if water quality data. This includes administrators, environmental authorities, and other

users. The system administrator is in charge of the entire system, including user management, sensor configuration, and data management. The environmental management authorities use this system to monitor water quality in real-time and respond to any alarm signals that are sent for unsafe water conditions. The general users or public can access basic information like the water quality status and reports through the web interface. This structure of multiple users helps in safe access, monitoring and decision-making in the management of the river.




Fig.1. Water Quality Monitoring System

V. SENSOR DATA COLLECTION MODULE

The function of the sensor data collection module is to collect data on the quality of water in the river in real time. This module uses sensors like pH, turbidity, temperature, dissolved oxygen, and salinity sensors. These sensors continuously measure the quality of water in the river and send signals continuously measure the quality of water in the river and send signals to the microcontroller. All sensors are connected to the ESP32 microcontroller. It reads the values using its input pins. Since most sensors have analog output, the microcontroller converts them to digital using the Analog to Digital converter.

The collected data us processed and ready for transmission to the cloud platform. Continuous monitoring will enable us to detect changes in water quality in its earliest stages. This module lays the foundation for the system by providing reliable and real-time input values.




Fig. 2. Sensor Collecting Unit

VI. WATER QUALITY PREDICTION (SVM MODEL)

The water quality prediction module employs a Support Vector Machine (SVM) algorithm to classify

the water conditions based on the sensor readings. The parameters for this module are pH values, turbidity, temperature, dissolved oxygen, and salinity. This module assists in finding out if the water is safe or unsafe. The data that is collected before prediction requires some preprocessing steps like cleaning, normalization, and feature extraction. This helps in making the model more accurate and reliable.

The SVM algorithm analyzes the parameters and finds patterns associated with water conditions. From the analysis, the model classifies the water status and sends the result to the system. If unsafe conditions are identified, it assists the alert module for further action. This intelligent prediction helps in the early detection of pollution and improves the decision-making process for the river.




Fig. 3. Communication and Data Transmission.

VII. MONITORING AND VISUALIZATION MODULE

The task of the monitoring and visualization module is to show the water quality information in an easy and understandable manner. The module receives real-time information from the cloud server and displays the information on the parameters such as

pH, turbidity, temperature, dissolved oxygen, and salinity. The information on the web-based dashboard. The module uses graphs, charts, and indicators to show the information in a visual manner. Users can view the real-time information and trends of water quality parameters. The dashboard also displays the water quality status as safe or not safe based on the prediction model. The dashboard also

allows remote access, enabling the user to access the data remotely. The module aids in decision-making through better understanding of the river conditions.

VIII. ALERT & NOTIFICATION SYSTEM

The dashboard also displays the water quality status as safe or unsafe using the prediction model. This module also has the ability to access the data remotely. This module helps in decision-making with clear and precise information about the condition of the river. The alerts are sent once the condition of the water is identified as unsafe using the above module. This helps the environmental authorities respond to the condition of the water and prevent further contamination of the water. This module helps in the proper management of the river.

IX. ACTUATOR CONTROL & WATER MANAGEMENT MODULE

The role of the actuator control and water management module is to take automatic actions based on the water quality conditions that have been identifies. The system that are controlled by the microcontroller. When the water quality parameters exceed the limits, the system sends signals to activate the actuators. This helps in reducing pollution levels and improving water quality. The system works hand-in-hand with the prediction and alert system. For instance, in situations where turbidity levels are high and the level of dissolved oxygen is low, the system

can be used to activate aerators. This is an automated system that helps in effective water management. By integrating monitoring and controlling actions, the system can be used to ensure effective environmental.

A. Working

The proposed IOT-based advanced water quality monitoring system works on the principle of continuously monitoring and analyzing the parameters of the water in the river in real-time. pH, turbidity, temperature, dissolved oxygen, and salinity sensors are developed in the water to measure the different parameters of water quality. These sensors are connected to the ESP32 microcontroller, which collects the data and converts the analog signal to a digital signal using the Analog-to-Digital convertor (ADC). The data is then processed and ready for further analysis. The data is then transmitted to the cloud platform using IOT technologies like Wi-Fi or GSM. At the same time, data preprocessing techniques are applied to the data and then the data is given as input to the Support Vector Machine (SVM) algorithm to classify the water quality as safe or unsafe. If the sensor values are within the limits, the system will continue its work without any interruption. But if any value exceeds its threshold limit, the system recognizes this condition as a problem. In some cases, the system can automatically switch on the pumps or filters to maintain the water quality. This process helps to monitor, the river, detect any pollution, and maintain the river properly.



Fig.4. Working of EV Battery with Accident Detection Systems

B. Flow Chart

The system starts by collecting water samples from the river using different sensors such as pH, turbidity, temperature, dissolved oxygen, and salinity. These sensors continuously measure water quality parameters and send the data to the ESP32 microcontroller. The microcontroller converts analog signals into digital values using ADC and process the data in real time. The processed data is transmitted to the cloud platform using IOT communication technologies. In the cloud, data preprocessing techniques are applied to clean and normalize the data. Then, the Support Vector Machine (SVM) model analyzes the data and predicts whether the water quality is safe or unsafe.

Finally, the system presents the results to the user through the web or mobile interface, indicating whether the water is safe or not. If any parameter crosses the threshold limit, an alarm is sent to take immediate action. This process is repeated in a loop to monitor and manage the water quality in real time.




Fig.5.Flowchart of EV Battery with Accident Detection Systems

C. Result



Fig. 6. EV Battery along with Accident Detection Systems

The proposed IoT-based water management system was able to subvisual gather data from various, such as PH, dissolved oxygen, turbidity, and salinity sensors. These continuously monitored water quality and transmitted data to a cloud platform for analysis and visualization. The data collected was utilized for training and testing the Support Vector Machine model for water quality classification. The Support Vector Machine model was seen to have good prediction accuracy for water quality classification based on different categories, such as safe and unsafe water. By adjusting hyperparameters, it was even to have better accuracy for water quality classification based on parameters like PH and turbidity.

Overpack, it was seen that the system was reliable, fast, and cost-effective for monitoring purposes when compared to traditional methods. The real-time analysis feature of this system can be useful in detecting contamination at an early stage, thus making it suitable for applications in river tanks.

X. CONCLUSION

The paper proposes an IOT-based Water Management System for the real-time monitoring of water quality for river tank water. They use sensors to measure the water quality parameters such as pH, dissolved oxygen, turbidity, and salinity levels. The measured values are then passed through a support vector machine (SVM) to ensure the classification of water quality. The proposed system eliminates the limitations faced while using traditional methods to monitor water quality. The system is cost-effective and time-efficient for monitoring and detecting water

contamination. The result indicate that the system ensures a good prediction performance with parameter tuning. The integration of IoT, cloud computing, and machine learning can enhance water quality management. The proposed system can assist authorities in taking timely acting for water safety. In the future, more work van be done on building more models and its large-scale deployment.

ACKNOWLEDGMENTS

The authors would like to express their sincere gratitude to the management and faculty members of the Department of Computer Science and Engineering for their continuous support and encouragement throughout the completion of this project. The authors are especially thankful to the project guide for providing valuable guidance, constructive suggestions, and technical support during the development of this work. Their insights and motivation greatly helped in successfully completing the project. The authors also extend their appreciation to the laboratory staff and friends who provided assistance and resources during the implementation and testing of the system. Finally, the authors would like to thank the institution for providing the necessary facilities and opportunities to carry out this project successfully.

REFERENCES

- [1] F. Dolan, J. Lamontagne, R. Link, M. Hejazi, P. Reed, and J. Edmonds, "Evaluating the economic impact of water scarcity in a changing world," *Nat. Commun.*, vol. 12, no. 1, pp. 1–10, Mar. 2021.
- [2] B. Cheng and H. Li, "Impact of climate change and human activities on economic values produced by ecosystem service functions of rivers in water shortage area of Northwest China," *Environ. Sci. Pollut. Res.*, vol. 27, no. 21, pp. 26570–26578, Jul. 2020.
- [3] F. Hamlet, D. Huppert, and D. P. Lettenmaier, "Economic value of long-lead streamflow forecasts for Columbia River hydropower," *J. Water Resour. Plan. Manage.*, vol. 128, no. 2, pp. 91–101, Mar. 2002.
- [4] R. K. Singh, K. Sharma, M. Agrawal, and F. M. Marshall, "Health risk assessment of heavy metals via dietary intake of foodstuffs," *Food Chem. Toxicol.*, vol. 48, no. 2, pp. 611–619, Feb. 2010.
- [5] K. Ghosh, M. A. Bhatt, and H. P. Agrawal, "Effect of long-term application of treated sewage water on heavy metal accumulation in vegetables," *Environ. Monit. Assess.*, vol. 184, no. 2, pp. 1025–1036, Feb. 2012.
- [6] J. D. Brender, "Human health effects of exposure to nitrate, nitrite, and nitrogen dioxide," in *Just Enough Nitrogen: Perspectives on How to Get There*, 2020, pp. 283–294.
- [7] T. E. Arbuckle, G. J. Sherman, P. N. Corey, D. Walters, and B. Lo, "Water nitrates and CNS birth defects: A population-based case-control study," *Arch. Environ. Health*, vol. 43, no. 2, pp. 162–167, Apr. 1988.
- [8] T. Tiyasha et al., "Dual water choices: Assessment of influential factors using unsupervised machine learning," *IEEE Access*, vol. 9, pp. 150532–150544, 2021.
- [9] P. P. Belgali, V. V. Kulkarni, P. B. Harale, and R. V. Jadhav, "IoT based EV battery health monitoring system," *Int. J. Innov. Res. Electr. Electron. Instrum. Control Eng.*, 2024.
- [10] W. Z. W. ZhaoShi et al., "Assessing River water quality using water quality index in Lake Taihu Basin, China," *Sci. Total Environ.*, vol. 612, pp. 914–922, Jan. 2018.
- [11] S. K. Kumar et al., "Hydro-geochemistry and application of water quality index for groundwater quality assessment," *Appl. Water Sci.*, vol. 5, no. 4, pp. 335–343, Dec. 2015.
- [12] Y. Li et al., "Urbanization and agriculture intensification jointly enlarge spatial inequality of river water quality," *Sci. Total Environ.*, vol. 878, Art. no. 162559, Jun. 2023.
- [13] M. Chen, L. Zhang, and Y. Wang, "Design of human-computer interaction for in-vehicle information display system," *Procedia Comput. Sci.*, vol. 91, pp. 1076–1082, 2016.
- [14] M. Alzola-Andres et al., "Pharmaceutical residues in stranded dolphins in the Bay of Biscay," *Sci. Total Environ.*, vol. 912, Art. no. 168570, Feb. 2024.
- [15] J. Prüss-Ustün et al., "Burden of disease from inadequate water, sanitation and hygiene," *Int. J. Hyg. Environ. Health*, vol. 222, no. 5, pp. 765–777, Jun. 2019.