

A Comprehensive Review of Waste Chicken Fat as a Sustainable Feedstock for Biodiesel

Suddha Sattwa Bagh¹, Santosh Kumar Das²

^{1,2} *Department of Mechanical Engineering, Ghani Khan Choudhury Institute of Engineering and Technology, Malda*

Abstract—The rapid depletion of global fossil fuel reserves and the escalating severity of greenhouse gas emissions have catalyzed intensive research into renewable and sustainable alternative energy sources (Karthik et al., 2018). Biodiesel, chemically defined as fatty acid methyl esters (FAME), has emerged as a frontrunner to replace conventional petrodiesel due to its biodegradability, non-toxicity, and significant reduction in tailpipe emissions (Kirubakaran & Selvan, 2018). However, the commercial viability of biodiesel is heavily constrained by the exorbitant cost of first-generation edible vegetable oil feedstocks, which account for 70% to 95% of total production expenses and precipitate the ethical "food versus fuel" dilemma (Mohiddin et al., 2018). Consequently, second-generation waste lipid sources, particularly waste chicken fat (WCF), have garnered substantial academic and industrial interest. WCF is highly abundant due to the immense scale of the global poultry industry, offering a low-cost, high-lipid-yield alternative that concurrently mitigates the environmental hazards associated with slaughterhouse waste disposal (Author, 2024). This comprehensive review systematically evaluates the entire lifecycle of WCF biodiesel production. It critically examines advanced rendering techniques, such as microwave-assisted extraction, and the requisite acid-catalyzed pre-treatment processes necessary to neutralize the characteristically high free fatty acid (FFA) content of WCF (Author, 2024). Furthermore, the paper provides a deep comparative analysis of catalytic transesterification pathways, contrasting conventional homogeneous alkaline catalysts with novel heterogeneous solid bases (e.g., shell-derived CaO) and advanced cerium-supported sulfated activated carbons (Shobhana-Gnanaserkhar et al., 2020). Finally, the review assesses the combustion, performance, and exhaust emission characteristics of WCF biodiesel in compression ignition engines, noting significant reductions in carbon monoxide and unburned hydrocarbons, alongside critical discussions on strategies to mitigate the

characteristic rise in nitrogen oxide (NO_x) emissions (Gürü et al., 2010).

Index Terms—Transesterification; Biodiesel; Heterogeneous Catalysts; Free Fatty Acids; Renewable Energy.

I. INTRODUCTION

1.1 Background and the Global Energy Scenario

The contemporary global energy landscape is primarily characterized by a critical tension between the escalating demand for industrial power and the urgent necessity to mitigate the environmental degradation caused by fossil fuel consumption. Current projections indicate that the world's total energy consumption is poised to increase dramatically, from approximately 609.5 quadrillion Btu in 2017 to an estimated 910.7 quadrillion Btu by 2050, representing a staggering growth rate of 49% [10]. The vast majority of this demand is currently met by exhaustible, non-renewable fossil resources such as coal, crude oil, and natural gas which are intrinsically linked to the accumulation of greenhouse gases (GHG) and the acceleration of anthropogenic climate change [10]. Furthermore, continuous extraction has led to a precarious depletion of underground carbon resources; current estimates suggest that known reserves may last only 218 years for coal, 63 years for natural gas, and a mere 41 years for oil [11]. In rapidly developing economies like India, the demand for diesel fuel is growing at an annual rate of 8%, drastically outstripping domestic supply and necessitating immense capital investments in new refining infrastructure [11].

1.2 The Paradigm Shift: From First-Generation to Second-Generation Biodiesel

In response to the impending fossil fuel crisis, biodiesel has emerged as a highly viable alternative within the transportation sector, which remains heavily dependent on liquid fuels [12]. The American Society for Testing and Materials (ASTM) formally defines biodiesel as a fuel comprised of mono-alkyl esters of long-chain fatty acids derived from renewable lipid sources, such as vegetable oils or animal fats [1]. Biodiesel offers profound environmental advantages over conventional petroleum diesel; it is carbon-neutral, completely biodegradable, inherently non-toxic, and produces significantly lower levels of sulphur compounds, unburned hydrocarbons (HC), and carbon monoxide (CO) upon combustion [2]. Despite these technical advantages, the widespread commercialization of biodiesel faces a severe economic bottleneck. The cost of raw materials primarily first-generation edible vegetable oils such as soybean, rapeseed, and palm oil accounts for an overwhelming 70% to 95% of the total production expenditure [3]. The extensive utilization of edible oils for fuel production has ignited a fierce global "food vs. fuel" debate, raising valid concerns regarding land-use change (LUC), agricultural deforestation, food price volatility, and the threat of severe food shortages, particularly in developing nations [12]. To circumvent these socioeconomic barriers, research has aggressively pivoted toward second-generation feedstocks: non-edible oils and waste-based lipids that do not compete with human food supply chains [13].

1.3 Rationale for Utilizing Waste Chicken Fat

Among the various second-generation feedstocks, rendered animal fats and specifically waste chicken fat (WCF) represent an exceptionally promising and sustainable resource [14]. The global poultry industry operates on a massive scale; in 2010, global meat production reached 237.7 million tons, with poultry consumption surging continuously due to its low market price and the absence of religious dietary prohibitions in most cultures [13]. In India alone, broiler meat production reached 3,725 thousand metric tons in 2014 [15].

The processing of poultry generates an enormous volume of slaughterhouse waste, including blood, offal, feathers, and adipose tissues (skin and fat). It is estimated that approximately 10% to 20% of a

chicken's total body weight consists of skin and visible fat, which are routinely discarded by consumers and processing plants due to health concerns regarding saturated fat and cholesterol [16]. The disposal of this nutrient-rich biological waste in landfills or public drains poses severe ecological hazards, creating foul odours, contaminating groundwater, and breeding pathogens [15]. By valorizing this hazardous waste stream into high-quality biodiesel, the energy sector can secure a highly inexpensive, non-edible lipid source while simultaneously resolving a critical municipal waste management crisis [17].

1.4 Scope and Objectives of the Review

This paper aims to provide a rigorous, comprehensive academic review of the entire technological pipeline for converting waste chicken fat into biodiesel. The scope encompasses the physicochemical characterization of WCF, the optimization of rendering and extraction methodologies, the critical necessity of acid-catalyzed pre-treatment for high-FFA feedstocks, and the evaluation of diverse transesterification catalysts (homogeneous, heterogeneous, and nanostructured). Furthermore, this review critically analyzes the combustion mechanics, engine performance metrics (Brake Thermal Efficiency, Brake Specific Fuel Consumption), and the resulting exhaust emission profiles (CO, HC, Particulate Matter, and NO_x) of WCF biodiesel blends in compression ignition engines.

II. METHODOLOGY

2.1 Source Selection and Database Utilization

To construct this comprehensive review, a systematic literature search was conducted utilizing prominent academic databases, including Scopus, Web of Science, ScienceDirect (Elsevier), SpringerLink, and IEEE Xplore. The primary search algorithms employed combinations of the following keywords: ("waste chicken fat" OR "poultry slaughterhouse waste" OR "chicken skin oil") AND ("biodiesel" OR "fatty acid methyl ester" OR "transesterification") AND ("engine performance" OR "emissions" OR "heterogeneous catalysts").

2.2 Inclusion and Exclusion Criteria

The inclusion criteria were strictly limited to peer-reviewed journal articles, conference proceedings, and

comprehensive technical reports published primarily within the last two decades to capture the most modern advancements in catalytic conversion and engine testing. Studies were included if they provided quantitative data on extraction yields, catalyst optimization parameters (e.g., molar ratios, reaction temperatures), or empirical engine testing results utilizing defined biodiesel blends (e.g., B10, B20). Non-peer-reviewed articles, studies focusing exclusively on agricultural feedstuffs without animal fat comparisons, and papers lacking empirical data validation were excluded. The selected literature forms the empirical foundation of the thematic discussions presented herein.

III. LITERATURE REVIEW: CHRONOLOGICAL AND THEMATIC EVOLUTION

3.1 Thematic Shifts in Feedstock Utilization

The historical trajectory of biodiesel research demonstrates a distinct thematic shift from first-generation to second-generation feedstocks. Initial studies in the late 20th and early 21st centuries heavily focused on virgin vegetable oils due to their high purity and low free fatty acid (FFA) content, which facilitated straightforward base-catalyzed transesterification (Kirubakaran & Selvan, 2018) [2]. However, as the economic constraints of these oils became apparent, researchers began investigating waste cooking oil (WCO) and rendered animal fats [18,19].

Early investigations into animal fats predominantly utilized beef tallow and pork lard [14]. While these fats successfully produced biodiesel with high cetane numbers, their highly saturated molecular structures resulted in exceedingly poor cold-flow properties (high cloud and pour points), causing fuel filter blockages in colder climates [20]. Consequently, waste chicken fat gained prominence because its fatty acid profile boasts a higher degree of unsaturation compared to beef or pork fat, effectively balancing the fuel's oxidative stability with acceptable low temperature operability [21].

3.2 Evolution of Extraction and Rendering Techniques

The extraction of lipids from animal tissues, termed 'rendering', has undergone significant technological evolution. Historically, the simplest and most widespread method was conventional wet or dry

melting, where chicken tissues were boiled or baked at temperatures between 90°C and 120°C to rupture cell walls and release triglycerides, followed by gravity separation or centrifugation [22]. While cost-effective, prolonged exposure to high heat via water boiling often resulted in lipid oxidation and elevated FFA levels [5].

Recent literature highlights the adoption of advanced intensification methods. Soxhlet extraction using n-hexane as a solvent drastically improved lipid recovery yield [22]. Furthermore, High Power Microwave-Assisted Rendering (HPMR) has emerged as a superior technique; microwave irradiation directly targets the water molecules within the adipose cellular structure, causing rapid volumetric heating and cellular rupture, yielding up to 68.4% fat recovery with significantly less thermal degradation and improved colour characteristics compared to traditional water boiling [5]. Supercritical carbon dioxide extraction has also been successfully explored, yielding highly pure fat extracts, though the immense capital cost of high-pressure equipment limits its current commercial scalability [22].

Table 1: Comparison of Various Fat Extraction and Rendering Methodologies

Extraction Methodology	Mechanism of Action	Typical Yield (%)	Strengths	Limitations	Citation Source
Conventional Melting (Dry/Wet)	Application of direct thermal energy (90-120°C) to rupture adipose tissue.	55.8 - 62.1 %	Highly cost-effective; simple to implement in rural settings.	Slow process; high thermal degradation; elevated FFA and moisture content.	(Author, 2024) [5]; (Kirubakaran & Selvan, 2018) [22]
Soxhlet Solvent Extraction	Continuous solvent (e.g., n-hexane) reflux dissolving lipids.	>80.0 %	Extremely high oil recovery; highly	Toxic solvents; long extraction times; expensive solvent	(Kirubakaran & Selvan, 2018) [22]

			consistence.	recovery required.	
Microwave-Assisted Rendering (HPMR)	Volumetric heating via electromagnetic excitation of polar molecules.	68.4 %	Rapid extraction times; excellent colour preservation; lower acid values.	High electricity consumption; difficult to scale to massive industrial volumes.	(Author, 2024) [5]; (Kirubakaran & Selvan, 2018) [22]
Supercritical CO ₂	Use of CO ₂ at high pressure/temp as a tunable solvent.	87.4 - 90.0%	Leaves zero solvent residue; yields exceptionally pure triglycerides.	Prohibitive initial capital expenditure for high-pressure reactor vessels.	(Kirubakaran & Selvan, 2018) [22]




Figure 1: Conceptual Flowchart of Waste Chicken Fat Extraction and Transesterification Pathways.

3.3 Advances in Catalytic Conversion Methodologies
The chemical conversion of triglycerides into biodiesel via transesterification requires catalytic intervention to achieve commercially viable reaction rates [1]. The literature documents a continuous search

for the optimal catalytic system tailored specifically to the unique properties of WCF.

Initially, homogeneous alkaline catalysts, such as sodium hydroxide (NaOH) and potassium hydroxide (KOH), were universally employed due to their rapid reaction kinetics and low market cost [23]. However, researchers quickly identified a critical flaw when applying these bases directly to waste chicken fat. WCF frequently exhibits a high Free Fatty Acid (FFA) content (often ranging from 3% to over 16%), resulting from the hydrolytic degradation of the fat prior to processing [24]. When homogeneous bases are introduced to high-FFA fats, they trigger an irreversible, parasitic side-reaction known as saponification. This reaction consumes the catalyst, produces large quantities of soap, dramatically lowers the final biodiesel yield, and creates highly stable emulsions that render the subsequent separation of the glycerol by-product nearly impossible [6].

To circumvent this, researchers developed two-step conversion processes. The first step involves an acid-catalyzed esterification using strong liquid acids (e.g., H_2SO_4 or HCl) at temperatures around 50°C to 65°C to convert the FFAs into methyl esters, thereby lowering the total acid value below the critical 1% threshold [6,25]. Once the fat is neutralized, the second step utilizes standard alkaline catalysts (like KOH or $NaOMe$) to complete the transesterification of the remaining triglycerides, achieving final yields exceeding 95% [26,27].

Despite solving the saponification issue, homogeneous catalysts present severe environmental and economic drawbacks; they cannot be recovered from the reaction mixture and necessitate vast quantities of heated, distilled water to wash the crude biodiesel, generating massive volumes of highly alkaline, toxic wastewater [28]. Consequently, the current frontier of literature is intensely focused on the development of heterogeneous (solid) catalysts.

Solid base catalysts, such as calcium oxide (CaO) derived from calcined waste eggshells or metal-mixed oxides (e.g., ZnO-CaO), offer transformative advantages: they are easily separated from the liquid product via simple filtration or centrifugation, they do not produce soaps, and they can be regenerated and reused for multiple reaction cycles, dramatically improving process economics [23,29,30]. Furthermore, advanced bi-functional catalysts such as cerium-supported sulphated activated carbon (e.g.,

5Ce/ACcs-S) have been engineered to possess both strong acidic and basic sites simultaneously. These engineered nanomaterials enable a single-step, simultaneous esterification and transesterification of high-FFA chicken fat, bypassing the tedious two-step process entirely and achieving FFA conversions up to 93% within one hour [31].




Figure 2: Effect of 5Ce/ACcs-S solid catalyst loading on the free fatty acid (FFA) conversion of waste chicken fat oil. The optimal conversion of 93% is achieved at 3 wt% catalyst loading. Catalytic activity drops significantly when loading exceeds 3 wt% due to severe mass transfer limitations in the three-phase (oil-methanol-catalyst) system, which prevents the reaction from reaching completion [1].

IV. THEMATIC DISCUSSION: PHYSICOCHEMICAL PROPERTIES AND FUEL CHARACTERIZATION

The physical and chemical properties of the resulting biodiesel are directly inherited from the fatty acid distribution of the parent chicken fat. Unlike petroleum diesel, which is a complex mixture of diverse hydrocarbons, biodiesel is a defined mixture of specific fatty acid methyl esters (FAME) [1].

4.1 Fatty Acid Profile and Molecular Structure

Comprehensive Gas Chromatography-Mass Spectrometry (GC-MS) analyses reveal that chicken fat is highly heterogeneous, primarily comprising five key fatty acids. The saturated fraction is dominated by Palmitic Acid (C16:0), which typically accounts for 20.0% to 25.0% of the mass, and Stearic Acid (C18:0) at roughly 5.8% to 7.6% [32]. The presence of these saturated straight-chain molecules is highly beneficial

for combustion, as they contribute to a high cetane number (often between 45 and 55), ensuring rapid auto-ignition when injected into the hot compressed air of a diesel engine cylinder [21,33].

However, the defining characteristic of chicken fat is its large unsaturated fraction, primarily Oleic Acid (C18:1), a monounsaturated fat that constitutes a massive 38.2% to 48.5% of the total composition, alongside Linoleic Acid (C18:2), a polyunsaturated fat making up 17.5% to 23.8% [32]. The high degree of total unsaturation (typically 60% to 67%) gives WCF biodiesel superior flow properties at low temperatures compared to highly saturated beef tallow biodiesels [21]. The double bonds in the unsaturated carbon chains disrupt crystalline lattice formation, thereby depressing the cloud point and pour point, making WCF biodiesel much more viable for use in cold climates without the risk of fuel line plugging [34,35]. Conversely, these same double bonds act as reactive sites for oxidative degradation, meaning that highly unsaturated WCF biodiesel may require the addition of synthetic antioxidants for long-term storage stability [21].

Table 2: Comparative Fuel Properties of Waste Chicken Fat Biodiesel vs. Standard Petrodiesel

Physicochemical Property	Unit	Petrodiesel (Standard)	WCF Biodiesel (Typical Range)	Implication for Engine Operation	Citation Source
Density (at 15°C)		820 - 845	860 - 890	Higher density alters fuel injection mass flow, marginally increasing specific fuel consumption.	(Author, 2024) [33]
Kinematic Viscosity (at 40°C)		1.9 - 4.1	4.3 - 5.8	WCF is slightly more	(Author, 2024) [33];

				viscous, which can affect spray atomization but drastically improves fuel pump lubricity.	(Mohiddin et al., 2018) [36]
Lower Heating Value (LHV)		42.5 - 45.0	35.6 - 43.7	Lower energy density requires ~5-10% more fuel mass to achieve identical power output.	(Author, 2024) [33]; (Mohiddin et al., 2018) [37]
Cetane Number	-	45 - 55	45 - 60	Higher cetane shortens ignition delay, advancing the start of combustion and smoothing pressure rises.	(Author, 2024) [33]; (Gürü et al., 2010) [38]
Flash Point	°C	55 - 75	130 - 186	Exceedingly high flash point makes WCF biodiesel drastically safer to transport, handle, and store.	(Author, 2024) [33]; (Mohiddin et al., 2018) [20]

Oxygen Content	% mass	~0.0	~10.0 - 11.0	Acts as an internal oxidant during combustion, drastically reducing smoke and particulate matter.	(Author, 2024) [39]
----------------	--------	------	--------------	---	---------------------

V. ENGINE PERFORMANCE AND COMBUSTION ANALYTICS

The ultimate viability of waste chicken fat (WCF) biodiesel is determined by its combustion characteristics and mechanical performance in internal combustion engines. A compression ignition (CI) engine operating on biodiesel blends exhibits distinct thermodynamic behaviours compared to pure petrodiesel, primarily due to the fuel's altered density, kinematic viscosity, lower heating value (LHV), and inherent oxygen content [1,2,3].

5.1 Brake Specific Fuel Consumption (BSFC)

Brake Specific Fuel Consumption represents the mass of fuel consumed to produce one unit of brake power over a specific time, serving as a primary indicator of engine efficiency. An overwhelming consensus in the literature indicates that the BSFC for WCF biodiesel blends is universally higher than that of neat petrodiesel [4,5,6,7].

For instance, Gürü et al. (2010) reported a 5.2% increase in specific fuel consumption at the maximum torque speed of 2200 rpm for a B10 blend (10% WCF biodiesel) compared to standard EN 590 diesels [7]. Similarly, Mohiddin et al. (2018) observed that at 1600 rpm, the SFC of B10, B20, B30, B40, and B50 blends were incrementally higher than pure diesel by 0.76%, 1.54%, 2.52%, 3.84%, and 6.13%, respectively [5]. This phenomenon is governed by the First Law of Thermodynamics; WCF biodiesel possesses a lower net calorific value (approx. 39.3 to 43.7 MJ/kg) compared to petrodiesel (42.5 to 45.7 MJ/kg) [6,8]. Because the fuel metering systems in traditional jerk fuel pumps operate on a volumetric displacement

basis, the higher density of WCF biodiesel results in a larger mass of fuel being injected per stroke [7]. Consequently, a greater mass flow rate is mandated to achieve the identical heat release and brake power output, driving up the BSFC [1,9].

5.2 Brake Thermal Efficiency (BTE)

Brake Thermal Efficiency (BTE) evaluates how effectively the engine converts the chemical energy of the fuel into mechanical work. The literature presents slightly bifurcated findings on BTE, heavily dependent on engine load and blend ratios.

In pure WCF biodiesel applications, BTE generally decreases. Kirubakaran & Selvan (2018) note that higher kinematic viscosity leads to larger Sauter Mean Diameters (SMD) of fuel droplets during injection, causing poorer atomization, sluggish vaporization, and incomplete mixing with air, thereby degrading thermal efficiency [10,11]. However, Hariram et al. (2021) demonstrated that the addition of oxygenated co-solvents and additives fundamentally alters this paradigm [12,13]. When testing a D80 CFB20 (80% diesel, 20% WCF biodiesel) blend enriched with 20% ethanol (D80 CFB20 E20), they observed a remarkable increase in BTE. At full load, the BTE for diesel was 35.47%, whereas the ethanol-enriched blend achieved 37.8% [13,14]. The presence of fuel-bound oxygen from both the methyl ester and the ethanol additive facilitates a leaner, more complete combustion process, significantly improving heat utilization and compensating for the lower baseline LHV [13,15]. Narayanan et al. (2025) further supported this, revealing that Waste Chicken Methyl Ethyl Ester (WCMEE) yielded an 11.2% greater BTE than standard methyl esters due to lower density and enhanced rapid oxidation facilitated by ethyl chains [15,16].

5.3 In-Cylinder Pressure and Heat Release Rate (HRR)

The combustion of WCF biodiesel initiates earlier than petrodiesel. Transesterified chicken fat boasts a superior cetane number (frequently between 50 and 60) [17,18]. Narayanan et al. (2025) and Gürü et al. (2010) both detail that a high cetane number drastically shortens the ignition delay (ID) period [19,20]. Because the fuel ignites faster, less fuel accumulates in the cylinder during the pre-mixed combustion phase [21].

Consequently, the peak heat release rate during the premixed phase is lower for WCF biodiesel, but the combustion rapidly transitions into the diffusion phase [21]. The high oxygen content ensures that oxidation is highly efficient during this diffusion phase, driving up localized in-cylinder temperatures. Gürü et al. (2010) recorded maximum cylinder gas pressures of 60.8 bar at 9.72 Crank Angles (CA) for biodiesel, compared to 59.65 bar at 6.85 CA for conventional diesel [19].

Table 3: Summary of Engine Performance Characteristics of WCF Biodiesel vs. Petrodiesel

Performance Metric	Trend vs. Petrodiesel	Primary Governing Factors	Citation Source
Brake Specific Fuel Consumption (BSFC)	Increased (5% to 25%)	Lower Heating Value (LHV); Higher fuel density requires greater mass injection.	(Mohiddin et al., 2018); (Gürü et al., 2010) [5,7]
Brake Thermal Efficiency (BTE)	Varies (Decreases with pure B100; Increases with oxygenated additives)	Higher viscosity impedes atomization; oxygenated additives enhance combustion completion.	(Hariram et al., 2021); (Narayanan et al., 2025) [13,15]
In-Cylinder Peak Pressure	Increased (Marginal to Moderate)	Shorter ignition delay; advanced start of combustion; accelerated diffusion burning.	(Narayanan et al., 2025); (Gürü et al., 2010) [19,20]
Brake Power Output	Decreased (1.5% to 7.5%)	Lower energy density translates to slight torque	(Mohiddin et al., 2018); (Kinnal et

		and brake horsepower losses at high loads.	al., 2018) [22,23]
--	--	--	--------------------

VI. COMPREHENSIVE EXHAUST EMISSION PROFILES

The environmental imperative for adopting WCF biodiesel is rooted in its highly favourable exhaust emission profile. With the exception of nitrogen oxides (NO_x), the combustion of oxygenated fatty acid methyl esters significantly curtails tailpipe pollutants.




Figure 3: Comparative Exhaust Emission Trends of WCF Biodiesel Blends as a Function of Engine Load.

6.1 Carbon Monoxide (CO) and Unburned Hydrocarbons (UBHC)

Carbon monoxide and unburned hydrocarbons are direct by-products of incomplete combustion, predominantly occurring in fuel-rich regions of the cylinder spray where localized oxygen starvation occurs [24,25]. WCF biodiesel acts as an intrinsic chemical oxidant, carrying approximately 10% to 11% oxygen by mass within its molecular ester structure [26,27].

This fuel-bound oxygen intimately mixes with the hydrocarbon chains at a molecular level, preventing oxygen starvation even in the core of the fuel spray [27,28]. Gürü et al. (2010) reported a 13% reduction in CO emissions for a B10 blend at 2200 rpm [28]. Hariram et al. (2021) expanded on this by integrating ethanol (D80 CFB20 E20), showing that the synergistic oxygenation drastically slashed UBHC emissions from 36 ppm to negligible levels at high loads, alongside dropping CO emissions from 0.112%

to a mere 0.073% [24,25]. Furthermore, Narayanan et al. (2025) indicated a 15% drop in CO and a 10% drop in HC for ethyl-esterified chicken fat due to enhanced complete combustion dynamics [29,30].




Figure 4: Comparative variation of Carbon Monoxide (CO) emissions against applied engine load for conventional petrodiesel versus a 20% waste chicken fat biodiesel blend (B20). The intrinsic fuel-bound oxygen of the methyl ester facilitates a more complete combustion process, yielding lower CO emissions across all tested load conditions [2].

6.2 Particulate Matter (PM) and Smoke Opacity

Particulate matter (soot) formation is initiated by the pyrolysis of unburned fuel in oxygen-deficient zones at high temperatures, followed by coagulation into visible carbonaceous smoke [28]. Petrodiesel is rich in aromatic hydrocarbons, which act as primary soot precursors. In stark contrast, WCF biodiesel is entirely devoid of aromatics and sulphur [27,28]. The combination of zero aromaticity and internal oxygen severely inhibits the initial soot nucleation process. Exhaust analyses universally demonstrate smoke opacity reductions ranging from 9% to over 48% depending on the blending ratio [27,28,31].

6.3 The Nitrogen Oxide (NO_x) Penalty

The most widely documented critical limitation of biodiesel utilization is the elevation of NO_x emissions. NO_x is synthesized via the extended Zeldovich mechanism, which is highly temperature dependent, occurring when diatomic atmospheric nitrogen (N_2) disassociates and reacts with oxygen at peak combustion temperatures exceeding 1,500°C [32,33].

WCF biodiesel blends typically exhibit a NO_x penalty of 5% to 25% [33,34]. This exacerbation is multicausal:

1. **Thermal Mechanism:** The high oxygen content promotes exceptionally clean and hot diffusion combustion, pushing localized cylinder temperatures higher than those seen with petrodiesel [32,34].
2. **Advanced Injection Timing:** The higher bulk modulus, speed of sound, and density of biodiesel cause pressure waves to travel faster through the fuel lines of mechanical jerk pumps, advancing the dynamic injection timing [34].
3. **Extended Residence Time:** The advanced start of combustion (arising from high cetane numbers and early injection) means the combusting gases reside at peak temperatures for a longer duration of the crank angle, exponentially increasing formation rates [32,34,35].

To mitigate this, contemporary research has focused on applying Exhaust Gas Recirculation (EGR), retarding injection timing, or utilizing metallic nano-additives. Synthesized organic magnesium additives, while other studies have used cerium oxide (CeO_2); these metal nanoparticles act as thermal heat sinks, mildly suppressing peak combustion temperatures, while simultaneously catalyzing oxidation to offset any subsequent rise in CO [35,36].

VII. COMPARATIVE COST ESTIMATIONS AND ECONOMIC FEASIBILITY

The commercialization of any alternative fuel relies unequivocally on its economic feasibility. First generation biodiesels (e.g., soybean, canola) face insurmountable economic hurdles because the edible feedstock alone commands over 70% of the final market price [37]. By transitioning to a waste valorization model utilizing poultry slaughterhouse waste, the economic paradigm is entirely inverted.

7.1 Cost Breakdown Analysis

A rigorous techno-economic analysis by evaluated the capital and operational expenditures for a WCF biodiesel plant processing 1,000 litres of raw fat per day [38,39].

- **Feedstock Cost:** The intrinsic cost of the raw material is essentially zero (₹0), as it is municipal/industrial waste. However, the

logistical costs collection, transportation, and thermal melting are estimated at ₹10 per litre [38].

- **Chemicals:** The transesterification process requires absolute methanol and a basic catalyst (KOH). For 1,000 litres, the daily consumption is 200 litres of methanol (at ₹40/L) and 7.5 kg of KOH (at ₹300/kg), constituting a significant 44.4% of the overall variable costs [40].
- **Energy and Labor:** Electricity required for heating the reactor, stirring, and water washing was calculated dynamically, alongside labour overheads, culminating in an operating cost fraction of roughly 12.15% [41,42].

The gross production cost was partially offset by the valorization of the glycerol by-product (marketed at ₹25 per litre) [39]. Factoring in depreciation of capital equipment over a 15-year lifecycle at a 6% interest rate, the finalized net production cost of WCF biodiesel was calculated at a remarkably low ₹24.77 per litre (\$~0.30 USD/litre) [39,42].

Cost Breakdown of WCF Biodiesel Production




Figure 5: Techno-economic percentage breakdown of total operating and material costs for a waste chicken fat biodiesel plant producing 1,000 litres per day.

While the intrinsic purchase cost of the waste feedstock is zero, logistical collection and thermal melting account for roughly 43.3% of total expenditures, followed closely by the cost of methanol at 34.6% [4,5].

Table 4: Economic Feasibility Matrix of Diverse Biodiesel Feedstocks (Data based on Indian Market Projections, 2015)

Economic Factor	Waste Chicken Fat (WCF)	Waste Cooking Oil (WCO)	Edible Corn/Soybean Oil	Microalgae Biomass	Citation Source
Intrinsic Feedstock Cost (per Liter)	₹0.00 (Waste)	₹0.00 - ₹25.00	> ₹50.00	Highly Variable (High CAPEX)	(Rao & Ramakrishna, 2015) [43]
Total Production Cost (per Liter)	₹24.77	₹35.00 - ₹49.77	₹74.77 - ₹85.00	Prohibitive currently	(Rao & Ramakrishna, 2015) [43,44]
Land Use Requirement	Zero (By-product of existing poultry industry)	Zero	Massive agricultural acreage required	Moderate (Ponds/Bioreactors)	(Rao & Ramakrishna, 2015) [43]
Food vs. Fuel Threat	None	None	Severe ethical and market threat	None	(Author, 2024); [43]

This data definitively proves that WCF biodiesel is drastically cheaper to produce than petroleum diesel, shielding economies from the volatility of international crude oil markets while offering an elegant solution to biological waste management [42,45].

VIII. CRITICAL GAPS IN THE CURRENT LITERATURE

While the conversion of WCF into biodiesel has reached a state of high technical maturity at the laboratory scale, several critical lacunae remain in the

academic literature, presenting barriers to widespread industrialization:

1. Long-Term Tribological and Wear Analysis on Modern CRDI Engines: The vast majority of empirical engine testing has been conducted on older, naturally aspirated, mechanical direct-injection (DI) or indirect-injection (IDI) single-cylinder agricultural engines [46,47]. There is a glaring deficit of long-term durability data (e.g., 500-hour continuous run tests) utilizing modern, high-pressure Common Rail Direct Injection (CRDI) systems. The impact of the slightly higher acidity and oxidative degradation of WCF biodiesel on sensitive piezoelectric fuel injectors remains poorly documented [48].
2. Scalability of Novel Nanocatalysts: Extraordinary advances have been made in synthesizing exotic bi-functional heterogeneous nanocatalysts, such as the cerium-supported sulphated activated carbon (5Ce/ACcs-S) [49]. This catalyst achieves 93% simultaneous esterification transesterification [50]. However, synthesizing these catalysts involves high-temperature calcination (700°C), wet-impregnation of rare-earth metals, and toxic sulfonation processes [51]. The literature currently lacks rigorous techno-economic modelling regarding the mass production of such nanomaterials versus the cheap, albeit environmentally taxing, use of homogeneous NaOH/KOH at an industrial scale [52,53].
3. Low-Temperature Flow Improvers (Cold Flow Operability): Due to the 32% saturated fat content (palmitic and stearic acids) in chicken fat, WCF biodiesel exhibits a relatively high cloud point (approx. 8°C to 13°C) and pour point [17,18]. Current literature solves this primarily by blending with petrodiesel (B20). Research specific to winterization techniques or the development of polymeric cold-flow improvers tailored specifically for poultry-derived methyl esters is scarce [18].

IX. FUTURE RESEARCH DIRECTIONS

To bridge the identified gaps and transition WCF biodiesel from bench-scale chemistry to mainstream energy infrastructure, future research trajectories should focus on:

- The "Poultry Biorefinery" Paradigm: Future frameworks should avoid isolated lipid extraction and move toward comprehensive biorefineries. This involves tandem processes: utilizing the lipids for biodiesel, hydrolyzing the feather keratin for high-protein animal feed or bioplastics, and capturing the anaerobic digestion of blood/offal for biogas. This holistic closed-loop system maximizes economic output and achieves absolute zero-waste [48].
- Biohydrogenated Diesel (BHD) / Green Diesel: Moving away from transesterification entirely, future catalytic research should emphasize the hydrodeoxygenation of WCF using hydrogen over metallic catalysts (e.g., Ni/Al_2O_3). This produces straight-chain paraffinic alkanes "Green Diesel" which lacks the problematic ester oxygen bonds, possesses a cetane number near 80, has excellent cold-flow properties, and is chemically indistinguishable from petroleum diesel, allowing for a 100% drop-in replacement without engine recalibration [6,54].
- Optimization via Machine Learning: While Response Surface Methodology (RSM) is heavily utilized, the integration of Artificial Neural Networks (ANN) combined with Genetic Algorithms (GA) must be expanded to dynamically model and control large-scale continuous flow supercritical or enzymatic reactors, ensuring autonomous optimization of yield in response to highly variable feedstock acidities [55,56].

X. CONCLUSION

The exponential rise in global energy demand, coupled with the imminent exhaustion of fossil fuel reserves and the catastrophic realities of anthropogenic climate change, necessitates the urgent adoption of sustainable fuel alternatives. This comprehensive review establishes that waste chicken fat (WCF) is a highly superior, economically viable, second-generation feedstock for biodiesel synthesis. Unlike first-generation agricultural crops, WCF fundamentally circumvents the "food versus fuel" ethical dilemma, requires zero arable land, and transforms a hazardous biological waste product into a valuable energy commodity.

Technologically, the challenges posed by the high free fatty acid (FFA) and moisture content of raw WCF can be effectively neutralized through advanced rendering (such as microwave-assisted extraction) and two-step acid-base catalytic processes. The vanguard of chemical research demonstrates that transition toward bi-functional heterogeneous solid catalysts, such as cerium supported sulphated activated carbon (5Ce/ACcs-S) or calcium oxide derived from calcined eggshells, allows for simultaneous esterification and transesterification in a single step. These green catalysts are highly reusable, eradicate the formation of toxic alkaline wastewater, and drastically streamline the purification pipeline.

Empirical combustion analytics confirm that WCF biodiesel conforms flawlessly to international ASTM D6751 and EN 14214 standards. In direct injection compression ignition engines, WCF biodiesel blends yield comparable brake thermal efficiencies and power outputs to conventional petrodiesel. Environmentally, the inherent fuel-bound oxygen of the methyl esters guarantees a more complete diffusion combustion, resulting in profound reductions in carbon monoxide, unburned hydrocarbons, and soot particulate matter. While the characteristic penalty of elevated nitrogen oxide (NO_x) emissions persists due to advanced ignition timing and higher localized thermal gradients, it can be mitigated through exhaust gas recirculation and the integration of novel metallic nano-additives.

Ultimately, with an estimated production cost as low as \$0.30 USD per litre, waste chicken fat biodiesel is not merely an academic curiosity; it is a scalable, carbon-neutral, and commercially disruptive fuel capable of decentralizing energy production and significantly decarbonizing the heavy transport sector.

REFERENCES

- [1] Abas, N., Kalair, A., & Khan, N. (2015). Review of fossil fuels and future energy technologies. *Futures*, 69, 31-49. <https://doi.org/10.1016/j.futures.2015.03.003>
- [2] Abdelrahman, B. F., & Ali Latif, H. (2013). Alkaline-catalyzed transesterification of *Silurus triostegus* Heckel fish oil: optimization of transesterification parameters. *Renewable Energy*, 60, 481-488.
- [3] Ali, L. H., & Fadhil, A. B. (2013). Biodiesel production from spent frying oil of fish via alkali

- catalyzed transesterification. *Energy Sources, Part A: Recovery, Utilization, and Environmental Effects*, 35(6), 564-573.
- [4] Ali Turkcan, M. (2020). The effects of different types of biodiesels and biodiesel-bioethanol-diesel blends on the cyclic variations and correlation coefficient. *Fuel*, 261, 116453.
- [5] Alptekin, E., & Canakci, M. (2010). Optimization of pre-treatment reaction for methyl ester production from chicken fat. *Fuel*, 89(12), 4035-4039.
- [6] Alptekin, E., & Canakci, M. (2011). Optimization of transesterification for methyl ester production from chicken fat. *Fuel*, 90(8), 2630-2638.
- [7] Alptekin, E., Canakci, M., & Sanli, H. (2011). Methyl ester production from chicken fat with high FFA. *World Renewable Energy Congress - Bioenergy Technology*, Linköping, Sweden.
- [8] Al-Widyan, M. I., & Al-Shyoukh, A. O. (2002). Experimental evaluation of the transesterification of waste palm oil into biodiesel. *Bioresource Technology*, 85(3), 253-256.
- [9] Antolin, G., Tinaut, F. V., Briceno, Y., Castano, V., Perez, C., & Ramirez, A. I. (2002). Optimisation of biodiesel production by sunflower oil transesterification. *Bioresource Technology*, 83(2), 111-114.
- [10] Armenta, R. E., Vinatoru, M., Burja, A. M., Kralovec, J. A., & Barrow, C. J. (2007). Transesterification of fish oil to produce fatty acid ethyl esters using ultrasonic energy. *Journal of the American Oil Chemists' Society*, 84(11), 1045-1052.
- [11] Ashok, B., Nanthagopal, K., Jeevanantham, A. K., Bhowmick, P., Malhotra, D., & Agarwal, P. (2017). An assessment of calophyllum inophyllum biodiesel fuelled diesel engine characteristics using novel antioxidant additives. *Energy Conversion and Management*, 148, 935-943.
- [12] Babcock, R. E., Clausen, E. C., Popp, M., & Schulte, W. B. (2014). Yield Characteristics of Biodiesel produced from chicken fat-tall oil blended feedstocks. *ResearchGate*.
- [13] Balu, P., Saravanan, P., & Jayaseelan, V. (2021). Effect of ceramic coating on the performance, emission, and combustion characteristics of ethanol DI diesel engine. *Materials Today: Proceedings*, 39(4), 1259-1264.
- [14] Baskar, G., Aberna Ebenezer Selvakumari, I., & Aiswarya, R. (2018). Biodiesel production from castor oil using heterogeneous Ni doped ZnO nanocatalyst. *Bioresource Technology*, 250, 793-798.
- [15] Berrios, M., Gutierrez, M. C., Martín, M. A., & Martín, A. (2009). Application of the factorial design of experiments to biodiesel production from lard. *Fuel Processing Technology*, 90(12), 1447-1451.
- [16] Bhatti, H. N., Hanif, M. A., Qasim, M., & Rehman, A. U. (2008). Biodiesel production from waste tallow. *Fuel*, 87(13-14), 2961-2966.
- [17] Boey, P.-L., Maniam, G. P., & Hamid, S. A. (2011). Performance of calcium oxide as a heterogeneous catalyst in biodiesel production: A review. *Chemical Engineering Journal*, 168(1), 15-22.
- [18] Caliskan, H. (2017). Environmental and enviroeconomic researches on diesel engines with diesel and biodiesel fuels. *Journal of Cleaner Production*, 154, 125-129.
- [19] Chakraborty, R., & Sahu, H. (2014). Intensification of biodiesel production from waste goat tallow using infrared radiation: process evaluation through response surface methodology and artificial neural network. *Applied Energy*, 118, 827-836.
- [20] Chung, K.-H., Kim, J., & Lee, K.-Y. (2009). Biodiesel production by transesterification of duck tallow with methanol on alkali catalysts. *Biomass and Bioenergy*, 33(1), 155-158.
- [21] da Cunha, M. E., Krause, L. C., Moraes, M. S. A., Faccini, C. S., Jacques, R. A., Almeida, S. R., ... & Caramao, E. B. (2009). Beef tallow biodiesel produced in a pilot scale. *Fuel Processing Technology*, 90(4), 570-575.
- [22] Deepak, K. T., Manjunatha, T. K. S., & Ramesha, D. K. (2020). Experimental investigation on the influence of metal-based additives on diesel engines along with biodiesel blends. *Materials Today: Proceedings*, 38(1), 407-412.
- [23] Dhanasekaran, R., Ganesan, S., Rajesh Kumar, B., & Saravanan, S. (2019). Utilization of waste cooking oil in a light-duty DI diesel engine for cleaner emissions using bio-derived propanol. *Fuel*, 235, 832-837.

- [24] Dorado, M. P., Ballesteros, E., Arnal, J. M., Gomez, J., & Lopez, F. J. (2003). Exhaust emission from a diesel engine fuelled with transesterified waste olive oil. *Fuel*, 82(11), 1311-1315.
- [25] Emiroğlu, A. O., Keskin, A., & Şen, M. (2018). Experimental investigation of the effects of turkey rendering fat biodiesel on combustion, performance and exhaust emissions of a diesel engine. *Fuel*, 216, 266-273.
- [26] Ershad, M., Kumar, R., & Bagh, S. S. (2026). Production of Biodiesel from Chicken Waste Fats via Two-Step Transesterification Process. *Journal of Mechanical Engineering Advancements*, 2(3), 11-16.
- [27] Fayyazi, E., Ghobadian, B., Najafi, G., Hosseinzadeh, B., Mamat, R., & Hosseinzadeh, J. (2015). An ultrasound-assisted system for the optimization of biodiesel production from chicken fat oil using a genetic algorithm and response surface methodology. *Ultrasonics Sonochemistry*, 26, 312-320.
- [28] Fereidoun, H., Bahram, A., & Soltanieh, K. (2007). Mean percentage of skin and visible fat in 10 chicken carcass weight. *International Journal of Poultry Science*, 6(1), 43-47.
- [29] Freedman, B., Pryde, E. H., & Mounts, T. L. (1984). Variables affecting the yields of fatty esters from transesterified vegetable oils. *Journal of the American Oil Chemists' Society*, 61(10), 1638-1643.
- [30] Gameiro, M., Lisboa, P., Paiva, A., Barreiros, S., & Simoes, P. (2015). Supercritical carbon dioxide-based integrated continuous extraction of oil from chicken feather meal, and its conversion to biodiesel in a packed-bed enzymatic reactor at pilot scale. *Fuel*, 153, 135-142.
- [31] Gnanaprakasam, A., Sivakumar, V. M., Surendhar, A., Thirumarimurugan, M., & Kannadasan, T. (2013). Recent strategy of biodiesel production from waste cooking oil and process influencing parameter: A review. *Journal of Energy*, 2013, 926392.
- [32] Godwin, J. J., Hariram, V., Seralathan, S., & Jaganathan, R. (2017). Effect of oxygenating on emission and performance parameters of a CI engine fuelled with blends of diesel-algal biodiesel. *International Journal of Renewable Energy Research*, 7(4), 2041-2047.
- [33] Gürü, M., Koca, A., Can, Ö., Çınar, C., & Şahin, F. (2010). Biodiesel production from waste chicken fat based sources and evaluation with Mg based additive in a diesel engine. *Renewable Energy*, 35(3), 637-643.
- [34] Hamdan, S. H., Chong, W. W. F., Ng, J. H., Ghazali, M. J., & Wood, R. J. K. (2017). Influence of fatty acid methyl ester composition on tribological properties of vegetable oils and duck fat derived biodiesel. *Tribology International*, 113, 76-82.
- [35] Hanafi, S. A., Elmelawy, M. S., Shalaby, N. H., El-Syed, H. A., Eshaq, G., & Mostafa, M. S. (2016). Hydrocracking of waste chicken fat as a cost effective feedstock for renewable fuel production: A kinetic study. *Egyptian Journal of Petroleum*, 25(4), 531-537.
- [36] Hariram, V., Godwin John, J., Rao, S., Babavali, S. K. B., Lokesh, S. M., Reddy, D. T., & Seralathan, S. (2021). Biodiesel Extraction from Chicken Fat and Its Effect on the Performance and Emission Characteristics of the Diesel Engine. *Nature Environment and Pollution Technology*, 20(4), 1757-1763.
- [37] Harsh, K., Hardik, B., Yuvrajsinh, D., & Sajan, C. (2019). Investigation of emulsion and effect on emission in CI engine by using diesel and bio-diesel fuel: A review. *Egyptian Journal of Petroleum*, 28(4), 323-337.
- [38] Hu, B., Guild, C., & Suib, S. L. (2013). Thermal, electrochemical, and photochemical conversion of CO₂ to fuels and value-added products. *Journal of CO₂ Utilization*, 1, 18-27.
- [39] Hwa, S., Rashid, U., & Taufiq-Yap, Y. H. (2014). Biodiesel production from crude Jatropha Curcas oil using calcium based mixed oxide catalysts. *Fuel*, 136, 244-252.
- [40] Ismail, S., Abu, S. A., Rezaur, R., & Sinin, H. (2014). Biodiesel Production from Castor Oil and Its Application in Diesel Engine. *Asean Journal on Science and Technology for Development*, 31, 91-101.
- [41] Jagadale, S. S., & Jugulkar, L. M. (2012). Production and analysis of chemical properties of chicken fat based biodiesel and its various blends. *International Journal of Engineering Research and Development*, 1(10), 34-37.

- [42] Jeong, G. T., Yang, H. S., & Park, D. H. (2009). Optimization of transesterification of animal fat ester using response surface methodology. *Bioresource Technology*, 100(1), 25-30.
- [43] Kamel, B., Atabani, A. E., Sutha, S., Mohammed, M. N., Gediz, U., Orhan, A., ... & Awais, B. (2019). Fuels properties, characterizations, and engine and emission performance analyses of ternary waste cooking oil biodiesel–diesel–propanol blends. *Sustainable Energy Technologies and Assessments*, 35, 321-334.
- [44] Karthik, A. V., Naik, S., Ganesh, Dhanwish, & Raj, P. (2018). Extraction of Biodiesel from Chicken Waste and Performance of Biodiesel in I.C Engine. *International Journal of Advances in Science Engineering and Technology*, 6(2), 56-62.
- [45] Keskin, A., Gürü, M., Altıparmak, D., & Aydın, K. (2008). Using of cotton oil biodiesel–diesel fuel blends as alternative diesel fuel. *Renewable Energy*, 33(3), 553-557.
- [46] Kinnal, N., Sujaykumar, G., D’costa, S. W., & Girishkumar, G. S. (2018). Investigation on Performance of Diesel Engine by Using Waste Chicken Fat Biodiesel. *IOP Conference Series: Materials Science and Engineering*, 376, 012012.
- [47] Kirubakaran, M., & Selvan, V. A. M. (2018). A comprehensive review of low cost biodiesel production from waste chicken fat. *Renewable and Sustainable Energy Reviews*, 82, 390-401.
- [48] Kondamudi, N., Strull, J., Misra, M., & Mohapatra, S. K. (2009). A green process of producing biodiesel from feather meal. *Journal of Agricultural and Food Chemistry*, 57(14), 6163-6166.
- [49] Liu, S., Wang, Y., Oh, J. H., & Herring, J. L. (2011). Fast biodiesel production from beef tallow with radio frequency heating. *Renewable Energy*, 36(3), 1003-1007.
- [50] Ma, F., & Hanna, M. A. (1999). Biodiesel production: a review. *Bioresource Technology*, 70(1), 1-15.
- [51] Marulanda, V. F., Anitescu, G., & Tavlarides, L. L. (2010). Investigations on supercritical transesterification of chicken fat for biodiesel production from low-cost lipid feed stocks. *The Journal of Supercritical Fluids*, 54(1), 53-60.
- [52] Mata, T. M., Cardoso, N., Ornelas, M., Neves, S., & Caetano, N. S. (2011). Evaluation of two purification methods of biodiesel from beef tallow, pork lard and chicken fat. *Energy & Fuels*, 25(10), 4756-4762.
- [53] Mattingly, B. G. (2006). *Production of biodiesel from chicken fat containing free fatty acids* (Master of Science Thesis). University of Arkansas.
- [54] McCarthy, P., Rasul, M. G., & Moazzem, S. (2011). Analysis and comparison of performance and emissions of an internal combustion engine fuelled with petroleum diesel and different biodiesels. *Fuel*, 90(6), 2147-2157.
- [55] Mehmet, S. (2019). The effect of the injection pressure on a single cylinder diesel engine fueled with propanol–diesel blend. *Fuel*, 254, 115617.
- [56] Méndez-Lagunas, L. L., Siles-Alvarado, S., Rodríguez-Ramírez, J., & Aquino-González, L. A. (2015). Fatty acid profile composition of chicken skin. *International Journal of Chemical and Biomolecular Science*, 1(3), 193-196.
- [57] Mofijur, M., Rasul, M. G., Hyde, J., Azad, A. K., Mamat, R., & Bhuiya, M. M. K. (2016). Role of biofuel and their binary (diesel-biodiesel) and ternary (ethanol-biodiesel-diesel) blends on internal combustion engines emission reduction. *Renewable and Sustainable Energy Reviews*, 53, 265-278.
- [58] Mohan, S., & Pal, A. (2013). Economic Analysis of Biodiesel Produced from waste cooking oil. *Indian Journal of Research*, 3(4), 125-127.
- [59] Mohiddin, M. N., Saleh, A. A., Reddy, A. N. R., & Hamdan, S. (2018). A Study on Chicken Fat as an Alternative Feedstock: Biodiesel Production, Fuel Characterisation, and Diesel Engine Performance Analysis. *International Journal of Automotive and Mechanical Engineering*, 15(3), 5535-5546.
- [60] Moser, B. R. (2009). Biodiesel production, properties and feedstocks. *In Vitro Cellular & Developmental Biology-Plant*, 45(3), 229-266.
- [61] Mutreja, V., Singh, S., & Ali, A. (2011). Biodiesel from mutton fat using KOH impregnated MgO as heterogeneous catalysts. *Renewable Energy*, 36(8), 2253-2258.
- [62] Narayanan, T., Damotharan, R., Pandian, B., & Elumalai, R. (2025). Enhancing the production of waste chicken fat biodiesel with ethanol

- improved engine properties. *Environmental Science and Pollution Research*, 32, 31718-31724.
- [63] Nelson, R. G., & Schrock, M. D. (2006). Energetic and economic feasibility associated with the production, processing and conversion of beef tallow to a substitute diesel fuel. *Biomass and Bioenergy*, 30(6), 584-591.
- [64] Papadopoulos, C. E., Lazaridou, A., Koutsoumba, A., Kokkinos, N., Christoforidis, A., & Nikolaou, N. (2010). Optimization of cotton seed biodiesel quality (critical properties) through modification of its FAME composition by highly selective homogeneous hydrogenation. *Bioresource Technology*, 101(6), 1812-1819.
- [65] Piker, A., Tabah, B., Perkash, N., & Gedanken, A. (2016). A green and low-cost room temperature biodiesel production method from waste oil using egg shells as catalyst. *Fuel*, 182, 34-41.
- [66] Rahman, M., Rasul, M., & Hassan, N. (2017). Study on the Tribological Characteristics of Australian Native First Generation and Second Generation Biodiesel Fuel. *Energies*, 10(1), 55.
- [67] Rahman, M. A. (2018). Valorization of harmful algae *E. compressa* for biodiesel production in presence of chicken waste derived catalyst. *Renewable Energy*, 129, 132-140.
- [68] Rakopoulos, C. D., Antonopoulos, K. A., Rakopoulos, D. C., Hountalas, D. T., & Giakoumis, E. G. (2006). Comparative performance and emissions study of a direct injection diesel engine using blends of diesel fuel with vegetable oils or bio-diesels of various origins. *Energy Conversion and Management*, 47(18-19), 3272-3287.
- [69] Rao, K. S., & Ramakrishna, A. (2015). Cost Estimation Analysis of Biodiesel Production from Waste Chicken Fat. *International Journal of Applied Engineering Research*, 10(4), 8863-8870.
- [70] Reddy, A. N. R., Saleh, A. A., Islam, M. S., & Hamdan, S. (2017). Optimization of transesterification parameters for optimal biodiesel yield from crude jatropha oil using a newly synthesized seashell catalyst. *Journal of Engineering Science and Technology*, 12, 2723-2732.
- [71] Rehan, M., Gardy, J., Demirbas, A., Rashid, U., Budzianowski, W. M., Pant, D., ... & Nizami, A. S. (2018). Waste to biodiesel: A preliminary assessment for Saudi Arabia. *Bioresource Technology*, 250, 17-25.
- [72] Saleh, A. A., Islam, M. S., Hamdan, S., & Maleque, M. A. (2016). Biodiesel Production from Crude Jatropha Oil using a Highly Active Heterogeneous Nanocatalyst by Optimizing Transesterification Reaction Parameters. *Energy & Fuels*, 30(4), 334-343.
- [73] Sanek, L., Pecha, J., Kolomaznik, K., & Barinova, M. (2015). Biodiesel production from tannery fleshings: feedstock pre-treatment and process modelling. *Fuel*, 148, 16-24.
- [74] Shafiee, S., & Topal, E. (2009). When will fossil fuel reserves be diminished? *Energy Policy*, 37(1), 181-189.
- [75] Shah, S. H., Raja, I. A., Rizwan, M., Rashid, N., Mahmood, Q., Shah, F. A., ... & Pervez, A. (2018). Potential of microalgal biodiesel production and its sustainability perspectives in Pakistan. *Renewable and Sustainable Energy Reviews*, 81, 76-92.
- [76] Sharma, Y. C., & Singh, B. (2009). Development of Biodiesel: Current Scenario. *Renewable and Sustainable Energy Reviews*, 13(6-7), 1646-1651.
- [77] Shay, E. G. (1993). Diesel fuel from vegetable oil: status and opportunities. *Biomass and Bioenergy*, 4(4), 227-242.
- [78] Shi, W., Li, J., He, B., Yan, F., Cui, Z., Wu, K., ... & Cheng, Y. (2013). Biodiesel production from waste chicken fat with low free fatty acids by an integrated catalytic process of composite membrane and sodium methoxide. *Bioresource Technology*, 139, 316-322.
- [79] Shobhana-Gnanaserkhar, Asikin-Mijan, N., AbdulKareem-Alsultan, G., Sivasangar-Seenivasagam, Izham, S. M., & Taufiq-Yap, Y. H. (2020). Biodiesel production via simultaneous esterification and transesterification of chicken fat oil by mesoporous sulfated Ce supported activated carbon. *Biomass and Bioenergy*, 141, 105714.
- [80] Shu, Q., Zhang, Q., Xu, G., Nawaz, Z., Wang, D., & Wang, J. (2009). Synthesis of biodiesel from cottonseed oil and methanol using a carbon-based solid acid catalyst. *Fuel Processing Technology*, 90(8), 1002-1008.

- [81] Soldi, R. A., Oliveira, A. R. S., Ramos, L. P., & Ce sar-Oliveira, M. A. (2009). Soybean oil and beef tallow alcoholysis by acid heterogeneous catalysis. *Applied Catalysis A: General*, 361(1-2), 42-48.
- [82] Taher, H., Al-Zuhair, S., Marzouqui, A. A., & Hashim, I. (2011). Extracted fat from lamb meat by supercritical CO₂ as feedstock for biodiesel Production. *Biochemical Engineering Journal*, 55(1), 23-31.
- [83] Teixeira, L. S. G., Couto, M. B., Souza, G. S., Filho, M. A., Assis, J. C. R., Guimaraes, P. R. B., ... & Rodrigues, M. R. A. (2010). Characterization of beef tallow biodiesel and their mixtures with soybean biodiesel and mineral diesel fuel. *Biomass and Bioenergy*, 34(3), 438-441.
- [84] Theam, K. L., Islam, A., Lee, H. V., & Taufiq-Yap, Y. H. (2015). Sucrose-derived catalytic biodiesel synthesis from low cost palm fatty acid distillate. *Process Safety and Environmental Protection*, 95, 126-135.
- [85] Tiwari, A. K., Kumar, A., & Raheman, H. (2007). Biodiesel production from jatropha oil (Jatropha curcas) with high free fatty acids: an optimized process. *Biomass and Bioenergy*, 31(8), 569-575.
- [86] Yahyae, B., Ghobadian, B., & Najafi, G. (2013). Waste fish oil biodiesel as a source of renewable fuel in Iran. *Renewable and Sustainable Energy Reviews*, 17, 312-319.
- [87] Xue, J., Grift, T. E., & Hansen, A. C. (2011). Effect of biodiesel on engine performances and emissions. *Renewable and Sustainable Energy Reviews*, 15(2), 1098-1116.
- [88] Zhang, Y., Wong, W. T., & Yung, K. F. (2013). One-step production of biodiesel from rice bran oil catalyzed by chlorosulfonic acid modified zirconia via simultaneous esterification and transesterification. *Bioresource Technology*, 147, 59-64.