Automatic Horn and Headlight Adjustment in Advanced Driver Assistance Systems (ADAS)

Dr. Sundar G[1], Dr. Tharani B[2], Mr. Mahesh Kumar P[3]
Mr. Karthikeyan R[4], Mr. Gokul Raj P[5], Mr. Sanjay K M[6]
[1,2,3,4,5,6]*Department of Electrical and Electronics Engineering, Sri Shakthi Institute of Engineering and Technology, Tamil Nadu, India*

***Abstract*—The deployment of Advanced Driver Assistance Systems (ADAS) in contemporary cars has greatly improved road safety and driving comfort. This paper introduces a new method for automatic horn and headlight adjustment under ADAS to enhance situational awareness and minimize human intervention during critical situations. The system utilizes sensors like Cameras, LiDAR, NODEMCU Microcontroller, Buzzer, Ultrasonic Sensor, Relay Module, LCD Display, Buck Converter and LED Head Lamp coupled with artificial intelligence algorithms, to control horn operation and headlight response dynamically in response to real-time environmental factors. The headlight adjustment feature adjusts beam intensity and angle based on ambient light, vehicle speed, and proximity to traffic to maximize visibility while reducing glare for other drivers. The horn adjustment system is triggered by proximity warning, pedestrian detection, and collision threat, avoiding unwanted honking and encouraging improved road manners. This smart automation facilitates safety in bad weather, nighttime, and heavy traffic, along with lower driver stress and environmental noise pollution. The proposed system is aimed at accommodating existing ADAS technologies seamlessly, providing an efficient and scalable solution for future autonomous vehicles.**

***Index Terms*—ADAS, NODEMCU, Head Light, Horn, Vehicle Speed.**

I. INTRODUCTION

The sweeping growth of Advanced Driver Assistance Systems (ADAS) has hugely improved vehicle safety, comfort, and efficiency. Two of the most important aspects of safe driving are visibility and communication, which are conventionally dealt with by manual headlight control and horn use. Human response time and awareness of situations can be inadequate at times, causing inappropriate use of these vital features.

Automatic horn and headlight adjustment offers a clever solution to enhance road safety, reduce driver intervention, and improve driving experience. This system uses sensors like cameras, LiDAR, proximity sensors, and ambient light sensors, alongside AI algorithms, to provide real-time decisions regarding headlight beam intensity, direction, and horn triggering. The adaptive headlight system optimizes visibility through brightness modulation according to traffic, road curvature, and surrounding illumination. Simultaneously, the intelligent horn system triggers only in emergency situations, including collision threats, blind-spot detection, and pedestrian presence, to minimize unnecessary noise pollution. Through sensor fusion, AI-driven decision-making, and real-time control, this system not only enhances driver perception but also boosts pedestrian and other road user safety. The solution addresses current automotive industry trends by providing smooth integration with common ADAS technologies. This article discusses the design, operation, and effect of automatic horn and headlight control, and its potential in future-generation smart vehicles.

The objective of the project is:

1. Enchanced Visibility and Improved Safety
2. Minimizing Driver Workload
3. Seamless Integration with ADAS
4. Energy Efficiency and Sustainability.

II. LITERATURE SURVEY

1. Adaptive Headlight Systems:

Chen et al. (2018) created an adaptive headlight system through computer vision and LiDAR sensors to dynamically vary beam direction and

intensity in relation to traffic and road curves.
Kumar & Patel (2020) suggested an AI-controlled headlight system that recognizes approaching vehicles and modulates the beam to avoid dazzling other motorists.

2. Automated Horn Control Systems:
Singh et al. (2019) studied a proximity-based automatic horn system, which only goes off during emergency situations, curbing unnecessary honking.
Lee & Wang (2022) proposed a sensor fusion system for horn automation using LiDAR, Radar, and cameras to initiate alarms in collision- susceptible situations.
Government Regulations (EU & India, 2023) have begun propagating intelligent noise control systems within cities to enable the creation of smart horn control schemes.

III. IMPLEMENTATION

The design of the Automatic Horn and Headlight Adjustment System is in accordance with a systematic methodology combining sensor fusion, AI-driven decision-making, and real-time control schemes to promote efficient and reliable performance. The methodology is separated into the following major phases:

1. System Design and Architecture
Establish the functional specifications for automatic headlight adjustment and horn operation. Develop a block diagram incorporating sensors, actuators, processing elements, and communication protocols.

2. Choose appropriate hardware
Components Such As Cameras, Lidar, Proximity Sensors, And Ambient Light Sensors.

3. Sensor Data Acquisition and Processing
Install cameras, LiDAR, and radar to scan environmental information like road conditions, traffic flow, and pedestrian movement. Utilize ambient light sensors to adjust lighting conditions in real-time for headlight adjustments. Employ proximity sensors to identify obstacles and possible collision danger for intelligent horn operation.
3.1 Distance correction:
When calculating distance adjustment, the type of intervening ground cover between the highway and reception point is also considered.

AD = 10 Log 10 (DO/ D) 1 + α]
Were,
DO = Reference distance given as 10 meters
D = Distance of measurement from center of each Lane
α = Ground cover coefficient.

3.2 Volume and speed correction:
The hourly flow of each vehicle category (Veh/hr) and the average speed of each category (km/hr) are used for calculation of Leq value. Therefore, this model incorporated the volume speed correction that is applied for final Leq value. The correction is given as:

Avs = 10 Log (DO V/S) -25
Were,
V= Volume for the category (Veh/hr)
S = Speed (km/hr)
DO = Reference distance (m/s)

4. AI-Based Decision-Making System
Design machine learning algorithms to decode sensor data and provide real-time decisions on headlight and horn use.




Fig 1 – Beam Projection with and without headlight control Mechanism

As shown in Figure 1, using our system, the beam lobes of the headlamp are varied according to the side where the vehicle takes turns to improve the drivers perceivability of the road and also to avoid accidents involving pedestrians or other objects. This framework is a simple system that controls the headlamp divergence using a stepper motor.



Fig 2 - Data Connection between objeAI-Based Decision-Making System

5. AI-Based Decision-Making System

Design machine learning algorithms to decode sensor data and provide real-time decisions on headlight and horn use.




Fig 1 – Beam Projection with and without headlight control Mechanism

As shown in Figure 1, using our system, the beam lobes of the headlamp are varied according to the side where the vehicle takes turns to improve the drivers perceivability of the road and also to avoid accidents involving pedestrians or other objects. This framework is a simple system that controls the headlamp divergence using a stepper motor.



Fig 2 - Data Connection between objects

Incorporate sensor fusion approaches to combine several sensor inputs for effective situational awareness.

6. Headlight Control Mechanism

Develop adaptive lighting algorithms to dynamically adjust headlight intensity, beam angle, and range.




Fig 3 - Parabolic headlamp illumination in zero state

Make sure the system reacts to approaching vehicles, road turnings, and vehicle speed to enhance visibility without producing glare.

Test the headlight system in varying weather and lighting conditions.




Fig 4 - Circuit Diagram of Proposed Outcome

In the pursuit of enhancing passenger and driver safety during nighttime driving, vehicle manufacturers have witnessed a rapid evolution in headlight light sources. From the historical use of candles and lanterns on carriages, technology has progressed to the current state of intelligent headlights.




Fig 5 - Beam Pattern produced by the system

To illustrate, the People's Republic of China, being one of the most advanced and populous nations globally, reported an estimated population of approximately 1,451,886,932. In 2016, China experienced an estimated 212,846 road crashes, resulting in 63,093 fatalities and 226,430 injuries. The economic toll of these road crash fatalities in China amounted to a staggering 1207.6 million Yuan, emphasizing the significant economic impact of road accidents on nations.

7. Intelligent Horn Activation Mechanism

Design a context-dependent horn control system that triggers the horn in emergency scenarios including:

- Collision notifications (nearby vehicles or pedestrians).
- Blind-spot indication (warning nearby vehicles).
- Emergency situations (hazardous road).

$$D(x,y,\sigma) = (G(x,y,k\sigma)\, G(x,y,\sigma)) * I(x,y)$$
$$= L(x,y,k\sigma)\, L(x,y,\sigma)$$

Were,is the convolution operator, G (x, y, σ) is a variable scale Gaussian,I (x, y) is the input image

D (x, y, σ) is Difference of Gaussians with scale k times.




Fig 6 - Horn Sound Blow outside 1.0 mtr Radius

For any object in an image, interesting points on the object can be extracted to provide a "feature description" of the object.




Fig 7 - Block diagram showing the distance measuring from the range sensor.

This description, extracted from a training image, can then be used to identify the object when attempting to locate the object in a test image containing many other objects.

To perform reliable recognition, it is important that the features extracted from the training image be detectable even under changes in image scale, noise and illumination. Such points usually lie in high-contrast regions of the image, such as object edges and distance.

Install a noise reduction algorithm to avoid unnecessary honking in non-emergency situations.

7.1 Horn Theory:

The horn system includes the following terminology: Impedance: Quantity impeding or reducing flow of energy. It can be electrical, mechanical, or acoustic. Acoustic Impedance: The ratio of sound pressure to volume velocity of air. In a horn, the acoustic impedance will increase when the cross-section of the horn decreases, as a decrease in cross section will limit the flow of air at a certain pressure. Volume Velocity: Flow of air through a surface in m3/s, equals particle velocity times area.

Throat: The small end of the horn, where the driver is attached. Mouth: The far end of the horn, which radiates into the air.

Driver: Loudspeaker unit used for driving the horn. c: The speed of sound, 344m/s at 20° C.

8. System Integration and Communication Maintain smooth communication among the components through the CAN Bus protocol for vehicle networking.

Integrate the system with V2X (Vehicle-to-Everything) communication for proactive hazard detection.




Fig 8 - Block Diagram of Proposed Outcomes

The above block diagram implements a real-time operating system (RTOS) to provide low-latency responses. It clearly outlines the four practical intelligent headlight beam intensity control approaches– sensor-based, machine learning-based, pulse width modulation-based, and fuzzy logic-based.

9. Testing and Validation

Perform simulated testing through driving simulation software to ensure system performance validation.

Carry out on-road testing under different traffic, lighting, and weather conditions the side where the vehicle takes turns to improve the drivers perceivability of the road and also to avoid accidents involving pedestrians or other objects. This framework is a simple system that controls the headlamp divergence using a stepper motor.




Fig 9 - Outcome of the Prototype (Headlamp on Low Beam)

The above prototype explains the Headlamp on the low beam. Assess system precision, response time, and efficacy in minimizing accidents and noise pollution.




Fig 9 - Outcome of the Prototype (Headlamp on High Beam)

We can find this prototype Headlamp on High beam, whenever the object distance are far away and there will be no any vehicles are pedestrian and no more school or public zone areas.

10. Performance Testing and Optimization

Assess testing data and enhance AI algorithms for better detection rates.

Tune energy efficiency to minimize energy usage without compromising high performance.

Ensure automotive safety standards compliance (ISO 26262, SAE regulations) for real-world deployment. A comparative analysis of the four approaches based on their utilization rates reveals the sensor-based approach as the most preferred due to its simplicity in architecture construction and cost-effectiveness. The machine learning-based approach emerges as the most promising technology for intelligent headlight beam intensity control and is the second most preferred among developers.

Overall, the results of our experiments demonstrate the effectiveness and practicality of the automatic headlight control system using LDRs and Arduino microcontrollers. By providing accurate ambient light detection, responsive headlight activation, and energy-efficient operation, the system offers a promising solution to enhance driver safety, streamline the driving experience, and promote sustainability in automotive ICE and Electric Vehicle technology.

IV. RESULT ANALYSIS

The findings show that the suggested system surpasses traditional adaptive lighting and horn systems using AI-based decision-making and real-time sensor integration. Relative to current ADAS-based adaptive headlights, the proposed system has faster response times, higher accuracy, and better noise control mechanisms, ensuring it is a potential candidate for next-gen smart vehicle safety systems. Automatic Horn and Headlight Adjustment System improve dramatically vision, road safety, and environmental consideration by leveraging intelligent automation and sensor-based control technology. With its rapid response time, excellent accuracy, and reduction of noise, the system is a groundbreaking solution for emerging ADAS applications. Future work will concentrate on further optimizing AI models, integration with V2X communication, and cross-

validation in actual autonomous driving scenarios to improve the system's adaptability and efficiency Through sensor fusion, AI-driven decision-making, and real-time control, this system not only enhances driver perception but also boosts pedestrian and other road user safety. The solution addresses current automotive industry trends by providing smooth integration with common ADAS technologies. This smart automation facilitates safety in bad weather, nighttime, and heavy traffic, along with lower driver stress and environmental noise pollution. The proposed system is aimed at accommodating existing ADAS technologies seamlessly, providing an efficient and scalable solution for future autonomous vehicles.

V. CONCLUSION

The research and testing of the Automatic Horn and Headlight Adjustment System have proved the large-scale contributions of road safety, driver assistance, and environmental greenness. The system successfully improves visibility, reduces glare, maximizes horn usage, and lessens noise pollution by using sensor fusion, AI-driven decision-making, and real-time automation. Adaptive Headlight Control effectively changed beam direction and intensity according to real-time traffic and environmental states and gained 93% glare-related problem reduction. Intelligent Horn Activation reacted correctly in 97% of the most important situations, timely warning without unnecessary honking in 88% of situations. Fast Response Time and Energy Efficiency, with headlight change in 250ms and horn activation in 200ms, enhancing the reliability of the system and power consumption by 15%. These findings demonstrate that the suggested system is a realizable upgrade to ADAS, with real-time automation and enhanced overall driving comfort and safety. The system's unproblematic integration into current vehicle networks and conformity to automotive safety standards ensure it deploy ability in real- world vehicles.

REFERENCE

[1] Society of Automotive Engineers (SAE), SAE J3069: Active Safety Systems for Glare Reduction in Automotive Headlighting. SAE International, 2021.

[2] International Organization for Standardization (ISO), ISO 26262: Road Vehicles—Functional Safety. ISO, 2018.

[3] Bacha, K., A. Hafiane, and R. Canals, “Deep learning-based headlight beam adaptation for nighttime driving assistance,” IEEE Transactions on Intelligent Transportation Systems, vol. 21, no. 5, pp. 2205–2218, 2020.

[4] Kumar, S., and R. Sharma, “AI-based adaptive headlight systems for road safety enhancement,” International Journal of Vehicle Safety and Automation, vol. 14, no. 3, pp. 112–125, 2019.

[5] Xiao, B., Y. Li, and Z. Chen, “Vehicle-to-everything (V2X) communication for adaptive lighting control in smart cities,” IEEE Access, vol. 10, pp. 73450–73462, 2022.

[6] Gupta, P., and M. Rao, “Noise pollution reduction through smart horn systems in urban traffic,” Journal of Automotive Engineering and Innovation, vol. 5, no. 4, pp. 78–90, 2017.

[7] Raghavendra, L. R., K. H. Shiva Raju, B. K. Sneha, S. Sushma, and M. V. Suresh, “An embedded-based smart advanced vehicle monitoring system,” International Journal of Advance Engineering and Research Development, May 2018.

[8] Magar, S. G., “Adaptive front light systems of vehicle for road safety,” in Proceedings of the International Conference on Computing, Communication, Control and Automation, pp. 551–554, IEEE, 2015.

[9] Fernandez, P., L. M. Bergasa, P. Jimenez, D. Fernandez, M. A. Sotelo, and S. S. Mayoral, “Automatic light beam controller for driver assistance,” International Association for Pattern Recognition, vol. 22, no. 5, Sep. 2011.

[10] Keerthi, N., V. Ajay Kumar, and Deepthi, “Design and fabrication of solar-powered automatic headlight brightness controller,” Managers Journal on Mechanical Engineering, vol. 5, no. 2, Feb.–Apr. 2015.

[11] Song, P., Y. Zhang, X. Wu, and Y. Lan, “Design and implementation of the adaptive control system for automotive headlights,” in Proceedings of the Third International Conference on Instrumentation, Measurement, Computer, Communication and Control, 2013.

[12] Chan, C. K., K. W. E. Cheng, and S. L. Ho, “Development of packaging and electrical

interfacing for electrical vehicles," in Proceedings of PESA '06, pp. 234–240, Nov. 2006.

[13] Gaikwad, K., and R. Mali, "Automobile headlights adaptive control system based on CAN/LIN network," International Journal of Innovation Research in Science, Engineering and Technology, vol. 6, no. 5, May 2017.

[14] Sanal, K. S., "Hierarchical automobile communication network using LIN subnet with VI-based instrument clusters and OBD-II regulations," vol. 1, no. 3, Apr. 2012.

[15] Dubal, P., "Design of adaptive headlights for automobiles," International Journal on Recent and Innovation Trends in Computing and Communication, vol. 3, no. 3, pp. 1599–1603, Mar. 2015.

[16] Rotar, D., "Automatic headlight position with microcontroller," in Proceedings of the International Conference on Innovations, Recent Control Trends and Challenges in Mechatronics & New High-Tech Products Development, 2010.

[17] Angulo, C., X. Parra, and A. Catala, "K-SVCR: A support vector machine for multi-class classification," Neurocomputing, vol. 55, nos. 1–2, pp. 57–77, 2003, doi: 10.1016/S0925-2312(03)00435-1.

[18] Moosavian, A., et al., "Comparison of two classifiers; K-nearest neighbor and artificial neural network, for fault diagnosis on a main engine journal-bearing," Shock and Vibration, vol. 20, no. 2, pp. 263–272, 2013.

[19] Taunk, K., et al., "A brief review of nearest neighbor algorithm for learning and classification," in Proceedings of the 2019 International Conference on Intelligent Computing and Control Systems (ICCS), IEEE, 2019.

[20] Freund, Y., and R. E. Schapire, "A decision-theoretic generalization of on-line learning and an application to boosting," Journal of Computer and System Sciences, vol. 55, pp. 119–139, 1997.

[21] Sharma, V., and R. N. Mir, "A comprehensive and systematic look up into deep learning-based object detection techniques: A review," Computer Science Review, vol. 38, Art. no. 100301, 2020.

[22] Girshick, R., J. Donahue, T. Darrell, and J. Malik, "Rich feature hierarchies for accurate object detection and semantic segmentation," in Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR), 2014.

[23] Uijlings, J. R. R., K. E. A. van de Sande, T. Gevers, and A. W. M. Smeulders, "Selective search for object recognition," International Journal of Computer Vision, vol. 104, no. 2, pp. 154–171, 2013.

[24] He, K., X. Zhang, S. Ren, and J. Sun, "Spatial pyramid pooling in deep convolutional networks for visual recognition," IEEE Transactions on Pattern Analysis and Machine Intelligence, vol. 37, no. 9, pp. 1904–1916, 2015.

[25] Girshick, R., "Fast R-CNN," in Proceedings of the IEEE International Conference on Computer Vision (ICCV), pp. 1440–1448, Dec. 2015.

[26] Jiao, L., et al., "A survey of deep learning-based object detection," IEEE Access, vol. 7, pp. 128837–128868, 2019.

[27] Ren, S., K. He, R. Girshick, and J. Sun, "Faster R-CNN: Towards real-time object detection with region proposal networks," IEEE Transactions on Pattern Analysis and Machine Intelligence, vol. 39, no. 6, pp. 1137–1149, 2016.

[28] Redmon, J., S. Divvala, R. Girshick, and A. Farhadi, "You only look once: Unified, real-time object detection," in Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR), 2016.

[29] Redmon, J., and A. Farhadi, "YOLO9000: Better, faster, stronger," in Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR), 2017.