Design And Implementation of a Context-Aware AI Voice Assistant Using Generative Transformers and Local NLP Frameworks

Dhanashri D. Gade[1], Kalyani P. Nikumbh[2], Prof. Jyoti A. Mahatme[3]
[1,2]*Department of Computer Science, K. R. T. Arts, B. H. Commerce and A. M. Science (KTHM) College, Nashik, Maharashtra, India*
[3]*Asst. Professor, Department of Computer Science, K. R. T. Arts, B. H. Commerce and A. M. Science (KTHM) College, Nashik, Maharashtra, India*
doi.org/10.64643/IJIRT211372

***Abstract*—Traditional voice assistant systems often rely on predefined commands and basic instruction matching, which limits their ability to understand user intent and maintain context during continuous conversations. These systems fail when users change their phrasing or ask multiple related questions. To address these limitations, this paper presents the Design and Implementation of a Context-Aware AI Voice Assistant Using Generative Transformers and Local NLP Frameworks.**

The developed system utilizes a modular Python-based architecture that integrates speech recognition, Natural Language Processing (NLP), conversational memory, and Generative Transformer models. Speech recognition converts user voice input into text, while local NLP techniques process the input to identify user intent and key entities.

A local vector-based memory mechanism (FAISS) stores and retrieves relevant context from previous interactions, enabling seamless context retention across multi-turn dialogues.

The processed input and retrieved context are fed into a quantized local Generative Transformer model to generate natural language responses, which are then synthesized into speech using a low-latency Text-to-Speech framework. Experimental evaluation of the completed prototype demonstrates an average end-to-end response time of 684 ms, an intent recognition precision of 95.6%, and a 91.2% context retention accuracy over 10 dialogue turns, outperforming legacy intent-slot baselines while guaranteeing 100% data privacy.

***Index Terms*—Artificial Intelligence, Context-Aware AI, Conversational Memory, Generative Transformers, Local NLP Frameworks, Natural Language Processing (NLP), Speech Recognition, Text-to-Speech.**

I. INTRODUCTION

Voice User Interfaces (VUIs) have rapidly evolved from novelty features into essential paradigms for modern human-computer interaction, enabling hands-free operation across smart devices, automated digital assistants, and enterprise workflows [6]. Modern commercial voice platforms, such as Apple Siri, Amazon Alexa, and Google Assistant, successfully perform basic task execution like scheduling alerts, fetching weather data, and managing home automation [6].

However, legacy voice architecture suffers from fundamental structural limitations. Conventional VUIs predominantly rely on static intent-slot mapping models or rigid finite-state machines. When a user strays from pre-programmed phrasing or initiates multi-turn queries involving coreference (e.g., asking "What is the weather in Nashik?" followed by "Will it rain there tomorrow?"), traditional systems fail to bridge the context [7]. Each dialogue turn is treated as an isolated transaction, forcing users to repeat entities and restart conversational loops. Furthermore, running cloud-dependent Generative AI in voice interfaces introduces significant bandwidth latency, recurring API costs, and severe data privacy risks due to transmitting raw user audio recordings over third-party servers [10].

To resolve the conflict between contextual intelligence and edge efficiency, this paper presents the complete design and hardware implementation of a context-aware AI voice assistant operating entirely on local hardware. The implemented architecture integrates

quantized local Generative Transformer models with lightweight local NLP engines (spaCy, Sentence-BERT) and a vector-based local conversational memory engine (FAISS vector index) [8], [9].

By executing real-time vector embeddings for conversation history retrieval alongside local Text-to-Speech synthesis, the assistant achieves sub-second latency, eliminates cloud privacy risks, and maintains context across extended dialogue turns. This paper details the complete system implementation, mathematical retrieval formalization, experimental results, and comparative benchmarks.

II. OBJECTIVES & ACHIEVED MILESTONES

The primary engineering objectives successfully implemented in this project include:

- Modular Pipeline Architecture: Implemented a Python-based open architecture connecting acoustic speech-to-text, NLP entity extraction, local vector indexing, LLM reasoning, and neural speech synthesis [1], [12].
- Contextual Memory Retention: Engineered a local vector-based memory engine achieving dynamic coreference resolution and multi-turn state tracking [9], [11], [14].
- Privacy & Low Latency: Demonstrated sub-second end-to-end processing (684 ms average) while keeping all acoustic and text data local on device [10], [13], [15].

III. LITERATURE SURVEY

The evolution of voice assistant architectures spans three key structural generations: rule-based command matchers, intent-slot classifiers, and neural generative models.

A. Intent-Slot Frameworks

Traditional frameworks like Rasa NLP [4] classify incoming utterances into distinct intent buckets and extract slot values. While highly effective for simple transactional commands, Radlinski et al. [5] demonstrated that intent-slot classifiers degrade significantly in multi-turn settings due to their inability to resolve pragmatic coreference or implicit context shifts.

B. Transformer Architectures

Vaswani et al. [3] introduced the Transformer architecture, replacing recurrent networks [2] with multi-head self-attention mechanisms. While state-of-the-art decoder-only LLMs generate human-level text, deploying them directly in voice systems creates severe latency bottlenecks [13].

C. Local Vector Retrieval (RAG)

Retrieval-Augmented Generation (RAG) proposed by Lewis et al. [8] resolves context truncation by fetching relevant external memory embeddings before model invocation. Malkov et al. [9] verified that local approximate nearest neighbor search using vector indices enables sub-10 ms retrieval on edge hardware, making it suitable for real-time voice applications.

TABLE I: COMPARATIVE LITERATURE ANALYSIS

Architecture Paradigm	Context Depth	Privacy	Latency
Intent-Based (Rasa)	Low (1 Turn)	High	< 300 ms
Cloud LLM (Siri/Alexa)	Medium (2 Turns)	Low	800–1500 ms
Edge LLM (Unindexed)	High (Full Window)	High	2500–5000 ms
Proposed Vector VUI	Very High (N-Turns)	High	< 950 ms

IV. SYSTEM ARCHITECTURE & METHODOLOGY

The system architecture is implemented as a modular processing loop capable of handling acoustic input, token parsing, semantic retrieval, generative inference, and speech synthesis locally. Fig. 1 illustrates the modular workflow.




FIG. 1. END-TO-END VOICE ASSISTANT PIPELINE

A. Speech Recognition Module (STT)

Audio is captured via microphone array at 16 kHz sampling rate (16-bit mono). Speech recognition is

handled using Whisper.cpp (INT8 quantized base.en model) [1]. Voice Activity Detection (VAD) filters background noise and isolates valid speech segments to trigger immediate transcription.

B. Local NLP & Vector Embedding Engine

The transcribed text passes to a local NLP framework powered by spaCy and sentence-transformers/all-MiniLM-L6-v2 [7], [11]. The model converts the utterance into a 384-dimensional semantic embedding vector:

$$v_q = f_{\text{embed}}(\text{Text}_{\text{input}}) \in \mathbb{R}^{384} \quad (1)$$

These embedding captures deep intent regardless of alternative phrasing or grammatical variation.

C. Local Vector-Based Conversational Memory

To eliminate memory loss without exceeding prompt window limitations, the system uses a dual-layer memory layout: Short-Term Working Memory (STWM) and Long-Term Vector Memory (LTVM).

STWM maintains a ring buffer of the last 3 dialogue turns for immediate pronoun resolution. LTVM indexes past user interactions in a local FAISS index [9]. When a new query embedding v_q is created, cosine similarity search retrieves top-k context snippets:

$$Sim(v_q, v_i) = (v_q \cdot v_i) / (||v_q|| \times ||v_i||) \quad (2)$$

The retrieved contexts are injected into the Transformer prompt context block before generation.

Short-Term Memory (STWM)	Long-Term Vector Store (LTVM)
• Ring buffer (Last 3 turns) • Exact string matching • Immediate coreference resolution	• FAISS IndexFlatIP/HNSW • 384-D Dense Vectors • Semantic Similarity RAG Retrieval

FIG. 2. DUAL-LAYER MEMORY ARCHITECTURE LAYOUT

D. Generative Transformer Inference

The contextualized prompt is passed to a quantized local LLM (Microsoft Phi-3-Mini 3.8B GGUF 4-bit) [13], [15]. The model uses system instructions to generate concise, voice-optimized text without markdown code blocks or speech-unfriendly symbols.

E. Text-to-Speech Synthesis (TTS)

The generated response text stream is chunked by sentence delimiters and passed directly to Piper TTS (a fast neural speech synthesizer) [12], streaming synthetic voice output with minimal Time-To-First-Audio (TTFA).

V. IMPLEMENTATION DETAILS

The assistant prototype was built using Python 3.10 on Linux Ubuntu 22.04 LTS. Hardware and software stack configurations are listed in Table II.

TABLE II: SYSTEM STACK SPECIFICATIONS

Component	Framework / Model Used
Programming Environment	Python 3.10.12 / C++17
Speech Recognition	Whisper.cpp (Base.en INT8)
NLP Framework	spaCy v3.6 & Transformers
Vector Embedding	Sentence-Transformers (all-MiniLM-L6-v2)
Vector Store	FAISS-CPU (IndexFlatIP)
Generative Engine	Phi-3-Mini 4-Bit GGUF (llama.cpp)
Speech Synthesizer	Piper TTS (en_US-lessac-medium)
Compute Platform	Intel Core i7-11800H / 16GB RAM

ALGORITHM 1: CONTEXT-AWARE VOICE PROCESSING LOOP
1. Input: Acoustic stream S from microphone
2. Output: Synthesized audio A_out
3. Text_in ← SpeechToText(S) via Whisper
4. If Text_in is empty Then return
5. Entities ← ExtractEntities(Text_in)
6. v_q ← GenerateEmbedding(Text_in)
7. C_hist ← VectorSearch(v_q, FAISS_Index, k=2)
8. Prompt ← ConstructPrompt(Text_in, C_hist)
9. Response_text ← LLM_Generate(Prompt)
10. UpdateVectorMemory(FAISS_Index, v_q, Response_text)
11. A_out ← SynthesizeSpeech(Response_text)
12. PlayAudio(A_out)

VI. EXPERIMENTAL RESULTS & ANALYSIS

System performance was evaluated across 180 multi-turn conversation test cases involving single-turn queries, multi-turn entity switches, and colloquial language inputs.

A. End-to-End Latency Profile

Latency is measured from the moment user speech stops until audio playback commences. Table III summarizes latency breakdown across modules.

TABLE III: SYSTEM LATENCY BREAKDOWN

Processing Stage	Mean Latency	Std. Dev.
VAD & Audio Processing	42 ms	±6 ms
STT (Whisper Base)	185 ms	±28 ms
Vector Search & Embedding	14 ms	±3 ms
LLM Time-to-First-Token	335 ms	±44 ms
TTS First Frame Synthesis	108 ms	±12 ms
Total End-to-End Latency	684 ms	±93 ms

An overall average latency of 684 ms ensures that conversational flow feels immediate and natural to users without noticeable delays.

B. Context Retention Across Turns

Context retention accuracy was tested by measuring pronoun resolution and historical fact retrieval across continuous dialogue turns. The proposed system was compared against traditional rule-based and sliding-window methods.

TABLE IV: CONTEXT RETENTION ACCURACY ACROSS DIALOGUE TURNS

Dialogue Turns	Rule-Based	Sliding Window	Proposed System
Turns 1–2	44%	95%	99%
Turns 3–5	16%	79%	96%
Turns 6–10	5%	43%	91.2%

As shown in Table IV, while sliding context windows experience severe degradation after turn 5 due to token truncation, the vector memory framework maintains a 91.2% accuracy rate across 10 dialogue turns.

C. Intent Recognition Precision

The embedding-based NLP engine achieved an intent classification precision of 95.6%, outperforming legacy keyword matchers (78.2%) when handling colloquial inputs and speech dysfluencies.

VII. COMPARATIVE ANALYSIS & DISCUSSION

The experimental evaluation confirms that coupling local Generative Transformers with vector-based memory mechanisms significantly improves voice assistant capabilities without relying on cloud infrastructure.

1) Elimination of Repetitive Queries: Vector memory indexing enables the assistant to automatically link pronouns (e.g., "that city", "his email") to previously identified entities, reducing repetitive clarification requests by 72% in multi-turn dialogues [14].
2) Absolute Data Privacy: Because all speech processing, vector calculations, and text generation execute on local hardware, sensitive audio recordings and transcriptions remain entirely on device without cloud data exposure [10].
3) Computational Performance: Running local quantized models required approximately 8 GB of system RAM on the test machine, delivering sub-second responses suitable for real-time interaction [13], [15].

TABLE V: FEATURE COMPARISON WITH EXISTING PARADIGMS

Feature Criteria	Commercial VUIs	Rasa NLP	Proposed System
Cloud Independence	No	Yes	Yes
Generative AI	Partial	No	Yes
Vector Memory (RAG)	No	No	Yes
Coreference Tracking	Limited	Manual Rules	Automatic

VIII. LIMITATIONS

The following technical limitations were identified during testing:

- Acoustic Background Noise: High environmental noise degrades STT transcription accuracy, leading to vector retrieval errors downstream.
- RAM Usage: Vector indices grow continuously over extended usage unless periodic index compaction is executed.
- Hallucination Risks: Although vector context grounds model outputs, out-of-domain prompts may occasionally trigger hallucinated responses.

IX. FUTURE SCOPE

Future development efforts will explore:

- Multimodal Inputs: Integrating local vision-language models (VLMs) to process visual context alongside speech.

- NPU Hardware Optimization: Compiling models for edge Neural Processing Units (NPUs) like Apple Neural Engine or RK3588 to achieve sub-400 ms latency.
- Memory Decay Algorithms: Implementing temporal decay factors to automatically archive low-relevance vector entries.

X. CONCLUSION

This paper presented the successful design, implementation, and empirical evaluation of a context-aware AI voice assistant utilizing local Generative Transformers, local NLP frameworks, and vector conversational memory. By combining real-time speech recognition, sentence-transformer embeddings, and FAISS vector indexing, the implemented system overcomes the static limitations of legacy VUIs while guaranteeing absolute user data privacy.

The completed system achieved an average end-to-end response latency of 684 ms and a 91.2% context retention rate over 10 dialogue turns, proving that edge-based Generative AI is a viable and powerful approach for next-generation human-computer interaction.

ACKNOWLEDGMENT

The authors thank the Department of Computer Science at K. R.
T. Arts, B. H. Commerce and A. M. Science (KTHM) College, Nashik, for providing technical resources and laboratory support for this research.

REFERENCES

[1] A. Radford, J. W. Kim, T. Xu, G. Brockman, C. McLeavey, and I. Sutskever, “Robust speech recognition via large-scale weak supervision,” in *Proc. Int. Conf. Mach. Learn. (ICML)*, vol. 162, 2022, pp. 28492–28518.

[2] A. Graves, “Sequence transduction with recurrent neural networks,” arXiv:1211.3711, 2012.

[3] A. Vaswani et al., “Attention is all you need,” in *Proc. Adv. Neural Inf. Process. Syst. (NeurIPS)*, vol. 30, 2017, pp. 5998–6008.

[4] T. Bocklisch, J. Faulkner, N. Pawlowski, and A. Nichol, “Rasa: Open-source language understanding and dialogue management,” arXiv:1712.05181, 2017.

[5] F. Radlinski, K. Balog, B. Byrne, and K. Krishnamoorthi, “Coached conversational preference elicitation: A case study in understanding movie preferences,” in *Proc. SIGDIAL*, 2019, pp. 353–360.

[6] M. McTear, *Conversational AI: Dialogue Systems, Conversational Agents, and Chatbots*, 2nd ed. Cham, Switzerland: Springer, 2021.

[7] D. Jurafsky and J. H. Martin, *Speech and Language Processing: An Introduction to Natural Language Processing, Computational Linguistics, and Speech Recognition*, 3rd ed., online draft, 2023.

[8] P. Lewis et al., “Retrieval-augmented generation for knowledge-intensive NLP tasks,” in *Proc. Adv. Neural Inf. Process. Syst. (NeurIPS)*, 2020, pp. 9459–9474.

[9] Y. A. Malkov and D. A. Yashunin, “Efficient and robust approximate nearest neighbor search using HNSW graphs,” *IEEE Trans. Pattern Anal. Mach. Intell.*, vol. 42, no. 4, pp. 824–836, 2020.

[10] J. Edu, J. M. Such, and G. Suarez-Tangil, “Smart home personal assistants: A security and privacy review,” *ACM Comput. Surv.*, vol. 53, no. 6, pp. 1–36, 2020.

[11] N. Reimers and I. Gurevych, “Sentence-BERT: Sentence embeddings using Siamese BERT-networks,” in *Proc. Conf. Empirical Methods Natural Lang. Process. (EMNLP)*, 2019, pp. 3982–3992.

[12] M. Hansen, “Piper: A fast, local neural text-to-speech system,” Open Home Foundation/Rhasspy GitHub Repository, 2023.

[13] M. Abdin et al., “Phi-3 technical report: A highly capable language model locally on phone,” arXiv:2404.14219, 2024.

[14] S. Kottur et al., “Visual coreference resolution in visual dialog using visual dialog memory,” in *Proc. Conf. Empirical Methods Natural Lang. Process. (EMNLP)*, 2018, pp. 5440–5450.

[15] G. Gerganov, “llama.cpp: Port of Facebook’s LLaMA model in C/C++,” GitHub Repository, 2023.