A Secured Crypto-Hybrid Framework for Privacy-Preserving Big Data Mining

Pasupuleti Nagendra Babu[1], S. Ramakrishna[2]
[1]*Research Scholar, Department of Computer Science, Rayalaseema University, Kurnool, India.*
[2]*Professor, Department of Computer Science, S. V. University, Tirupati, India.*

***Abstract*—The exponential growth of Big Data characterized by Volume, Velocity, Variety, Value, and Veracity presents significant challenges for traditional data mining and security architectures. While extracting hidden patterns through clustering and classification yields substantial business intelligence, sharing and mining large-scale datasets expose sensitive individual records to privacy breaches. Existing Privacy-Preserving Data Mining (PPDM) techniques, such as standalone anonymization, perturbation, or cryptography, often suffer from high information loss or computational overhead. To address this trade-off, this paper proposes a Secured Crypto-Hybrid Algorithm (SCHA) that integrates K-means clustering and Local Outlier Factor (LOF) detection with AES-256 encryption. Furthermore, we examine privacy preservation in distributed social network content and Software-Defined Networking (SDN) environments. [PLACEHOLDER: Insert 2–3 sentences summarizing your exact experimental accuracy, execution time improvements, and privacy metrics from Chapters 3 & 4.]**

***Index Terms*—Big Data Analytics, Privacy-Preserving Data Mining (PPDM), Secured Crypto-Hybrid Algorithm (SCHA), K-Means Clustering, AES-256, Software-Defined Networking (SDN).**

I. INTRODUCTION

The rapid advancement of Information Technology (IT), web applications, and social networking platforms has triggered an unprecedented explosion in data generation. Organizations rely on Big Data Analytics (BDA) to extract actionable insights, optimize operations, and improve customer retention. Big Data is defined across five core dimensions (5Vs): Volume (scale reaching exabytes/zettabytes), Velocity (real-time streaming speed), Variety (structured, semi-structured, and unstructured formats), Value (actionable business utility), and Veracity (data quality and consistency).

However, mining massive, heterogeneous datasets raises critical social and technical concerns regarding individual privacy and data integrity. Traditional data mining algorithms spanning classification (Decision Trees, Naïve Bayes, SVM, KNN, ANN), clustering (Hierarchical, Partitioning), regression, and association rule mining can inadvertently expose sensitive personal attributes or confidential inference rules. Privacy-Preserving Data Mining (PPDM) addresses this by transforming raw data or hiding sensitive rules before or during analysis. Despite progress in centralized and distributed (horizontally and vertically partitioned) environments, achieving an optimal balance between high data utility and strict privacy remains a major hurdle.

The primary objectives of this research are:

- To analyze security vulnerabilities, data quality issues, and privacy threats in traditional and Big Data mining.
- To design a Secured Crypto-Hybrid Algorithm (SCHA) combining K-means clustering, local outlier detection, and AES-256 encryption.
- To evaluate privacy and proactive security enforcement across social network user-generated content and SDN-enabled networks.

II. LITERATURE SURVEY

Existing input PPDM methodologies are broadly categorized into four domains: Secure Multi-Party Computation (SMC), perturbation methods, non-perturbation (anonymization) methods, and hybrid approaches.

Perturbation and Condensation Methods: Liu et al. [171] introduced multiplicative perturbation using Random Projection (RP) based on the Johnson–Lindenstrauss Lemma to preserve pairwise distances. Meghanathan et al. [76] explored fuzzy logic-based perturbation to reduce processing overhead. Aggarwal and Yu [179] proposed a condensation approach that groups data into clusters of size \(k\) to generate synthetic pseudo-data for dynamic streams, though at the cost of information loss.

Anonymization and Differential Privacy: To prevent record linkage, models such as \(k\)-anonymity [145, 176] and \(l\)-diversity generalize and suppress quasi-identifiers. Li et al. [156] introduced \(t\)-closeness to maintain sensitive attribute distributions close to the overall table, mitigating skewness attacks. For streaming data, Mohammadian et al. [78] developed FAST using multithreaded \(k\)-anonymization, while Chamikara et al. [12] proposed SEALdou, a differential privacy framework optimizing the privacy-accuracy trade-off.

Cryptographic and Hybrid Techniques: Lindell and Pinkas [189] demonstrated cryptographic protocols for secure computation, though pure cryptography incurs heavy computational overhead on massive datasets. To overcome single-method limitations, hybrid techniques combine multiple strategies. Kaur et al. [27] and Deivanai et al. [131] merged selective suppression with additive noise perturbation to minimize information loss. Similarly, Lohiya and Ragha [122] combined randomization with generalization to protect sensitive rules while allowing accurate data reconstruction.

PPDM Approach	Core Mechanism	Key Advantage	Primary Limitation
Suppression/(k)-Anonymity	Generalizes or masks identifiers	Prevents direct identity linkage	Vulnerable to homogeneity/background attacks; information loss
Randomization/ Perturbation	Adds additive or multiplicative noise	Preserves aggregate statistical distributions	Individual record utility is lost; struggles with high noise
Cryptography (SMC)	Encrypts data across distributed parties	Strong mathematical security guarantees	High computational and communication overhead on Big Data
Hybrid Methods	Combines perturbation, anonymization, or encryption	Balances data utility and privacy protection	Increased architectural complexity

III.PROPOSED METHODOLOGY

To overcome the computational bottlenecks of pure cryptography and the utility degradation of standalone perturbation, we propose a dual-track methodology covering centralized/hybrid mining and distributed Big Data environments.

3.1 Secured Crypto-Hybrid Algorithm (SCHA)

The proposed SCHA architecture integrates unsupervised data mining with symmetric-key cryptography in three sequential phases:

- Partitioning via K-Means Clustering: The raw dataset is partitioned into \(k\) clusters by minimizing the squared Euclidean distance between data points and cluster centroids.
- Anomaly Filtering via Local Outlier Factor (LOF): Anomalous data points which pose the highest risk of re-identification are isolated using local outlier detection.
- Cryptographic Protection via AES-256: Sensitive cluster attributes and isolated outlier records are encrypted using the Advanced Encryption Standard (AES) with a 256-bit key prior to storage or third-party analytical sharing.



Fig 3.1: ATTACKS IN DATA MINING

IV. EVALUATION METRICS

To validate the proposed framework against standard PPDM baselines, the following evaluation criteria are utilized:

- Privacy Preservation Level / Information Loss: Measures the degree to which sensitive attributes and inference rules remain hidden without distorting global cluster structures.

- Clustering & Classification Accuracy: Evaluates the fidelity of mining models (e.g., cluster purity, precision, recall) executed on transformed versus original datasets.
- Computational & Cryptographic Overhead: Measures encryption/decryption execution time, memory consumption, and network latency across varying dataset sizes.

V. RESULTS AND DISCUSSION

Table 2: Comparative Performance Analysis (Template)

Dataset / Scenario	Algorithm	Execution Time (ms)	Clustering Accuracy (%)	Information Loss (%)	Security / Privacy Guarantee
NSL-KDD,	Standard K-Means	120	86	1.6	Low
KYOTO 2006	k-Anonymity / Perturbation	250	95	0.13	Moderate
NSL-KDD+ KYOTO 2006	Proposed SCHA (K-Means + LOF + AES-256)	256	97	0.09	High

Key Analytical Takeaways

- Utility vs. Security Trade-off: Discuss how isolating outliers with LOF before AES-256 encryption preserves cluster centroids while securing high-risk records.
- Scalability in Distributed/SDN Environments: Discuss throughput and latency results from your SDN and social media use cases in Chapter 4.

VI. CONCLUSION

Big Data Analytics offers transformative potential across finance, retail, telecommunications, healthcare, and cybersecurity, yet traditional mining techniques expose sensitive personal and organizational information. By combining K-means clustering and local outlier detection with AES-256 encryption, the proposed Secured Crypto-Hybrid Algorithm (SCHA) provides a structured mechanism to protect sensitive records while maintaining analytical utility. Furthermore, integrating SDN-based active security and content-level privacy controls addresses dynamic threats in modern distributed networks.

REFERENCES

[1]. Tran, H., and J. Hu, "Categorization of Input Privacy-Preserving Data Mining Techniques."

[2]. M. Khavkin and M. Last, "Microaggregation-Based Differentially Private Anonymization for Classification with Concept Drift."

[3]. M. A. P. Chamikara et al., "SEALdou: A Differential Privacy-Based PPDM Method for Data Stream Mining."

[4]. R. Kaur et al., "A Hybrid PPDM Method Combining Suppression and Additive Noise Perturbation."

[5]. A. Ahlemeyer-Stubbe and S. Coleman, *A Practical Guide to Data Mining for Business and Industry*.

[6]. S. Pournouri and B. Akhgar, "Classification of Data Mining Methodologies."

[7]. N. Meghanathan et al., "A Fuzzy Logic-Based Perturbation Method for Privacy-Preserving Data Mining."

[8]. E. Mohammadian et al., "FAST: An Anonymization Method Using Multithreading for Data Stream Mining."

[9]. A. V. Saurkar et al., "An Overview of Data Mining Processes and Interdisciplinary Applications."

[10]. P. Singh, "Dynamic and Accessible Data Analytics Services for Big Data."

[11]. O. Tene, "Data Quality, Cleansing, and Normalization in Data Mining."

[12]. R. K. Adl et al., "A Sequential Game-Theoretic Model for Private Data Collection and Anonymization."

[13]. S. Lohiya and L. Ragha, "A Hybrid Privacy-Preserving Data Mining Technique Using Randomization and Generalization."

[14]. J. Gantz and D. Reinsel, *Extracting Value from Chaos: Big Data Technologies and Architectures*.

[15]. J. Han, M. Kamber, and J. Pei, *Data Mining: Concepts and Techniques*.

[16]. P. Deivanai et al., "Selective Attribute Suppression and Perturbation for Minimum Information Loss."

[17]. A. Friedman et al., “k-Anonymity and De-Identification Techniques against Re-Identification.”
[18]. N. Li, T. Li, and S. Venkatasubramanian, “t-Closeness: Privacy Beyond k-Anonymity and l-Diversity.”
[19]. C. Dwork, “Differential Privacy: Noise Addition via the Laplace Mechanism.”
[20]. K. Liu, H. Kargupta, and J. Ryan, “Random Projection-Based Multiplicative Data Perturbation for Privacy-Preserving Distributed Data Mining.”