AI-Enabled Sports Intelligence: An Integrated IoT And Machine-Learning Framework For Real-Time Athlete Performance Monitoring

Dr. Kirankumar Premchand Johare
Department of Electronic Science and Computer Science Maratha Vidya Prasarak Samaj, Nashik, Maharashtra, India
doi.org/10.64643/IJIRT211715

***Abstract*—Contemporary sport produces continuous streams of physiological, biomechanical, positional and video data. In practice these streams are often collected by separate devices and examined through disconnected analytical routines.**

This paper presents an implementation-oriented AI–IoT framework that brings multimodal sensing, secure communication, edge and cloud processing, machine-learning analytics and human-centred decision support into a single coherent architecture for athlete performance monitoring. The framework is organised into five functional layers and is accompanied by a technical workflow, a mathematical design notation, an algorithmic sequence and a comparative table that contrasts conventional, device-isolated and integrated monitoring practices. Its distinctive feature is the joint treatment of athlete-specific baselines, time-synchronised multimodal data, explicit data-quality controls, uncertainty-aware outputs and mandatory human review, while privacy, affordability, interoperability and accessibility are treated as requirements that cut across every layer. The work is conceptual and grounded in the existing literature; it reports neither a recruited athlete cohort, a newly trained model nor measured performance gain. Instead, it sets out a practical pilot pathway together with evaluation criteria that cover measurement validity, data completeness, synchronisation error, latency, calibration, fairness and usability. The framework is intended to guide future sport-specific implementations in professional teams, educational institutions and community programmes, ensuring that algorithmic outputs assist rather than displace coaching and clinical judgement.

***Index Terms*—Artificial Intelligence (AI), Athlete Monitoring, Internet of Things (IoT), Machine Learning (ML), Sports Analytics**

I. INTRODUCTION

Athletic performance is the product of physical capacity, technical execution, tactical understanding, recovery status, psychological state and environmental conditions. Coaches normally interpret these factors through direct observation, training diaries and competition statistics. Wearable sensors, positioning systems and video platforms can supply frequent movement and physiological observations, yet the mere availability of additional data does not guarantee better decisions. Measurements must be reliable, temporally aligned, relevant to the question being asked and presented in a form that practitioners can interpret.

A recurring difficulty is fragmentation. Heart-rate monitors, inertial measurement units, GNSS/GPS devices and video systems frequently operate with different sampling rates, identifiers and data formats. When streams are poorly synchronised, a physiological response may be linked to the wrong movement event. Reviews of wearable technology underline the diversity of devices and the practical limits of their measurements [1], [2]. Parallel work on training load shows why physiological and external-load indicators must be read in context rather than in isolation [3].

Artificial Intelligence (AI) and machine learning can detect patterns in repeated observations, and recent syntheses document their expanding role in sports analytics [4]. Predictive accuracy alone, however, does not establish operational value. Outputs need to be timely, explainable, externally validated and governed by clear lines of responsibility [5].

This conceptual study therefore proposes an integrated AI–IoT framework for real-time athlete monitoring and examines three research questions:

1. How can heterogeneous wearable-sensor and video data be brought together within a single framework for athlete performance monitoring?
2. How can IoT connectivity and machine-learning methods turn integrated observations into timely, interpretable performance indicators?
3. What technical, organisational and ethical conditions are required for responsible deployment across professional, educational and community sporting environments?

The contribution is not a novel sensor or a new machine-learning algorithm. It is an implementation-oriented design that links multimodal observations to human-reviewed decisions. The architecture combines individual baselines, synchronised data streams, edge/cloud processing, uncertainty-aware interpretation and role-specific interfaces, while embedding consent, privacy, fairness, affordability and interoperability as standing design requirements.

II. LITERATURE REVIEW

Wearable devices used in sport typically include accelerometers, gyroscopes, inertial measurement units, heart-rate sensors and global positioning systems. Seçkin and colleagues review the concepts, challenges and opportunities associated with sports wearables [1]. Alzahrani and Ullah examine wearable technologies and biomechanical analytics for performance monitoring [2]. Training-load monitoring supplies an essential interpretive foundation; Halson clarifies the relationship between training load and fatigue [3]. Systematic reviews of AI-based sports analytics, such as that by Pietraszewski et al. [4], document the rapid growth of the field. Responsible deployment further requires attention to transparency and accountability, principles articulated in global AI ethics guidance [5].

Sports biomechanics research increasingly explores the combination of AI with wearable technology, movement analysis and injury-prevention strategies. Souaifi et al. map these applications and identify persistent translational obstacles [6]. Claudino and co-authors review AI methods for injury-risk assessment and performance prediction in team sports [7]. Both reviews endorse computational analysis while stressing that model performance must be evaluated within the specific sporting context.

Immersive and feedback technologies may complement monitoring systems. Bird discusses the use of virtual-reality head-mounted displays in applied sport psychology, including perceptual-cognitive training and rehabilitation [8]. At institutional level, Hirsh and Levental examine barriers and facilitators to the introduction of AI in physical education [9]. Their findings are pertinent to settings beyond elite sport, where coach and teacher readiness, available training and resource constraints shape adoption.

Sensor-enhanced wearables and automated analytics have been proposed as aids to injury prevention [10]. Bittencourt et al. advocate a complex-systems perspective on sports injuries, emphasising interacting patterns rather than isolated risk factors [11]. Espinosa and colleagues review wearable sensor technology in sports monitoring [12], while Aroganam et al. survey sensors employed in consumer sport applications [13]. Collectively these studies underline the necessity of matching sensor selection, placement and interpretation to the intended purpose.

Machine-learning studies of injury prediction illustrate both promise and methodological shortcoming. Van Eetvelde et al. review ML methods for sport-injury prediction and prevention [14]. Musat et al. provide a broad survey of AI-based injury-risk prediction techniques [15]. Bullock and colleagues report substantial concerns about the methodological conduct and validation of musculoskeletal injury-prediction models [16]. Leckey et al. highlight heterogeneity in injury definitions, cohorts and prediction windows, which can undermine the practical relevance of reported performance figures [17].

Injury identification is not synonymous with performance monitoring, yet it supplies useful evidence about how sensor-derived information should be interpreted. Canavan Dignam et al. review emerging technologies for injury identification in sports settings [18]. Adlou and co-authors compare optical, inertial and markerless motion-capture approaches and discuss accuracy considerations that vary by sport and environment [19]. Ren et al. offer an applied illustration of GPS-derived metrics combined with ML models for injury prediction in professional rugby union [20]. Yuan et al. address methodological issues in ML-based sports-injury prediction, including interpretability and generalisability [21]. These

sources support a cautious distinction between monitoring indicators, risk estimates and clinical diagnosis.

Finally, responsible implementation requires transparent model development and evidence that can be reviewed by independent parties. Bullock et al. argue that open-science practices are needed to improve prediction models in sports medicine and performance [22]. This argument reinforces the need for documented data procedures, model versioning, transparent evaluation, meaningful consent and human oversight within the framework proposed here.

III. RESEARCH GAP, PROBLEM STATEMENT AND NOVELTY

The literature records clear progress in wearable sensing, sports analytics, motion capture and injury-risk modelling. Yet the practical route from raw observation to an interpretable coaching decision is seldom described as a single, coherent system. Monitoring platforms frequently remain device-specific; multimodal streams are difficult to synchronise; model outputs often omit uncertainty information; and implementation requirements for resource-constrained settings receive limited attention. Evidence reviews further show that predictive models can be constrained by small or narrowly sampled datasets, weak external validation and inconsistent outcome definitions [14], [16], [17].

The research problem may therefore be stated as follows: how can heterogeneous athlete-monitoring data be integrated into an affordable, interpretable and responsibly governed system that supports timely performance decisions across diverse sporting environments? The gap is not merely a shortage of sensors or algorithms. It is the absence of a coherent, role-aware and validation-conscious pathway from measurement to action.

A. Novelty and Original Contribution of the Proposed Framework

The proposed framework offers an integrated design approach organised around five coordinated features. First, it brings physiological, movement, positional and video-derived observations into a common athlete-and-session data structure. Second, it interprets changes against individual baselines and training context, thereby reducing reliance on generic thresholds. Third, it allocates processing between edge and cloud resources according to latency, connectivity, privacy and computational demands. Fourth, it treats uncertainty and data-quality status as integral parts of every AI output, so that an alert is never presented as a definitive diagnosis.

Fifth, it routes consequential outputs to the appropriate human reviewer and embeds consent, access control, fairness, affordability and interoperability throughout the system. The novelty claims therefore rests on the coordinated architecture and decision pathway rather than on the invention of any individual component technology. The contribution remains conceptual and awaits empirical testing.

IV. PROPOSED AI–IoT FRAMEWORK AND METHODOLOGY

The study adopts a literature-informed conceptual framework-development method. It identifies users and the decisions they must make, maps relevant data sources, defines system layers and governance requirements, and specifies a pilot-evaluation plan. No athlete dataset was collected and no machine-learning model was trained for this paper.

The architecture comprises five connected layers: (1) Data Acquisition, (2) IoT communication, (3) edge/cloud processing, (4) AI/ML analytics, and (5) Intelligent decision support. Governance and safeguards apply across all layers.




Fig. 1. Proposed five-layer AI-enabled sports intelligence architecture with cross-cutting governance requirements.

The acquisition layer may incorporate heart-rate monitors, inertial measurement units, GNSS/GPS units, video cameras and sport-specific sensors. Devices should be selected to answer defined questions. Pseudonymous athlete and session identifiers, precise timestamps and contextual metadata (sport, drill type, playing position and environmental conditions) link observations together. Data collection must remain proportionate to the stated purpose.

The communication layer employs Bluetooth Low Energy, Wi-Fi, cellular networks or a local gateway according to range, bandwidth, power constraints and venue conditions. Local buffering accommodates intermittent connectivity; time alignment is essential before streams are fused.

The processing layer verifies data integrity and missing values, harmonises measurement units, aligns timestamps and extracts features. Edge processing supports low-latency feedback; cloud services support longitudinal analysis. Sensitive data should be minimised and protected through encryption, role-based access control and defined retention policies.

The analytics layer may employ statistical methods, regression, classification, anomaly detection or time-series models. Model selection should reflect the decision at hand, the available sample size and the characteristics of the data. Evaluation should be performed on independent athletes or sessions, using temporal or external validation wherever feasible. Calibration, uncertainty estimates and subgroup performance should be examined alongside conventional discrimination metrics.



The decision-support layer supplies role-specific information: personal trends for athletes, session summaries for coaches, relevant observations for authorised medical staff and aggregated indicators for administrators. Alerts should describe the observed change, the relevant baseline, the data-quality status and the associated uncertainty. Human review remains indispensable for any consequential decision.

A. Proposed Mathematical Representation

Let the observation vector at time t be written as:

$X_t = [HR_t, ACC_t, IMU_t, GPS_t, V_t, E_t]$

where HR denotes heart-rate features, ACC acceleration features, IMU inertial features, GPS positional or movement features, V video-derived features and E relevant environmental or session-context features. Let B_t represent the athlete-specific baseline and C_t the training context.

A task-specific model may then be expressed as:

$\hat{Y}_t = f(X_t, B_t, C_t; \theta)$

where θ denotes model parameters and $\hat{Y}_t$ is a task-dependent estimate such as a workload indicator or movement category. The model output should be accompanied by an uncertainty estimate U_t and a data-quality flag Q_t.

B. Proposed Processing Algorithm

Step	Proposed operation
1	Acquire sensor and video observations for an identified training session.
2	Verify athlete and session identifiers, timestamps, measurement units and device status.
3	Synchronise streams and flag missing, implausible or low-quality observations.
4	Extract sport-relevant physiological, movement and video features.
5	Compare current features with the athlete’s baseline and the session context.
6	Apply a previously validated, task-appropriate ML model and estimate uncertainty.
7	If data quality is inadequate, request remeasurement or mark the output as unavailable.
8	If a meaningful change is detected, generate an explanatory alert for human review.
9	Otherwise continue routine monitoring and retain only authorised data.
10	Record reviewer feedback and monitor model and device performance over time.

A decision rule may be written:

$A_t = g(\hat{Y}_t, U_t, Q_t, B_t, C_t)$

where A_t is a proposed monitoring action (routine display, request for review, or explanatory alert). These expressions constitute a conceptual design

notation; they do not represent a trained model, a validated prediction equation or evidence of measured accuracy.

C. Operational Workflow

Figure 2 summarises the path from sensor observations to human-reviewed monitoring outputs. The workflow incorporates a quality gate before model inference and an uncertainty-and-context check before any alert is issued. This arrangement prevents a missing or unreliable sensor reading from being interpreted as a meaningful change in the athlete’s state.




Fig. 2. Conceptual workflow converting wearable and video observations into AI-assisted, human-reviewed performance-monitoring outputs.

D. Comparison with Existing Monitoring Approaches

Table 1 is a conceptual design comparison, not a measured head-to-head performance evaluation. It describes intended functional differences that should be tested during future implementation.

Dimension	Conventional monitoring	Isolated wearable platforms	Proposed integrated framework
Data sources	Manual observations or separate device feeds	Multiple devices, often separate dashboards	Wearable and video observations linked by common identifiers
Time alignment	Primarily manual or session-level	May differ by device or platform	Explicit timestamp synchronisation and quality checks
Interpretation	Practitioner experience and basic statistics	Device-specific analytics	Context-aware ML outputs and individual baselines
Uncertainty	Usually, informal	Not consistently exposed	Uncertainty and data-quality status accompany outputs
Decision pathway	Coach-led, often fragmented	Alerts may be platform-specific	Role-specific outputs with human review
Governance and access	Depends on local practice	Vendor or platform dependent	Consent, access, retention and audit requirements built into design
Deployment cost	Low equipment cost, high manual effort	Can require multiple subscriptions and devices	Modular adoption; begin with a validated minimum sensor set

V. APPLICATIONS AND DISCUSSION

In performance monitoring the framework can combine session duration, movement intensity, heart-rate response, acceleration profiles and video-derived technical observations. Multiple indicators are preferable to a single composite score that claims to represent overall ability. Individual baselines help interpret changes across training phases and specific drills.

For tactical analysis, positional and video features may describe spacing, transitions and player involvement. Interpretation remains sport-specific and must be reviewed by coaches. Longitudinal data can support talent-development programmes, yet early measurements should never be treated as fixed predictions. Models must be checked for subgroup bias and must not restrict participation opportunities.

With respect to workload and injury-risk support, sensor-derived features may help identify changes that warrant practitioner attention. Performance monitoring is not equivalent to injury diagnosis. Studies of injury prediction have highlighted methodological concerns relating to validation, outcome definitions and limited clinical utility [14], [16], [17]. Consequently, the proposed framework treats alerts as prompts for assessment rather than automatic instructions to modify training loads or return an athlete to competition.

A practical deployment should begin with a limited pilot in one sport and a clearly defined use case. The first stage establishes athlete consent, device procedures and baseline measurements. The second assesses sensor validity, data completeness and synchronisation accuracy. The third compares model outputs with independent reference measurements and qualified practitioner assessments. Only after these checks should outputs be considered for routine decision support.

The framework is intentionally modular. A school or community club may start with a small set of validated sensors and basic analytics, while a professional organisation may add video analysis, GNSS tracking and longitudinal cloud services. Total cost of ownership must include device replacement, maintenance, connectivity, secure storage, staff training and technical support. Affordability should never be achieved by accepting unvalidated measurements or inadequate privacy protections.

VI. EVALUATION REQUIREMENTS, LIMITATIONS AND FUTURE RESEARCH

A pilot study should pre-specify technical, analytical, operational and human-centred outcomes. Technical measures include data completeness, synchronisation error, packet loss, latency, battery life and device failure rates. Measurement validity should be tested against an appropriate reference standard for each variable and sport. Analytical metrics may include sensitivity, specificity, precision, recall, calibration and error. Data splitting must prevent athlete or session leakage; independent validation should be sought whenever possible.

Operational evaluation should examine timeliness, user understanding and alert burden. Feedback from athletes, coaches and medical practitioners can illuminate usability, trust, perceived surveillance and fit with existing workflows. Fairness should be assessed across relevant demographic and performance groups. Model versioning, audit trails and periodic revalidation are required as devices and populations change.

The framework has not been empirically evaluated. No athlete dataset was collected, no model was trained and no improvement in performance, injury incidence or coaching outcomes is claimed. The comparison table, mathematical expressions and algorithm are design artefacts, not experimental findings. Future work should pilot the system in a defined sport, validate sensor streams and test whether decision support measurably improves practitioner decisions.

VII. CONCLUSION

This paper has proposed a five-layer AI–IoT framework that connects multimodal athlete observations to human-reviewed decisions. RQ1 is addressed through common athlete and session identifiers, timestamp synchronisation, contextual metadata and data-quality checks. RQ2 is addressed through IoT communication, edge and cloud processing, and task-appropriate machine learning that is interpreted against individual baselines, session context and uncertainty estimates. RQ3 requires validated devices, secure and proportionate data collection, informed consent, transparent evaluation, fair access, interoperability, affordability and continuous human oversight.

The distinctive contribution is a coordinated pathway in which multimodal sensing feeds quality-controlled processing; analytics are interpreted against individual baselines and context; uncertain or low-quality outputs are explicitly flagged; and consequential alerts are directed to a responsible human reviewer. This integration addresses the gap between data collection and decision support without claiming that the component technologies are new or that benefits have already been demonstrated.

The framework remains conceptual and awaits validation. A staged pilot should establish measurement validity, synchronisation performance, latency, model calibration, fairness, usability and decision impact before any wider deployment is contemplated. Ultimately the value of the system will depend not on the number of sensors deployed or the complexity of the algorithms employed, but on whether it produces reliable, understandable and responsibly governed information that genuinely improves the work of athletes and practitioners.

ACKNOWLEDGMENT

The Author would like to thank MVP’s Sarchitnis Adv. Nitin Thakare and Management, as well as Dr. Nitin Jadhav, MVP’s Education Officer, Prof. Dr. Vasant B. Kadam, Principal, Shri. Bhagwan Kadlag, IQAC-Coordinator, Dr. Prashant Koli, NACC Coordinator, MVP’s K.K.W. ASC College, Nashik 422209, India for their encouragement and motivational support. Also thankful to Dr. A. V Patil, V. G. Wagh, Dr. A. D. Shaligram, and Prof. Dnyaneshwar W. Aher, Head of Department of Computer Science, K.T.H.M. College, Nashik 422002, Maharashtra, India.

Note: The authors have utilized artificial intelligence (AI) tools for language polishing and grammar checking. However, the core research ideas, findings, and conclusions are entirely the authors’ original work.

Funding: This research received no external funding.

REFERENCES

[1] A. Ç. Seçkin, B. Ateş, and M. Seçkin, “Review on Wearable Technology in Sports: Concepts, Challenges and Opportunities,” *Applied Sciences*, vol. 13, no. 18, Art. no. 10399, 2023, doi: 10.3390/app131810399.

[2] A. Alzahrani and A. Ullah, “Advanced biomechanical analytics: Wearable technologies for precision health monitoring in sports performance,” *Digital Health*, vol. 10, 2024, doi: 10.1177/20552076241256745.

[3] S. L. Halson, “Monitoring Training Load to Understand Fatigue in Athletes,” *Sports Medicine*, vol. 44, suppl. 2, pp. S139–S147, 2014, doi: 10.1007/s40279-014-0253-z.

[4] P. Pietraszewski *et al*., “The Role of Artificial Intelligence in Sports Analytics: A Systematic Review and Meta-Analysis of Performance Trends,” *Applied Sciences*, vol. 15, no. 13, Art. no. 7254, 2025, doi: 10.3390/app15137254.

[5] A. Jobin, M. Ienca, and E. Vayena, “The Global Landscape of AI Ethics Guidelines,” *Nature Machine Intelligence*, vol. 1, pp. 389–399, 2019, doi: 10.1038/s42256-019-0088-2.

[6] M. Souaifi, W. Dhahbi, N. Jebabli, H. İ. Ceylan, M. Boujabli, R. I. Muntean, and I. Dergaa, “Artificial Intelligence in Sports Biomechanics: A Scoping Review on Wearable Technology, Motion Analysis, and Injury Prevention,” *Bioengineering*, vol. 12, no. 8, Art. no. 887, 2025, doi: 10.3390/bioengineering12080887.

[7] J. G. Claudino, D. de O. Capanema, T. V. de Souza, J. C. Serrão, A. C. M. Pereira, and G. P. Nassis, “Current Approaches to the Use of Artificial Intelligence for Injury Risk Assessment and Performance Prediction in Team Sports: A Systematic Review,” *Sports Medicine - Open*, vol. 5, Art. no. 28, 2019, doi: 10.1186/s40798-019-0202-3.

[8] J. M. Bird, “The Use of Virtual Reality Head-Mounted Displays Within Applied Sport Psychology,” *Journal of Sport Psychology in Action*, vol. 11, no. 2, pp. 115–128, 2020, doi: 10.1080/21520704.2018.1563573.

[9] A. Hirsh and O. Levental, “Barriers and Facilitators to Implementing Artificial Intelligence in Teaching Physical Education,” *Journal of Physical Education, Recreation & Dance*, vol. 96, no. 7, pp. 16–25, 2025, doi: 10.1080/07303084.2025.2520207.

[10] M. Kovoor *et al*., “Sensor-enhanced wearables and automated analytics for injury prevention in sports,” *Measurement: Sensors*, vol. 32, Art. no. 101054, 2024, doi:

10.1016/j.measen.2024.101054.

[11] N. F. N. Bittencourt, W. H. Meeuwisse, L. D. Mendonça, A. Nettel-Aguirre, J. M. Ocarino, and S. T. Fonseca, “Complex systems approach for sports injuries: moving from risk factor identification to injury pattern recognition—narrative review and new concept,” *British Journal of Sports Medicine*, vol. 50, no. 21, pp. 1309–1314, 2016, doi: 10.1136/bjsports-2015-095850.

[12] H. G. Espinosa, A. C. Mears, A. Stamm, Y. Ohgi, and C. L. Coniglio, “Wearable sensor technology in sports monitoring,” *Sports Engineering*, vol. 28, no. 1, Art. no. 4, 2025, doi: 10.1007/s12283-025-00485-9.

[13] G. Aroganam, N. Manivannan, and D. Harrison, “Review on Wearable Technology Sensors Used in Consumer Sport Applications,” *Sensors*, vol. 19, no. 9, Art. no. 1983, 2019, doi: 10.3390/s19091983.

[14] H. Van Eetvelde, L. D. Mendonça, C. Ley, R. Seil, and T. Tischer, “Machine learning methods in sport injury prediction and prevention: a systematic review,” *Journal of Experimental Orthopaedics*, vol. 8, Art. no. 27, 2021, doi: 10.1186/s40634-021-00346-x.

[15] C. L. Musat *et al*., “Diagnostic Applications of AI in Sports: A Comprehensive Review of Injury Risk Prediction Methods,” *Diagnostics*, vol. 14, no. 22, Art. no. 2516, 2024, doi: 10.3390/diagnostics14222516.

[16] G. S. Bullock, J. Mylott, T. Hughes, K. F. Nicholson, R. D. Riley, and G. S. Collins, “Just How Confident Can We Be in Predicting Sports Injuries? A Systematic Review of the Methodological Conduct and Performance of Existing Musculoskeletal Injury Prediction Models in Sport,” *Sports Medicine*, vol. 52, no. 10, pp. 2469–2482, 2022, doi: 10.1007/s40279-022-01698-9.

[17] C. Leckey, N. van Dyk, C. Doherty, A. Lawlor, and E. Delahunt, “Machine learning approaches to injury risk prediction in sport: a scoping review with evidence synthesis,” *British Journal of Sports Medicine*, vol. 59, no. 7, pp. 491–500, 2025, doi: 10.1136/bjsports-2024-108576.

[18] L. Canavan Dignam, L. Ryan, M. McCann, and E. Daly, “Emerging Technologies for Injury Identification in Sports Settings: A Systematic Review,” *Applied Sciences*, vol. 15, no. 14, Art. no. 7874, 2025, doi: 10.3390/app15147874.

[19] B. Adlou, C. Wilburn, and W. Weimar, “Motion Capture Technologies for Athletic Performance Enhancement and Injury Risk Assessment: A Review for Multi-Sport Organizations,” *Sensors*, vol. 25, no. 14, Art. no. 4384, 2025, doi: 10.3390/s25144384.

[20] X. Ren, S. Boisbluche, K. Philippe, M. Demy, S. Äyrämö, I. Rautiainen, S. Ding, and J. Prioux, “Global Positioning System-Derived Metrics and Machine Learning Models for Injury Prediction in Professional Rugby Union Players,” *European Journal of Sport Science*, vol. 25, no. 10, Art. no. e70057, 2025, doi: 10.1002/ejsc.70057.

[21] J. Yuan, Q. Zeng, J. Li, Z. Cong, and Y. Zhang, “Machine learning applications in sports injury prediction: A narrative review,” *Science Progress*, vol. 108, no. 4, 2025, doi: 10.1177/00368504251385956.

[22] G. S. Bullock, P. Ward, F. M. Impellizzeri, S. Kluzek, T. Hughes, P. Dhiman, R. D. Riley, and G. S. Collins, “The Trade Secret Taboo: Open Science Methods are Required to Improve Prediction Models in Sports Medicine and Performance,” *Sports Medicine*, vol. 53, pp. 1841–1849, 2023, doi: 10.1007/s40279-023-01849-6.